
**Small craft — Inboard diesel engines
— Engine-mounted fuel, oil and
electrical components**

*Petits navires — Moteurs intérieurs diesels — Éléments des circuits
d'alimentation, des systèmes de lubrification et des systèmes
électriques fixés sur le moteur*

STANDARDSISO.COM : Click to view the full PDF of ISO 16147:2018



STANDARDSISO.COM : Click to view the full PDF of ISO 16147:2018



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 General	2
5 Engine fuel and oil system and components	2
5.1 General	2
5.2 High-pressure pipes	3
5.3 Low-pressure fuel lines	3
5.4 Fuel and lubrication oil filters	3
6 Electrical systems and components	3
6.1 General	3
6.2 Cranking motors	3
6.3 Wiring and connections	4
6.4 Relays, fuse boxes and electronic control modules (ECMs)	4
7 Installation manual	4

STANDARDSISO.COM : Click to view the full PDF of ISO 16147:2018

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of Standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 188, *Small craft, SC 2, Engines and propulsion systems*.

This second edition of ISO 16147 cancels and replaces the first edition (ISO 16147:2002), of which it constitutes a technical revision. It also incorporates the amendment ISO 16147:2002/Amd 1:2013.

The main changes compared to the previous edition are as follows:

- in [4.2](#), requirements for access to fuel and electrical components have been added;
- in [4.3](#), requirements for exposed operating or hot components have been added;
- in [4.4](#), requirements that installation of fuel and electrical components shall take account of the risk and spread of fire have been added;
- in [5.3.1](#), requirements and temperature requirements on material in low pressure fuel lines have been deleted;
- in [5.4](#), requirements on oil filters have been added;
- in [6.1.2](#), requirements that AC installations shall meet the requirements in IEC 60092-507 or ISO 13297 have been added;
- in [6.1.3](#), requirements that electronic shift and throttle components if engine mounted and part of engine delivery from manufacturer shall meet the requirements in ISO 25197 have been added;
- in [Clause 7](#), requirements to state return fuel temperature/energy and flow in installation manual have been deleted and replaced by information about fuel line dimensions.

Small craft — Inboard diesel engines — Engine-mounted fuel, oil and electrical components

1 Scope

This document establishes requirements for the design and installation of engine-mounted fuel, oil and electrical components on diesel inboard-mounted engines for minimizing fuel leakage, risk of electric shock and the risk of and/or the spread of fire on small craft of hull length up to 24 m.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7840:2013, *Small craft — Fire-resistant fuel hoses*

ISO 10088:2001, *Small craft — Permanently installed fuel systems and fixed fuel tanks*

ISO 10133, *Small craft — Electrical systems — Extra-low-voltage d.c. installations*

ISO 13297, *Small craft — Electrical systems — Alternating current installations*

ISO 25197, *Small craft — Electrical/electronic control systems for steering, shift and throttle*

IEC 60529, *Degrees of protection provided by enclosures (IP CODE)*

IEC 60092-507, *Electrical Installations in Ships — Part 507: Small vessels*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1

engine-mounted

component fixed to the marine inboard engine and which remains while the engine is in operation

3.2

diesel fuel

hydrocarbon fuel or blends of hydrocarbon fuels including bio-fuel which are liquids at atmospheric pressure and are used in compression-ignition engines

3.3

diesel engine

internal combustion engine that uses the heat of highly compressed air to ignite a spray of diesel fuel introduced after the start of the compression stroke

3.4

accessible

capable of being reached for inspection, removal or maintenance without removal of the permanent boat structure

Note 1 to entry: Hatches are not regarded as permanent boat structures in this sense, even if tools are needed to open them.

3.5

low-pressure fuel line

hose or pipe for fuel supply to high-pressure pumps or injection pumps including leak-off and return pipes from high-pressure pumps, injection pumps, injectors, etc.

3.6

high-pressure fuel pipe

fuel pipes from high-pressure pumps or injection pumps including high-pressure accumulators (rails)

3.7

fatty acid methyl ester

FAME

fuel composed of mono-alkyl esters of long-chain fatty acids derived from vegetable oils or animal fats

4 General

4.1 All material and components shall be suitable for intended use and capable of operation within an ambient temperature range of $-10\text{ }^{\circ}\text{C}$ to $+80\text{ }^{\circ}\text{C}$ without failure or leakage, and be capable of being stored without operation within an ambient temperature range of $-30\text{ }^{\circ}\text{C}$ to $+80\text{ }^{\circ}\text{C}$ without failure or leakage.

4.2 Engine-mounted fuel and electrical components and accessories that require frequent inspection and/or servicing shall be accessible.

4.3 Exposed operating or hot engine-mounted components that could cause personal injury shall be effectively shielded.

4.4 Installation of engine-mounted diesel fuel and electrical components shall take account of the risk and spread of fire. Special attention shall be paid to hot areas of engines. Routing of electrical wiring, in particular, shall be located away from heat sources and hot areas.

5 Engine fuel and oil system and components

5.1 General

5.1.1 Engine-mounted fuel and lubricating systems shall be leak free, such that there is no dripping or wetting of surface areas at the interface of connecting components and pipe joints due to misting atomization, or liquid from fuel or lubrication under normal operation.

5.1.2 All materials used in fuel systems shall be resistant to deterioration by the diesel fuel, including bio diesel that contains FAME and to other liquids or compounds with which they may come into contact under normal operating conditions, e.g. grease, lubricating oil, bilge solvents and sea water.

5.1.3 All sealing material, such as gaskets, o-rings, joint-rings, etc. shall be of the non-wicking, i.e. non-fuel-absorbent type.

5.1.4 Fuel and oil filters, flexible hoses including fittings and terminations shall, individually or as installed, withstand a 2,5 min fire test as described in ISO 10088:2001, Annex B or ISO 7840:2013, Annex A.

If the component is being tested as installed on an engine, the pan shall be large enough to extend beyond the vertical projection of the perimeter of the engine.

NOTE A permanently installed shielding of fuel return hoses, including their fittings and terminations, is accepted as protection against fire.

5.2 High-pressure pipes

5.2.1 High-pressure pipes shall be suitable for the pressure and pressure impulses in the system.

5.2.2 High-pressure pipes shall be secured to prevent vibrations leading to pipe fracture.

5.3 Low-pressure fuel lines

5.3.1 Flexible hoses shall meet the requirements of ISO 7840 and be secured by a metal hose clamp or permanently installed end fittings, such as a swaged sleeve, threaded insert or connections with compression ring sealings.

5.3.2 Hose connections having a nominal diameter of more than 25 mm shall have two hose clamps. The spud shall be at least 35 mm long to provide space for the clamps.

5.3.3 All low-pressure fuel lines shall be secured into position so as to prevent damage due to excessive vibration leading to pipe fracture. All flexible hoses shall be located away from non-insulated components with a surface temperature above 200 °C, but remain accessible for inspection and maintenance.

5.4 Fuel and lubrication oil filters

Fuel and lubricating oil filters shall

- be independently supported to avoid stress on pipe connections,
- be readily accessible, and
- not be mounted above turbochargers or uncooled exhaust gas manifolds.

6 Electrical systems and components

6.1 General

6.1.1 d.c. installations shall meet the requirements of ISO 10133.

6.1.2 a.c. installations shall meet the requirements of IEC 60092-507 or ISO 13297.

6.1.3 Electronic shift and throttle components if engine mounted and part of engine delivery from manufacturer shall meet the requirements of ISO 25197.

6.2 Cranking motors

Earth-return cranking motors shall be earthed (d.c. negative ground/earth) to the earth return system of the engine.

6.3 Wiring and connections

6.3.1 Cables and wiring shall be sized in accordance with ISO 10133.

6.3.2 Cables, wires and looms shall be

- of adequate length to prevent stressing of the cable and connections and chafing of the insulation;
- kept and secured well clear of rotating-shaft couplings, belts, etc.; and
- supported to minimize the effects of vibration and chafing.

6.3.3 Energized parts of electrical equipment shall be guarded against accidental contact by the use of enclosures.

6.3.4 Access to a.c. energized parts of the electrical system shall require the use of hand tools or have a protection of at least IP 2X according to IEC 60529.

6.3.5 Depending on the location, electrical equipment shall, as a minimum, have the following degree of protection:

- IEC 60529, IP X7 as a minimum, if exposed to short-term immersion;
- IEC 60529, IP X5 as a minimum, if exposed to splashing water;
- IEC 60529, IP 2X as a minimum, if located in protected locations inside the craft.

6.4 Relays, fuse boxes and electronic control modules (ECMs)

Relays, fuses and ECMs shall have the following degrees of protection or be enclosed in boxes having the same degrees of protection:

- IEC 60529, IP 67 as a minimum, if exposed to short-term immersion;
- IEC 60529, IP 55 as a minimum, if exposed to splashing water;
- IEC 60529, IP 20 as a minimum, if located in protected locations inside the craft.

7 Installation manual

The installation manual shall as a minimum include the following information:

- minimum fuel supply line inner diameter;
- minimum fuel return line inner diameter;
- maximum allowed vertical suction height for the inlet fuel pump;
- maximum length of the fuel supply line between the tank bottom and the fuel inlet line connection on the engine.

The engine manufacturer shall provide the necessary information if a cooler is required in the fuel return line including how it is to be installed.