

---

# INTERNATIONAL STANDARD



# 1639

---

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

---

## Wrought copper alloys — Extruded sections — Mechanical properties

*Alliages de cuivre corroyés — Profilés filés — Caractéristiques mécaniques*

First edition — 1974-11-01

STANDARDSISO.COM : Click to view the full PDF of ISO 1639:1974

---

UDC 669.3-42 : 539.3/.6

Ref. No. ISO 1639-1974 (E)

**Descriptors** : copper alloys, wrought products, profiles, extrusions, mechanical properties.

## FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 1639 was drawn up by Technical Committee ISO/TC 26, *Copper and copper alloys*, and circulated to the Member Bodies in December 1971.

It has been approved by the Member Bodies of the following countries :

Australia	France	South Africa, Rep. of
Austria	Hungary	Spain
Belgium	India	Sweden
Canada	Italy	Switzerland
Chile	Japan	Thailand
Czechoslovakia	Netherlands	Turkey
Denmark	Norway	United Kingdom
Egypt, Arab Rep. of	Portugal	U.S.A.
Finland	Romania	U.S.S.R.

The Member Body of the following country expressed disapproval of the document on technical grounds :

Germany

# Wrought copper alloys — Extruded sections — Mechanical properties

## 1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies the mechanical properties of extruded sections in wrought copper alloys the chemical compositions of which are listed in the appropriate International Standards (see 2.1).

NOTE — The term "extruded sections" does not exclude a combination of extruding and drawing.

## 2 REFERENCES

### 2.1 Chemical composition and forms of semi-manufactured products

ISO 426, *Wrought copper-zinc alloys — Chemical composition and forms of wrought products —*

*Part I : Non-lead, special and high tensile alloys.*

*Part II : Lead alloys.*

ISO 428, *Wrought copper-aluminium alloys — Chemical composition and forms of wrought products.*

ISO 430, *Wrought copper-nickel-zinc alloys — Chemical composition and forms of wrought products.*

### 2.2 Designations

ISO/R 1190, *Copper and copper alloys — Code of designation —*

*Part I : Designation of materials.*

*Part II : Designations of tempers.*

### 2.3 Test methods

ISO/R 399, *Vickers hardness test for copper and copper alloys (Test loads from 2.5 to 50 kgf).*

ISO/R 400, *Tensile testing of copper and copper alloys.*

ISO . . . , *Copper, copper alloys and alloyed copper — Selection of specimens and test pieces.*<sup>1)</sup>

## 3 ESSENTIAL PROPERTIES REQUIREMENTS

Table 1 embodies the principle that two properties are generally sufficient to define the condition of the material. The properties to be specified vary according to the temper and application of the material as set out in the table.

## 4 MECHANICAL PROPERTIES

The mechanical properties shown in table 2 refer to those which can be obtained in shapes of reasonably uniform mass distribution. The dimensional limitations applying to sections are difficult to define and must be the subject of agreement between the interested parties.

## 5 TEST METHODS

### 5.1 Tensile test

According to ISO/R 400.

### 5.2 Vickers hardness test

According to ISO/R 399, for test loads within the range from 2,5 up to 50 kgf.

### 5.3 Selection of test pieces

According to ISO . . .

1) In preparation.