

---

---

**Earth-moving machinery — Recyclability  
and recoverability — Terminology and  
calculation method**

*Engins de terrassement — Recyclabilité et récupérabilité —  
Terminologie et méthode de calcul*

STANDARDSISO.COM : Click to view the full PDF of ISO 16714:2008



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 16714:2008



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 16714 was prepared by Technical Committee ISO/TC 127, *Earth-moving machinery*, Subcommittee SC 3, *Machine characteristics, electrical and electronic systems, operation and maintenance*.

## Introduction

End-of-life machines contribute to the total volume of waste to be treated. As part of the machine life cycle, it is essential that recovery issues be taken into consideration during the design phase to ensure environmentally sound treatment.

Today, recycling has to be taken into account in addition to safety, emissions and fuel consumption when designing a machine. Consequently, there is need for an indicator to evaluate the ability and potential of new machines to be recovered/recycled.

The method for calculating recyclability and recoverability rates specified by this International Standard (similar to the one specified in ISO 22628:2002 for road vehicles) is based on four main stages inspired by the treatment of end-of-life machines. Recyclability/recoverability rates depend on the design and material properties of new machines and on the consideration of proven technologies — those technologies which have been successfully tested, at least on a laboratory scale, in this context.

The calculation method of this International Standard cannot in detail reflect the real process that will be applied to the machine at the end of its life.

STANDARDSISO.COM : Click to view the full PDF of ISO 16714:2008

# Earth-moving machinery — Recyclability and recoverability — Terminology and calculation method

## 1 Scope

This International Standard specifies a method, and defines related terms, for calculating the recyclability rate and the recoverability rate of earth-moving machinery as defined in ISO 6165, each expressed as a percentage by mass (mass fraction in percent) of the machine, which can potentially be

- recycled, reused or both (recyclability rate), or
- recovered, reused or both (recoverability rate).

NOTE Remanufacturing is included in re-use.

The calculation can be performed by the machine manufacturer from the time when a machine is initially put on the market.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6016, *Earth-moving machinery — Methods of measuring the masses of whole machines, their equipment and components*

ISO 6165, *Earth-moving machinery — Basic types — Identification and terms and definitions*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 6016 and the following apply.

### 3.1

#### **dismantlability**

ability of component parts to be removed from the machine

NOTE Adapted from ISO 22628:2002, definition 3.5.

### 3.2

#### **end-of-life machine**

machine that has completed its useful life and is taken out of service for disposal

**3.3 recovery**  
reprocessing in a production process of the waste materials for the original purpose or for other purposes, together with processing as a means of generating energy

[ISO 22628:2002, definition 3.4]

NOTE See Figure 1.

**3.4 recoverability**  
ability of component parts, materials or both that can be diverted from an end-of-life stream to be recovered

[ISO 22628:2002, definition 3.9]

**3.5 recoverability rate**  
 $R_{cov}$   
percentage by mass (mass fraction in percent) of the new machine potentially able to be recovered, reused or both

NOTE 1 Adapted from ISO 22628:2002, definition 3.10.

NOTE 2 See Figure 1.

**3.6 recycling**  
reprocessing in a production process of the waste materials for the original purpose or for other purposes, excluding processing as a means of generating energy

[ISO 22628:2002, definition 3.3]

NOTE See Figure 1.

**3.7 recyclability**  
ability of component parts, materials or both that can be diverted from an end-of-life stream to be recycled

[ISO 22628:2002, definition 3.7]

**3.8 recyclability rate**  
 $R_{cyc}$   
percentage by mass (mass fraction in percent) of the new machine potentially able to be recycled, reused or both

NOTE 1 Adapted from ISO 22628:2002, definition 3.8.

NOTE 2 See Figure 1.

**3.9 remanufacturing**  
process by which value is added to component parts of end-of-life machines in order to return them to their original same-as-new condition or better

**3.10 reusability**  
ability of component parts that can be diverted from an end-of-life stream to be reused

[ISO 22628:2002, definition 3.6]

**3.11**

**re-use**, noun

any operation by which component parts of end-of-life machines are used for the same purpose for which they were conceived

NOTE 1 Re-use includes **remanufacturing** (3.9).

NOTE 2 See Figure 1.

NOTE 3 Adapted from ISO 22628:2002, definition 3.2.

**3.12**

**total shipping mass**

$m_S$

mass of the base machine without an operator, with the fuel level at 10 % of tank capacity or with the minimum fuel level needed for machine shipping purposes as specified by the manufacturer, whichever is higher, with all fluid systems at the levels specified by the manufacturer and with empty sprinkler tank(s), if required, and with equipment, ballast, attachment, cab, canopy, operator-protective structures, wheels and counterweights as specified by the manufacturer and being designated for his production version

NOTE 1 If the manufacturer intends that the machine be partially disassembled for shipping purposes, the masses of the disassembled items are also stated.

NOTE 2 See Figure 1.

	<b>Recovery</b>		<b>Undefined residue</b>
(Component parts) <b>Re-use</b>	(Materials) <b>Recycling</b>	(Materials) <b>Energy recovery</b>	(Materials)
Recyclability rate <sup>a</sup>			
Recoverability rate <sup>a</sup>			
Total shipping mass			

<sup>a</sup> As a percentage of machine mass.

**Figure 1 — Key terms — Overview**

**4 Mass variables used in the calculation**

Table 1 presents and describes the symbols for the mass variables used in calculating the recyclability and recoverability rates.

**Table 1 — Variable masses and their symbols**

Symbol	Description
$m_P$	mass of materials taken into account at the pretreatment step
$m_D$	mass of materials taken into account at the dismantling step
$m_M$	mass of metals taken into account at the metals separation step
$m_{Tr}$	mass of materials taken into account at the non-metallic residue treatment step and which can be considered as recyclable
$m_{Te}$	mass of materials taken into account at the non-metallic residue treatment step and which can be considered for energy recovery
$m_S$	total shipping mass
All masses are expressed in kilograms.	

## 5 Calculation method

### 5.1 General

The calculation of the recyclability and recoverability rates is carried out through the following four steps on a new machine, for which component parts, materials or both can be taken into account at each step:

- a) pretreatment;
- b) dismantling;
- c) metals separation;
- d) non-metallic residue treatment.

A partial mass,  $m_P$ ,  $m_D$  or  $m_M$ , is determined, respectively, at each of the first three steps (see 5.3.1 to 5.3.3), while the partial masses  $m_{Tr}$  and  $m_{Te}$  are determined at the final step (see 5.3.4).

Annexes A and B give data presentation and a schematic representation of the method.

### 5.2 Materials breakdown

The materials breakdown, including the machine component parts, materials or both, is established by their classification into the following categories:

- a) metals;
- b) polymers, excluding elastomers;
- c) elastomers;
- d) glass;
- e) fluids;
- f) modified organic natural materials (MONM), such as leather, wood, cardboard and cotton fleece;
- g) others (components, materials or both, for which a detailed material breakdown cannot be established, e.g. compounds, electronics, electrics).

The total mass of each category can then be determined (see Annex A).

This breakdown may be done at each step of the calculation for each partial mass mentioned in 5.1.

### 5.3 Determination of $m_P$ , $m_D$ , $m_M$ , $m_{Tr}$ and $m_{Te}$

#### 5.3.1 Pretreatment — Determination of $m_P$

At this step, at least the following machine component parts, materials or both shall be taken into account:

- all fluids;
- batteries;
- oil filters;
- tyres;

- tyre wheels;
- roller drum;
- rubber track;
- rubber shoe pads;
- bucket;
- catalytic converters;
- urea tank.

NOTE Fluids include fuel, engine oil, machine hydraulic system oil, transmission/gearbox oil (including differential or transfer box or both), power steering oil, coolant, brake fluid, shock absorber fluid, air conditioning refrigerant, windscreen washer fluid, engine mounting oil and hydraulic suspension fluid.

For the purposes of the calculation, these component parts and materials are considered reusable or recyclable.

Determine the mass,  $m_P$ , as the sum of the masses of these component parts and materials.

### 5.3.2 Dismantling — Determination of $m_D$

At this step, certain other of the machine's reusable or recyclable component parts may be taken into account, based on the following.

As a general requirement, a component part shall be considered reusable, recyclable or both based on its dismantlability, assessed by

- accessibility,
- fastening technology, and
- proven dismantling technologies.

NOTE Certain component parts can be reusable through the remanufacturing procedure, based on design life as well as proven remanufacturing technologies and processes.

As a specific requirement, a component part shall be considered recyclable based on

- its material composition, and
- proven recycling technologies.

In order to be recyclable, a component part or material shall be linked to a proven recycling technology.

At this step, at least the following machine component parts, materials or both shall also be taken into account:

- engine;
- hydraulic circuit components (hydraulic pump, hydraulic control valve, swing drive motor, travel drive motor, etc.) excepting flexible hoses, filter cartridges and accumulators;
- operator's cab, including window glass, cab door (if disassembling possible) and operator's seat;

- boom;
- arm;
- counterweight;
- suspension system.

The reusability of a component part shall also be subject to considerations of safety and environmental hazards.

Determine the mass,  $m_D$ , as the sum of the masses of all parts considered as reusable or recyclable.

### 5.3.3 Metals separation — Determination of $m_M$

At this step, all metals, both ferrous and non-ferrous, that have not already been accounted for in the previous steps shall be taken into account. Both ferrous and non-ferrous metals are considered as recyclable.

Determine the mass,  $m_M$ , as the sum of the mass of the metal remaining in the machine after the previous steps.

### 5.3.4 Non-metallic residue treatment — Determination of $m_{Tr}$ and $m_{Te}$

Other materials remaining (i.e. those not taken into account at the pretreatment, dismantling and metals separation steps) constitute the non-metallic residue.

At this step, the residual non-metallic recyclable materials, or both these and the residual non-metallic recoverable materials, may be taken into account.

Determine  $m_{Tr}$ , as the sum of the mass of non-metallic residue considered as recyclable on the basis of proven recycling technologies (see Table A.1);

Determine  $m_{Te}$ , as the sum of the remaining masses that can potentially be used for energy recovery after determination of  $m_P$ ,  $m_D$ ,  $m_M$  and  $m_{Tr}$ .

NOTE Technologies for energy recovery of polymers and elastomers are industrialized on a large scale, world-wide. Polymers, elastomers and other modified organic natural materials can potentially be recovered through those technologies.

## 5.4 Calculation of recyclability/recoverability rate, $R_{cyc}/R_{cov}$

### 5.4.1 Recyclability rate

Calculate the recyclability rate,  $R_{cyc}$ , of the machine, as a percentage by mass (mass fraction in percent), using the formula:

$$R_{cyc} = \frac{m_P + m_D + m_M + m_{Tr}}{m_S} \times 100$$

### 5.4.2 Recoverability rate

Calculate the recoverability rate,  $R_{cov}$ , of the machine, as a percentage by mass (mass fraction in percent), using the formula:

$$R_{cov} = \frac{m_P + m_D + m_M + m_{Tr} + m_{Te}}{m_S} \times 100$$

## **Annex A** (normative)

### **Data presentation**

The data for the calculation shall be reported using the following table, either on paper or in electronic form. The materials breakdown section is optional.

STANDARDSISO.COM : Click to view the full PDF of ISO 16714:2008

Table A.1 — Presentation of data

Model/Type:							Total shipping mass, $m_S$ : kg	
Materials breakdown	Metals	Polymers (excluding elastomers)	Elastomers	Glass	Fluids	MONM	Others	
	Mass (kg)							
Pretreatment ( $m_P$ )	Mass (kg)							
	All fluids	$m_{P1}$						
	Batteries	$m_{P2}$						
	Oil filters	$m_{P3}$						
	Tyres	$m_{P4}$						
	Tyre wheels	$m_{P5}$						
	Roller drum	$m_{P6}$						
	Rubber track	$m_{P7}$						
	Rubber shoe pads	$m_{P8}$						
	Bucket	$m_{P9}$						
	Catalytic converters	$m_{P10}$						
	Urea tank	$m_{P11}$						
$m_P$ total (sum $m_{P1}$ to $m_{P11}$ ) =								
Dismantling ( $m_D$ )								
Part number	Name	Mass (kg)	Part number	Name	Mass (kg)	Mass (part 7 to x) (kg)		
1			4			$m_{Dx}^a$		
2			5					
3			6					
$m_{D1}$ total (sum 1 to 3) =			$m_{D2}$ total (sum 4 to 6) =			$m_D$ total ( $m_{D1} + m_{D2} + m_{Dx}$ ) =		
Metals separation ( $m_M$ )						Mass (kg)		
Remaining machine metallic content:						$m_M =$		
Non-metallic residue treatment ( $m_{Tr}$ and $m_{Te}$ )	Recyclable materials ( $m_{Tr}$ )							
	Technology number	Name	Mass (kg)					
	1		$m_{Tr1}$					
	2		$m_{Tr2}$					
	3 to x <sup>a</sup>		$m_{Tr3-x}$					
	$m_{Tr}$ total (sum $m_{Tr1}$ to $m_{Trx}$ ) =							
	Energy recoverable materials ( $m_{Te}$ )						Mass (kg)	
Remaining quantity of organic materials (polymers, elastomers, MONM, etc.):						$m_{Te} =$		
Recyclability rate		$R_{cyc} = \frac{m_P + m_D + m_M + m_{Tr}}{m_S} \times 100$				%		
Recoverability rate		$R_{cov} = \frac{m_P + m_D + m_M + m_{Tr} + m_{Te}}{m_S} \times 100$				%		
<sup>a</sup> Please add a separate list for additional parts or technologies.								