
**Road vehicles — Open interface for
embedded automotive applications —**

Part 1:

**General structure and terms, definitions
and abbreviated terms**

*Véhicules routiers — Interface ouverte pour applications automobiles
embarquées —*

Partie 1: Structure générale et termes, définitions et termes abrégés

STANDARDSISO.COM : Click to view the full PDF of ISO 17356-1:2005



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 17356-1:2005

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Terms, definitions and abbreviated terms	1
3 Structure of ISO 17356	17
Annex A (informative) History and rationale of OSEK/VDX	19
Bibliography	21

STANDARDSISO.COM : Click to view the full PDF of ISO 17356-1:2005

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 17356-1 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 3, *Electrical and electronic equipment*.

ISO 17356 consists of the following parts, under the general title *Road vehicles — Open interface for embedded automotive applications*:

- *Part 1: General structure and terms, definitions and abbreviated terms*
- *Part 2: OSEK/VDX specifications for binding OS, COM and NM*
- *Part 3: OSEK/VDX operating system (OS)*
- *Part 4: OSEK/VDX communication (COM)*
- *Part 5: OSEK/VDX network management (NM)*
- *Part 6: OSEK/VDX implementation language (OIL)*

Road vehicles — Open interface for embedded automotive applications —

Part 1: General structure and terms, definitions and abbreviated terms

1 Scope

This part of ISO 17356 outlines the general structure of, and defines terms and abbreviations used in relation to, the specification of the software open interface for embedded automotive applications given by the other parts of ISO 17356.

2 Terms, definitions and abbreviated terms

For the purposes of this document, the following terms, definitions and abbreviated terms apply.

2.1

acceptance filtering

mechanism which decides whether each received protocol frame is to be taken into account by the local node or ignored

2.2

activate

action of changing a task from the suspended to the ready state

NOTE The transition is achieved by a system service.

2.3

actual configuration

set of all operable nodes to which communication access is possible

NOTE See **operability of a node** (2.81).

2.4

address-related communication

type of communication between nodes using node addresses where each address-related communication message contains certain data and — either explicitly or implicitly — the node address of the transmitter and the receiver

NOTE 1 See **node addressing** (2.76).

NOTE 2 The communication of the network management is based completely on address-related communication.

2.5

alarm

association between a counter and a task, event or callback such that the task, event or callback occurs when a particular counter value is reached

NOTE 1 The expiry value can be defined relative to the current counter value or can be an absolute value.

NOTE 2 Alarms can be defined to be either single-shot or cyclic.

NOTE 3 An alarm is statically assigned at system generation time to one counter and a task, event or alarm callback routine.

**2.6
alarm callback**

short function, provided by the application, called when an alarm expires but before any task is activated or event set

**2.7
alarm management**

manipulation of an alarm's running/cancelled state, and the counter value at which it next expires

NOTE Alarm management is based on the counter concept. Alarms are a way of linking alarm callbacks, task activation or event setting to counter values.

**2.8
alive message**

message used to announce an initialized and operable node for integration in the actual configuration

NOTE 1 See **operability of a node** (2.81).

NOTE 2 A dedicated NM message is used for this purpose.

**2.9
application program interface
API**

description of the application's interface to the operating system, communications and network management functions

**2.10
application error**

error where the operating system cannot execute the requested service correctly, but assumes the correctness of its internal data, and calls centralized error treatment

**2.11
arbitration**

mechanism that guarantees that a simultaneous access made by multiple stations results in contention where one frame will survive uncorrupted

**2.12
basic conformance class
BCC**

conformance class of the operating system in which only basic tasks are permitted

NOTE Two basic conformance classes are distinguished: BCC1 and BCC2.

**2.13
basic task
BT**

task that can only release the processor when it terminates, when the operating system executes a higher-priority task or when an interrupt occurs

NOTE 1 A basic task can only enter the task states suspended, ready and running.

NOTE 2 It is not possible for a basic task to wait for an event.

**2.14
broadcast**

case of multicast whereby a single message is addressed to all nodes simultaneously

**2.15
busOff**

condition of switching off from the bus so that protocol frames can neither be sent nor received

2.16 callout

general mechanism, based upon function calls, allowing the behaviour of the interaction layer to be customized and enhanced

NOTE 1 Callouts are configured statically, are invoked in response to the passage of a message or I-PDU and cannot be changed at run-time.

NOTE 2 The prototype for a callout allows it to return a value that determines further treatment by the IL of the message or I-PDU.

2.17 controller area network CAN

protocol originally defined for use as a communication network for control application in vehicles

2.18 certification

process of determining whether an implementation is consistent with a given reference model

NOTE The scope of the reference model has to be settled according to the objectives of the project and all constraints necessary to fulfil those objectives incorporated in the reference model.

2.19 COM-callback

short function, provided by the application, which can be called by the interaction layer as a notification mechanism (class 1)

NOTE No parameters are passed to a COM-callback routine and it does not have a return value. A COM-callback routine runs either on interrupt level or on task level.

2.20 communication layer

set of all entities and elements which constitute a communication layer based on the ISO/OSI reference model

NOTE For the basic model, see ISO 7498-1.

2.21 configurability

ability to set the parameters of a system in terms of static values

EXAMPLE Number of tasks, RAM size for stack, size of message buffer.

2.22 confirmation

service primitive via which a service provider informs a service user about the result of a preceding service request

NOTE The confirmation service primitive is defined by the ISO/OSI reference model (ISO 7498).

2.23 conformance class CC

subset of services chosen by the application

NOTE 1 In each module (operating system, communication, network management), a pool of services is provided, with each of these being divided into a number of defined subsets. Applications can choose to use a particular subset of the services in order to reduce demands on the CPU and memory.

NOTE 2 The subsets are upwardly compatible and are described as conformance classes.

2.24
connection

logical communication channel between a transmitter and a receiver

NOTE A message is sent by exactly one transmitter and is received by exactly one receiver.

2.25
constructional element

definition and declaration services for system objects

2.26
counter

system object that registers recurring events such as time or angle

NOTE A counter is represented by a count and some counter-specific constants.

2.27
critical section

sequence of instructions where mutual exclusion is ensured

NOTE Such a section is called "critical" because shared data is modified within it.

2.28
data consistency

content of a given message correlating unambiguously to the operation performed on the message by the application such that no unforeseen sequence of operations may alter the content and thereby render it inconsistent with respect to its allowed and expected value

2.29
data link layer

communication layer, consisting of the communication hardware and the communication driver software, that provides services for the transfer of I-PDUs

2.30
deadlock

tasks that block one another so that further processing of the tasks concerned is no longer possible

EXAMPLE Each of two tasks waits for the reception of a message to be sent by the other task before sending its own message.

2.31
direct node monitoring

active monitoring of a node by another node in the network

NOTE For this purpose, the monitored node sends an NM message according to a dedicated and uniform algorithm. For the network-wide synchronization of NM messages, a logical ring is used.

2.32
deadline monitoring

informing of the application via the notification mechanism that a message has not been received from another node within a specified interval, or if a request to send an I-PDU has not been completed by the DLL within a specified interval

2.33
error handling

error service provided to handle errors detected by the operating system

NOTE The basic framework is predefined and has to be completed by the user, thus giving the user a choice of efficient centralized or decentralized error handling.

2.34**error hook**

routine (ErrorHook) called when a system service returns a StatusType value not equal to E_OK or when an error is detected during task activation or event setting

2.35**event**

method of task synchronization peculiar to extended task whereby a task may suspend its execution without terminating

NOTE The task suspends its execution by waiting for an event and continues when an appropriate event is set. Basic tasks cannot use events.

2.36**event mechanism**

means of task synchronization using events

2.37**extended conformance class****ECC**

conformance class of the operating system in which basic and extended tasks are permitted

NOTE Two extended conformance classes are distinguished: ECC1 and ECC2.

2.38**extended task****ET**

task that is allowed to use additional operating system services, which may result in a waiting state

NOTE An extended task can enter the task state *suspended*, *ready*, *running* or *waiting*.

2.39**fatal error**

error where the operating system can no longer assume correctness of its internal data

NOTE In this case, the operating system calls the centralized system shutdown.

2.40**frame**

data unit determined according to the data link protocol specifying the arrangement and meaning of bits or bit fields in the data transferred across the transfer medium

2.41**full pre-emptive scheduling**

scheduling where a task which is presently running may be pre-empted at any instruction by the occurrence of a trigger condition pre-set by the operating system that puts the running task into the ready state as soon as a higher-priority task becomes ready

NOTE The pre-emptee's context is saved so that it can be continued at the location where it was pre-empted.

2.42**group addressing**

addressing of several receiver nodes, implemented using multicast connections, in a single address-related NM message

NOTE See **address-related communication** (2.4).

2.43

hook routine

user-defined function which will be called by the operating system only under certain circumstances and in a defined context

NOTE Hook routines may be used for tracing or application-dependent debugging purposes, user-defined extensions to context switches and in error handling. Most operating system services are not allowed in hook routines.

2.44

indication

service primitive where a service provider informs a service user about the occurrence of either an internal event or a service request issued by another service user

NOTE The indication service primitive is defined by the ISO/OSI reference model (ISO 7498).

2.45

indirect node monitoring

monitoring of a node by "listening" to dedicated application communication messages

NOTE Indirect node monitoring is based on monitored state messages which are sent periodically.

2.46

interaction layer

communication layer that implements the interface between the application and other potential communication layers such as the DLL and network layers

NOTE 1 The communication services of the interaction layer are independent of both microcontroller and network protocol.

NOTE 2 The interaction layer enables internal and network-wide communication by means of UnQueued messages and Queued messages.

2.47

internal communication

exchange of messages between tasks belonging to the same node

2.48

internal resource

resource which is not visible to the user and therefore cannot be addressed by the system functions GetResource and ReleaseResource

NOTE Internal resources are managed strictly internally within a clearly defined set of system functions.

2.49

interrupt

enforced suspension of the execution of the current program section

2.50

interrupt latency

time between the moment an interrupt occurs and the execution of the first instruction of the interrupt service routine

2.51

interrupt level

priority level provided by the CPU for ISRs

NOTE To keep the interrupt latency as short as possible, it is preferable that only absolutely indispensable actions be performed at interrupt level.

2.52**interrupt service routine**

function that provides the main processing of an interrupt

2.53**intertask communication**

mode of information interchange between tasks

NOTE In the course of intertask communication, messages are logically copied from the local area of a task (transmitter) to the local area of another task (receiver).

2.53**I-PDU**

collection of messages for simultaneous transfer between nodes in a network

NOTE At the sending node, the interaction layer (IL) is responsible for packing messages into an I-PDU and then sending it to the underlying layer (transport layer or DLL) for transmission; at the receiving node, the DLL (or transport layer) rebuilds the I-PDU and passes it to the IL, which then unpacks the messages.

2.54**ISR category**

trade-off between ISR response time and API complexity

NOTE Interrupt processing is subdivided into two categories of ISRs: Category 1 comprises all ISRs which do not use operating system services and are, therefore, typically faster for entry and exit than category 2 ISRs. Category 1 ISRs are only allowed to use a very restricted set of operating system services, whereas category 2 ISRs are allowed to use a less restricted set but are typically inherently slower.

2.55**latency time**

time delay between the request of an activity and its execution

2.56**limp home**

operating mode in NM which is entered in case of an error which cannot be corrected

2.57**limp home configuration**

set of all nodes which cannot participate in direct node monitoring due to failure

2.58**limp home message**

dedicated NM message used for notifying a node that the system has entered the limp home state

2.59**logical ring**

structure imposed by software rather than physical arrangement that orders the nodes within a network such that every node has exactly one successor and one predecessor and a pathway exists from any node to any other node

NOTE 1 The nodes are arranged in terms of a ring. The logical ring is used for the network-wide synchronization of NM messages. In a logical ring, the communication sequence is defined independently of the network structure; therefore, each node is assigned a logical successor — the first logical node is the successor of the last logical node in the ring.

NOTE 2 A ring message is always sent from a node to its logical successor.

2.60**message**

fundamental unit of data transfer between an application and a COM's IL and, therefore, also of intra- and inter-ECU communications

NOTE A message can be 0 or more bits long and could contain some application-specific data ranging from a bit to a large array or structure. Therefore, messages can support event and signal-based communication as well as more complex interfaces.

2.61

mixed pre-emptive scheduling

scheduling policy which enables the use of both full-pre-emptive and non-pre-emptive scheduling policies for the execution of different tasks on the same system

NOTE The distinction is made via a task attribute (pre-emptable/non-pre-emptable).

2.62

multiple task requesting

property of a task that allows it to have more than one activation outstanding

NOTE 1 See **activate** (2.2).

NOTE 2 The operating system receives and records activation. On terminating the task (see *terminate*), the operating system checks whether any activation are outstanding. If there are any, the task immediately re-enters the running state.

2.63

mutual exclusion

prevention by one task of one or more other tasks running for a specified section of code

2.64

one-to-N connection

1:N connection

logical communication channel between a transmitter and N receivers

NOTE A message is sent by exactly one transmitter and is received by N receivers.

2.65

network configuration

set of nodes in the network

NOTE Within network management (NM), two configurations are distinguished: actual configuration and limp home configuration.

2.66

network management

NM

ensuring of the safety and availability of a communications network of autonomous control units

EXAMPLE 1 Initialization of the node and network-related (global) activities.

EXAMPLE 2 Co-ordination of global NM operating modes.

NOTE NM distinguishes between node-related (local) and network-related (global) activities.

2.67

NMBus-sleep

non-participation in NM communication

NOTE This is an NM operating mode. A request for this mode request must be confirmed by all nodes in the network.

2.68

NM callback

short function provided by the application which can be called by the interaction layer as a notification mechanism (class 1) so that NM can be informed of the network's state

NOTE 1 A parameter can be passed to an NM-callback routine and does not have a return value.

NOTE 2 An NM-callback routine runs either on interrupt level or on task level.

2.69**NM infrastructure**

order structures and addressing mechanisms (window) which are accessed by the network management, including a communication infrastructure for the exchange of NM messages, so that each node is able to communicate with any other node on the network in a straightforward fashion

EXAMPLE Logical ring.

2.70**NMLimpHome**

NM operating mode which is entered in case of an error which cannot be remedied

2.71**NM message**

NMPDU exchanged between NM entities

NOTE The NM distinguishes between regular ring messages, alive messages and limp home messages.

2.72**NM operating mode****NM mode**

specific behaviour of the NM

NOTE 1 The NM can enter different local operating (e.g. Nmoff) and global operating (e.g. sleep) modes. The transition to a different global operating mode requires a network-wide coordination, i.e. the local NM for each node has to enter the same global mode. Local operating modes only affect the local NM of a node and are transparent for all the other nodes.

NOTE 2 Operating modes of the application are not managed by the NM.

2.73**NM protocol data unit****NMPDU**

NM message communicated between the sending and receiving NM entities containing an address field with source and destination address, a control field with an op-code and an optional data field with application-specific ring data

2.74**NMSleep mode**

NM operating mode where the node does not participate in NM communication

NOTE The NM distinguishes between a local sleep mode and a global sleep mode. In both cases, the transition into the sleep mode is notified network-wide. The difference between the two is that a local sleep mode request must not be confirmed by the other nodes in the network, whereas a global sleep mode request must be confirmed by all nodes in the network.

2.75**node**

network topological entity where one or more physical data links meet

NOTE Each node is separately addressable on the network.

2.76**node addressing**

method by which each node on a network is uniquely identified so that it can be referred to by other members of the network

NOTE 1 Addresses are used to transmit address-related NM messages from one node to another.

NOTE 2 Individual node addressing is implemented using 1:1 connections. Several nodes can be addressed using group addressing.

2.77

non-pre-emptive scheduling

scheduling policy in which a task switch is only performed via one of a selection of explicitly defined system services (explicit rescheduling points)

2.78

non-pre-emptable task

task which can not be pre-empted by other tasks

NOTE 1 See **pre-empt** (2.86).

NOTE 2 Such a task only releases the processor at rescheduling points.

2.79

offline

state of the data link layer in which only NM communication is allowed

NOTE This implies that no application communication is possible.

2.80

online

normal state of the data link layer where both application and network management communication are possible

2.81

operability of a node

possibility of a node to participate in the NM's direct or indirect node monitoring

2.82

OSEKtime

operating system especially tailored to the needs of time-triggered architectures

2.83

OS processing level

processing level for the execution of operating system services

2.84

overrun

attempt to store data in memory beyond allocated capacity

EXAMPLE Exceeding the length of the queue in a queued message object.

2.85

PostTaskHook

system hook routine called upon leaving a task either due to pre-emption by another task or by termination

2.86

pre-empt

change in a task from running to ready state, imposed by the scheduler when it decides to switch to another task

NOTE In the case of a non-pre-emptive scheduling policy, pre-emption only occurs at explicit rescheduling points.

2.87

pre-emptable task

task which can be pre-empted by any task of higher priority

NOTE See **pre-empt** (2.86).

2.88**PreTaskHook**

system hook routine called before entering or returning to a task

2.89**priority ceiling protocol**

mechanism used to prevent deadlocks and priority inversion within the framework of resource management

2.90**protocol**

formal set of conventions or rules governing the exchange of information between protocol entities comprising syntax and semantics of the protocol messages as well as the instructions on how to react to them

2.91**protocol entity**

task or procedure for handling a protocol

2.92**queue**

data storage area organized so that more than one datum can be inserted and data are removed in their order of insertion

2.93**queued message**

message that appears in a queue

2.94**ready**

state of being prepared to meet all functional prerequisites for a transition into the running state, waiting for allocation of the processor

NOTE The scheduler decides which ready task is executed next, the state is reached via the state transitions activate, release and pre-empt, and is exited by start.

2.95**re-entrant**

function that can be called again during an interruption of its execution where both calls are executed correctly

2.96**rescheduling point**

operating system calls which cause the activation of the scheduler

EXAMPLE Explicit call of the scheduler, successful termination of a task.

NOTE This exists in full-pre-emptive, mixed pre-emptive system and non-pre-emptive system.

2.97**regular ring message**

normal NM message, containing network status information, that is also used to indicate a station logoff or local sleep mode, or to request for global sleep mode

NOTE See **NMSleep mode** (2.74).

2.98**release**

change of a task from waiting to ready state caused by at least one event occurring for which the task has previously been waiting

2.99
reply message

dedicated NM message for replying to the reception of a request message

NOTE The reply message can be used by a slave of a logical star.

2.100
request

service primitive where a service user requests a service from a service provider

NOTE The service primitive is defined by the ISO/OSI reference model (ISO 7498).

2.101
request message

dedicated NM message for requesting the transmission of a reply message

NOTE This can be used by the master of a logical star.

2.102
resource

operating system providing abstraction to support task and ISR coordination by mutual exclusion in critical sections

NOTE 1 A task or ISR that locks a resource cannot be pre-empted or interrupted by any other task or ISR that is also declared as one that might also lock that resource.

NOTE 2 The assignment of resources to tasks and ISRs is performed at system generation time and cannot be changed by the application.

2.103
resource management

manipulation at run-time of resources either implicitly (in the case of internal resources) or via the get-and-release calls

2.104
response

service primitive used by a service user in order to reply to a preceding indication from service provider

NOTE The service primitive is defined by the ISO/OSI reference model (ISO 7498).

2.105
ring data

data sent, using an NMPDU's data field, and received by the application, with guaranteed data consistency

2.106
ring message

normal NM message containing the network status information and also used to indicate a node's local sleep mode or to request global sleep mode

NOTE See **NMSleep mode** (2.74).

2.107
running

task state assigned to the CPU so that its instructions can be executed

NOTE Only one task can be in the running state at any point in time. The state is entered by the state transition start and can be exited via the state transition wait, pre-empt or terminate.

2.108**scalability**

setting of the scope of capabilities of a system as determined by its functionality

NOTE See **conformance class** (2.23)

2.109**scheduler**

OS sub-system that decides whether a task switch should be put into the running state according to the selected scheduling policy

NOTE The scheduler can be considered to occupy a resource which can also be occupied by any task. Thus a task can block the scheduler to achieve arbitrary periods where it is the only task that can run.

2.110**scheduling policy**

policy used by the scheduler to determine whether a task may or may not be pre-empted by another task

NOTE Three scheduling policies are distinguished: non-pre-emptive, full-pre-emptive and mixed-pre-emptive scheduling.

2.111**segmented communication****segmented data transfer**

transfer of application data that cannot fit into a single protocol frame by the transmitter disassembling the data into segments that are small enough to fit into protocol frames, sending the segments and then the receiver reassembling the data

NOTE See **I-PDU** (2.53)

2.112**semaphore**

means for the synchronization of access to shared data

NOTE See **resource management** (2.103)

2.113**severe error**

error where the operating system could not achieve the requested service, but assumes the correctness of its internal data and calls centralized error treatment

NOTE Additionally, the operating system returns the error by the status information for decentralized error handling.

2.114**start**

change of a task from ready to running state, thereby causing the task to be executed

2.115**startupHook**

system hook routine called after the operating system start-up and before the scheduler is running

2.116**suspended**

task state of being passive and not occupying any dynamic OS or memory resources

NOTE 1 A task in this state is on before it is entered, or can reach it via the status transition terminate.

NOTE 2 To exit the state, the task is activated.

2.117

system generation service

definition and directive which is necessary to set-up module at compile time

2.118

ShutdownHook

system hook routine called when a system shutdown is requested by the application or by the operating system

2.119

task

entity consisting of code and management information controlled by the scheduler

NOTE 1 The applications running on the ECU are composed of tasks and ISRs. Tasks can be executed concurrently with other tasks under the control of the scheduler according to the task priority assigned to it and the selected scheduling policy.

NOTE 2 From a programmer's point-of-view, a task is a C-like function.

NOTE 3 A distinction is made between basic tasks and extended tasks.

2.120

task level

processor's processing priority where most application software is executed

NOTE 1 Some application software is also executed in ISRs.

NOTE 2 Tasks are executed according to the priority assigned to them and the selected scheduling policy.

NOTE 3 Other processing levels are interrupt level and operating system level.

2.121

task management

manipulation of a task's state

NOTE Task management is achieved by activation [see **activate** (2.2)] and termination [see **terminate** (2.126)] of tasks, as well as by use of the scheduler.

2.122

task priority

measure of the precedence with which the task is to be executed

NOTE 1 Initial priorities are defined statically. However, as the application runs, tasks can change their priority [see **priority ceiling protocol** (2.89)].

NOTE 2 Depending upon the CC, more than one task may be declared at the same priority within a system.

NOTE 3 Tasks of equal priority are started according to the order in which they are activated.

2.123

task state

condition distinguishing a task by which it is either running, ready, waiting or suspended

NOTE 1 See **running** (2.107), **ready** (2.94), **waiting** (2.133) and **suspended** (2.116).

NOTE 2 Basic tasks cannot change to the state waiting.

NOTE 3 A task can only be in one state at any one time.

2.124**task switching time**

time between the occurrence of the “task switch event” up to the execution of the first instruction of the “new” task

2.125**task switching mechanism**

mechanism, managed by the scheduler, that performs a context switch to a selected task

2.126**terminate**

change of a task from running to suspended state

NOTE 1 The running task causes its transition into the suspended state by means of a system service.

NOTE 2 A task can only terminate itself.

2.127**unacknowledged communication****unacknowledged data transfer**

status under which the transmitter receives no data from the receiver confirming that the message has been received

2.128**unidirectional communication**

data transfer mode characterized by data being exchanged in one direction only

2.129**unqueued message**

message that is overwritten upon arrival of a new message, and where the application's read operation is non-destructive, thereby allowing the same message data to be read more than once

2.130**unsegmented communication****unsegmented data transfer**

transfer of data that fits within a single bus frame

2.131**validation**

ensuring of the correctness of a specification

2.132**wait**

change of a task from running to waiting state, thereby causing the running task temporarily to suspend execution but without the loss of its context

2.133**waiting**

task state in which the task is unable to continue execution owing to its awaiting at least one event

NOTE 1 Lower priority tasks can run while the task waits for an event to permit it to continue operation.

NOTE 2 Only extended tasks can enter the waiting state.

NOTE 3 Event reception causes the task to be released and therefore to make the transition into the ready state.

2.134**warning**

return value that is not E_OK and is not equivalent to an error, giving complementary information related to a system service execution

API	application program interface
BCC	basic conformance class
BNF	Backus-Naur form
BT	basic task
CAN	controller area network
CC	conformance class
CCC	communication conformance class
COM	communication
CPU	central processing unit
DLL	data link layer
ECC	extended conformance class
ECU	electronic control unit
EPROM	erasable programmable read only memory
ET	extended task
FIFO	first in first out
IL	interaction layer
ISR	interrupt service routine
LIFO	last in first out
MSB	most significant bit
NM	network management
NMPDU	NM protocol data unit
OIL	OSEK implementation language
OS	operating system
OSEK	abbreviation of the German <i>Offene Systeme und deren Schnittstellen für die Elektronik im Kraftfahrzeug</i> — “open system and its corresponding interfaces for automotive electronics”
UML	unified modelling language
UUDT	unacknowledged unsegmented data transfer
VDX	vehicle distributed executive