



**International
Standard**

ISO 17419

**Intelligent transport systems —
Cooperative systems — Globally
unique identification**

**AMENDMENT 1: Regions of a closed
polygon in a plane**

*Systèmes intelligents de transport — Systèmes coopératifs —
Identification unique au niveau global*

AMENDEMENT 1: Régions d'un polygone fermé dans un plan

**First edition
2018-05**

**AMENDMENT 1
2024-01**

STANDARDSISO.COM : Click to view the full PDF of ISO 17419:2018/Amd 1:2024



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 204, *Intelligent transport systems*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 278, *Intelligent transport systems*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

STANDARDSISO.COM : Click to view the full PDF of ISO 17419:2018/Amd 1:2024

Intelligent transport systems — Cooperative systems — Globally unique identification

AMENDMENT 1: Regions of a closed polygon in a plane

6.9.4

Insert after the bullet list the following paragraph:

The definition of regions, i.e. areas, associated with a closed polygon, shall be as specified in Annex C.

Annex C

Add the following annex after Annex B, before the Bibliography:

STANDARDSISO.COM : Click to view the full PDF of ISO 17419:2018/Amd 1:2024

Annex C (normative)

Closed polygons and their associated regions

C.1 Closed polygon in a two-dimensional Euclidean space

A closed polygon in a two-dimensional Euclidean (or flat) space is an object consisting of an ordered set of $N > 2$ straight line segments, referred to as edges E_i , ($i = 1, \dots, N$), or sides, connected such that no two segments intersect (or cross), and such that the first and last edges in the set share an end-point. An end-point of an edge is referred to as vertex.

Assuming that associated with the two-dimensional (2-D) space is a two-dimensional or three-dimensional coordinate system for expressing points in that 2-D space, an equivalent description is as an ordered set of N coordinate points, P_i , ($i = 0, \dots, N-1$), referred to as vertices, with edges having adjacent vertices as end-points, noting that the first and last vertices are considered as being adjacent.

As closed polygons divide the 2-D space (which in general is infinite) into two non-intersecting subspaces, means for uniquely identifying and labelling the two subspaces (also referred to as two regions or two areas) are necessary. To accomplish this, directed edges are defined such that each edge, E_i , has a "tail", the $(i-1)$ th vertex P_{i-1} in the ordered list, and a "head", the i th vertex P_i for $i = 1, \dots, N-1$, with the N th directed edge having its tail as the vertex P_{i-1} and its head as the vertex P_0 as shown in Figures C.1 and C.2.

Furthermore, in order to be able to use the concepts of "right" and "left" to identify the regions (areas) and noting that a 2-D plane divides the 3-D space into two 3-D half-spaces, the particular half-space from which the 2-D plane is being viewed shall be specified. Since most regions relevant to ITS are relative to the surface of the Earth, it is convenient to think of the 2-D space as being (nearly) parallel to that surface and viewing the polygon in that space from "above", i.e. from outside the Earth. That is the convention that shall be applicable herein.

NOTE 1 In future editions of this document, the content of this annex will potentially be expanded from 2-D Euclidean spaces (planes) with 2-D manifolds to 3-D objects such as ellipsoids or geoids, in which case the specification of which 3-D region is used as the viewpoint is straightforward since there is an obvious "inside" and "outside" of the object.

NOTE 2 In future editions of this document, the content of this annex will potentially provide for different edge definitions such as "constant-bearing", "constant-latitude/longitude", "geodesic", etc.

NOTE 3 For the purposes of calculating whether a given point in 3-D space is in the right or left region, the polygonal region is assumed to be planar and an orthonormal projection onto that plane is performed. If the specified vertices of the polygon do not all lie in a common plane such as can be the case for a large geographic region whose vertices are given in latitude, longitude and possibly altitude coordinates, the vertices need to be projected onto a common plane to ensure the polygonal region is planar.

C.2 Right and left regions of a closed polygon

Closed polygons as defined herein specify two regions: a "right region" ("R") and a "left region" ("L"). Standing at the tail of a directed edge and looking at the head of that same directed edge, the "right region" shall be to the right and the "left region" shall be to the left. All regions specified using closed polygons shall be the "right regions" thereof.

For example, an ITS regulatory region as described in 6.9.4 is specified by the "right region" of a closed polygon. The order of the vertices of that closed polygon determine whether the "right region" is the interior or the exterior of the closed polygon as shown in Figures C.1 and C.2. By reversing the ordering of the vertices (equivalently the direction of the edges), the interior of the closed polygon changes from being a

"right region" ("R") to being a "left region" ("L"), and consequently the ITS regulatory region changes from being the interior to being the exterior of the closed polygon.




Figure C.1 — Right ("R") and left ("L") regions of a closed polygon — Example 1




Figure C.2 — Right ("R") and left ("L") regions of a closed polygon — Example 2

C.3 Area specified by GeoPolygon

The area defined by the ASN.1 type `GeoPolygon` specified in A.3 shall be the "right region" of the closed polygon defined by the vertices P_0, P_1, \dots, P_{N-1} contained in `GeoPolygon` with P_0 being the first entry in `GeoPolygon` and the other vertices, P_i , following in ascending order up to P_{N-1} .

Typically, the example of Figure C.1 applies, as in this example the "right region" is a finite size area, being the interior of the closed polygon, whilst in the example of Figure C.2 the "right region" is an infinite area, being the exterior of a closed polygon in an infinite 2-D plane.

C.4 Specification of closed polygons on curved surfaces

Specification of closed polygons on curved surfaces such as the Earth are out of scope of this document.

STANDARDSISO.COM : Click to view the full PDF of ISO 17419:2018/Amd 1:2024