

# INTERNATIONAL STANDARD

**ISO**  
**1797-1**

First edition  
1992-02-15

**AMENDMENT 1**  
1997-12-15

---

---

## Dental rotary instruments — Shanks —

### Part 1: Shanks made of metals

#### AMENDMENT 1

*Instruments rotatifs dentaires — Queues —*

*Partie 1:  
Queues en matériaux métalliques*

*AMENDEMENT 1*



Reference number  
ISO 1797-1:1992/Amd.1:1997(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Amendment 1 to International Standard ISO 1797:1992 was prepared by Technical Committee ISO/TC 106, *Dentistry*, Subcommittee SC 4, *Dental instruments*.

© ISO 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization  
Case postale 56 • CH-1211 Genève 20 • Switzerland  
Internet central@iso.ch  
X.400 c=ch; a=400net; p=iso; o=isocs; s=central

Printed in Switzerland

# Dental rotary instruments — Shanks —

## Part 1: Shanks made of metals

### AMENDMENT 1

Page 4

After subclause 5.4 add the following subclause 5.5.

#### 5.5 Marking

Marking, if envisaged, should be outside the fitting length  $l_1$ .

If the marking is applied within the fitting length  $l_1$ , the outside diameter of the marking shall not exceed the effective diameter of the shank.

Marking shall be resistant to disinfection, cleaning and sterilization according to the manufacturer's instructions.