
**Building construction machinery and
equipment — Pedestrian-controlled
vibratory plates — Terminology and
commercial specifications**

*Machines et matériels pour la construction des bâtiments — Plaques
vibrantes guidées à la main — Terminologie et spécifications
commerciales*

STANDARDSISO.COM : Click to view the full PDF of ISO 19433:2008



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 19433:2008



COPYRIGHT PROTECTED DOCUMENT

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 19433 was prepared by Technical Committee ISO/TC 195, *Building construction machinery and equipment*.

STANDARDSISO.COM : Click to view the full PDF of ISO 19433:2008

Introduction

The purpose of this International Standard is to define the main terms and commercial specifications for pedestrian-controlled vibratory plates used for material (soil and asphalt) compaction. These machines are typically used in the building trades to improve material density characteristics.

STANDARDSISO.COM : Click to view the full PDF of ISO 19433:2008

Building construction machinery and equipment — Pedestrian-controlled vibratory plates — Terminology and commercial specifications

1 Scope

This International Standard provides a terminology and sets out the commercial specifications for pedestrian-controlled vibratory plates used in building construction. It is applicable to both forward- and reversible-type plates. These plate compactors are intended for the mechanical compaction of all disturbed soil, sand or aggregates used for load-bearing purposes — whether in new construction or repairs.

2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

2.1

pedestrian-controlled vibratory plate

direct- or remote-controlled machine designed for the purpose of improving material density and stiffness

NOTE The machine compacts material through vibration and impact force generated by the vibrator shaft to the base plate and transmitted to the material.

2.1.1

forward-type vibratory plate

machine designed to move in only one direction, forward

See Figure 1 a).

2.1.2

reversible-type vibratory plate

machine designed to move in two directions, both forward (away from the operator) and reverse (towards the operator)

See Figure 1 b).

2.2

prime mover

driving energy source for vibrator mechanism

2.3

transmission

system of components that translates the prime mover energy to the vibrator mechanism


2.4

base plate

machine element that locates the vibrator mechanism and comes in contact with the material being compacted

See Figure 1.


- 2.5**
vibrator shaft
shaft with an eccentric mass that generates vibration when rotated
- 2.6**
vibrator mechanism
system of components, utilizing the vibrator shaft, affixed to the base plate
- 2.7**
vibration frequency
number of vibrator cycles per second
- 2.8**
eccentric radius
distance, offset from the radius of rotation, at which the eccentric mass is considered concentrated
- 2.9**
eccentric mass
vibrator shaft element whose mass is radially offset from the shaft centre line
- 2.10**
eccentric moment
static moment
product of the eccentric mass and the eccentric radius
- 2.11**
centrifugal force
calculated value which considers the vibrator shaft eccentric moment and vibrator shaft frequency
- NOTE This value can be calculated using the equation given in Annex A.
- 2.12**
operating mass
machine mass with equipment, attachments and all fluid systems (i.e. hydraulic oil, engine oil, lubrication oil, transmission oil) at the levels specified by the manufacturer, and — when applicable — with the fuel and water tanks half-full
- 2.13**
shipping mass
machine mass as configured for shipping
- 2.14**
water system
container and delivery system used to lubricate the base plate for asphalt applications
- 2.15**
maximum travel speed
maximum horizontal distance the vibratory plate travels over material being compacted in a given unit of time, measured in both forward and reverse directions



Key


- 1 prime mover
- 2 transmission
- 3 vibrator mechanism
- 4 base plate
- 5 dampers
- 6 guide handle
- 7 operator control assembly
- 8 expanders
- 9 water system

Figure 1 — Structure of pedestrian-controlled vibratory plates



- a Position of eccentric mass for forward movement.
- b Position of eccentric mass for reverse movement.
- c Position of eccentric mass for in-place vibration.

Figure 2 — Double vibrator's eccentric mass positions for vibratory plate directional control



Key

- H_1 overall height in operating position
- H_2 overall height
- L_1 overall length with handle in operating position
- L_2 base plate length
- W_1 overall width
- W_2 base plate width

Figure 3 — Machine dimensions

STANDARDSISO.COM : Click to view the full PDF of ISO 19433:2008

3 Commercial specifications

3.1 General

The following general data shall be presented:

- a) model and type;
- b) manufacturer;
- c) serial number;
- d) prime mover type (internal combustion engine, electric, pneumatic);
- e) operating mass kg;
- f) base plate size ($W_2 \times L_2$) mm (see Figure 3);
- g) centrifugal force kN;
- h) vibration frequency Hz;
- i) maximum travel speed:
 - forward m/min;
 - reverse m/min;
- j) overall dimensions in operating mode (see Figure 3):
 - length, L_1 mm;
 - width, W_1 mm;
 - height, H_1 mm.

3.2 Prime mover

3.2.1 For internal combustion engine

The following combustion engine data shall be presented:

- a) internal combustion engine type:
 - with spark ignition or
 - compression ignition;
- b) model;
- c) manufacturer;

- d) swept capacity cm^3 ;
- e) operating revolutions min^{-1} ;
- f) engine net power kW (according to the standard specified by manufacturer);
- g) fuel type;
- h) fuel tank capacity l.

3.2.2 For electric motor

The following electric motor data shall be presented:

- a) model and type;
- b) rated current A;
- c) voltage, phase, and frequency V/phase/Hz;
- d) maximum operating revolutions min^{-1} .

3.2.3 For pneumatic drive

The following pneumatic drive data shall be presented:

- a) maximum supply pressure MPa;
- b) air consumption rate m^3/h ;
- c) cycle rate at stated pressure and flow Hz.

3.3 Other data

The following other data shall be presented (if applicable):

- a) water tank (if any) capacity l;
- b) mass of the machine equipped with expanders as an optional attachment kg;
- c) shipping mass kg.

STANDARDSISO.COM : Click to view the full PDF of ISO 19433:2008

Annex A (informative)

Example of centrifugal force calculation — Single-shaft vibratory plate

The centrifugal force can be calculated from the formula:

$$F = \frac{m \cdot r \cdot \pi^2 \cdot n^2}{900\,000} = \frac{m \cdot r \cdot \pi^2 \cdot f^2}{250}$$

where

- F is the centrifugal force, in kilonewtons;
- m is the eccentric (unbalanced) mass, in kilograms;
- r is the eccentric radius, in metres;
- n is the shaft rotation, in min^{-1} or revolutions per minute;
- f is the vibration frequency, in hertz.

STANDARDSISO.COM : Click to view the full PDF of ISO 19433:2008