



**International
Standard**

ISO 20346

**Personal protective equipment —
Protective footwear**

AMENDMENT 1

*Équipement de protection individuelle — Chaussures de
protection*

AMENDEMENT 1

**Third edition
2021-12**

**AMENDMENT 1
2024-01**

STANDARDSISO.COM : Click to view the full PDF of ISO 20346:2021/Amd 1:2024

STANDARDSISO.COM : Click to view the full PDF of ISO 20346:2021/Amd 1:2024



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 94, *Personal Safety — Personal protective equipment*, Subcommittee SC 3, *Foot protection*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 161, *Foot and leg protectors*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

STANDARDSISO.COM : Click to view the full PDF of ISO 20346:2021/Amd 1:2024

Personal protective equipment — Protective footwear

AMENDMENT 1

Clause 2 Normative references

Update the reference “ISO 20344:2021” with “ISO 20344:2021+Amd.1:2024” and update the references throughout the document accordingly.

Change the title of EN 13832-3:2018 to read as follows:

“Footwear protecting against chemicals — Part 3: Requirements for prolonged contact with chemicals”

5.1, Table 2

In the section “Upper”, add an “X” in the last two cells of the row “Tear strength” to read as follows:

Tear strength	5.4.3	X		X	X
---------------	-------	---	--	---	---

In the section “Upper”, add an “X” in the last two cells of the row “Water vapour permeability and coefficient”, to read as follows:

Water vapour permeability and coefficient	5.4.6	X		X	X
---	-------	---	--	---	---

5.3.2.5

Replace the subclause with the following:

“When non-metallic toecaps are tested according to ISO 20344:2021+Amd.1:2024, 5.6.2 at an impact energy of (100 ± 2) J, the clearance under the toecap, at the moment of impact, shall not be less than the appropriate value given in ISO 22568-2:2019, Table 3. In addition, the non-metallic toecap shall not develop sharp edges or any cracks passing through the material (i.e. through which light can be seen). During the assessment of the non-metallic toecap designed with perforations the criteria whether light can be seen shall not be applied to the perforation.”

5.3.2.6, 2nd sentence

Delete the words “delamination or” to read as follows:

“In addition, the toecap shall not develop any cracks, which go through the material, i.e. through which light can be seen.”

5.3.2.7, 2nd sentence

Delete the words “delamination or” to read as follows:

“In addition, the toecap shall not develop any cracks, which go through the material, i.e. through which light can be seen.”

5.3.3

Replace the subclause with the following:

“When tested in accordance with ISO 20344:2021+Amd.1:2024, 5.7 there shall be no leakage of air. For design A of class II footwear, this requirement is not applicable.”

5.3.6, 3rd paragraph

Replace the paragraph with the following:

“For each leather part tested in accordance with ISO 20344:2021+Amd.1:2024, 6.11, the chromium VI content shall be less than 3,0 mg/kg.”

5.4.1.1, 2nd sentence

Add the wording “, except for water vapour permeability and water vapour coefficient (see 5.4.6).” to the end of the sentence, to read as follows:

“Any materials in the upper below the height defined in Table 8 shall meet the requirements of the upper (see Table 2), except for water vapour permeability (WVP) and water vapour coefficient (WVC) (see 5.4.6).”

5.4.1.2

Replace the text above Figure 6 with the following:

“Hybrid footwear (3.19) consists of two classes of materials: foot section, Area A, class II material and extended section, area B, class I material.

The Area A, shall be measured as H, between the lowest point of the top of the visible polymer (or rubber) part and the ground (see Figure 6) and shall have a minimum height corresponding to the values given in Table 8 for design B. All material extensions above belong to area B.

All materials shall meet the requirements of the upper depending on the class of material (see Table 2).”

5.4.6

Replace the subclause with the following:

“Footwear shall comply with one of the following criteria's:

- a) If the upper contains an area of maximum 10 % of non-water vapour permeable material, measured according to ISO 20344:2021+Amd.1:2024, 6.2.3, all remaining materials shall fulfil a water vapour permeability of at least 0,8 mg/(cm²·h) and the water vapour coefficient shall be at least 15 mg/cm² when tested in accordance with ISO 20344:2021+Amd.1:2024, 6.6, 6.7 and 6.8

b) If the upper contains an area of maximum 50 % of non-water vapour permeable material, measured according to ISO 20344:2021+Amd.1:2024, 6.2.3, all remaining materials shall fulfil a water vapour permeability of at least 2,0 mg/(cm²·h)”

5.5.4, Title

Add the abbreviations “WVP” and “WVC” to the title of the subclause, to read as follows:

“Water vapour permeability (WVP) and coefficient (WVC)”

5.5.4, 2nd paragraph

Add the wording “and WVC” to the end of the paragraph, to read as follows:

“No test is required, when lining material is present only in the heel area (5.2.3). When there is no stiffener or the stiffener is perforated, the material shall comply also WVP and WVC.”

5.7.3, 2nd paragraph

Delete the word “membrane” in the sentence and add a 3rd paragraph, to read as follows:

“When the insole is covered by a lining, the test piece shall be taken from both, the lining and insole in combination.

The requirement is not applicable for the insoles, where a membrane construction fulfilling the requirement “WR” covers the insole.”

5.7.4.1

Add the following second paragraph:

“No abrasion test on the insole is required if the lining or a part of the lining completely covers the insole.”

5.8.5

Replace the subclause with the following:

“This requirement is not applicable for rigid outsoles (see ISO 20344:2021+Amd.1:2024, 8.5).

For outsoles tested in accordance with ISO 20344:2021+Amd.1:2024, 8.6,

— The cut growth shall be not greater than 4 mm after 30 000 flex cycles.

— Spontaneous cracks are acceptable, unless one of the following conditions occurs:

- deeper than 1,5 mm;
- longer than 4 mm;
- more than five in number;

For footwear with metallic insert, any damage of the insert shall not be taken into account

NOTE The flexing resistance of metallic inserts is assessed according to 6.2.1.4.1.”

5.8.7

Replace the subclause with the following:

“Tested in accordance with ISO 20344:2021+Amd.1:2024, 5.2, the bond strength between the various layers of multi-layer outsoles shall be not less than 4,0 N/mm. If there is tearing of the material, the measured strength shall not be less than 3,0 N/mm.”

6.1

In Table 16, replace the term “Scuff cap abrasion” by “Scuff cap”, to be in line with the changed title in 6.2.9.

6.2.1.1.3

Replace the subclause with the following:

“For footwear with non-metallic inserts (type PL) tested in accordance with ISO 20344:2021+Amd.1:2024, 5.10.4.2.2.:

- no perforation shall occur at any of the four measurements,
- no separation of the layers (tent effect ISO 22568-4:2021, 3.2) shall occur during all tests.”

6.2.1.1.4

Add the following sentence at the end of the paragraph:

“No separation of the layers shall occur during all tests.”

6.2.1.3

Add the following paragraph between paragraph 2 and 3:

“If the non-metallic perforation resistant insert is used as an insole (e.g., Strobel, cemented lasted) the above allowances are not applicable.”

6.2.1.3

Add the following paragraph at the end of the subclause:

“Non metallic perforation resistant inserts and insoles shall have no holes other than those created by stitching.”

6.2.7, last paragraph

Replace the paragraph with the following:

“Tested in accordance with ISO 20344:2021+Amd.1:2024, 5.22, the average value of the test results for outer ankle protection shall not exceed 10 kN and no single value shall exceed 15 kN. If inner ankle protection is claimed, it also shall meet these requirements.”

6.2.9, Title

Replace the title with the following:

“Scuff cap”

6.2.9

Add the following text as a first paragraph:

“During the testing of ergonomic features (see ISO 20344:2021+Amd.1:2024, 5.1), when worn by a wearer during kneeling, the scuff cap shall prevent the contact between the upper and a flat ground.”

Clause 7 b)

Delete “,i.e. ISO 20346:2021”, to read:

“b) reference to this document;”

Clause 7, last paragraph

Change the reference to EN 13832-3 to a dated reference EN 13832-3:2018”

8.2

Add the following subclause as a new 8.2.1 and renumber the following subclauses accordingly:

“8.2.1 General

This document does not cover electrically insulating footwear as covered by EN 50321-1:2018^[8].”

8.2.2

Replace the text of the subclause with the following:

“Additional information shall be given regarding antistatic properties:

“Antistatic footwear should be used if it is necessary to minimize electrostatic build-up by dissipating electrostatic charges, thus avoiding the risk of spark ignition of, for example, flammable substances and vapours, and if the risk of electric shock from mains voltage equipment cannot be completely eliminated from the workplace. Antistatic footwear introduces a resistance between the foot and ground but may not offer complete protection. Antistatic footwear is not suitable for work on live electrical installations.

The electrical resistance of antistatic footwear can be changed significantly by flexing, contamination, or moisture. This footwear might not perform its intended function if worn in wet conditions.

Class I footwear can absorb moisture and can become conductive if worn in moist and wet conditions. Class II footwear is resistant to moist and wet conditions and should be used if the risk of exposure exists.

If the footwear is worn in conditions where the soling material becomes contaminated, wearers should always check the antistatic properties of the footwear before entering a hazard area.