

INTERNATIONAL
STANDARD

ISO
20661

First edition
2020-01

**Ships and marine technology — Cutter
suction dredger supervisory and
control systems**

STANDARDSISO.COM : Click to view the full PDF of ISO 20661:2020



Reference number
ISO 20661:2020(E)

© ISO 2020

STANDARDSISO.COM : Click to view the full PDF of ISO 20661:2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms, definitions and abbreviated terms	1
3.1 Terms and definitions.....	1
3.2 Abbreviated terms.....	1
4 Components and structure	2
4.1 Components.....	2
4.2 Structure.....	2
5 General requirements	2
5.1 Operating position and control mode.....	2
5.1.1 Operating position.....	2
5.1.2 Control modes.....	2
5.2 External communication.....	2
5.3 Diagnostic.....	3
5.4 Visualization of the system information.....	3
5.5 HMI graphics.....	3
5.5.1 Alarm level.....	3
5.5.2 Conventions on graphic colours.....	4
5.5.3 Brightness of the HMI.....	4
5.6 Alarm.....	4
5.7 Calibration of system.....	4
6 Functional requirements	5
6.1 Preset/setup.....	5
6.2 Spuds and spud carrier system.....	5
6.3 Cutter system.....	5
6.4 Submersible dredge pump system.....	5
6.5 Inboard dredge pumps.....	6
6.6 Dredge valves.....	6
6.7 Ladder winches.....	6
6.8 Swing winches.....	6
6.9 Anchor hoisting winches and guy winches.....	7
6.10 Dredging profile monitor (DPM).....	7
6.11 Measurement sensor and meter.....	7

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 8, *Ships and marine technology*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document describes the supervisory and control system for a number of components, functions and systems that can, but do not have to, be installed on board of a cutter dredger. It does not prescribe that all described components, functions and systems need to be installed.

STANDARDSISO.COM : Click to view the full PDF of ISO 20661:2020

[STANDARDSISO.COM](https://standardsiso.com) : Click to view the full PDF of ISO 20661:2020

Ships and marine technology — Cutter suction dredger supervisory and control systems

1 Scope

This document specifies the components and structure, general requirements, and subsystem functional requirements, of cutter suction dredger supervisory and control systems.

It is applicable only to the installed components, functions or systems. It covers the design, manufacture and modifications.

2 Normative references

The following referenced documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8384, *Ships and marine technology — Dredgers — Vocabulary*

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purpose of this document, the terms and definitions given in ISO 8384 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1.1

cutter suction dredger supervisory and control system

CSD-SCS

system used for supervising and controlling the dredging operations performed by a cutter suction dredger

3.1.2

depth of cutter

distance from the water surface to the lower edge of the cutter head

3.2 Abbreviated terms

CCS	Cutter control system
CSD	Cutter suction dredger
CSD-SCS	Cutter suction dredger supervisory and control system

DPM	Dredging profile monitor
HMI	Human machine interface
SCADA	Supervisory control and data acquisition

4 Components and structure

4.1 Components

The CSD is usually equipped with a CSD-SCS used for monitoring and controlling the dredging operations performed by the CSD.

The CSD-SCS is an integrated system which consists of an integrated SCADA system comprising a CCS and a DPM.

The SCADA system is used to monitor and control the main dredging installation, cutter drive system, dredge pump system, dredging valves, swing winches, ladder winch, anchor and anchor boom winches (if any) and the spud and spud carriage system.

The DPM is both used to measure the position and heading of the dredger, and the position and depth of the cutter, and to provide for visualization in the plan view with a numeric window and side views.

4.2 Structure

The SCADA and DPM should either be independent or linked by a network to create an integrated dredging control system.

5 General requirements

5.1 Operating position and control mode

5.1.1 Operating position

The CSD-SCS should have local and remote operating positions.

5.1.2 Control modes

The CSD-SCS should have the following control modes:

- a) manual: manual operation by handle/button/knob and in graphical user interface;
- b) emergency: direct operation through hardwire, only for dredging equipment that affects the safety of the ship.

5.2 External communication

The system should have the following communication devices interfacing with the standard industrial devices protocols:

- a) a heading sensor, such as a gyro compass;
- b) a tide measurement device, such as a tide receiver;
- c) a depth measurement device, such as an echo sounder.

5.3 Diagnostic

A CSD-SCS should provide the following diagnostic information:

- a) equipment failure;
- b) interlocking between equipment;
- c) interlocking between operation position;
- d) communication failure;
- e) sensor failure.

5.4 Visualization of the system information

The monitoring and control stations on the dredging desk are provided for the visualization of the system process.

All relevant measurement and computation data values are displayed in a series of real time process display pages in graphical or numeric form.

The mimic pages should be provided on the system stations to be freely selected by the user. These views comprise the following:

- a) main dredging overview;
- b) preset page;
- c) DPM view;
- d) CCS view;
- e) cutter and cutter drive system;
- f) dredge pumps with relevant data and dredge pipelines with valves;
- g) swing winches;
- h) ladder winches;
- i) spud and spud carriage systems;
- j) production relevant data;
- k) diagnostic pages.

5.5 HMI graphics

5.5.1 Alarm level

In HMI graphics, the CSD-SCS alarm level can be set in two colours.

EXAMPLE Red is the highest level alarm, meaning danger; yellow is the secondary level alarm, meaning warning or abnormal condition.

This principle can be applied to all graphical symbols, function-keys, and digital data.

5.5.2 Conventions on graphic colours

The HMI graphic colours can be specified as follows.

- a) For HMI graphics, cold tone colours are recommended, and for non-operating graphical interfaces, warm tone colours can be adopted.
- b) The colour matching of the HMI graphics should make the flow chart simple and clear with harmonious and consistent colours. It is advisable that the number of colours adopted not be excessive.
- c) Colour adoption of the HMI graphics can be in accordance with the specifications in [Table 1](#).

Table 1 — Convention on graphical adoptions

Colour	General meaning	Meaning of colour in combination with graphical symbol	Meaning of colour in combination with digital data
Red	Danger	Highest level alarm	Highest level alarm
Yellow	Warning	Abnormal condition, secondary alarm	Abnormal condition, secondary alarm
Grey	Static state	Stop, shut down, disconnection	None
Cyan	Special meaning	Remote control, etc.	None
Blue	Secondary importance	Backup equipment	Tag number
White	Safe, program in activation status	None	Measured value or status value, dynamic data
Green	Safe, program in activation status	Normal operation, working, open, shut down, graphic value	None

5.5.3 Brightness of the HMI

The brightness of the HMI graphics should match that of the environment. For screen in bridge, the HMI can have a “night” display mode, and brightness of the screen should be lowered enough not to affect the sailors lookout in the night.

5.6 Alarm

The system should give the alarm in case dredging equipment fails or running parameters are oversetting values.

5.7 Calibration of system

The system should have the following calibration functions for the position and headings of the dredger, the depth of the cutter, and other sensors parameters:

- a) the calibration parameter settings;
- b) the calibration and adjustment of the measurement instruments and sensors.

6 Functional requirements

6.1 Preset/setup

The following preset points should be included.

- a) Dimensions settings: special geometrical parameters of the dredger used for the calculations of monitoring and control values can be entered by authorized personnel only.
- b) System settings: control parameters to adjust the behaviour and characteristic of system components can be entered.
- c) Process settings: all settings that the dredge operator may change for typical operation.

6.2 Spuds and spud carrier system

The system should have the following functions for the working spud with carrier and auxiliary spud:

- a) move each spud up or down;
- b) activate free fall for each spud;
- c) spud carrier fully in;
- d) spud carrier fully out;
- e) spud carrier one step in;
- f) spud carrier one step out;
- g) spud carrier in;
- h) spud carrier out;
- i) display the relevant measured values for spuds and the spud carrier system on the SCADA monitors in graphical or numeric form.

6.3 Cutter system

The system should have the following functions for cutter systems:

- a) cutter drive start;
- b) cutter drive stop;
- c) cutter emergency stop;
- d) cutter speed control;
- e) cutter manual local control for (safe) cutter change;
- f) display the relevant measured values for the cutter system on the SCADA monitors in graphical or numeric form.

6.4 Submersible dredge pump system

The system should have the following functions for the submersible dredge pump system:

- a) to start all subsystems of the submersible dredge pump;
- b) to stop all subsystems of the submersible dredge pump;