

First edition
2019-05

AMENDMENT 1
2022-10

**Road vehicles — Liquefied petroleum
gas (LPG) fuel systems components —**

Part 6:
Pressure relief valves (PRV)

AMENDMENT 1

*Véhicules routiers — Équipements pour véhicules utilisant le gaz de
pétrole liquéfié (GPL) comme combustible —*

Partie 6: Vannes de contrôle de la surpression

AMENDEMENT 1



Reference number
ISO 20766-6:2019/Amd.1:2022(E)

© ISO 2022

STANDARDSISO.COM : Click to view the full PDF of ISO 20766-6:2019/Amd 1:2022



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 41, *Specific aspects for gaseous fuels*.

A list of all parts in the ISO 20766 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

STANDARDSISO.COM : Click to view the full PDF of ISO 20766-6:2019/Amd 1:2022

Road vehicles — Liquefied petroleum gas (LPG) fuel systems components —

Part 6: Pressure relief valves (PRV)

AMENDMENT 1

Clause 3, add the following term entry.

3.2

flow capacity

measured relieving capacity of a pressure relief valves (PRV) measured at the flow-rating pressure, expressed in m³/min of air at a temperature of 15,6 °C and at a pressure of 100 kPa

Clause 4, add the following item.

d) the flow capacity.

Clause 5, first list item.

Replace the text with the following:

— mounting location (shall communicate with the vapour phase portion of the tank); and

6.1

Replace Table 1 with the following:

Table 1 — Applicable tests

Test	Applicable	Test procedure as required by ISO 20766-2	Specific test requirements of this document
Hydrostatic strength	X	X	X (see 6.2)
Leakage	X	X	X (see 6.3)
Excess torque resistance	X	X	
Bending moment	X	X	
Continued operation	X		X (see 6.4)
Corrosion resistance	X	X	
Operational test	X		X (see 6.5)
Vibration resistance	X	X	
Brass material compatibility	X	X	
Oxygen ageing	X	X	

Table 1 (continued)

Test	Applicable	Test procedure as required by ISO 20766-2	Specific test requirements of this document
Non-metallic material immersion	X	X	
Ozone ageing	X	X	
Resistance to dry-heat	X	X	
Temperature cycle test	X	X	
Flow capacity test	X		X (see 6.6)

6.5.2, c)

Replace the text with the following:

c) Repeat a) and b) at -40 °C or -20 °C and 85 °C or 120 °C (if required by the operating conditions). At each test temperature, the following criteria shall be met:

6.6

Add a new subclause.

6.6 Flow capacity test

A flow capacity test on each sample is to be conducted at a flow-rating pressure of 120 % of the maximum set pressure. The measured standard flow capacity should be at least $17,7\text{ m}^3/\text{min}$ when the pressure relief valve is considered a pressure relief device. In other cases, the minimum flow capacity shall be at least $Q \Rightarrow 10,66 \times A^{0,82}$,

where

Q is the flow of air in standard m^3/min (100 kPa absolute at 15 °C);

A is the exterior surface of the container in m^2 .

During flow capacity tests on each sample, there shall be no evidence of chattering or other abnormal operating conditions.

The flow capacity of each sample of a safety valve shall fall within a range of 10 % of the highest observed capacity.

6.7

Add a new clause.

6.7 Creep test

A non-metallic part containing liquid LPG shall comply with the leakage tests mentioned in 6.3 after having been submitted to a hydraulic pressure of 2,25 times the maximum operating pressure at a temperature of 120 °C during a minimum of 96 h. Water or any other suitable hydraulic fluid may be used as a test medium.