
**Cinematography — Spectral response of
photographic audio reproducers for
analog dye sound tracks on 35 mm film**

*Cinématographie — Réponse spectrale de lecteurs audio avec des
pistes sonores analogiques de couleurs sur film de tirage 35 mm*

STANDARDSISO.COM : Click to view the full PDF of ISO 20859:2005



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 20859:2005

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 20859 was prepared by Technical Committee ISO/TC 36, *Cinematography*.

STANDARDSISO.COM : Click to view the full PDF of ISO 20859:2005

Cinematography — Spectral response of photographic audio reproducers for analog dye sound tracks on 35 mm film

1 Scope

This International Standard specifies the spectral response of the photographic audio reproducer light source and receptor as a unit, including any optical filtering that can be interposed.

The analog sound track formats suitable for reproduction using such a reproducer include the cyan dye-only track (without redevelopment of silver) and both conventional and “high magenta” soundtracks (with redevelopment of silver).

2 Spectral response

2.1 The peak or maximum response of the combined audio reproducer light source, filter and receptor shall be 660 nm $^{+20}_{-30}$ nm.

2.2 The integrated response of the unit to all wavelengths greater than 800 nm shall be less than 5 % of the total integrated response measured from 400 nm to 800 nm.

Annex A (informative)

Additional data

The reproduction of analog photographic sound tracks has long employed a tungsten light source and an infrared-sensitive photocell. The light beam is modulated by changes in the infrared energy absorption of the silver sound track image. This practice dates from black and white practice. When colour release prints were introduced, the practice of redeveloping a silver sound track, which consists of silver, magenta dye and cyan dye, was employed in order to maintain compatibility with all existing infrared-sensitive reproducers fitted to projectors. A change to dye-only sound tracks is taking place in order to provide environmental and other benefits. The elimination of the need for silver sound track redevelopment will allow a simplification of the colour positive process with savings in the use of hazardous chemicals and water. Discontinuation of silver redevelopment in release prints will eliminate the discharge of silver into the environment because, when used, release prints are ultimately destroyed. The red-sensitive sound reproducers required for dye tracks employ solid-state light emitting diodes (LED) or lasers with a longer lifetime than tungsten lamps, providing increased reliability of sound reproduction in theatres.

The conversion of sound reproducers from infrared-sensitive devices (for silver sound tracks) to red-sensitive devices (for cyan dye sound tracks) requires an intermediate sound track format called "high magenta". The "high magenta" sound track eliminates the cyan dye from the silver sound track, thus making the transmission level from 600 nm to 1 000 nm almost equal. This almost equal transmission range produces good sound quality, including cancellation of cross-modulation distortion, for infrared-sensitive readers and all types of red-sensitive readers.

A dye-only soundtrack needs to use the dye density to modulate the scanning beam. Unlike the silver density that exists at all wavelengths, the cyan dye in film does not have sufficient density to modulate the scanning beam at wavelengths of less than 600 nm and at wavelengths of greater than 750 nm. Reading the cyan dye-only soundtrack too far away from its wavelength of maximum absorption will cause degradation of sound quality (higher cross-modulation distortion, lower high-frequency response and lower signal-to-noise ratio). The purpose of limiting the spectral response of the audio reproducer is to use advantageously the absorption of the cyan dye image to modulate the scanning beam and to maintain the maximum sound quality of which the cyan dye record is capable.