

---

---

**Nuclear fuel technology — Determination  
of the O/M ratio in MOX pellets —  
Gravimetric method**

*Technologie du combustible nucléaire — Détermination du rapport O/M  
dans les pastilles MOX — Méthode gravimétrique*

STANDARDSISO.COM : Click to view the full PDF of ISO 21484:2008



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 21484:2008



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 21484 was prepared by Technical Committee ISO/TC 85, *Nuclear energy*, Subcommittee SC 5, *Nuclear fuel technology*.

[STANDARDSISO.COM](http://STANDARDSISO.COM) : Click to view the full PDF of ISO 21484:2008

# Nuclear fuel technology — Determination of the O/M ratio in MOX pellets — Gravimetric method

## 1 Scope

This International Standard describes a method for determining the oxygen-to-metal (O/M) ratio in mixed uranium-plutonium oxide (U,Pu)O<sub>2±X</sub> pellets.

## 2 Principle

The (U,Pu)O<sub>2±X</sub> sample is submitted to controlled oxidation-reduction under thermodynamic conditions designed to change the O/M ratio to a value of 2,000. The initial stoichiometric deviation, *X*, is determined from the sample mass difference before and after heat treatment.

## 3 Reactions

The principal reactions are as follows:

- a)  $(U,Pu)O_{2\pm X} \pm x/2 O_2 \rightarrow (U,Pu)O_{2,000}$
- b)  $(U,Pu)O_{2\pm X} + xH_2 \rightarrow (U,Pu)O_{2,000} + xH_2O$

## 4 Reagents

During the analysis, unless otherwise stated, use only reagents of recognized analytical grade and distilled or demineralized water or water of equivalent purity.

**4.1 Nitric acid solution**, with a volume fraction of 50 %.

**4.2 Purge gas**.

**4.2.1 Air**, with a volume fraction of 99,99 % purity grade.

**4.2.2 Argon**.

**4.2.3 Hydrogen or hydrogen/argon mixtures**, with a volume fraction of 99,99 % purity grade, to which water vapour may be added to obtain an oxygen potential ( $\Delta G_0$ ) approaching  $-420 \text{ kJ}\cdot\text{mol}^{-1}$  ( $-100 \text{ kcal}\cdot\text{mol}^{-1}$ ).

## 5 Apparatus

**5.1 Muffle furnace**, having provision for measuring the temperature and sweeping the hearth with various gases.

**5.2 Crucibles**, made of platinum or quartz.

**5.3 Analytical balance**, with an accuracy of at least  $\pm 0,1$  mg.

## 6 Sampling

A representative sample (at least one pellet) shall be taken from the pellet batch for analysis.

If necessary, care shall be taken to avoid sample oxidation during the sampling procedure. Typical precautions include performing the sampling operation under argon atmosphere, placing the sample in an argon-filled bottle, etc. The laboratory performing the analyses shall establish the procedure.

## 7 Procedure

### 7.1 Preliminary test

The balance shall be checked at regular intervals using a standard weight.

### 7.2 Preparation of the crucibles

The crucibles shall be clean and weighed before use. An example of a cleaning procedure that could be used is as follows:

**7.2.1** Clean the crucibles by heating them in nitric acid (4.1) to a temperature near the boiling point.

**7.2.2** Rinse thoroughly with deionized water.

**7.2.3** Dry the crucibles in the furnace for 30 min at 150 °C under argon atmosphere.

**7.2.4** Allow the crucibles to cool to 35 °C in the furnace under argon atmosphere.

**7.2.5** Remove each crucible from the furnace and weigh it to within  $\pm 0,1$  mg.

**7.2.6** Record the crucible mass,  $m_0$ , in grams.

### 7.3 Weighing of the sample

**7.3.1** Place the pellets, sampled as indicated in Clause 6, in an empty crucible.

**7.3.2** Weigh the crucible containing the pellets to within  $\pm 0,1$  mg.

**7.3.3** Record the mass,  $m_1$ , in grams, of the crucible containing the pellets.

### 7.4 Heat treatment cycles

#### 7.4.1 General

The sample shall be heat treated in such a way that the O/M ratio is changed to exactly 2,000. The duration of the oxidation-reduction cycles, and the gas flow rates in the furnace, shall be optimized according to the nature of the furnace used, the number of sample pellets measured, the pellet composition, etc.

Load the furnace with the crucible containing the sample pellets. Apply the desired heat treatment cycle.

## 7.4.2 Example 1

7.4.2.1 Under argon sweeping, raise the temperature to  $900\text{ }^{\circ}\text{C} \pm 30\text{ }^{\circ}\text{C}$  and hold for 5 min.

7.4.2.2 Under air sweeping, maintain the furnace temperature for 1 min to 7 min at  $900\text{ }^{\circ}\text{C} \pm 30\text{ }^{\circ}\text{C}$ .

7.4.2.3 Under argon sweeping, maintain the furnace temperature for 5 min at  $900\text{ }^{\circ}\text{C} \pm 30\text{ }^{\circ}\text{C}$ .

7.4.2.4 Under argon +5 %  $\text{H}_2$  sweeping, maintain the furnace temperature for 8 h to 13 h at  $900\text{ }^{\circ}\text{C} \pm 30\text{ }^{\circ}\text{C}$ .

7.4.2.5 Under argon +5 %  $\text{H}_2$  sweeping, shut off the furnace heating and allow the temperature to drop to  $150\text{ }^{\circ}\text{C}$ .

## 7.4.3 Example 2

7.4.3.1 Heat the samples for 16 h at  $800\text{ }^{\circ}\text{C}$ , in an atmosphere comprising a volume fraction of 4 %  $\text{H}_2$  in argon saturated with water at room temperature.

7.4.3.2 Cool under dry argon containing a volume fraction of 4 %  $\text{H}_2$ .

## 7.5 Final weighing

7.5.1 Remove the crucible from the furnace.

7.5.2 Weigh the crucible to within 0,1 mg.

7.5.3 Record the mass,  $m_2$ , in grams, of the crucible after oxidation-reduction heat treatment.

## 8 Calculation

### 8.1 Mean atomic mass of oxide after heat treatment

Calculate the mean atomic mass of oxide after heat treatment, when O/M = 2,000 exactly, using Equation (1):

$$A_t = \frac{[A_t(\text{Pu})]\text{Pu \%} + [A_t(\text{U})]\text{U \%} + [A_t(\text{Am})]\text{Am \%}}{\text{Pu \%} + \text{U \%} + \text{Am \%}} + 2A_t(\text{O}) \quad (1)$$

where

$A_t$  is the mean atomic mass of the oxide of heavy metals;

$A_t(\text{Pu})$  is the mean atomic mass of plutonium in the oxide;

$A_t(\text{U})$  is the mean atomic mass of uranium in the oxide;

$A_t(\text{Am})$  is the mean atomic mass of americium in the oxide;

Pu % is the mole fraction, in percentage, of plutonium in the oxide;

U % is the mole fraction, in percentage, of uranium in the oxide;

Am % is the mole fraction, in percentage, of americium in the oxide;

$A_t(\text{O})$  is the atomic mass of oxygen (15,999 4).

## 8.2 Calculation of O/M ratio

Calculate the O/M ratio using Equation (2):

$$O/M = 2,000 - \frac{A_t \times (m_2 - m_1)}{A_t(O) \times (m_2 - m_0)} \quad (2)$$

where

- $m_0$  is the mass, in grams, of the empty crucible;
- $m_1$  is the mass, in grams, of the crucible with test sample before oxidation-reduction;
- $m_2$  is the mass, in grams, of the crucible with test sample after oxidation-reduction heat treatment;
- $A_t(O)$  is the atomic mass of oxygen (15,999 4);
- $A_t$  is the mean atomic mass of heavy metals in the oxide.

## 9 Precision

### 9.1 Accuracy

Thirty determinations on stoichiometric mixed oxide pellets containing approximately 7 % plutonium give a mean O/M ratio of 2,000.

### 9.2 Precision

The standard deviation calculated from 30 determinations by two operators on a control sample of stoichiometric mixed oxide pellets containing approximately 7 % plutonium is better than 0,001.

### 9.3 Sensitivity

Typically, for a 15 g sample, a change in weight of 0,5 mg results in a change in O/M ratio of 0,001.

## 10 Test report

The test report shall contain the following information:

- all information necessary for the identification of the sample tested;
- reference to this International Standard;
- test method used;
- results of the test, including the results of the individual determinations and their mean, calculated as specified in Clause 8;
- any deviations from the procedure specified in this International Standard;
- any unusual features (anomalies) observed during the test;
- date of the test.