
**Ships and marine technology —
Transmitting heading devices (THDs) —**

**Part 2:
Geomagnetic principles**

*Navires et technologie maritime — Dispositifs de transmission de
données de pilotage —*

Partie 2: Principes géomagnétiques

STANDARDSISO.COM : Click to view the full PDF of ISO 22090-2:2004



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 22090-2:2004

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
1 Scope	1
2 Normative references	2
3 Terms and definitions	2
4 Performance requirements	3
4.1 Functionality	3
4.2 Information	3
4.3 Fore-and-aft mark	4
4.4 Heading information	4
4.5 Electrical wiring	4
4.6 Non-magnetic housing	4
4.7 Alarm signal	4
5 Accuracy	4
5.1 General	4
5.2 Accuracy of transmission data	4
5.3 Static error (settle point error)	4
5.4 Dynamic error	4
5.5 Follow-up error	5
5.6 Settling time requirements to the directional system	5
5.7 Correcting the magnetic heading for magnetic variations	5
5.8 Adjusting of magnetic deviations and heeling error	5
5.9 Means of adjusting the deviation by vertical soft iron on the ship	5
5.10 Protection of correcting devices	6
5.11 Update rate	6
6 Type tests	6
6.1 General	6
6.2 Transmission error tests	6
6.3 Fore-and-aft mark tests	6
6.4 Heading information tests	6
6.5 Static error test	7
6.6 Follow-up error test	7
6.7 Settling time test	7
6.8 Tests for correcting the magnetic heading by magnetic variations	7
6.9 Tests for adjusting magnetic deviations	7
6.10 Tests for means of adjusting the deviation by vertical soft iron	8
6.11 Dynamic accuracy	8
6.12 Update rate test	8
6.13 Malfunction test	8
7 Marking and identification	8
Annex A (informative) Equivalent requirements in ISO 22090-2 and IMO Resolution MSC.116(73)	9
Bibliography	10

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 22090-2 was prepared by Technical Committee ISO/TC 8, *Ships and marine technology*, Subcommittee SC 6, *Navigation*.

ISO 22090 consists of the following parts, under the general title *Ships and marine technology — Transmitting heading devices (THDs)*:

- *Part 1: Gyro-compasses*
- *Part 2: Geomagnetic principles*
- *Part 3: GNSS principles*

Ships and marine technology — Transmitting heading devices (THDs) —

Part 2: Geomagnetic principles

1 Scope

This part of ISO 22090 specifies the construction, performance and testing of devices employing only magnetic means as transmitting heading devices required by chapter V, SOLAS 1974 (as amended).

A Transmitting Heading Device (THD) is an electronic device that provides information about the ship's true heading.

In addition to the general requirements contained in IMO Resolution A.694(17) to which IEC 60945 is associated and the relevant standard for the sensing part used, the THD equipment shall comply with the following minimum requirements.

Where the IMO performance standards which apply to the sensing part do not specify a geographical operating area the THD shall operate

- a) at a minimum rate of turn 20 °/s, and
- b) from 70° latitude south to 70° latitude north as a minimum.

The THDs complying with the requirements contained in this part of ISO 22090 can be used for heading information as contained in Chapter V of the SOLAS Convention.

In addition such THDs should meet the dynamic requirements contained in the HSC Code, chapter 13 for the carriage of a suitable device providing heading information.

NOTE 1 Several technologies can be used to detect and transmit heading information. It is illogical to standardize the detection of the heading separately from the transmission of the heading. Therefore, separate parts of this part of ISO 22090 refer to different technologies. The requirements of this part of ISO 22090 only apply to the principle of the Geomagnetic one. Other technologies are covered in other parts of ISO 22090.

NOTE 2 All requirements that are extracted from the recommendation of IMO Resolution MSC. 116 (73) on performance standards for transmitting heading devices are printed in italics.

A standard magnetic compass with a pickup sensor could be applied as a sensing part of this standard of geomagnetic principle. However the IMO performance resolution MSC.116(73) requires that the THD should be met for the dynamic requirements of the HSC code. Nevertheless, when the THD would be only used other than the HSC, the limit of rate of turn may be 6°/s instead of 20°/s .

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 449, *Ships and marine technology — Magnetic compasses, binnacles and azimuth reading devices — Class A*

ISO 11606:2000, *Ships and marine technology — Marine electromagnetic compasses*

IEC 60945, *Maritime navigation and radiocommunication equipment and systems — General requirements — Methods of testing and required test results*

IEC 61162 (all parts), *Maritime navigation and radiocommunication equipment and systems — Digital interfaces*

IMO Resolution A.424(XI): *Performance standards for gyro-compasses*

IMO Resolution A.821(19): *Performance standards for gyro-compasses for high-speed craft*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

geomagnetic principle

principle of the THDs depending, for its directional properties, upon the magnetism of the earth

3.2

heading

any ship's heading to be input to the THD function.

NOTE It is defined by the direction of the vertical projection of the fore-and-aft line of the ship onto the horizontal plane. When measured relative to the true North, magnetic North or compass North, it is respectively defined as true heading, magnetic heading or compass heading, and is usually expressed in degrees as a three-figure group, starting from North, in a clockwise direction around the compass card.

3.3

true heading

horizontal angle between the vertical plane passing through the true meridian and the vertical plane passing through the craft's fore-and-aft datum line, measured from true north (000°) clockwise through 360°

3.4

magnetic compass

instrument designed to seek the direction of magnetic North in azimuth and to hold that direction permanently

3.5

magnetic sensor

magnetic sensing part which detects the geomagnetic field concerning heading information with or without a magnetic compass and outputs the information to a processor

3.6

processor

device which obtains the ship's magnetic heading information for a transmitting part by adjusting the magnetic deviations

3.7**transmitting part**

device which receives heading information from the sensing part and converts this to the required accurate signal

3.8**sensing part**

sensing function of detecting any heading information connected to the transmitting device

3.9**follow-up error**

error caused by the delay between the existence of a value to be sensed and the availability of the corresponding signal or data stream at the output of the system

EXAMPLE *The difference between the real heading of the turning vessel and the available information at the output of the system.*

NOTE *A follow-up error disappears when the system is static.*

3.10**transmission and resolution error**

error which is caused by the method used to transmit the original information to a receiving device

NOTE *Such a method may have a limited capability to code any possible value of the information, e.g. step output with 1/6° resolution. This error is caused by the method used inside the THD and at its output to code the information.*

3.11**static error**

error caused by any reason and which stays unchanged in value during the operation of the system, measured under static conditions

3.12**dynamic error**

error caused by dynamic influences acting on the system, such as vibration, roll, pitch or linear acceleration

NOTE *This error may have an amplitude and usually a frequency related to the environmental influences and the parameters of the system itself.*

4 Performance requirements**4.1 Functionality**

Geomagnetic principles of THDs detect the horizontal component of the geomagnetic field, and generates a ship's true heading signal for other devices.

In one type of sensor which utilizes a magnetic compass, the performances and requirements of the compass shall conform to the ones referred to ISO 449, and the other type of sensor shall fulfil the performance requirements concerning the marine electromagnetic compasses in ISO 11606.

4.2 Information

4.2.1 *All displays with the exception of the sensor, and all outputs of heading, shall indicate true heading.*

4.2.2 *Manually entered values used for electronic correction shall be indicated by adequate means.*

4.3 Fore-and-aft mark

On the bottom part of the binnacle and/or the housing of the sensor system, a fore-and-aft mark shall be inscribed to facilitate installation in the fore-and-aft line of the ship. The units shall be installed on the fore-and-aft line of the ship. In magnetic-compass-type THDs, it shall be in the vertical plane passing through the centre of the compass card and the main lubber mark to within $\pm 0,5^\circ$.

4.4 Heading information

The THD shall provide true heading information to the other navigational equipment.

At least one output shall be in accordance with the relevant international marine interface standard: IEC 61162 series as amended.

4.5 Electrical wiring

Electrical wiring, such as that for the direct-current power supply and that for connecting the units, shall not produce any perceptible errors in the heading information.

4.6 Non-magnetic housing

The housing of the magnetic sensor system shall be non-magnetic.

4.7 Alarm signal

An alarm shall be provided to indicate malfunctions of the THD or a failure of the power supply.

An alarm output shall be provided for any alarm conditions.

5 Accuracy

5.1 General

The THD shall meet at least the following accuracy at the output of the device under sea conditions as specified in IMO Resolution A.424(XI) or A.821(19) as applicable.

5.2 Accuracy of transmission data

The transmission error, including the resolution error, shall be less than $\pm 0,2^\circ$.

5.3 Static error (settle point error)

The static errors shall be less than $\pm 1,0^\circ$ (95 %).

5.4 Dynamic error

The dynamic error amplitude shall be less than $\pm 1,5^\circ$ (95 %). The dynamic error frequency for test shall be less than 0,033 Hz equivalent to a period not shorter than 30 s if the amplitude of the dynamic error exceeds $\pm 0,5^\circ$.

5.5 Follow-up error

The follow-up error for the rates of turn shall be

- less than $\pm 0,5^\circ$ up to a rate of $10^\circ/\text{s}$; and
- less than $\pm 1,5^\circ$ at a rate of between $10^\circ/\text{s}$ and $20^\circ/\text{s}$.

5.6 Settling time requirements to the directional system

In magnetic-compass-type sensors, the directional system shall always settle in the original direction. Following an initial deflection of the card of 90° from the magnetic meridian, the time taken to return finally to within 1° of the magnetic meridian, shall not exceed $\sqrt{57600/H}$ s at a temperature of $20^\circ\text{C} \pm 3^\circ\text{C}$, where H is the horizontal component of the magnetic flux density in microteslas (μT) at the place of testing.

5.7 Correcting the magnetic heading for magnetic variations

In order to get true headings, correcting the magnetic heading for magnetic variations shall be carried out within the errors of $0,5^\circ$. The means of correcting magnetic variation may be either automatic, or manual then automatic.

The values used for electronic compensation should be indicated by adequate means and shall be stored such that values are automatically recovered when switching on.

5.8 Adjusting of magnetic deviations and heeling error

It shall be possible to adjust the coefficients A , B , C and D so that the residual value of each coefficient is less than $\pm 1^\circ$.

5.8.1 Check by bearings

The binnacles shall contain a device for correcting the deviation due to the horizontal components of the ship's permanent magnetism. This device shall be capable of correcting a coefficient A up to $\pm 3^\circ$, coefficients B and C of up to at least $(720/H)^\circ$, a coefficient D of up to $\pm 7^\circ$, vertical component of the ship's magnetic field (producing the heeling error) of up to $\pm 75 \mu\text{T}$, H being as defined in 5.6.

5.8.2 Check by magnetic fields

In electromagnetic-compass-type THDs, each coefficient of residual deviations shall be obtained by the following equations.

$$B = \frac{180^\circ}{\pi} \times \frac{n_N - n_S}{2n'}, C = \frac{180^\circ}{\pi} \times \frac{n_W - n_E}{2n'}, D = \frac{180^\circ}{\pi} \times \frac{(n_N + n_S) - (n_W + n_E)}{4n'}$$

where n_N , n_E , n_S , n_W are the ship's northern magnetic field when the ship's heading is N, E, S and W respectively. The n' is the mean value of n_N , n_E , n_S , n_W . Coefficient A shall be negligibly small in electromagnetic-compass-type THDs.

The compensating devices shall be protected against accidental alterations.

5.9 Means of adjusting the deviation by vertical soft iron on the ship

Means of adjusting the deviation by vertical soft iron on the ship should be provided.

5.10 Protection of correcting devices

Any correcting devices or parameters shall be protected against inadvertent operation.

5.11 Update rate

The THD shall update a new heading at least once every 50 ms.

6 Type tests

6.1 General

Type testing shall be carried out before the instruments covered come into regular service. For type testing, only new devices are acceptable.

The THD shall be tested for accuracy with the sensing part connected. If the sensing part is so designed as to be included in the transmitting part, the equipment shall be tested altogether.

Unless otherwise stated in this part of ISO 22090, all tests shall be carried out in accordance with the requirements of IEC 60945.

Tests in a static magnetic field shall be carried out in an authorized test room.

Devices which have passed the type tests, and comply with the requirements, shall be so certified in the language of the test authority and in English.

Copies of the certificate shall be issued on demand. They shall be explicitly marked "copy".

Acceptance of type-test certificates between countries will be a matter for mutual agreement.

The THD shall be tested for accuracy with the sensing part connected. If the sensing part is so designed that it is included in the transmitting part, the equipment shall be tested all parts.

6.2 Transmission error tests

On a rotating test stand, adjust the heading mark of the THD until the output shows 000,0, then slowly rotate the stand 10°. The readings of the transmission output shall meet the requirements of 5.2.

6.3 Fore-and-aft mark tests

In magnetic-compass-type THDs, the examination may be carried out on a rotating test stand with the aid of a plumb line and with the compass in the binnacle.

In electromagnetic compass type THDs, the examination shall be verified by visual inspection or electrical measurements.

The results shall fulfil the requirements specified in 4.3.

6.4 Heading information tests

This test can be carried out in the same way as the static error test mentioned in 6.5, checking the readings of the output heading. The results shall fulfil the requirements specified in 4.4.

6.5 Static error test

6.5.1 Magnetic-compass-type THD

The static error applies to the compass without fluxgate sensors. The fluxgate of a THD shall be placed so that the influence on the card heading shall not exceed $1,0^\circ$ on any heading.

The examination may be carried out on a compass test stand. After having brought the rotation centre of the compass card into the rotation axis of the test stand, the static error can be read at the card graduation by means of a telescope or any other appropriate means, when the vertical plane of the sight passing through the rotation axis has been aligned with the magnetic meridian in advance. This measurement shall be carried out on at least four equidistant headings.

The static error shall be within $\pm 1,0^\circ$ (95 %).

If the test is undertaken in the compass bowl, it should be noted that the resulting value then includes the deviation due to any magnetic material in the compass and/or in the fluxgate sensor.

6.5.2 Electromagnetic-compass-type THD

After having brought the fore-and-aft line of the sensor housing into the line passing through the centre of the test stand and the zero line orientated north, the static error can be read by comparing the output heading with the rotation angle. This measurement shall be carried out on at least four equidistant headings. The test results shall conform with the requirements of 5.3.

6.6 Follow-up error test

Set up the magnetic sensor on a test platform, and rotate the platform at a rate of $20^\circ/\text{s}$. The readings of the heading output shall fulfil the requirements specified in 5.5.

6.7 Settling time test

The card, if fitted, is deflected 90° , held there for at least 10 s and then released. The time, in seconds, taken to return finally to within 1° of the magnetic meridian shall not exceed the value required in 5.6. This is repeated on the other side of the meridian and the mean is taken.

6.8 Tests for correcting the magnetic heading by magnetic variations

After indicating the magnetic heading on the display, when a few values of magnetic variations are manually or automatically input to the system, all the true headings indicated shall be within the accuracy of the requirement of 5.7. In the system containing a positioning system, after bringing the system to a position of which the magnetic field is not disturbed, turn the system so that the direction of the fore-and-aft mark from the centre aligns with a distant object of which the true bearing is known. The true heading indication coincidence shall also be within the accuracy of the requirement in 5.7.

6.9 Tests for adjusting magnetic deviations

The sensing part is placed on the test stand and aligned on north or south. An external magnetic force sufficiently far away to create a reasonably even field in the vicinity of the directional element is applied until a deviation of $(720/H)^\circ$ is obtained. This deviation is then corrected by the magnets. The resulting deviation shall not exceed the values required in 5.8.1. Repeat on east and/or west.

The amount of deviation of D that can be corrected can be checked by placing the compass and binnacle on a test stand on a quadrennial course, with and without the correctors in position. In the electromagnetic-compass-type sensor, the maximum amount of D in 5.8.1 which is to be corrected is measured in the quadrennial course with and without the switch of correction of coefficient D in the maximum values. The result shall fulfil the requirement in 5.8.1.

6.10 Tests for means of adjusting the deviation by vertical soft iron

When the THD is provided with Flinders' s bars, they shall be checked visually.

6.11 Dynamic accuracy

Mount the sensing part on a test stand, then the motion tests shall be carried out with the following nominal simple harmonic table motions. Also record the heading.

- Roll axis: peak amplitude $20^\circ \pm 2^\circ$, period $6 \text{ s} \pm 1 \text{ s}$.
- Pitch axis: peak amplitude $10^\circ \pm 2^\circ$, period $10 \text{ s} \pm 1 \text{ s}$.
- Yaw axis: peak amplitude $5^\circ \pm 1^\circ$, period being $15 \text{ s} \pm 1 \text{ s}$.

At the end of the period of 5 min duration tests, the mean values of the recorded heading shall be within $\pm 1,5^\circ$ of the original heading. The result shall fulfil the requirement of 5.4.

6.12 Update rate test

Observe the heading output rate and ensure that it is a minimum of 50 ms.

6.13 Malfunction test

A visible and audible alarm as required in 4.7 and THD shall be tested according to the following test procedure.

- Malfunction tests:

Using the manufacturer's self-check functions.

- Power failure tests:

Main power supply to be off.

To confirm an alarm output for any alarm conditions.

7 Marking and identification

Each unit of the THDs shall be marked with the following:

- the identification of the manufacturer;
- the equipment-type number or identification of the model which was type tested;
- the serial number of the unit;
- the year of manufacture (not necessary if the year of manufacture can be read by the serial number);

The presence of the markings on the unit of the THDs specified above shall be checked by visual inspection.