

---

---

**Conveyor belts with textile carcass —  
Widths and lengths**

*Courroies transporteuses à carcasse textile — Largeurs et longueurs*

STANDARDSISO.COM : Click to view the full PDF of ISO 251:2003



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 251:2003

© ISO 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 251 was prepared by Technical Committee ISO/TC 41, *Pulleys and belts (including veebelts)*, Subcommittee SC 3, *Conveyor belts*.

This third edition cancels and replaces the second edition (ISO 251:1987), which has been technically revised.

STANDARDSISO.COM : Click to view the full PDF of ISO 251:2003



# Conveyor belts with textile carcass — Widths and lengths

## 1 Scope

This International Standard specifies the widths and lengths of conveyor belts with a textile carcass. It also specifies the corresponding tolerances.

It is not applicable to light conveyor belts as described in EN 873<sup>[1]</sup>, as tolerances on the widths and lengths of cut light conveyor belts are given in ISO 15147<sup>[2]</sup>.

NOTE The lengths of conveyor belts are not standardized.

## 2 Widths and tolerances

The widths of conveyor belts and permissible tolerances shall be as given in Table 1.

Table 1 — Nominal widths and tolerances of open-ended conveyor belts

Dimensions in millimetres

Nominal width	Tolerance
300	± 5
400	± 5
500	± 5
600	± 6
650	± 6,5
800	± 8
1 000	± 10
1 200	± 12
1 400	± 14
1 600	± 16
1 800	± 18
2 000	± 20
2 200	± 22
2 400	± 24
2 600	± 26
2 800	± 28
3 000	± 30
3 200	± 32

### 3 Tolerances on lengths

The permissible tolerances for the lengths of conveyor belts, measured loose, shall be as given in Tables 2 and 3.

**Table 2 — Tolerances on length for endless conveyor belts**

Length m	Tolerance mm
≤ 15	± 50
> 15 but ≤ 20	± 75
> 20	± 0,5 % of the length in metres

**Table 3 — Tolerances on length for open-ended conveyor belts**

Belt delivery condition	Tolerance (maximum permissible difference between delivered length and ordered length )	
	As one length	$\begin{matrix} +2,5 \% \\ 0 \end{matrix}$
In several lengths	for each single length or as one length $\pm 5 \%$	for the sum of all lengths $\begin{matrix} +2,5 \% \\ 0 \end{matrix}$