

INTERNATIONAL
STANDARD

ISO
2589

IULTCS/IUP
4

Second edition
2002-12-15

**Leather — Physical and mechanical
tests — Determination of thickness**

Cuir — Essais physiques et mécaniques — Détermination de l'épaisseur

STANDARDSISO.COM : Click to view the full PDF of ISO 2589:2002



Reference number
ISO 2589:2002(E)
IULTCS/IUP 4

© ISO 2002

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 2589:2002

© ISO 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword.....	iv
1 Scope	1
2 Normative references	1
3 Principle	1
4 Apparatus	1
5 Sampling and sample preparation	2
6 Procedure	2
7 Expression of results	2
8 Test report	2

STANDARDSISO.COM : Click to view the full PDF of ISO 2589:2002

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 2589 was prepared by the Physical Test Commission of the International Union of Leather Technologists and Chemists Societies (IUP Commission, IULTCS) in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 289, *Leather*, the secretariat of which is held by UNI, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement). It is based on IUP 4 originally published in *J. Soc. Leather Trades Chemists* **42**, p. 387, (1958) and declared an official method of the IULTCS in 1959. An updated version was published in *J. Soc. Leather Tech. Chem.* **82**, p. 225, (1998) and a further revision published in *J. Soc. Leather Tech. Chem.* **84**, p. 311, (2000) and reconfirmed as an official method in March 2001. This latest revision now includes the number of test measurements to be taken.

This second edition cancels and replaces the first edition (ISO 2589:1972), which has been technically revised.

Leather — Physical and mechanical tests — Determination of thickness

1 Scope

This International Standard specifies a method for determining the thickness of leather. The method is applicable to all types of leather of any tannage. The measurement is valid for both the whole leather and a test sample.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2418 *Leather - Chemical, physical and mechanical and fastness tests – Sampling location*

ISO 2419 *Leather - Physical and mechanical tests - Sample preparation and conditioning*

3 Principle

The leather is placed in a gauge under a specified load for a specified time and the thickness read directly.

4 Apparatus

4.1 Test machine, including the following:

4.1.1 Gauge, graduated to read to 0,01 mm directly with an accuracy of $\pm 0,02$ mm over the whole scale length.

4.1.2 Anvil, comprising the flat horizontal surface of a cylinder of diameter 10,00 mm $\pm 0,05$ mm projecting 3,0 mm $\pm 0,1$ mm above the surface of a concentric flat circular platform of diameter 50,0 mm $\pm 0,2$ mm.

NOTE The circular platform of 50 mm diameter helps to support medium weight leathers which might otherwise present a convex surface to the presser foot. The anvil is raised 3 mm above the platform so that errors are avoided in measurements on heavy leathers which are not flat.

4.1.3 Presser foot, having a flat circular surface of diameter 10,0 mm $\pm 0,05$ mm, coaxial with the anvil and capable of movement normal to the face of the anvil. The contacting surfaces of the anvil and presser foot shall be dead weight loaded with 393 g ± 10 g. Movements of the presser foot shall give a direct reading of the movement on the gauge (4.1.1).

NOTE The loads and dimensions quoted in 4.1.3 give a pressure of 49,1 kPa (500 g/cm²).

4.1.4 **Rigid stand**, to hold the gauge (4.1.1), anvil (4.1.2) and presser foot (4.1.3).

5 Sampling and sample preparation

- 5.1 Official sample in accordance with ISO 2418. 5 measurements to be taken, distributed across the sample.
- 5.2 Sample prepared for other tests. 3 measurements to be taken, distributed across the sample.
- 5.3 Sample of unknown origin. 5 measurements to be taken, distributed across the sample.
- 5.4 For very heavy, firm leathers, a smaller sample is recommended to avoid curvature. 3 measurements to be taken, distributed across the sample.
- 5.5 For whole hides, 5 measurements for each location should be taken.

Condition all samples in accordance with ISO 2419.

6 Procedure

Place the apparatus on a flat, horizontal surface. Place the sample in the gauge grain side up if this can be identified. If the grain cannot be identified place the sample in the gauge with either surface upwards. Apply the load gently and record the thickness 5 s \pm 1 s after full loading is reached.

7 Expression of results

The results shall be expressed as the arithmetic mean and range to the nearest 0,01 mm.

8 Test report

The test report shall include the following:

- a) reference to this International Standard, i.e. ISO 2589:2002;
- b) the results obtained expressed to the nearest 0,01 mm;
- c) the standard atmosphere used for conditioning and testing as given in ISO 2419 (i.e. 20 °C/65 % rh, or 23 °C/50 % rh);
- d) any deviations from the method specified in this International Standard;
- e) full details for identification of the sample.