
**Petroleum products — Calculation of
viscosity index from kinematic viscosity**

*Produits pétroliers — Calcul de l'indice de viscosité à partir de
la viscosité cinématique*

STANDARDSISO.COM : Click to view the full PDF of ISO 2909:2002



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 2909:2002

© ISO 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
1 Scope.....	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Determination	2
6 Calculation.....	2
7 Expression of results.....	8
8 Precision	8
9 Test report.....	9

STANDARDSISO.COM : Click to view the full PDF of ISO 2909:2002

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 2909 was prepared by Technical Committee ISO/TC 28, *Petroleum products and lubricants*.

This third edition cancels and replaces the second edition (ISO 2909:1981), which has been technically revised.

STANDARDSISO.COM : Click to view the full PDF of ISO 2909:2002

Petroleum products — Calculation of viscosity index from kinematic viscosity

1 Scope

This International Standard describes two procedures for calculating the viscosity index (VI) of petroleum products and related materials, such as lubricating oils, from their kinematic viscosities at 40 °C and 100 °C.

Procedure A is applicable to petroleum products of viscosity index up to and including 100.

Procedure B is applicable to petroleum products of viscosity index 100 or greater.

NOTE The results obtained from the calculation of VI from kinematic viscosities determined at 40 °C and 100 °C are virtually the same as those obtained from the former VI system using kinematic viscosities determined at 37,78 °C and 98,89 °C.

This International Standard does not apply to petroleum products with kinematic viscosities less than 2,0 mm²/s at 100 °C. Table 1 applies to petroleum products with kinematic viscosities between 2 mm²/s and 70 mm²/s at 100 °C. Equations are provided for calculating the viscosity index of petroleum products having kinematic viscosities above 70 mm²/s at 100 °C.

NOTE In cases where kinematic viscosity data are not available at temperatures of 40 °C and 100 °C, an estimate may be made of the viscosity index by calculating the kinematic viscosity at temperatures of 40 °C and 100 °C from data obtained at other temperatures. Such viscosity index data may be considered as suitable for information only and not for specification purposes.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3104:1994, *Petroleum products — Transparent and opaque liquids — Determination of kinematic viscosity and calculation of dynamic viscosity*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

viscosity index

VI

number used to characterize the variation of the kinematic viscosity of a petroleum product with temperature

NOTE For products of similar kinematic viscosity, the higher the viscosity index, the smaller the effect of temperature on its kinematic viscosity.

4 Principle

Kinematic viscosities at 40 °C and 100 °C are determined by a standard test method and the viscosity index is calculated from these test data using known correlations.

5 Determination

Determine the kinematic viscosity of the sample at 40 °C and 100 °C in accordance with ISO 3104.

6 Calculation

6.1 General

Calculate the viscosity index using one of the procedures given in 6.2 and 6.3.

6.2 Procedure A

6.2.1 Use procedure A for petroleum products of viscosity index up to and including 100 (see the note to 8.2).

6.2.2 If the kinematic viscosity of the petroleum product at 100 °C is in the range of 2 mm²/s to 70 mm²/s, extract from Table 1 the corresponding values of *L* and *H*:

where

L is the kinematic viscosity, expressed in millimetres squared per second, at 40 °C of a petroleum product of viscosity index 0 having the same kinematic viscosity at 100 °C as the petroleum product whose viscosity index is to be calculated;

H is the kinematic viscosity, expressed in millimetres squared per second, at 40 °C of a petroleum product of viscosity index 100 having the same kinematic viscosity at 100 °C as the petroleum product whose viscosity index is to be calculated.

Measured values which are not listed but which are within the range of Table 1 may be obtained by linear interpolation.

6.2.3 If the measured kinematic viscosity of the petroleum product at 100 °C is above 70 mm²/s, calculate the values of *L* and *H* using the following equations:

$$L = 0,835 3Y^2 + 14,67Y - 216 \quad (1)$$

$$H = 0,168 4Y^2 + 11,85Y - 97 \quad (2)$$

where *Y* is the kinematic viscosity, expressed in millimetres squared per second, at 100 °C of the petroleum product whose viscosity index is to be calculated.

6.2.4 Calculate the viscosity index, VI, of the petroleum product using the following equation:

$$VI = \frac{L - U}{L - H} \times 100 \quad (3)$$

where *U* is the kinematic viscosity, expressed in millimetres squared per second, at 40 °C of the petroleum product whose viscosity index is to be calculated.

Table 1 — Measured values of L and H for kinematic viscosity

Kinematic viscosity at 100 °C mm ² /s	L	H	Kinematic viscosity at 100 °C mm ² /s	L	H
2,00	7,994	6,394	6,00	57,97	38,19
2,10	8,640	6,894	6,10	59,74	39,17
2,20	9,309	7,410	6,20	61,52	40,15
2,30	10,00	7,944	6,30	63,32	41,13
2,40	10,71	8,496	6,40	65,18	42,14
2,50	11,45	9,063	6,50	67,12	43,18
2,60	12,21	9,647	6,60	69,16	44,24
2,70	13,00	10,25	6,70	71,29	45,33
2,80	13,80	10,87	6,80	73,48	46,44
2,90	14,63	11,50	6,90	75,72	47,51
3,00	15,49	12,15	7,00	78,00	48,57
3,10	16,36	12,82	7,10	80,25	49,61
3,20	17,26	13,51	7,20	82,39	50,69
3,30	18,18	14,21	7,30	84,53	51,78
3,40	19,12	14,93	7,40	86,66	52,88
3,50	20,09	15,66	7,50	88,85	53,98
3,60	21,08	16,42	7,60	91,04	55,09
3,70	22,09	17,19	7,70	93,20	56,20
3,80	23,13	17,97	7,80	95,43	57,31
3,90	24,19	18,77	7,90	97,72	58,45
4,00	25,32	19,56	8,00	100,0	59,60
4,10	26,50	20,37	8,10	102,3	60,74
4,20	27,75	21,21	8,20	104,6	61,89
4,30	29,07	22,05	8,30	106,9	63,05
4,40	30,48	22,92	8,40	109,2	64,18
4,50	31,96	23,81	8,50	111,5	65,32
4,60	33,52	24,71	8,60	113,9	66,48
4,70	35,13	25,63	8,70	116,2	67,64
4,80	36,79	26,57	8,80	118,5	68,79
4,90	38,50	27,53	8,90	120,9	69,94
5,00	40,23	28,49	9,00	123,3	71,10
5,10	41,99	29,46	9,10	125,7	72,27
5,20	43,76	30,43	9,20	128,0	73,42
5,30	45,53	31,40	9,30	130,4	74,57
5,40	47,31	32,37	9,40	132,8	75,73
5,50	49,09	33,34	9,50	135,3	76,91
5,60	50,87	34,32	9,60	137,7	78,08
5,70	52,64	35,29	9,70	140,1	79,27
5,80	54,42	36,26	9,80	142,7	80,46
5,90	56,20	37,23	9,90	145,2	81,67

Table 1 — Measured values *L* and *H* for kinematic viscosity (continued)

Kinematic viscosity at 100 °C mm ² /s	<i>L</i>	<i>H</i>	Kinematic viscosity at 100 °C mm ² /s	<i>L</i>	<i>H</i>
10,0	147,7	82,87	14,0	263,3	135,4
10,1	150,3	84,08	14,1	266,6	136,8
10,2	152,9	85,30	14,2	269,8	138,2
10,3	155,4	86,51	14,3	273,0	139,6
10,4	158,0	87,72	14,4	276,3	141,0
10,5	160,6	88,95	14,5	279,6	142,4
10,6	163,2	90,19	14,6	283,0	143,9
10,7	165,8	91,40	14,7	286,4	145,3
10,8	168,5	92,65	14,8	289,7	146,8
10,9	171,2	93,92	14,9	293,0	148,2
11,0	173,9	95,19	15,0	296,5	149,7
11,1	176,6	96,45	15,1	300,0	151,2
11,2	179,4	97,71	15,2	303,4	152,6
11,3	182,1	98,97	15,3	306,9	154,1
11,4	184,9	100,2	15,4	310,3	155,6
11,5	187,6	101,5	15,5	313,9	157,0
11,6	190,4	102,8	15,6	317,5	158,6
11,7	193,3	104,1	15,7	321,1	160,1
11,8	196,2	105,4	15,8	324,6	161,6
11,9	199,0	106,7	15,9	328,3	163,1
12,0	201,9	108,0	16,0	331,9	164,6
12,1	204,8	109,4	16,1	335,5	166,1
12,2	207,8	110,7	16,2	339,2	167,7
12,3	210,7	112,0	16,3	342,9	169,2
12,4	213,6	113,3	16,4	346,6	170,7
12,5	216,6	114,7	16,5	350,3	172,3
12,6	219,6	116,0	16,6	354,1	173,8
12,7	222,6	117,4	16,7	358,0	175,4
12,8	225,7	118,7	16,8	361,7	177,0
12,9	228,8	120,1	16,9	365,6	178,6
13,0	231,9	121,5	17,0	369,4	180,2
13,1	235,0	122,9	17,1	373,3	181,7
13,2	238,1	124,2	17,2	377,1	183,3
13,3	241,2	125,6	17,3	381,0	184,9
13,4	244,3	127,0	17,4	384,9	186,5
13,5	247,4	128,4	17,5	388,9	188,1
13,6	250,6	129,8	17,6	392,7	189,7
13,7	253,8	131,2	17,7	396,7	191,3
13,8	257,0	132,6	17,8	400,7	192,9
13,9	260,1	134,0	17,9	404,6	194,6

Table 1 — Measured values *L* and *H* for kinematic viscosity (continued)

Kinematic viscosity at 100 °C mm ² /s	<i>L</i>	<i>H</i>	Kinematic viscosity at 100 °C mm ² /s	<i>L</i>	<i>H</i>
18,0	408,6	196,2	24,0	683,9	301,8
18,1	412,6	197,8	24,2	694,5	305,6
18,2	416,7	199,4	24,4	704,8	309,4
18,3	420,7	201,0	24,6	714,9	313,2
18,4	424,9	202,6	24,8	725,7	317,0
18,5	429,0	204,3	25,0	736,5	320,9
18,6	433,2	205,9	25,2	747,2	324,9
18,7	437,3	207,6	25,4	758,2	328,8
18,8	441,5	209,3	25,6	768,8	332,7
18,9	445,7	211,0	25,8	779,7	336,7
19,0	449,9	212,7	26,0	790,4	340,5
19,1	454,2	214,4	26,2	801,6	344,4
19,2	458,4	216,1	26,4	812,8	348,4
19,3	462,7	217,7	26,6	824,1	352,3
19,4	467,0	219,4	26,8	835,5	356,4
19,5	471,3	221,1	27,0	847,0	360,5
19,6	475,7	222,8	27,2	857,5	364,6
19,7	479,7	224,5	27,4	869,0	368,3
19,8	483,9	226,2	27,6	880,6	372,3
19,9	488,6	227,8	27,8	892,3	376,4
20,0	493,2	229,5	28,0	904,1	380,6
20,2	501,9	233,0	28,2	915,8	384,6
20,4	510,8	236,4	28,4	927,6	388,8
20,6	519,9	240,1	28,6	938,6	393,0
20,8	528,8	243,5	28,8	951,2	396,6
21,0	538,4	247,1	29,0	963,4	401,1
21,2	547,5	250,7	29,2	975,4	405,3
21,4	556,7	254,2	29,4	987,1	409,5
21,6	566,4	257,8	29,6	998,9	413,5
21,8	575,6	261,5	29,8	1 011	417,6
22,0	585,2	264,9	30,0	1 024	421,7
22,2	595,0	268,6	30,5	1 055	432,4
22,4	604,3	272,3	31,0	1 086	443,2
22,6	614,2	275,8	31,5	1 119	454,0
22,8	624,1	279,6	32,0	1 151	464,9
23,0	633,6	283,3	32,5	1 184	475,9
23,2	643,4	286,8	33,0	1 217	487,0
23,4	653,8	290,5	33,5	1 251	498,1
23,6	663,3	294,4	34,0	1 286	509,6
23,8	673,7	297,9	34,5	1 321	521,1

Table 1 — Measured values *L* and *H* for kinematic viscosity (continued)

Kinematic viscosity at 100 °C mm ² /s	<i>L</i>	<i>H</i>	Kinematic viscosity at 100 °C mm ² /s	<i>L</i>	<i>H</i>
35,0	1 356	532,5	55,0	3 126	1 066
35,5	1 391	544,0	55,5	3 180	1 082
36,0	1 427	555,6	56,0	3 233	1 097
36,5	1 464	567,1	56,5	3 286	1 112
37,0	1 501	579,3	57,0	3 340	1 127
37,5	1 538	591,3	57,5	3 396	1 143
38,0	1 575	603,1	58,0	3 452	1 159
38,5	1 613	615,0	58,5	3 507	1 175
39,0	1 651	627,1	59,0	3 563	1 190
39,5	1 691	639,2	59,5	3 619	1 206
40,0	1 730	651,8	60,0	3 676	1 222
40,5	1 770	664,2	60,5	3 734	1 238
41,0	1 810	676,6	61,0	3 792	1 254
41,5	1 851	689,1	61,5	3 850	1 270
42,0	1 892	701,9	62,0	3 908	1 286
42,5	1 935	714,9	62,5	3 966	1 303
43,0	1 978	728,2	63,0	4 026	1 319
43,5	2 021	741,3	63,5	4 087	1 336
44,0	2 064	754,4	64,0	4 147	1 352
44,5	2 108	767,6	64,5	4 207	1 369
45,0	2 152	780,9	65,0	4 268	1 386
45,5	2 197	794,5	65,5	4 329	1 402
46,0	2 243	808,2	66,0	4 392	1 419
46,5	2 288	821,9	66,5	4 455	1 436
47,0	2 333	835,5	67,0	4 517	1 454
47,5	2 380	849,2	67,5	4 580	1 471
48,0	2 426	863,0	68,0	4 645	1 488
48,5	2 473	876,9	68,5	4 709	1 506
49,0	2 521	890,9	69,0	4 773	1 523
49,5	2 570	905,3	69,5	4 839	1 541
50,0	2 618	919,6	70,0	4 905	1 558
50,5	2 667	933,6			
51,0	2 717	948,2			
51,5	2 767	962,9			
52,0	2 817	977,5			
52,5	2 867	992,1			
53,0	2 918	1 007			
53,5	2 969	1 021			
54,0	3 020	1 036			
54,5	3 073	1 051			

6.2.5 The calculation method using Table 1 is indicated by the example shown below:

Measured oil properties	
Kinematic viscosity at 40 °C, mm ² /s	73,30
Kinematic viscosity at 100 °C, mm ² /s	8,860

From Table 1 by interpolation, $L = 119,94$

From Table 1 by interpolation, $H = 69,48$

$$VI = \frac{119,94 - 73,30}{119,94 - 69,48} \times 100$$

$$VI = 92,43$$

$$VI = 92$$

6.3 Procedure B

6.3.1 Use procedure B for petroleum products of viscosity index 100 or greater (see the note to 8.2).

6.3.2 If the kinematic viscosity of the petroleum product at 100 °C is in the range 2 mm²/s to 70 mm²/s, extract the corresponding value of H from Table 1. Measured values which are not listed, but which are within the range of Table 1, may be obtained by linear interpolation.

6.3.3 If the measured kinematic viscosity of the petroleum product at 100 °C is greater than 70 mm²/s, calculate the value of H using equation (2) (see 6.2.3 for the definition of Y)

$$H = 0,168 4Y^2 + 11,85Y - 97 \quad (2)$$

6.3.4 Calculate the viscosity index, VI, of the petroleum product using the following equation:

$$VI = \frac{(10^n) - 1}{0,007 15} + 100 \quad (4)$$

where

$$n = \frac{\log_{10} H - \log_{10} U}{\log_{10} Y}$$

U is the kinematic viscosity, expressed in millimetres squared per second, at 40 °C of the petroleum product whose viscosity index is to be calculated;

Y is the kinematic viscosity, expressed in millimetres squared per second, at 100 °C of the petroleum product whose viscosity index is to be calculated.

6.3.5 The method is illustrated by the example shown below:

Measured oil properties	
Kinematic viscosity at 40 °C, mm ² /s	22,83
Kinematic viscosity at 100 °C, mm ² /s	5,050