
Rolling bearings — Accessories —

Part 1:

**Dimensions for adapter sleeve
assemblies and withdrawal sleeves**

Roulements — Accessoires —

Partie 1: Dimensions des manchons de serrage et de démontage

STANDARDSISO.COM : Click to view the full PDF of ISO 2982-1:2013



STANDARDSISO.COM : Click to view the full PDF of ISO 2982-1:2013



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	2
5 Dimensions	3
5.1 General	3
5.2 Adapter sleeve assemblies with taper 1:12	3
5.3 Withdrawal sleeves with taper 1:12	5
5.4 Withdrawal sleeves with taper 1:30	7

STANDARDSISO.COM : Click to view the full PDF of ISO 2982-1:2013

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 2982-1 was prepared by Technical Committee ISO/TC 4, *Rolling bearings*.

This second edition cancels and replaces the first edition (ISO 2982-1:1995), which has been technically revised. In particular, the title has been corrected and approximate values for B_2 are indicated.

ISO 2982 consists of the following parts, under the general title: *Rolling bearings — Accessories*:

- *Part 1: Dimensions for adapter sleeve assemblies and withdrawal sleeves*
- *Part 2: Dimensions for locknuts and locking devices*

Rolling bearings — Accessories —

Part 1:

Dimensions for adapter sleeve assemblies and withdrawal sleeves

1 Scope

This part of ISO 2982 specifies:

- boundary dimensions of adapter sleeves with taper 1:12 and withdrawal sleeves with tapers 1:12 and 1:30 for rolling bearings of a number of dimension series as specified in ISO 15;
- the outside diameter of suitable locknuts;
- distance from bearing small bore face to outer face of locknut;
- distance from bearing small bore face to outer face of bolt head;
- overall length of withdrawal sleeve and bearing ring.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 15, *Rolling bearings — Radial bearings — Boundary dimensions, general plan*

ISO 2982-2, *Rolling bearings — Accessories — Part 2: Dimensions for locknuts and locking devices*

ISO 5593, *Rolling bearings — Vocabulary*

ISO 15241, *Rolling bearings — Symbols for physical quantities*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5593 and the following apply.

3.1

adapter sleeve assembly

assembly comprising an adapter sleeve, a locknut, and a locking device

3.2

locking clip

part in C-shape for securing a locknut

3.3

locking clip assembly


assembly comprising a locking clip and a bolt

4 Symbols

For the purposes of this document, the symbols given in ISO 15241 and the following apply.

The symbols shown in [Figure 1](#) and the values given in [Table 1](#), [Table 2](#), [Table 3](#), [Table 4](#) and [Table 5](#) denote nominal dimensions, unless specified otherwise.

- B_1 adapter sleeve length or withdrawal sleeve length
- B_2 distance from bearing small bore face to outer face of locknut
- B_3 distance from bearing small bore face to outer face of bolt head
- B_4 overall length of withdrawal sleeve and bearing ring
- B_5 slot width (for lockwasher inner tab or locking clip)
- B_6 slot length
- d bearing bore diameter
- d_1 bore diameter of sleeve
- d_2 outside diameter of locknut
- G designation of screw thread



a) Adapter sleeve with locknut and lockwasher

b) Adapter sleeve with locknut and locking clip assembly

c) Withdrawal sleeve

Figure 1 — Adapter sleeve assemblies and withdrawal sleeve

5 Dimensions

5.1 General

Dimensions of adapter sleeve assemblies and boundary dimensions of withdrawal sleeves and overall lengths of withdrawal sleeve and bearing ring are given in [Table 1](#), [Table 2](#), [Table 3](#), [Table 4](#) and [Table 5](#).

Thread lengths are not specified but shall be appropriate for securing adapter sleeve with locknut or for withdrawing a rolling bearing on the withdrawal sleeve with locknut. Dimensions of locknuts, lockwashers, and locking clip assemblies for the adapter sleeves are given in ISO 2982-2. The locknuts are also suitable for the dismounting of the withdrawal sleeves.

5.2 Adapter sleeve assemblies with taper 1:12

Dimensions of adapter sleeve assemblies with taper 1:12 are given in [Table 1](#), [Table 2](#) and [Table 3](#). Slot lengths, B_6 , are not specified but

- shall be at least long enough that lockwasher or locking clip can be installed when rolling bearing, adapter sleeve, and locknut are secured onto a shaft, and
- shall not be longer than 1,3 times thread lengths.

Table 1 — Dimensions of adapter sleeve assemblies with taper 1:12 ($15 \leq d \leq 110$)

Dimensions in millimetres

d	d_1	B_2 ≈	B_5 min.	d_2	B_1					G
					Suitable for bearing dimension series					
					02	22, 03	31	32	23	
15	12	6	5	25	19	22	—	—	25	M15 × 1
17	14	6	5	28	20	24	—	—	27	M17 × 1
20	17	7	5	32	24	28	—	—	31	M20 × 1
25	20	8	6	38	26	29	—	—	35	M25 × 1,5
30	25	8	6	45	27	31	—	—	38	M30 × 1,5
35	30	9	7	52	29	35	—	—	43	M35 × 1,5
40	35	10	7	58	31	36	—	—	46	M40 × 1,5
45	40	11	7	65	33	39	—	—	50	M45 × 1,5
50	45	12	7	70	35	42	—	—	55	M50 × 1,5
55	50	12	9	75	37	45	—	—	59	M55 × 2
60	55	13	9	80	38	47	—	—	62	M60 × 2
65	60	14	9	85	40	50	—	—	65	M65 × 2
70	60	14	9	92	41	52	—	—	68	M70 × 2
75	65	15	9	98	43	55	—	—	73	M75 × 2
80	70	17	11	105	46	59	—	—	78	M80 × 2
85	75	18	11	110	50	63	—	—	82	M85 × 2
90	80	18	11	120	52	65	—	86	86	M90 × 2
95	85	19	11	125	55	68	—	90	90	M95 × 2
100	90	20	13	130	58	71	76	97	97	M100 × 2
105	95	20	13	140	60	74	80	101	101	M105 × 2
110	100	21	13	145	63	77	81	105	105	M110 × 2

Table 2 — Dimensions of adapter sleeve assemblies with taper 1:12 ($120 \leq d \leq 440$)

Dimensions in millimetres

<i>d</i>	<i>d</i> ₁	<i>B</i> ₂ ≈	<i>B</i> ₃ max.	<i>B</i> ₅ min.	<i>d</i> ₂	<i>B</i> ₁		<i>d</i> ₂	<i>B</i> ₁		<i>G</i>
						Suitable for bearing dimension series			Suitable for bearing dimension series		
						39	30, 02, 12		31, 22, 03, 13	32, 23	
120	110	22	—	15	145	60	72	155	88	112	M120 × 2
130	115	23	—	15	155	65	80	165	92	121	M130 × 2
140	125	24	—	17	165	66	82	180	97	131	M140 × 2
150	135	26	—	17	180	76	87	195	111	139	M150 × 2
160	140	28	—	19	190	78	93	210	119	147	M160 × 3
170	150	29	—	19	200	79	101	220	122	154	M170 × 3
180	160	30	—	21	210	87	109	230	131	161	M180 × 3
190	170	31	—	21	220	89	112	240	141	169	M190 × 3
200	180	32	—	21	240	98	120	250	150	176	M200 × 3
220	200	—	41	20	260	96	126	—	—	—	Tr220 × 4
220	200	35	—	25	—	—	—	280	161	186	Tr220 × 4
240	220	—	46	20	290	101	133	—	—	—	Tr240 × 4
240	220	37	—	25	—	—	—	300	172	199	Tr240 × 4
260	240	—	46	20	310	116	145	—	—	—	Tr260 × 4
260	240	39	—	29	—	—	—	330	190	211	Tr260 × 4
280	260	—	50	24	330	121	152	—	—	—	Tr280 × 4
280	260	41	—	29	—	—	—	350	195	224	Tr280 × 4
300	280	—	54	24	360	140	168	—	—	—	Tr300 × 4
300	280	—	53	24	—	—	—	380	208	240	Tr300 × 4
320	300	—	55	24	380	140	171	—	—	—	Tr320 × 5
320	300	—	56	24	—	—	—	400	226	258	Tr320 × 5
340	320	—	58	24	400	144	187	—	—	—	Tr340 × 5
340	320	—	72	28	—	—	—	440	254	288	Tr340 × 5
360	340	—	58	28	420	144	188	—	—	—	Tr360 × 5
360	340	—	75	28	—	—	—	460	259	299	Tr360 × 5
380	360	—	62	28	450	164	193	—	—	—	Tr380 × 5
380	360	—	77	32	—	—	—	490	264	310	Tr380 × 5
400	380	—	66	28	470	168	210	—	—	—	Tr400 × 5
400	380	—	82	32	—	—	—	520	272	328	Tr400 × 5
420	400	—	66	32	490	168	212	—	—	—	Tr420 × 5
420	400	—	90	32	—	—	—	540	304	352	Tr420 × 5
440	410	—	77	32	520	189	228	—	—	—	Tr440 × 5
440	410	—	90	36	—	—	—	560	307	361	Tr440 × 5

Table 3 — Dimensions of adapter sleeve assemblies with taper 1:12 ($460 \leq d \leq 1\ 060$)

Dimensions in millimetres

d	d_1	B_3 max.	B_5 min.	d_2	B_1		d_2	B_1		G
					Suitable for bearing dimension series			Suitable for bearing dimension series		
					39	30		31	32	
460	430	77	32	540	189	234	—	—	—	Tr460 × 5
460	430	95	36	—	—	—	580	326	382	Tr460 × 5
480	450	77	36	560	200	237	—	—	—	Tr480 × 5
480	450	95	36	—	—	—	620	335	397	Tr480 × 5
500	470	85	36	580	208	247	—	—	—	Tr500 × 5
500	470	100	40	—	—	—	630	356	428	Tr500 × 5
530	500	90	40	630	216	265	—	—	—	Tr530 × 6
530	500	105	40	—	—	—	670	364	447	Tr530 × 6
560	530	97	40	650	227	282	—	—	—	Tr560 × 6
560	530	110	45	—	—	—	710	377	462	Tr560 × 6
600	560	97	40	700	239	289	—	—	—	Tr600 × 6
600	560	110	45	—	—	—	750	399	487	Tr600 × 6
630	600	97	45	730	254	301	—	—	—	Tr630 × 6
630	600	120	50	—	—	—	800	424	521	Tr630 × 6
670	630	102	45	780	264	324	—	—	—	Tr670 × 6
670	630	131	50	—	—	—	850	456	558	Tr670 × 6
710	670	112	50	830	286	342	—	—	—	Tr710 × 7
710	670	135	55	—	—	—	900	467	572	Tr710 × 7
750	710	112	55	870	291	356	—	—	—	Tr750 × 7
750	710	141	60	—	—	—	950	493	603	Tr750 × 7
800	750	112	55	920	303	366	—	—	—	Tr800 × 7
800	750	141	60	—	—	—	1 000	505	618	Tr800 × 7
850	800	115	60	980	308	380	—	—	—	Tr850 × 7
850	800	147	70	—	—	—	1 060	536	651	Tr850 × 7
900	850	125	60	1 030	326	400	—	—	—	Tr900 × 7
900	850	154	70	—	—	—	1 120	557	660	Tr900 × 7
950	900	125	60	1 080	344	420	—	—	—	Tr950 × 8
950	900	154	70	—	—	—	1 170	583	675	Tr950 × 8
1 000	950	125	60	1 140	358	430	—	—	—	Tr1000 × 8
1 000	950	154	70	—	—	—	1 240	609	707	Tr1000 × 8
1 060	1 000	125	60	1 200	372	447	—	—	—	Tr1060 × 8
1 060	1 000	154	70	—	—	—	1 300	622	—	Tr1060 × 8

5.3 Withdrawal sleeves with taper 1:12

Boundary dimensions of withdrawal sleeves with taper 1:12 and overall lengths of withdrawal sleeve and bearing ring are given in [Table 4](#).

Table 4 — Boundary dimensions of withdrawal sleeves with taper 1:12, and overall lengths of withdrawal sleeve and bearing ring

Dimensions in millimetres

d	d ₁	B ₁ max.	B ₄	B ₁ max.	B ₄	B ₁ max.	B ₄	B ₁ max.	B ₄	B ₁ max.	B ₄	B ₁ max.	B ₄	B ₁ max.	B ₄	B ₁ max.	B ₄	G
		Suitable for bearing dimension series																
		39		02		30		03, 13		22		31		32		23		
40	35	—	—	25	27	—	—	29	32	29	32	—	—	—	—	40	43	M45 × 1,5
45	40	—	—	26	29	—	—	31	34	31	34	—	—	—	—	44	47	M50 × 1,5
50	45	—	—	28	31	—	—	35	38	35	38	—	—	—	—	50	53	M55 × 2
55	50	—	—	29	32	—	—	37	40	37	40	—	—	—	—	54	57	M60 × 2
60	55	—	—	32	35	—	—	40	43	40	43	—	—	—	—	58	61	M65 × 2
65	60	—	—	32,5	36	—	—	42	45	42	45	—	—	—	—	61	64	M70 × 2
70	65	—	—	33,5	37	—	—	43	47	43	47	—	—	—	—	64	68	M75 × 2
75	70	—	—	34,5	38	—	—	45	49	45	49	—	—	—	—	68	72	M80 × 2
80	75	—	—	35,5	39	—	—	48	52	48	52	—	—	—	—	71	75	M90 × 2
85	80	—	—	38,5	42	—	—	52	56	52	56	—	—	—	—	74	78	M95 × 2
90	85	—	—	40	44	—	—	53	57	53	57	—	—	63	67	79	83	M100 × 2
95	90	—	—	43	47	—	—	57	61	57	61	—	—	67	71	85	89	M105 × 2
100	95	—	—	45	49	—	—	59	63	59	63	64	68	73	77	90	94	M110 × 2
105	100	—	—	47	51	—	—	62	66	62	66	68	72	78	82	—	—	M115 × 2
105	100	—	—	—	—	—	—	—	—	—	—	—	—	—	—	94	98	M120 × 2
110	105	—	—	50	54	—	—	63	67	68	72	68	72	82	86	98	102	M120 × 2
120	115	—	—	53	57	60	64	69	73	75	79	75	79	90	94	105	109	M130 × 2
130	125	—	—	53	57	67	71	74	78	78	82	78	82	98	102	115	119	M140 × 2
140	135	—	—	56	61	68	73	77	82	83	88	83	88	104	109	125	130	M150 × 2
150	145	—	—	60	65	72	77	83	88	96	101	96	101	114	119	135	140	M160 × 3
160	150	—	—	64	69	77	82	88	93	103	108	103	108	124	130	140	146	M170 × 3
170	160	59	64	69	74	85	90	93	98	104	109	104	109	134	140	146	152	M180 × 3
180	170	66	71	69	74	92	98	—	—	105	110	116	122	140	146	154	160	M190 × 3
190	180	66	71	73	78	96	102	—	—	112	117	125	131	145	152	160	167	M200 × 3
200	190	77	83	77	82	102	108	—	—	—	—	—	—	—	—	—	—	Tr210 × 4
200	190	—	—	—	—	—	—	—	—	118	123	134	140	153	160	170	177	Tr220 × 4
220	200	77	83	85	91	111	117	—	—	—	—	—	—	—	—	—	—	Tr230 × 4
220	200	—	—	—	—	—	—	—	—	130	136	145	151	181	189	181	189	Tr240 × 4
240	220	77	83	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Tr250 × 4
240	220	—	—	96	102	116	123	—	—	144	150	154	161	189	197	189	197	Tr260 × 4
260	240	94	100	105	111	128	135	—	—	155	161	172	179	205	213	205	213	Tr280 × 4
280	260	94	100	105	113	131	139	—	—	155	163	175	183	212	220	212	220	Tr300 × 4
300	280	112	119	—	—	145	153	—	—	170	178	192	200	228	236	—	—	Tr320 × 5
320	300	112	119	—	—	149	157	—	—	180	190	209	217	246	254	—	—	Tr340 × 5
340	320	112	119	—	—	162	171	—	—	—	—	225	234	264	273	—	—	Tr360 × 5
360	340	112	119	—	—	167	176	—	—	—	—	229	238	274	283	—	—	Tr380 × 5
380	360	130	138	—	—	170	180	—	—	—	—	232	242	284	294	—	—	Tr400 × 5
400	380	130	138	—	—	183	193	—	—	—	—	240	250	302	312	—	—	Tr420 × 5
420	400	130	138	—	—	186	196	—	—	—	—	266	276	321	331	—	—	Tr440 × 5
440	420	145	153	—	—	194	205	—	—	—	—	270	281	330	341	—	—	Tr460 × 5
460	440	145	153	—	—	202	213	—	—	—	—	285	296	349	360	—	—	Tr480 × 5
480	460	158	167	—	—	205	217	—	—	—	—	295	307	364	376	—	—	Tr500 × 5
500	480	162	172	—	—	209	221	—	—	—	—	313	325	393	405	—	—	Tr530 × 6
530	500	175	185	—	—	230	242	—	—	—	—	325	337	412	424	—	—	Tr560 × 6
560	530	180	190	—	—	240	252	—	—	—	—	335	347	422	434	—	—	Tr600 × 6
600	570	192	202	—	—	245	259	—	—	—	—	355	369	445	459	—	—	Tr630 × 6
630	600	210	222	—	—	258	272	—	—	—	—	375	389	475	489	—	—	Tr670 × 6
670	630	216	228	—	—	280	294	—	—	—	—	395	409	500	514	—	—	Tr710 × 7
710	670	228	240	—	—	286	302	—	—	—	—	405	421	515	531	—	—	Tr750 × 7
750	710	234	246	—	—	300	316	—	—	—	—	425	441	540	556	—	—	Tr800 × 7
800	750	245	257	—	—	308	326	—	—	—	—	438	456	550	568	—	—	Tr850 × 7

Table 4 (continued)

d	d ₁	B ₁ max.	B ₄	B ₁ max.	B ₄	B ₁ max.	B ₄	B ₁ max.	B ₄	B ₁ max.	B ₄	B ₁ max.	B ₄	B ₁ max.	B ₄	B ₁ max.	B ₄	G
		Suitable for bearing dimension series																
		39		02		30		03, 13		22		31		32		23		
850	800	258	270	—	—	325	343	—	—	—	—	462	480	585	603	—	—	Tr900 × 7
900	850	265	277	—	—	335	355	—	—	—	—	475	495	585	605	—	—	Tr950 × 8
950	900	282	297	—	—	355	375	—	—	—	—	500	520	600	620	—	—	Tr1000 × 8
1 000	950	296	311	—	—	365	387	—	—	—	—	525	547	630	652	—	—	Tr1060 × 8
1 060	1 000	310	325	—	—	385	407	—	—	—	—	540	562	—	—	—	—	Tr1120 × 8

5.4 Withdrawal sleeves with taper 1:30

Boundary dimensions of withdrawal sleeves with taper 1:30 and overall lengths of withdrawal sleeve and bearing ring are given in [Table 5](#).

STANDARDSISO.COM : Click to view the full PDF of ISO 2982-1:2013