International Standard

ISO 3098/4

Technical drawings — Lettering — Part 4 : Cyrillic characters

Dessins techniques — Écriture — Partie 4 : Caractères cyrilliques

First edition — 1984-06-15

UDC 744.43 : 003.349.2/.7   Ref. No. ISO 3098/4-1984 (E)

Descriptors : drawings, technical drawings, symbols, letters (symbols), cyrillic characters, writing.

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been authorized has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 3098/4 was developed by Technical Committee ISO/TC 10, *Technical drawings*, and was circulated to the member bodies in April 1982.

It has been approved by the member bodies of the following countries :

Australia	France	Poland
Austria	Germany, F. R.	Romania
Belgium	Hungary	Spain
Canada	India	Sweden
China	Italy	Switzerland
Czechoslovakia	Japan	USSR
Denmark	Netherlands	Venezuela
Egypt, Arab Rep. of	New Zealand	Yugoslavia
Finland	Norway	

No member body expressed disapproval of the document.

Technical drawings — Lettering — Part 4 : Cyrillic characters

1 Scope and field of application

This part of ISO 3098 specifies proportions and establishes dimensions of cyrillic Russian characters[1] for use with texts and/or as symbols in technical drawings and associated documents. It primarily concerns characters written with the aid of stencils, but is equally applicable to freehand lettering or other appropriate methods.

2 Reference

ISO 3098/1, *Technical drawings — Lettering — Part 1 : Currently used characters.*

3 General requirements

See ISO 3098/1.

4 Dimensions

See ISO 3098/1.

5 Examples

The following examples are given only as a guide to illustrate the principles established in clauses 3 and 4.

NOTE — To obtain constant line-density, avoid blotting at intersecting lines and facilitate writing, the characters shall be formed so that lines cross, or meet, at approximately right angles.

---

1) Other cyrillic alphabets include a number of additional characters which should be formed in a similar way.

Lettering A inclined

АБВГДЕЖЗИЙКЛМНОПР

СТУФХЦЧШЩЪЫЬЭЮЯ

абвгдежзийклмнопрст

уфхцчшщъыьэюя

Lettering A vertical

АБВГДЕЖЗИЙКЛМНОПР

СТУФХЦЧШЩЪЫЬЭЮЯ

абвгдежзийклмнопрст

уфхцчшщъыьэюя

Lettering B inclined

АБВГДЕЖЗИЙКЛ

МНОПРСТУФХЦЧ

ЩЦЪЫЬЭЮЯ

абвгдежзийклм

нопрстуфхцчш

щцъыьэюя