
INTERNATIONAL STANDARD



31/II

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Quantities and units of periodic and related phenomena

Grandeurs et unités de phénomènes périodiques et connexes

First edition — 1978-03-15

STANDARDSISO.COM : Click to view the full PDF of ISO 31-2:1978

UDC 53.081

Ref. No. ISO 31/II-1978 (E)

Descriptors : quantities, units of measurement, periodic variations, frequencies, waveforms, damping, definitions, symbols, international system of units.

Price based on 6 pages

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been set up has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 31/II was developed by Technical Committee ISO/TC 12, *Quantities, units, symbols, conversion factors and conversion tables*, and was circulated to the member bodies in August 1975.

It has been approved by the member bodies of the following countries :

Australia	Germany	Poland
Austria	Hungary	Portugal
Belgium	India	Romania
Bulgaria	Ireland	South Africa, Rep. of
Canada	Israel	Switzerland
Czechoslovakia	Mexico	Turkey
Denmark	Netherlands	United Kingdom
Finland	Norway	

The member bodies of the following countries expressed disapproval of the document on technical grounds :

Japan*
Sweden
U.S.A.
U.S.S.R.

- * Disagreement concerning the decimal marker only.

This International Standard cancels and replaces ISO Recommendation R 31/II-1958, of which it constitutes a technical revision.

Quantities and units of periodic and related phenomena

INTRODUCTION

This document, containing a table of *quantities and units of periodic and related phenomena*, is part II of ISO 31, which deals with quantities and units in the various fields of science and technology. The complete list of parts of ISO 31 is as follows :

Part 0 : *General introduction — General principles concerning quantities, units and symbols.*

Part I : *Quantities and units of space and time.*

Part II : *Quantities and units of periodic and related phenomena.*

Part III : *Quantities and units of mechanics.*

Part IV : *Quantities and units of heat.*

Part V : *Quantities and units of electricity and magnetism.*

Part VI : *Quantities and units of light and related electromagnetic radiations.*

Part VII : *Quantities and units of acoustics.*

Part VIII : *Quantities and units of physical chemistry and molecular physics.*

Part IX : *Quantities and units of atomic and nuclear physics.*

Part X : *Quantities and units of nuclear reactions and ionizing radiations.*

Part XI : *Mathematical signs and symbols for use in the physical sciences and technology.*

Part XII : *Dimensionless parameters.*

Part XIII : *Quantities and units of solid state physics.*

Arrangement of the tables

The tables of quantities and units in ISO 31 are arranged so that the quantities are presented on left-hand pages and the units on corresponding right-hand pages.

All units between two full lines belong to the quantities between the corresponding full lines on the left-hand pages.

Where the numbering of the items has been changed in the revision of a part of ISO 31, the number in the preceding edition is shown in parentheses on the left-hand page under the new number for the quantity; a dash is used to indicate that the item in question did not appear in the preceding edition.

Tables of quantities

The most important quantities within the field of this document are given together with their symbols and, in most cases, definitions. These definitions are given merely for identification; they are not intended to be complete.

The vectorial character of some quantities is pointed out, especially when this is needed for the definitions, but no attempt is made to be complete or consistent.

In most cases only one symbol for the quantity is given¹⁾; where two or more symbols are given for one quantity and no special distinction is made, they are on an equal footing.

Tables of units

Units for the corresponding quantities are given together with the international symbols and the definitions. For further information, see also part 0.

The units are arranged in the following way :

1) The names of the SI units are given in large print (larger than text size). The SI units and their decimal multiples and sub-multiples formed by means of the SI prefixes are particularly recommended. The decimal multiples and sub-multiples are not explicitly mentioned.

2) The names of non-SI units which may be used together with SI units because of their practical importance or because of their use in specialized fields are given in normal print (text size).

1) When two types of sloping letters exist (for example as with ϑ , θ ; φ , ϕ ; and g , g) only one of these is given. This does not mean that the other is not equally acceptable.

3) The names of non-SI units which may be used temporarily together with SI units are given in small print (smaller than text size).

The units in classes 2 and 3 are separated by a broken line from the SI units for the quantities concerned.

4) Non-SI units which should not be used together with SI units are given in annexes in some parts of ISO 31. The annexes are not integral parts of the standard. They are arranged in three groups :

a) *Units of the CGS-system with special names*

It is generally preferable not to use CGS-units with special names and symbols together with SI units.

b) *Units based on the foot, pound and second and some other unit*

c) *Other units*

These are given for information, especially regarding the conversion factor. The use of those units marked with † is deprecated.

Remark on supplementary units

The Conférence générale des poids et mesures (CGPM : General Conference for Weights and Measures) has classified the SI units, radian and steradian, as "supplementary units", deliberately leaving open the question of whether they are base units or derived units, and consequently the question of whether angle and solid angle are to be considered as base quantities or derived quantities.

In ISO 31, plane angle and solid angle are treated as derived quantities (see also part 0). They are defined in ISO 31 as ratios of two lengths and of two areas respectively, and consequently they are treated as dimensionless quantities. Although in this treatment the coherent unit for both quantities is the number 1, it is convenient to use the special names radian and steradian instead of the number 1 in many practical cases.

If plane angle and solid angle were treated as base quantities, the units radian and steradian would be base units and could not be considered as special names for the number 1. Such a treatment would require extensive changes in ISO 31.

Number of digits in numerical statements¹⁾

All numbers in the column "Definition" are exact.

In the column "Conversion factors" the conversion factors on which the calculation of others are based are normally given to seven significant digits. When they are exact and contain seven or fewer digits and where it is not obvious from the context, the word "exactly" is added, but when they can be terminated after more than seven digits they may be given in full. When the conversion factors are derived from experiment, they are given with the number of significant digits justified by the accuracy of the experiments. Generally, this means that in such cases the last digit only is in doubt. When, however, experiment justifies more than seven digits, the factor is usually rounded off to seven significant digits.

The other conversion factors are given to not more than six significant digits; when they are exactly known and contain six or fewer digits and where it is not obvious from the context, the word "exactly" is added.

Numbers in the column "Remarks" are given to a precision appropriate to the particular case.

SPECIAL REMARKS

Remark on level difference

In ISO 31, level difference is defined as the natural logarithm of the ratio of two quantities of the same kind. It is a dimensionless quantity. Although the coherent unit corresponding to this definition is the number 1, it is convenient in practice to use the special name neper.

The expression for level difference in terms of Briggsian logarithms follows from the definition.

The relation between the neper and the decibel, the units commonly used for expressing level difference, is

$$1 \text{ dB} = \frac{\ln 10}{20} \text{ Np}$$

The relation between the bel and decibel is $1 \text{ dB} = 10^{-1} \text{ B}$, but only the decibel is given in ISO 31 since the bel is not often used.

1) The decimal sign is a comma on the line. In documents in the English language, a comma or a dot on the line may be used.

STANDARDSISO.COM : Click to view the full PDF of ISO 31-2:1978

2. Periodic and related phenomena

Quantities
2-1.1 ... 2-6.2

Item No.	Quantity	Symbol	Definition	Remarks
2-1.1	period, periodic time	T	Time of one cycle	
2-2.1	time constant of an exponentially varying quantity	$\tau, (T)$	Time after which the quantity would reach its limit if it maintained its initial rate of variation	If a quantity is a function of time given by $F(t) = A + Be^{-t/\tau}$ then τ is the time constant
2-3.1	frequency	f, ν	$f = 1/T$	
2-3.2	rotational frequency	n	Number of revolutions divided by time	
2-4.1	angular frequency, circular frequency, pulsatance	ω	$\omega = 2\pi f$	
2-5.1	wavelength	λ		
2-6.1	wave number	σ	$\sigma = 1/\lambda$	The vector quantities corre- sponding to wave number and circular wave number are called wave vector and propagation vector respectively
2-6.2	circular wave number	k	$k = 2\pi\sigma$	

2. Periodic and related phenomena

Units
2-1.a . . . 2-6.a

Item No.	Name of unit	International symbol for unit	Definition	Conversion factors	Remarks
2-1.a	second	s			
2-2.a	second	s			
2-3.a	hertz	Hz	1 Hz is the frequency of a periodic phenomenon of which the period is 1 s		
2-3.b	reciprocal second, second to the power minus one	s ⁻¹	1 Hz = 1 s ⁻¹		The designations "revolutions per minute" (r/min) and "revolutions per second" (r/s) are widely used for rotational frequency in specifications on rotating machinery ¹⁾
2-4 a	radian per second	rad/s			See the Introduction
2-4 b	reciprocal second, second to the power minus one	s ⁻¹			
2-5 a	metre	m			
2-5.b	ångström	Å	1 Å = 10 ⁻¹⁰ m	1 Å = 10 ⁻¹⁰ m (exactly) = 0,1 mm	
2-6 a	reciprocal metre, metre to the power minus one	m ⁻¹			

1) See also IEC Publication 27-1 (1971)

Quantities
2-7.1 ... 2-11.3

2. Periodic and related phenomena (concluded)

Item No.	Quantity	Symbol	Definition	Remarks
2-7.1	amplitude level difference, field level difference	L_F	$L_F = \ln (F_1/F_2)$ where F_1 and F_2 represent two amplitudes of the same kind	These quantities are dimensionless. If $P_1/P_2 = (F_1/F_2)^2$ then $L_P = L_F$ Similar names, symbols and definitions apply to level differences based on other quantities which are linear or quadratic functions of the amplitudes, respectively. The quantity on which the level difference is based should be specified in the name and the subscript of the symbol, e.g. field strength level difference L_E .
2-8.1	power level difference	L_P	$L_P = \frac{1}{2} \ln (P_1/P_2)$ where P_1 and P_2 represent two powers	A level difference from a standard situation is described simply as "level"
2-9.1	damping coefficient	δ	If a quantity is a function of time given by $F(t) = Ae^{-\delta t} \sin [\omega (t - t_0)]$ then δ is the damping coefficient	$\tau = 1/\delta$ is the time constant (relaxation time) of the amplitude. The quantity $\omega (t - t_0)$ is called the phase
2-10.1	logarithmic decrement	λ	Product of damping coefficient and period.	This quantity is dimensionless
2-11.1	attenuation coefficient	α	If a quantity is a function of distance x given by $F(x) = Ae^{-\alpha x} \cos [\beta (x - x_0)]$ then α is the attenuation coefficient and β is the phase coefficient	The quantity $l = 1/\alpha$ is called the attenuation length. The quantity $\beta (x - x_0)$ is called the phase
2-11.2	phase coefficient	β		
2-11.3	propagation coefficient	γ	$\gamma = \alpha + j\beta$	

2. Periodic and related phenomena (concluded)

Units
2-7.a . . . 2-11.a

Item No.	Name of unit	International symbol for unit	Definition	Conversion factors	Remarks
2-7.a	neper	Np	1 Np is the amplitude level difference when $\ln (F_1/F_2) = 1$		See the Introduction, special remarks The numerical value of L_F expressed in decibels is given by $20 \lg(F_1/F_2)$ and the numerical value of L_P expressed in decibels is given by $10 \lg(P_1/P_2)$
2-7.b	decibel	dB	1 dB is the amplitude level difference when $20 \lg (F_1/F_2) = 1$	$1 \text{ dB} = \frac{\ln 10}{20} \text{ Np}$ $= 0,115\ 129 \text{ Np}$	
2-8.a	neper	Np	1 Np is the power level difference when $\frac{1}{2} \ln (P_1/P_2) = 1$		
2-8.b	decibel	dB	1 dB is the power level difference when $10 \lg (P_1/P_2) = 1$	$1 \text{ dB} = \frac{\ln 10}{20} \text{ Np}$ $= 0,115\ 129 \text{ Np}$	
2-9.a	reciprocal second, second to the power minus one	s^{-1}			
2-9.b	neper per second	Np/s			See the Introduction, special remarks
2-10.a	neper	Np			See the Introduction, special remarks
2-11.a	reciprocal metre, metre to the power minus one	m^{-1}			

[STANDARDSISO.COM](https://standardsiso.com) : Click to view the full PDF of ISO 31-2:1978

STANDARDSISO.COM : Click to view the full PDF of ISO 31-2:1978