
**Timekeeping instruments — Wrist-
chronometers with spring balance
oscillator**

*Instruments horaires — Chronomètres-bracelet à oscillateur balancier-
spiral*

STANDARDSISO.COM : Click to view the full PDF of ISO 3159:2009



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 3159:2009



COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 3159 was prepared by Technical Committee ISO/TC 114, *Horology*.

This second edition cancels and replaces the first edition (ISO 3159:1976) which has been technically revised.

STANDARDSISO.COM : Click to view the full PDF of ISO 3159:2009

[STANDARDSISO.COM](https://standardsiso.com) : Click to view the full PDF of ISO 3159:2009

Timekeeping instruments — Wrist-chronometers with spring balance oscillator

1 Scope

This International Standard lays down the definition of the term “chronometer”, describing the categories, the test programme and the acceptable minimum requirements for wrist-chronometers.

NOTE Wristwatches using a tuning fork oscillator are subjected to these tests pending the availability of separate standards.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3158, *Timekeeping instruments — Symbolization of control positions*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

chronometer

precision wristwatch regulated for different positions and for various conditions of use

NOTE 1 Conformity to the definition of chronometer will be certified by a neutral official authority that checks the watch, or if necessary the movement, and issues an official certificate.

NOTE 2 A wristwatch described as a “chronometer” must satisfy the minimum requirements laid down in Clause 7.

4 Categories of wristwatch

Wristwatches are divided into two categories dependent on casing diameter or casing-up surface.

Category	Casing diameter mm	Casing-up surface mm ²
1	> 20	> 314
2	≤ 20	≤ 314

5 Definition of criteria

5.1 General

The condition of the watch designated by the letter E_i is obtained by subtracting the standard reference time from the time indicated by the watch. The time is observed to within limits of $\pm 0,5$ s.

The condition is rounded to the nearest full second.

The daily rate, M_i , is obtained by subtracting the condition observed 24 h earlier from the condition on the day of observation; it is expressed by the following formula:

$$M_i = \frac{1}{t_d}(E_i - E_{i-1})$$

where

$$t_d = 1 \text{ (one day);}$$

$$i = 1, 2, \dots, 15.$$

By convention, this daily rate, M_i , is expressed in seconds per days (s/d). It is positive if the watch gains and negative if the watch loses.

5.2 \bar{M} : mean daily rate

\bar{M} is the arithmetic mean of daily rates during the first ten days of the tests.

$$\bar{M} = \frac{1}{10}(M_1 + M_2 + \dots + M_{10})$$

5.3 \bar{V} : mean variation in rates

\bar{V} is the arithmetic mean of the five absolute values of variations in rates obtained for the five positions of the watch during the first ten days of the tests.

$$\bar{V} = \frac{1}{5}(|M_2 - M_1| + |M_4 - M_3| + \dots + |M_{10} - M_9|)$$

NOTE The variation in rate is the difference between two consecutive daily rates in identical environmental conditions.

5.4 V_{\max} : greatest variation in rates

V_{\max} is the absolute value of the greatest of the five variations in rates with regard to the five positions of the watch during the first ten days of the tests.

$$V_{\max} = |M_{i+1} - M_i|_{\max}$$

where $i = 1, 3, 5, 7, 9$.

5.5 D: difference between the rates in horizontal and vertical positions of the watch

D is obtained by subtracting the average of the rates observed in position CH (9th day and 10th day) from the average of the rates observed in position 6H (1st day and 2nd day).

$$D = \frac{1}{2}(M_1 + M_2) - \frac{1}{2}(M_9 + M_{10})$$

5.6 P: greatest deviation in rates

P is the absolute value of the greatest of the ten differences between one of the first ten rates and the mean daily test rate.

$$P = |M_i - \bar{M}|_{\max}$$

where $i = 1, 2, \dots, 10$.

5.7 C: variation in rate as a function of temperature

C is obtained by subtracting the rate at 8 °C from the rate at 38 °C, the total being divided by the temperature difference, expressed in degrees Celsius.

$$C = \frac{M_{13} - M_{11}}{30}$$

5.8 R: resumption of the rate

R is obtained by subtracting the average of the first two rates from the last rate.

$$R = M_{15} - \frac{M_1 + M_2}{2}$$

STANDARDSISO.COM : Click to view the full PDF of ISO 3159:2009

6 Test programme¹⁾

Day	Position ^a	Nominal temperature ^b °C	E_i	M_i
0	6H	23	E_0	
1	6H	23	E_1	M_1
2	6H	23	E_2	M_2
3	3H	23	E_3	M_3
4	3H	23	E_4	M_4
5	9H	23	E_5	M_5
6	9H	23	E_6	M_6
7	FH	23	E_7	M_7
8	FH	23	E_8	M_8
9	CH	23	E_9	M_9
10 ^c	CH	23	E_{10}	M_{10}
11	CH	8	E_{11}	M_{11}
12	CH	23	E_{12}	M_{12}
13	CH	38	E_{13}	M_{13}
14	6H	23	E_{14}	M_{14}
15	6H	23	E_{15}	M_{15}
<p>^a See ISO 3158.</p> <p>^b The tolerance on the temperature is ± 1 °C.</p> <p>^c Auxiliary mechanisms, the functions of which can be interrupted, shall be made to function only on the 10th day.</p>				

1) Normally, there shall be no interruption during the tests.