
**Ships and marine technology — Propulsion
plants for ships —**

Part 2:

**Vocabulary for controllable-pitch propeller
plants**

*Navires et technologie maritime — Installations de propulsion
des navires —*

Partie 2: Vocabulaire pour installations avec hélice à pas variable



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 3715-2:2001

© ISO 2001

The reproduction of the terms and definitions contained in this International Standard is permitted in teaching manuals, instruction booklets, technical publications and journals for strictly educational or implementation purposes. The conditions for such reproduction are: that no modifications are made to the terms and definitions; that such reproduction is not permitted for dictionaries or similar publications offered for sale; and that this International Standard is referenced as the source document.

With the sole exceptions noted above, no other part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 3715 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 3715-2 was prepared by Technical Committee ISO/TC 8, *Ships and marine technology*, Subcommittee SC 3, *Piping and machinery*.

ISO 3715 consists of the following parts, under the general title *Ships and marine technology — Propulsion plants for ships*:

- *Part 1: Vocabulary for geometry of propellers*
- *Part 2: Vocabulary for controllable-pitch propeller plants*

Ships and marine technology — Propulsion plants for ships —

Part 2:

Vocabulary for controllable-pitch propeller plants

Scope

This part of ISO 3715 gives terms and definitions applicable exclusively to continuously variable and hydraulic operated controllable-pitch propeller units. It does not cover controllable-pitch propeller units for which only a few specified pitch settings apply.

General vocabulary for the geometry of screw propellers is given in ISO 3715-1 and is also valid for controllable-pitch propellers.

Normative reference

The following normative document contains provisions which, through reference in this text, constitute provisions of this part of ISO 3715. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO 3715 are encouraged to investigate the possibility of applying the most recent edition of the normative document indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 3715-1, *Ships and marine technology — Propulsion plants for ships — Part 1: Vocabulary for geometry of propellers*

Terms and definitions

1

controllable-pitch propeller

screw propeller with controllable pitch of the blades

NOTE Figure 1 shows a controllable-pitch propeller unit and its individual components.

1.1

controllable-pitch reversible propeller

screw propeller with controllable pitch of the blades in positive and negative range of pitch angle

1.2

controllable-pitch non-reversible propeller

screw propeller with controllable-pitch of the blades in the positive range of pitch angle

1.3

controllable-pitch propeller including feathering position

screw propeller with controllable pitch of the blades in positive and negative range of pitch angle and in feathering position

ISO 3715-2:2001(E)

2 Blade

See definition in ISO 3715-1.

2.1

blade attachment

component part for force-locking and form-locking connection of a blade with the hub

2.2

blade bearing

bearing of the blade in the hub

NOTE Diagrammatic sketches of other types of bearings are given in Figures 2, 3 and 4.

2.3

blade seal

seal between blade and hub to prevent seawater from leaking in and oil and grease from leaking out

3 Hub

See definition in ISO 3715-1.

NOTE If applicable, the cap may be part of the hub.

3.1

hub connection

component for force-locking and form-locking connection of hub with propeller shaft

4

flange protection

protection of the aft flange of propeller shaft against mechanical and/or corrosive influence

5

shaft

carrier of power and control transmission

5.1

propeller shaft

shaft with arrangement for attachment of propeller

5.2

intermediate shaft

shaft between propeller shaft and oil distribution box or gear

6

control unit

systems transforming a rated pitch value into an actual value and supporting it

7

hydraulic unit

components that serve the generation, controlling and transmission of the oil circuit/oil pressure and for operating the control transmission and control mechanism

NOTE These components include pumps, valves, pipe lines, tanks, filters, coolers, etc.

8

control system

system to feed a rated pitch value, given by a control system, into the hydraulic unit

9

pitch control

system to support the given rated pitch value

10

feedback system

system using the actual pitch value for control purposes

11

pitch indicator

device to indicate the actual pitch value

12

control transmission

device to transmit actual pitch values into the control mechanism

13

oil-distribution box

device to feed and draw the control medium to and off the shaft (axial and peripheric) to operate the control mechanism

14

servomotor

device consisting of piston and cylinder to transform oil pressure into control force and oil circuit into adjustment path

15

oil-transfer tube

connection inside the shafts between oil distribution box and servomotor

NOTE Movable pipes within the shaft may also be used for feedback of actual pitch values and for transmission of forces.

16

**pitch-actuating rod
push/pull rod**

connection between servomotor and control mechanism for force transmission and to feed back actual pitch values

17

control mechanism

device inside the hub to transmit the control force and to transform the path of the servomotor into a control angle of a blade

NOTE Diagrammatic sketches of other types of mechanisms are given in Figures 5 and 6.

18

take-home equipment

device that enables the propeller to operate like a fixed-bladed propeller when the control unit fails

19

control system

input device for rated pitch values

19.1

remote control system

control system separate from the control unit

NOTE This could be in the ship's control station and/or steering stand.

19.2

manual control system

control system fitted to the control unit

NOTE This could be in the back-up control.

20 Pitch

See definition in ISO 3715-1.

20.1

design pitch

positive pitch resulting from the propeller design calculation

NOTE Preferable pitch is at $0,7R$.

20.2

nominal pitch

positive pitch, which enables a defined operation condition such as ship speed, power, shaft speed

NOTE The nominal pitch may differ from the design pitch.

20.3

maximum ahead pitch

maximum adjustable positive pitch

NOTE The maximum ahead pitch is larger than the design pitch by a given value.

20.4

maximum astern pitch

maximum adjustable negative pitch

20.5

range of pitch angle

control angle of the blade position

20.6

commanded pitch

value of pitch given by the control system to be realized

20.7

actual pitch

value of pitch at the time of viewing

20.8

tolerance of pitch setting

permissible deviation of the actual pitch value from the commanded pitch value related to design pitch

20.9

time for pitch changing

time being necessary to move the blade from one defined pitch to another

21

zero thrust position

blade position at which the rotating propeller with the ship speed at zero does not produce any thrust

22

feathering position

pitch position at which the unrelated propeller produces the lowest resistance

23

trailing position

defined pitch for the trailed propeller when ship is going ahead

NOTE This is normally the highest possible pitch required to achieve low rotational frequency.

24

angle of blade position

angular position of the blade relative to the blade axis (spindle axis)

25

zero point of blade position

zero value of the blade angle positioned close to the zero thrust position

26

windmilling

propeller operating as a turbine in the wake of an operating ship and delivering power to the shaft

27

nominal pressure

pressure for which the hydraulic unit has been designed under defined operating conditions

28

testing pressure

static pressure above the nominal pressure for testing purpose of the hydraulic unit under defined conditions

29

pitch-changing pressure


pressure necessary to change the pitch of the blades

30

pitch-keeping pressure

pressure necessary to retain the blades at a given pitch

STANDARDSISO.COM : Click to view the full PDF of ISO 3715-2:2001



Key

1	Controllable-pitch propeller	2	Shafts	3	Control unit	4	Control system
1.1	Blade	2.1	Propeller shaft	3.1	Hydraulic unit	4.1	Remote control system
1.2	Hub	2.2	Intermediate shaft	3.2	Control equipment	4.2	Manual control system
				3.3	Pitch control		
				3.4	Control transmission		
				3.5	Control mechanism		

Figure 1 — Controllable-pitch propeller unit




Figure 2 — Collar bearing




Figure 3 — Trunnion bearing




Figure 4 — Collar-trunnion bearing