
INTERNATIONAL STANDARD



3832

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Road vehicles — Luggage compartments of passenger cars — Method of measuring the reference volume

Véhicules routiers — Coffres à bagages des voitures particulières — Méthode de mesurage du volume de référence

First edition — 1976-05-15

STANDARDSISO.COM : Click to view the full PDF of ISO 3832:1976

UDC 629.113

Ref. No. ISO 3832-1976 (E)

Descriptors : road vehicles, passenger cars, luggage compartments, tests, measurement, volume.

Price based on 2 pages

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 3832 was drawn up by Technical Committee ISO/TC 22, *Road vehicles*, and was circulated to the Member Bodies in May 1975.

It has been approved by the Member Bodies of the following countries :

Austria	Hungary	Spain
Belgium	Iran	Sweden
Bulgaria	Italy	Switzerland
Chile	Japan	Turkey
Czechoslovakia	Netherlands	United Kingdom
Finland	Poland	Yugoslavia
France	Romania	
Germany	South Africa, Rep. of	

The Member Body of the following country expressed disapproval of the document on technical grounds :

Brazil

Road vehicles — Luggage compartments of passenger cars — Method of measuring the reference volume

1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies a method of measuring the reference volume of the luggage compartment of a passenger car.

2 REFERENCES

ISO 2416, *Passenger cars — Load distribution.*

ISO . . ., *Road vehicles — Definitions of points H and R.*¹⁾

3 DEFINITIONS

3.1 unit module : A rectangular parallelepiped, with round edges of maximum radius 10 mm, 8 dm³ in volume, and of the following dimensions :

- length 400 ± 4 mm
- width 200 ± 2 mm
- height 100 ± 1 mm

3.2 reference volume of a luggage compartment : The sum total of the volumes of unit modules (3.1) which can be introduced into a luggage compartment, according to the procedure specified below.

This volume may be used for comparison of vehicles.

The numerical value, expressed in cubic decimetres, shall be followed by the note "in accordance with ISO 3832".

4 PROCEDURE

4.1 Measurement of the volume of closed luggage compartment without direct connection with the passenger compartment

The internal fitting of the luggage compartment shall be as planned by the manufacturer (spare wheel, jack, etc.).

Fill the luggage compartment with the largest possible number of "unit modules" (3.1). The piling up of "unit modules" shall not impede the closing of the compartment.

4.2 Measurement of the volume of luggage compartments open to the passenger compartment

Where special provisions, such as folding or removable rear seat or back have been made by the manufacturer to obtain maximum loading volume, separate measurements shall be made with :

- the rear seats and back in the normal position for sitting passengers;
- the rear seats and/or back folded or removed.

1) In preparation.