
Packaging — Complete, filled transport packages — General rules for the compilation of performance test schedules

Emballages — Emballages d'expédition complets et pleins — Règles générales pour l'établissement de programmes d'essais d'aptitude à l'emploi

STANDARDSISO.COM : Click to view the full PDF of ISO 4180:2009



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 4180:2009



COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Distribution systems	2
5 Hazards	2
6 Tests	2
6.1 General	2
6.2 Appropriate application of tests	2
6.3 Levels of intensity	3
7 Determination of criteria for acceptance	3
8 Selection of package attitude	3
9 Compilation of test schedules	4
9.1 Case 1: distribution system well defined and intensity of hazards determined	4
9.2 Case 2: distribution system undefined and intensity of hazards unknown	4
10 Case 1	4
10.1 Preferred test sequence	4
10.2 Preferred test parameters	4
10.3 Atmospheric conditioning (performed in accordance with ISO 2233)	5
10.4 Low pressure tests (performed in accordance with ISO 2873)	5
10.5 Horizontal impact (performed in accordance with ISO 2244)	5
10.6 Vertical impact (performed in accordance with ISO 2248)	7
10.7 Random vibration tests (performed in accordance with ISO 13355)	9
10.7.1 Mounting of package on the test vibration table	9
10.7.2 Test power spectral densities (PSD)	9
10.8 Stacking	11
10.8.1 Stacking (performed in accordance with ISO 2234)	11
10.8.2 Stacking test using a compression tester (performed in accordance with ISO 12048)	11
10.9 Test simulating different hazards	12
11 Case 2	12
12 Documentation	15
12.1 Test specification	15
12.2 Test report	16
Annex A (informative) Methods of quantifying damage to a package and/or its contents	17
Bibliography	18

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 4180 was prepared by Technical Committee ISO/TC 122, *Packaging*, Subcommittee SC 3, *Performance requirements and tests for means of packaging, packages and unit loads (as required by ISO/TC 122)*.

This first edition of ISO 4180 cancels and replaces ISO 4180-1:1980 and ISO 4180-2:1980.

STANDARDSISO.COM : Click to view the full PDF of ISO 4180:2009

Packaging — Complete, filled transport packages — General rules for the compilation of performance test schedules

1 Scope

This International Standard establishes general rules to be used for the compilation of performance test schedules for complete, filled transport packages intended for use within any distribution system except for the packages used for dangerous goods.

For a known distribution environment with experimental data available (case 1), this International Standard provides guide lines for the compilation of appropriate test schedules.

For an unknown distribution environment (case 2), this International Standard provides test schedules in dependence of the test specimen mass and forecast destination.

This International Standard also gives the factors to be considered in assessing the criteria of acceptance of such packages after they have been subjected to a package performance test schedule.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2206, *Packaging — Complete, filled transport packages — Identification of parts when testing*

ISO 2233, *Packaging — Complete, filled transport packages and unit loads — Conditioning for testing*

ISO 2234, *Packaging — Complete, filled transport packages and unit loads — Stacking tests using a static load*

ISO 2244, *Packaging — Complete, filled transport packages and unit loads — Horizontal impact tests*

ISO 2248, *Packaging — Complete, filled transport packages — Vertical impact test by dropping*

ISO 2873, *Packaging — Complete, filled transport packages and unit loads — Low pressure test*

ISO 4178, *Complete, filled transport packages — Distribution trials — Information to be recorded*

ISO 8318, *Packaging — Complete, filled transport packages and unit loads — Sinusoidal vibration tests using a variable frequency*

ISO 12048, *Packaging — Complete, filled transport packages — Compression and stacking tests using a compression tester*

ISO 13355:2001, *Packaging — Complete, filled transport packages and unit loads — Vertical random vibration test*

EN 14149, *Packaging — Complete, filled transport packages and unit loads — Impact test by rotational drop*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 performance test schedule
single laboratory test, or series of tests, intended to ascertain the performance, under working conditions, of the subject under test

3.2 complete, filled transport package
packaging, including contents, prepared for distribution

NOTE ISO 21067 [6] provides terminology relating to packaging.

3.3 distribution system
operations which take place after a package has been filled and closed, including all handling, transport and storage operations up to and including delivery to the user

4 Distribution systems

Distribution systems exist in great variety and complexity, but however great the complexity, they may be considered to be combinations of a number of simple elements. These simple elements are:

- a) transport of packages from one point to another, with or without change of mode of transport (where transport shall be considered to include the loading and unloading operations);
- b) storage.

5 Hazards

During distribution, a transport package is subjected to a number of hazards which might cause damage. These hazards are the result of a number of factors, the most important of which are:

- a) the characteristics of the distribution system, i. e. the carrier, the mode of transport, the geographic area;
- b) the design of the package, i.e. its dimensions, mass and shape and the mechanical characteristic of the materials of which it is composed.

6 Tests

6.1 General

Laboratory tests on transport packages aim to simulate or represent the distribution hazards.

6.2 Appropriate application of tests

The appropriate application of tests requires

- a) a knowledge of the stress arising from these hazards, and
- b) the capability of reproducing these stresses by a particular test or, alternatively, of producing damage identical to that observed in practice.

6.3 Levels of intensity

The levels of intensity selected for the tests could depend on the factors in 6.2 and:

- a) the mass of the package;
- b) the distance and the geographic location of the destination;
- c) the degree of assurance that the package should give;
- d) the nature of the contents and the frequency and value of the consignment.

7 Determination of criteria for acceptance

The criteria for acceptance of a complete filled transport package might be determined by

- the reduction of quality of the package and/or its contents,
- the extent of loss of package contents,
- the extent of deterioration of the package and/or its contents, or
- whether the damaged package represents a hazard or potential hazard in subsequent distribution, including storage.

In determining the extent of damage that is acceptable the following factors should be considered:

- a) the unit value of the contents;
- b) the number of units in the complete, filled transport package;
- c) the number of complete, filled transport packages in the consignment;
- d) the cost of distribution.

In addition it should be considered whether the contents are

- non-dangerous, or
- dangerous.

Methods of quantifying damage to a package are given in Annex A.

8 Selection of package attitude

The package attitude selected for use in the test should be the attitude of the package presented by the hazard being simulated by the test.

9 Compilation of test schedules

9.1 Case 1: distribution system well defined and intensity of hazards determined

In this case, the performance test schedule shall be written using the experimental test data acquired in accordance with ISO 4178. Applicable tests shall be chosen depending on the distribution system. Appropriate test sequence and test intensity shall be chosen.

The steps of the procedure are as follows:

- a) identify the simple elements in the distribution system;
- b) decide what hazards these elements involve;
- c) decide which tests are necessary to represent or simulate these hazards (including, for example, decisions concerning appropriate conditioning, package attitude, interposed hazards, duration of vibration and number of impacts);
- d) decide the test sequence;
- e) decide what are the test intensities associated with the particular package and distribution system combination concerned.

9.2 Case 2: distribution system undefined and intensity of hazards unknown

Very often, the package manufacturer does not have a clear knowledge of the distribution system, and the intensities of the hazards are unknown.

In this case, this International Standard provides *recommended* performance test schedules.

Choice criteria are the mass and the destination of the package.

10 Case 1

10.1 Preferred test sequence

A typical test sequence is:

- a) conditioning for testing;
- b) climatic treatment;
- c) vibration;
- d) stacking;
- e) impacts.

Other tests may be interposed in the test schedule as appropriate. When circumstances require a different order, this should be reported.

10.2 Preferred test parameters

To allow repeatability and reproducibility, test levels and parameters should be chosen among those proposed in this paragraph and should comply with the included recommendations.

10.3 Atmospheric conditioning (performed in accordance with ISO 2233)

Table 1 — Preferred test parameters

Temperature		Relative humidity %
°C	°K	
-55	218	—
-35	238	—
-18	255	—
+5	278	85
+20	293	65
+20	293	90
+23	296	50
+27	300	65
+30	303	65
+30	303	90
+35	308	65
+35	308	90
+40	313	65
+40	313	90
+55	328	30

10.4 Low pressure tests (performed in accordance with ISO 2873)

Table 2 — Preferred test pressures

Pressure hPa	Corresponding altitude m
800	about 2 000 (a pass through the Alps)
650	about 3 500 (aircraft)
550	about 5 000 (the city of La Paz, Bolivia)
360	about 8 000 (unpressurized aircraft)
190	about 12 000 (unpressurized aircraft)

10.5 Horizontal impact (performed in accordance with ISO 2244)

The test can be defined using an impact velocity chosen from Table 3.

Table 3 — Preferred impact test velocities

Preferred test velocities m/s
1,0
1,3
1,5
1,8
2,2
2,7
3,3
4,0
5,0
7,0

These shocks can also be defined in terms of wave shape, peak acceleration and duration. This method of defining shocks is only possible where a test lab has a sophisticated acquisition system and suitable accelerometers. Recording these data improves the quality of the test. The severity is well determined and the reproducibility is assured.

In this case, test parameters are given in Tables 4 to 6.

Table 4 — Shock definitions: preferred wave shapes

Preferred wave shapes
Half sine
Sawtooth
Trapezium

Table 5 — Shock definitions: preferred duration

Preferred duration ms
6
11
20
30
40
50
100

Table 6 — Shock definitions: preferred peak acceleration

Preferred peak acceleration m/s ²
50
100
150
200
300
400
500
600
800
1 000

The horizontal impact test is defined by choosing an impact velocity or duration and peak acceleration from Table 3, Table 5 or Table 6 for the type of waveform desired (see Table 4).

10.6 Vertical impact (performed in accordance with ISO 2248)

The fall height shall be chosen from Table 7.

Table 7 — Preferred test heights

Preferred test heights mm
50
100
150
200
300
400
500
600
800
1 000
1 200
1 500
1 800
2 100

These shocks can also be defined in terms of wave shape, duration and peak acceleration. This method of defining shocks is only possible where a test lab has a sophisticated acquisition system and suitable accelerometers. Recording these data improves the quality of the test. The severity is well determined and the reproducibility is assured.

In this case, test parameters shall be from Table 4, Table 8 and Table 9.

Table 8 — Shock definitions: preferred durations

Preferred durations ms
6
11
20
30
40
50
70
100

Table 9 — Shock definitions: preferred peak accelerations

Preferred peak accelerations m/s ²
50
100
150
200
300
400
500
600
800
1 000
1 200
1 500

The vertical impact test is defined by choosing a fall height (i.e. impact velocity) or duration and peak acceleration from Tables 7 to 9, for the type of waveform desired (see Table 4).

10.7 Random vibration tests (performed in accordance with ISO 13355)

10.7.1 Mounting of package on the test vibration table

If the method of fastening the packaged product to a transportation vehicle is known, that method shall, where practicable, be replicated.

If the packaged product is capable of being fastened to a transportation vehicle in a number of known ways then, from engineering knowledge of the dynamic behaviour of the product, the worst case shall be selected so that faults are most likely to be revealed. If this is not apparent, a selection of worst cases shall be made from amongst the various possibilities.

Where the packaged product is fastened to a transportation vehicle but the method varies in an unpredictable way, it shall be mechanically connected to the test apparatus as detailed in the relevant specification. This may be in a manner which only engineering judgement can decide and shall be based upon faults considered most likely to be revealed.

If the packaged product is intended, or is likely, to be carried in a transportation vehicle without being fastened down, or with some degree of freedom, that method shall, where practicable, be replicated.

If the packaged product is intended to be fastened to a transportation vehicle but it is considered likely that, in practice, it might not be fastened down, the relevant specification may require the test without clamping to the test table. This may be in addition to the appropriate test where the product is fastened down.

10.7.2 Test power spectral densities (PSD)

When performing the random vibration test, use the spectrum given in ISO 13355:2001, Annex A. If another spectrum is desired, the criteria to determine test power spectral densities (PSD) shall be as follows.

When recordings relevant to the distribution system are available, the test spectrum derived from the recordings shall not have a number of break points exceeding 15.

The preferred test parameters are given in Tables 11 to 14.

Table 11 — Preferred random test parameters: test frequency ranges

Preferred test frequency ranges
Hz
3 to 200
5 to 300
5 to 500

Table 12 — Preferred random test parameters: root mean square accelerations

Preferred root mean square accelerations m/s ²
3
5
7,5
10
12,5
15

Table 13 — Preferred random test parameters: test durations

Preferred test durations min
10
20
30
40
60
90
120

Table 14 — Preferred random test parameters: stack height for superimposed loads

Height of the stack m
1,50
1,80
2,50
3,50

10.8 Stacking

10.8.1 Stacking (performed in accordance with ISO 2234)

Table 15 — Stacks: preferred heights of stack

Preferred heights of stack m
1,50
2,00
2,50
3,50
5,00
7,00

Table 16 — Stacks: duration under load

Duration under load
1 day
2 days
3 days
1 week
2 weeks
3 weeks
4 weeks

10.8.2 Stacking test using a compression tester (performed in accordance with ISO 12048)

Table 17 — Preferred loads

Preferred loads N
250
500
750
1 000
1 500
2 000
2 500
3 000
multiples of 1 000

10.9 Test simulating different hazards

In some cases the distribution system can include different hazards described in the relevant International Standards, such as the repetitive shocks test (ISO 2247), the toppling test (ISO 8768), the rolling test (ISO 2876), the stability test (ISO 10531) and the water spray test (ISO 2875).

In this case, a test representing these conditions should be added to the test schedules to fully reproduce the environmental conditions.

In case a compression of the sides is possible (package that can be clamped), a compression test on the sides interested by the clamp is necessary.

11 Case 2

For the reasons given in 9.2, this clause provides *recommended* performance test schedules.

The test schedules may be changed as agreed by the involved stakeholders. In this case, the change and the reason should be added to the test report. Drop heights for these test schedules are given in Table 19.

Choice criteria are the mass and the destination of the package.

The following three classes of packages exist, depending on the mass of the package.

- a) Gross mass \leq 30 kg (see Table 18).
- b) Gross mass $>$ 30 kg and \leq 100 kg (see Table 20).
- c) Gross mass $>$ 100 kg (see Table 21).

The following three classes of severities exist, depending on the destination of the package.

- Level 1: very long range transportations ($>$ 2500 km), or expected poor conditions of transport infrastructures.
- Level 2: long range national transportations or international transportations, with adequate roads and rails, in a temperate climate.
- Level 3: short range national transportations ($<$ 200 km), without particular hazards.

Table 18 — Test schedules and intensities for packages of mass less than 30 kg

Basic sequence	Test type	Reference standard	Intensity			Notes
			lowest 3	2	highest 1	
Conditioning	Atmospheric	ISO 2233	23 °C at 50 % relative humidity			If other conditions are desired choose atmospheric conditioning from Table 1
Shock	Drop tests	ISO 2248	See Table 9			Choose drop height depending upon package mass. Perform drops on three faces: 3, 2 and 5, in accordance with ISO 2206, four edges and four corners surrounding the base
Compression	Static load	ISO 12048	Maximum load	Maximum load × 2	Maximum load × 3	Maximum load [package mass × (number of stacked elements – 1)] Apply load and release
Transport vibration	Vibration	Random PSD ISO 13355	Nominal PSD ISO 13355 15 min	Nominal PSD ISO 13355 90 min	Nominal PSD ISO 13355 180 min	PREFERRED TEST Perform the test along the vertical axis If the vertical axis is undefined and the orientation of the package during transportation is unpredictable, perform the test along three axis (the test time along each axis is 5 min, 30 min or 60 min)
		ISO 8318 Sinusoidal	7 m/s ² 15 min	7 m/s ² 90 min	7 m/s ² 180 min	It is recommended to conduct the test with variable frequency
Transport vibration	Repetitive shock	Random PSD ISO 13355	Nominal PSD ISO 13355 10 min	Nominal PSD ISO 13355 20 min	Nominal PSD ISO 13355 30 min	Use random PSD with no clamping of units to table surface
Compression	Static load	ISO 12048	Apply maximum load for 24 h			Impose maximum expected load [package mass × (number of stacked elements – 1)]
Shock	Drop tests	ISO 2248	See Table 9			Choose drop height depending upon package mass. Perform drops on three faces: 3, 2 and 5 in accordance with ISO 2206, four edges and four corners surrounding the base

Table 19 — Drop height

Mass (kg)	Test intensity (height in cm)		
	3	2	1
0 to 10	60	80	100
10,1 to 20	45	60	80
20,1 to 30	30	45	60

Table 20 — Test schedules and intensities for packages of gross mass > 30 kg and ≤ 100 kg

Basic sequence	Test type	Reference standard	Intensity			Notes
			lowest 3	2	highest 1	
Conditioning	Atmospheric	ISO 2233	23 °C at 50 % relative humidity			If other conditions are desired choose atmospheric conditioning from Table 1
Shock	Horizontal impact test	ISO 2244	1 m/s	1,5 m/s	2 m/s	Apply impact once on each side face
Compression	Static load	ISO 12048	Maximum load	Maximum load × 2	Maximum load × 3	Maximum load [package mass × (number of stacked elements – 1)] Apply load and release
Transport vibration	Vibration	Random PSD ISO 13355	Nominal PSD ISO 13355 15 min	Nominal PSD ISO 13355 90 min	Nominal PSD ISO 13355 180 min	PREFERRED TEST Perform the test along the vertical axis. If the vertical axis is undefined and the orientation of the package during transportation unpredictable, perform the test along three axis (the test time along each axis is 5 min, 30 min or 60 min)
		ISO 8318 Sinusoidal	7 m/s ² 15 min	7 m/s ² 90 min	7 m/s ² 180 min	It is recommended to conduct the test with variable frequency
Transport vibration	Repetitive shock	Random PSD ISO 13355	Nominal PSD ISO 13355 10 min	Nominal PSD ISO 13355 20 min	Nominal PSD ISO 13355 30 min	Use random PSD with no clamping of units to table surface
Compression	Static load	ISO 12048	Apply maximum load for 24 h			Impose maximum expected load [package mass × (number of stacked elements – 1)]
Shock	For package ≤ 70 Kg	ISO 2248 Vertical impact	15 cm	30 cm	40 cm	Perform one drop on the base, one drop on each edge of the base and one drop on each corner of the base
Shock	Drop tests for package > 70 Kg	EN 14149 Rotational drop	10 cm	20 cm	30 cm	Perform drop on two adjacent edges of the base of the package from the prescribed height

Table 21 — Test schedules and intensities for packages of gross mass > 100 kg

Basic sequence	Test type	Reference standard	Intensity			Notes
			lowest 3	2	highest 1	
Conditioning	Atmospheric	ISO 2233	23 °C at 50 % Relative Humidity			If other conditions are desired choose atmospheric conditioning from Table 1
Shock	Horizontal impact test	ISO 2244	1 m/s	1,5 m/s	2 m/s	Apply impact once on each side face
Compression	Static load	ISO 12048	Maximum load	Maximum load × 2	Maximum load × 3	Maximum load [package mass × (number of stacked elements – 1)] Apply load and release
Transport vibration	Vibration	Random PSD ISO 13355	Nominal PSD ISO 13355 15 min	Nominal PSD ISO 13355 90 min	Nominal PSD ISO 13355 180 min	PREFERRED TEST Perform test in vertical direction only
		ISO 8318 sinusoidal	7 m/s ² 15 min	7 m/s ² 90 min	7 m/s ² 180 min	It is recommended to conduct the test with variable frequency
Transport vibration	Repetitive shock	Random PSD ISO 13355	Nominal PSD ISO 13355 10 min	Nominal PSD ISO 13355 20 min	Nominal PSD ISO 13355 30 min	Use random PSD with no clamping of units to table surface
Compression	Static load	ISO 12048	Apply maximum load for 24 h			Impose maximum expected load [package mass × (number of stacked elements – 1)] In case a compression of the sides is possible (package that can be clamped), a compression test on the sides affected by the clamp is necessary
Shock	Drop tests	ISO 14149 Rotational drop	10 cm	20 cm	30 cm	Perform drop on two adjacent edges of the base of the package from the prescribed height

12 Documentation

12.1 Test specification

Before starting the tests, a test specification shall be written, including the following particulars.

- Reference to this International Standard.
- Information relevant to the kind of distribution, including recordings acquired.
- A description of each test, of the items to be tested and of their number.
- The criteria of acceptance.