

INTERNATIONAL STANDARD

ISO 4250-1

First edition
1988-03-01

AMENDMENT 1
1990-12-15

Narrow and wide base off-road tyres and rims —

Part 1:

Tyre designation and dimensions

AMENDMENT 1

Pneumatiques et jantes à base étroite et à base large pour engins de génie civil —

Partie 1: Désignation et cotes des pneumatiques

AMENDEMENT 1



Reference number
ISO 4250-1 : 1988/Amd.1 : 1990 (E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Amendment 1 to International Standard ISO 4250-1 was prepared by Technical Committee ISO/TC 31, *Tyres, rims and valves*, Sub-Committee SC 6, *Off-the-road tyres and rims*.

STANDARDSISO.COM : Click to view the full PDF of ISO 4250-1:1988/Amd 1:1990

© ISO 1990

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization

Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Narrow and wide base off-road tyres and rims —

Part 1: Tyre designation and dimensions

AMENDMENT 1

Page 2, clause 6

Add, in numerical order, the following references to tables:

Table 3a): Narrow base tyres on SDC rims.

Table 5a): 65 series tyres.

Page 2, clause 8

Add, in numerical order, the following references to tables:

Table 6a): Diagonal and radial tyres for road graders.

Table 9): Diagonal and radial 65 series tyres.

Page 3, table 3

Add the following values after the designation 36.00 — 51.

Tyre size designation	Measuring rim width Code	Design new tyre ¹⁾		In-service ²⁾	
		Section width	Overall diameter ³⁾	Maximum overall width	Maximum overall diameter ³⁾
37.00 — 57	27.00	1 016	3 370	1 118	3 524

Beneath the existing table 3, add the following table 3a).

Table 3a) – Tyre dimensions for narrow base tyres on SDC rims

Dimensions in millimetres

Tyre size designation ^{1), 2)}	Measuring rim width Code	Design new tyre ³⁾		In-service ⁵⁾	
		Section width	Overall diameter ⁴⁾	Maximum overall width	Maximum overall diameter ⁴⁾
10.00 – 24 TG	8.00	283	1 151	306	1 184
12.00 – 24 TG	8.00	312	1 226	337	1 263
13.00 – 24 TG	8.00	333	1 278	360	1 318
14.00 – 24 TG	8.00	362	1 348	391	1 392
16.00 – 24 TG	10.00	427	1 459	474	1 527

- 1) For radial tyres, replace the dash (–) in the size designation with "R"
- 2) "TG" is a designation to be used to identify tyres mounted on SDC rims.
- 3) Design new tyre dimensions quoted in the tables are used for tyre design purposes only.
- 4) Figures are based on tyres with normal tread depth. The machine manufacturer should recognize that tyres with deep tread and corresponding increased overall diameter may be used.
- 5) In-service dimensions are the maximum dimensions for grown tyres in-service for use by machine manufacturers in designing for tyre clearances.

Max. overall width = [design new tyre section width (S.W.)] × (1 + tolerance)

Tolerances: S.W. < 380 mm: + 8 %
> 380 mm: + 11 %

Max. overall diameter = (design new tyre overall diameter – rim diameter) × (1 + tolerance) + rim diameter

Tolerances: S.W. < 380 mm: + 6 %
> 380 mm: + 8 %

NOTE – See ISO 4250-3 for rim diameter values.

STANDARDS.PK.COM · Click to view the full PDF of ISO 4250-1:1988/Amd 1:1990

Beneath the existing table 5, add the following table 5a).

Table 5a) – Tyre dimensions for 65 series tyres

Dimensions in millimetres

Tyre size designation ¹⁾	Measuring rim width Code	Design new tyre ²⁾		In-service ⁴⁾	
		Section width	Overall diameter ³⁾	Maximum overall width	Maximum overall diameter ³⁾
25/65 – 25	20.00	635	1 486	705	1 554
30/65 – 25	24.00	762	1 656	846	1 738
30/65 – 29	24.00	762	1 758	846	1 840
35/65 – 33	28.00	889	2 029	987	2 124
40/65 – 39	32.00	1 016	2 352	1 128	2 461
45/65 – 45	36.00	1 143	2 675	1 269	2 798
50/65 – 51	40.00	1 270	2 997	1 410	3 133

- 1) For radial tyres, replace the dash (–) in the size designation with "R".
- 2) Design new tyre dimensions quoted in the tables are used for tyre design purposes only.
- 3) Figures are based on tyres with normal tread depth. The machine manufacturer should recognize that tyres with deep tread and corresponding increased overall diameter may be used.
- 4) In-service dimensions are the maximum dimensions for grown tyres in-service for use by machine manufacturers in designing for tyre clearances.

Max. overall width = [design new tyre section width (S.W.)] × (1 + tolerance)

Tolerances: S.W. < 380 mm: + 8 %
 > 380 mm: + 11 %

Max. overall diameter = (design new tyre overall diameter – rim diameter) × (1 + tolerance) + rim diameter

Tolerances: S.W. < 380 mm: + 6 %
 > 380 mm: + 8 %

NOTE – See ISO 4250-3 for rim diameter values.

Page 6, table 6

Add the following values after the designation 36.00 — 51:

Tyre size designation	Recommended rims
37.00 — 57	27.00/6.0

Page 6

Beneath the existing table 6, add the following table 6a).

Table 6a) — Recommended rims for diagonal and radial tyres for road graders ¹⁾

Tyre size designation ^{2), 3)}	Recommended rims ⁴⁾
10.00 — 24 TG	8.00 TG SDC
12.00 — 24 TG	8.00 TG SDC
13.00 — 24 TG	8.00 TG SDC 10.00 VA SDC
14.00 — 24 TG	8.00 TG SDC 10.00 VA SDC
16.00 — 24 TG	10.00 VA SDC

1) The tyre and rim/wheel manufacturer should be consulted for confirmation of the suitability of the tyre/wheel assembly for the intended service or for the use of alternative rims.

2) For radial tyres, replace the dash (—) in the size designation with "R".

3) "TG" is a designation to be used to identify tyres mounted on SDC rims.

4) See ISO 4250-3 for rim contours.

Page 6

Beneath the existing table 8, add the following table 9.

Table 9 — Recommended rims for diagonal and radial 65 series tyres

Tyre size designation ^{1), 2)}	Recommended rims
25/65 — 25	19.50/2.0 20.00/2.0
30/65 — 25	24.00/3.0
30/65 — 29	24.00/3.0
35/65 — 33	28.00/3.5
40/65 — 39	32.00/4.0
45/65 — 45	36.00/4.5
50/65 — 51	40.00/4.5

1) The tyre and rim/wheel manufacturer should be consulted for confirmation of the suitability of the tyre/wheel assembly for the intended service or for the use of alternative rims.

2) For radial tyres, replace the dash (—) in the size designation with "R".

STANDARDSISO.COM : Click to view the full PDF of ISO 4250-1:1988/Amd.1:1990