

# INTERNATIONAL STANDARD

**ISO**  
**4759-1**

Second edition  
2000-11-15

---

---

## Tolerances for fasteners —

Part 1:

### **Bolts, screws, studs and nuts — Product grades A, B and C**

*Tolérances des éléments de fixation —*

*Partie 1: Vis, goujons et écrous — Grades A, B et C*



Reference number  
ISO 4759-1:2000(E)

© ISO 2000

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 4759-1:2000

© ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.ch](mailto:copyright@iso.ch)  
Web [www.iso.ch](http://www.iso.ch)

Printed in Switzerland

**Contents**

Page

Foreword.....	iv
1 <b>Scope</b> .....	1
2 <b>Normative references</b> .....	2
3 <b>Tolerances for metric bolts, screws and studs</b> .....	3
4 <b>Tolerances for metric nuts</b> .....	25
5 <b>Tolerances for tapping screws</b> .....	36
<b>Annex A</b> (informative) <b>Tolerances</b> .....	44
<b>Annex B</b> (informative) <b>Examples of dimensioned and toleranced fasteners</b> .....	46
<b>Annex C</b> (informative) <b>Examples of gauges and other measuring devices</b> .....	49

STANDARDSISO.COM : Click to view the full PDF of ISO 4759-1:2000

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 4759 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 4759-1 was prepared by Technical Committee ISO/TC 2, *Fasteners*, Subcommittee SC 7, *Reference Standards for fasteners (mainly covering terminology, dimensioning, sizes and tolerancing)*.

This second edition cancels and replaces the first edition (ISO 4759-1:1978), which has been technically revised.

ISO 4759 consists of the following parts, under the general title *Tolerances for fasteners*:

- *Part 1: Bolts, screws, studs and nuts — Product grades A, B and C*
- *Part 3: Plain washers for bolts, screws and nuts — Product grades A and C*

Annexes A to C of this part of ISO 4759 are for information only.

## Tolerances for fasteners —

### Part 1:

## Bolts, screws, studs and nuts — Product grades A, B and C

### 1 Scope

This part of ISO 4759 specifies a selection of tolerances for bolts, screws, studs and nuts with ISO metric threads and with product grades A, B and C and for tapping screws with product grade A.

**NOTE** The product grades refer to the size of the tolerances where grade A is the most precise and grade C is the least precise.

The tolerances, except tolerances for threads, are selected from the system of limits and fits specified in ISO 286-1 and ISO 286-2. The tolerances for metric threads are taken from the series of tolerance classes specified in ISO 965-3. The tolerances for tapping screw threads are covered in ISO 1478.

The tolerances of form and position are specified and indicated in accordance with ISO 1101, ISO 8015 and ISO 2692.

The tolerances specified in this part of ISO 4759 apply to fasteners prior to coating unless otherwise specified. See also ISO 4042.

Deviations from the tolerances specified in this part of ISO 4759 are only permitted in product standards where there are valid technical reasons. In cases where there is a difference between the tolerance requirements in this part of ISO 4759 and the product standard, the product standard takes precedence.

It is recommended that these tolerances also be used for non-standard fasteners.

Dimensions and tolerances given in this part of ISO 4759 are in millimetres.

## 2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO 4759. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO 4759 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 225:1983, *Fasteners — Bolts, screws, studs and nuts — Symbols and designation of dimensions.*

ISO 286-1:1988, *ISO system of limits and fits — Part 1: Bases of tolerances, deviations and fits.*

ISO 286-2:1988, *ISO system of limits and fits — Part 2: Tables of standard tolerance grades and limit deviations for holes and shafts.*

ISO 885:2000, *General purpose bolts and screws — Metric series — Radii under the head.*

ISO 965-3:1998, *ISO general purpose metric screw threads — Tolerances — Part 3: Deviations for constructional screw threads.*

ISO 1101:2000, *Geometrical Product Specifications (GPS) — Geometrical tolerancing — Tolerances of form, orientation, location and run-out.*

ISO 1478:1999, *Tapping screws thread.*

ISO 1479:1983, *Hexagon head tapping screws.*

ISO 2692:1988, *Technical drawings — Geometrical tolerancing — Maximum material principle.*

ISO 4032:1999, *Hexagon nuts, style 1 — Product grades A and B.*

ISO 4042:1999, *Fasteners — Electroplated coatings.*

ISO 4757:1983, *Cross recesses for screws.*

ISO 7053:1992, *Hexagon washer head tapping screws.*

ISO 7721:1983, *Countersunk head screws — Head configuration and gauging.*

ISO 8015:1985, *Technical drawings — Fundamental tolerancing principle.*

ISO 10509:1992, *Hexagon flange head tapping screws.*



ISO 10642:1997, *Hexagon socket countersunk head screws.*




ISO 10664:1999, *Hexalobular internal driving feature for bolts and screws.*

### 3 Tolerances for metric bolts, screws and studs





#### 3.1 Dimensional tolerances



Symbols and designations of dimensions are specified in ISO 225.




Feature	Tolerance for product grades				Notes																				
	A	B	C																						
<b>3.1.1 Tolerance level</b>																									
Shank and bearing surface	close	close	wide																						
Other features	close	wide	wide																						
<b>3.1.2 External thread</b>	6g	6g	8g (but 6g for property class 8.8 and higher)		For certain products and coatings, other tolerance classes for threads may be specified in the relevant product and coating standards.																				
<b>3.1.3 Driving features</b>	<table border="1"> <thead> <tr> <th><i>s</i></th> <th>Tolerance</th> <th><i>s</i></th> <th>Tolerance</th> </tr> </thead> <tbody> <tr> <td>≤ 30</td> <td>h13</td> <td>≤ 18</td> <td>h14</td> </tr> <tr> <td>&gt; 30</td> <td>h14</td> <td>&gt; 18 ≤ 60</td> <td>h15</td> </tr> <tr> <td></td> <td></td> <td>&gt; 60 ≤ 180</td> <td>h16</td> </tr> <tr> <td></td> <td></td> <td>&gt; 180</td> <td>h17</td> </tr> </tbody> </table>				<i>s</i>	Tolerance	<i>s</i>	Tolerance	≤ 30	h13	≤ 18	h14	> 30	h14	> 18 ≤ 60	h15			> 60 ≤ 180	h16			> 180	h17	
<i>s</i>	Tolerance	<i>s</i>	Tolerance																						
≤ 30	h13	≤ 18	h14																						
> 30	h14	> 18 ≤ 60	h15																						
		> 60 ≤ 180	h16																						
		> 180	h17																						
<b>3.1.3.1 External</b>																									
<b>3.1.3.1.1 Width across flats</b>																									
 <p>Figure 1</p>																									
 <p>Figure 2</p>																									




Feature	Tolerance for product grades			Notes						
	A	B	C							
<p>3.1.3.1.2 Width across corners</p>  <p>Figure 3</p>	$e_{\min} = 1,13 s_{\min}$ $e_{\min} = 1,12 s_{\min}$ for bolts and screws with flange and other cold forged heads without trimming operation									
 <p>Figure 4</p>	$e_{\min} = 1,3 s_{\min}$									
<p>3.1.3.1.3 Height of head</p>  <p>Figure 5</p>	js14	js15	<table border="1"> <thead> <tr> <th><i>k</i></th> <th>Tolerance</th> </tr> </thead> <tbody> <tr> <td>&lt; 10</td> <td>js16</td> </tr> <tr> <td>≥ 10</td> <td>js17</td> </tr> </tbody> </table>	<i>k</i>	Tolerance	< 10	js16	≥ 10	js17	
<i>k</i>	Tolerance									
< 10	js16									
≥ 10	js17									




STANDARDSISO.COM : Click to view the full PDF of ISO 4759-1:2000


Feature	Tolerance for product grades			Notes
	A	B	C	
 <p>Figure 6</p>	<p>For hexagon bolts and screws with flange, <math>k</math> is defined only as a maximum</p>			
<p>3.1.3.1.4 Wrenching height</p>  <p>Figure 7</p>	$k_{w \min}^a = 0,7 k_{\min}$			<p><math>k_w</math> defines the length over which <math>e_{\min}</math> applies but excluding any chamfer, washer face or radius specified in the appropriate product standard.</p> <p>The formulae for <math>k_{w \min}</math> only apply to the products illustrated.</p> <p><sup>a</sup> The symbol <math>k_w</math> replaces the previously used <math>k'</math>.</p>
 <p>Figure 8</p>	$k_{w \min}^b = 0,7 \left[ (k_{\max} - IT15) - \left( x + \frac{d_w \min - e_{\min}}{2} \tan \delta_{\max} \right) \right]$ <p><math>x</math> is the greater of <math>c_{\min} \times 1,25</math> or <math>c_{\min} + 0,4</math></p> <p><math>\delta</math> is the flange angle</p> <p>Dimensions <math>k_w^a</math>, <math>k</math>, <math>d_w</math>, <math>e</math> and <math>\delta</math> are in accordance with ISO 225.</p>			<p><sup>b</sup> For gauging, see annex A of the product standards</p>
	 <p>Figure 8 a)</p>			

Feature	Tolerance for product grades			Notes																								
	A	B	C																									
<p><b>3.1.3.2 Internal</b></p> <p><b>3.1.3.2.1 Hexagon sockets</b></p>  <p><b>Figure 9</b></p>	$e_{\min} = 1,14 s_{\min}$ <table border="1"> <thead> <tr> <th>s</th> <th>Tolerance</th> </tr> </thead> <tbody> <tr><td>0,7</td><td>EF8</td></tr> <tr><td>0,9</td><td>JS9</td></tr> <tr><td>1,3</td><td>K9</td></tr> <tr><td>1,5</td><td rowspan="4">D11</td></tr> <tr><td>2</td></tr> <tr><td>2,5</td></tr> <tr><td>3</td></tr> <tr><td>4</td><td>E11</td></tr> <tr><td>5</td><td rowspan="6">E12</td></tr> <tr><td>6</td></tr> <tr><td>8</td></tr> <tr><td>10</td></tr> <tr><td>12</td></tr> <tr><td>14</td></tr> <tr><td>&gt; 14</td><td>D12</td></tr> </tbody> </table>	s	Tolerance	0,7	EF8	0,9	JS9	1,3	K9	1,5	D11	2	2,5	3	4	E11	5	E12	6	8	10	12	14	> 14	D12	—	—	
s	Tolerance																											
0,7	EF8																											
0,9	JS9																											
1,3	K9																											
1,5	D11																											
2																												
2,5																												
3																												
4	E11																											
5	E12																											
6																												
8																												
10																												
12																												
14																												
> 14	D12																											
<p><b>3.1.3.2.2 Slots</b></p>  <p><b>Figure 10</b></p>	<table border="1"> <thead> <tr> <th>n</th> <th>Tolerance</th> </tr> </thead> <tbody> <tr> <td><math>\leq 1</math></td> <td>+ 0,20 + 0,06</td> </tr> <tr> <td><math>&gt; 1 \leq 3</math></td> <td>+ 0,31 + 0,06</td> </tr> <tr> <td><math>&gt; 3 \leq 6</math></td> <td>+ 0,37 + 0,07</td> </tr> </tbody> </table>	n	Tolerance	$\leq 1$	+ 0,20 + 0,06	$> 1 \leq 3$	+ 0,31 + 0,06	$> 3 \leq 6$	+ 0,37 + 0,07	—	—	<p>Tolerance field C13 for <math>n \leq 1</math></p> <p>C14 for <math>n &gt; 1</math></p>																
n	Tolerance																											
$\leq 1$	+ 0,20 + 0,06																											
$> 1 \leq 3$	+ 0,31 + 0,06																											
$> 3 \leq 6$	+ 0,37 + 0,07																											





Feature	Tolerance for product grades			Notes
	A	B	C	
<p><b>3.1.3.2.3 Depth of hexagon sockets and slots</b></p>  <p><b>Figure 11</b></p>	<p>The depth of hexagon sockets and slots is specified in product standards only as a minimum. It is restricted by the minimum wall thickness <math>w</math>.</p>	—	—	For the time being generally applicable tolerances cannot be specified.
<p><b>3.1.3.2.4 Cross recesses</b></p>	See ISO 4757 for all dimensions except penetration depths. For penetration depths see appropriate product standard.			
<p><b>3.1.3.2.5 Hexalobular recesses</b></p>	See ISO 10664 for all dimensions except penetration depths. For penetration depths see appropriate product standard.			
<p><b>3.1.4 Other features</b></p> <p><b>3.1.4.1 Head diameter</b></p>  <p><b>Figure 12</b></p>	h13 <sup>a</sup>	—	—	<sup>a</sup> ± IT13 for knurled heads
 <p><b>Figure 13</b></p>	h14	—	—	Combined control of diameter and height for counter-sunk head screws in accordance with ISO 7721 or ISO 10642.

Feature	Tolerance for product grades			Notes																							
	A	B	C																								
<p><b>3.1.4.2 Head height (except for hexagon heads)</b></p>  <p><b>Figure 14</b></p>	<p>≤ M5: h13 &gt; M5: h14</p>	—	—																								
 <p><b>Figure 15</b></p>	For countersunk head screws <i>k</i> is defined in product standards only as a maximum.			Combined control of diameter and height for countersunk head screws in accordance with ISO 7721 or ISO 10642.																							
<p><b>3.1.4.3 Bearing face diameter and height of washer-faced portion</b></p>  <p><b>Figure 16</b></p> <p>a Reference datum for <math>d_w</math></p>	<p><math>d_{w \min} = s_{\min} - IT16</math> for width across flats &lt; 21 mm  <math>d_{w \min} = 0,95 s_{\min}</math> for width across flats ≥ 21 mm  <math>d_{w \max} = s_{\text{actual}}</math></p> <table border="1"> <thead> <tr> <th rowspan="2">Thread diameter</th> <th colspan="2">c</th> </tr> <tr> <th>min.</th> <th>max.</th> </tr> </thead> <tbody> <tr> <td>≥ 1,6 to 2,5</td> <td>0,10</td> <td>0,25</td> </tr> <tr> <td>&gt; 2,5 to 4</td> <td>0,15</td> <td>0,40</td> </tr> <tr> <td>&gt; 4 to 6</td> <td>0,15</td> <td>0,50</td> </tr> <tr> <td>&gt; 6 to 14</td> <td>0,15</td> <td>0,60</td> </tr> <tr> <td>&gt; 14 to 36</td> <td>0,20</td> <td>0,80</td> </tr> <tr> <td>&gt; 36</td> <td>0,30</td> <td>1,0</td> </tr> </tbody> </table>	Thread diameter	c		min.	max.	≥ 1,6 to 2,5	0,10	0,25	> 2,5 to 4	0,15	0,40	> 4 to 6	0,15	0,50	> 6 to 14	0,15	0,60	> 14 to 36	0,20	0,80	> 36	0,30	1,0			For product grade C a washer face is not mandatory.
Thread diameter	c																										
	min.	max.																									
≥ 1,6 to 2,5	0,10	0,25																									
> 2,5 to 4	0,15	0,40																									
> 4 to 6	0,15	0,50																									
> 6 to 14	0,15	0,60																									
> 14 to 36	0,20	0,80																									
> 36	0,30	1,0																									

Feature	Tolerance for product grades			Notes
	A	B	C	
 <p>a Reference datum for <math>d_w</math></p> <p><b>Figure 17</b></p>	<p><math>d_w</math> is defined in product standards only as a minimum.</p>			
 <p>a Reference datum for <math>d_w</math></p> <p><b>Figure 18</b></p>	<p>Thread diameter</p> <p>&gt;                      ≤</p>		<p><math>d_w</math></p> <p>min.</p>	<p>For product grade A only</p>
	2,5	5	$d_k \text{ min} - 0,14$	
	5	10	$d_k \text{ min} - 0,25$	
	10	16	$d_k \text{ min} - 0,4$	
	16	24	$d_k \text{ min} - 0,5$	
	24	36	$d_k \text{ min} - 0,8$	
	36	—	$d_k \text{ min} - 1$	
 <p><b>Figure 19</b></p>	<p><math>d_a</math> for products without undercut is specified in ISO 885.</p>			<p><math>d_a</math> for undercut products, see the appropriate product standard.</p>

Feature	Tolerance for product grades			Notes
	A	B	C	
<p>3.1.4.4 Length</p>  <p>Figure 20</p>	js15	js17	$l \leq 150$ : js17 $l > 150$ : $\pm IT17$	

STANDARDSISO.COM: Click to view the full PDF of ISO 4759-1:2000

Feature	Tolerance for product grades			Notes
	A	B	C	
<p><b>3.1.4.5 Thread length</b></p> <p><b>Bolt</b></p>  <p><b>Tie rod</b></p>  <p><b>Stud</b></p>  <p><b>Figure 21</b></p>	$\begin{matrix} b + 2P \\ 0 \end{matrix}$	$\begin{matrix} b + 2P \\ 0 \end{matrix}$	$\begin{matrix} b + 2P \\ 0 \end{matrix}$	<p><math>P</math> is the pitch of thread.</p> <p><math>l_s</math> is the minimum length of the unthreaded (plain) shank.</p> <p><math>l_g</math> is the maximum length of the unthreaded shank (thread run-out included) and is therefore the minimum clamping length.</p> <p>Tolerance <math>+ 2 P</math> related to dimension <math>b</math> applies only where <math>l_s</math> and <math>l_g</math> are not specified in the product standard.</p> <p><math>b_m</math> refers to metal end of studs only.</p>
<p><b>3.1.4.6 Shank diameter</b></p>  <p><b>Figure 22</b></p>	$h13$	$h14$	$\pm IT 15$	<p>The tolerance is not applicable in the areas of the underhead fillet and thread run-out.</p>
<p>Reduced shank diameter <math>\approx</math> pitch diameter</p>				

**3.2 Geometrical tolerances**

In accordance with ISO 1101 and ISO 2692 the tolerances specified in Figures 23 to 57 do not necessarily imply the use of any particular method of production, measurement or gauging.




When the pitch diameter axis is specified as the datum and the coaxiality deviation of the major diameter axis relative to the pitch diameter axis is negligible, e.g. normally with rolled threads, the major diameter axis may be taken as the datum.





According to ISO 1101 when the datum is the thread axis the letters MD indicate that the datum reference is the major diameter axis.




The maximum material principle in accordance with ISO 2692 is used.




Feature	Tolerance <i>t</i> for product grades			Notes
	A	B	C	
<p><b>3.2.1 Driving feature</b></p> <p><b>3.2.1.1 Tolerances of form</b></p> <p><b>3.2.1.1.1 External</b></p> <p>6 × 120°</p> <p>s</p> <p>a</p> <p>⊕ 0(M)</p> <p>a 3 × simultaneously.</p> <p><b>Figure 23</b></p> <p>4 × 90°</p> <p>s</p> <p>a</p> <p>⊕ 0(M)</p> <p>a 2 × simultaneously.</p> <p><b>Figure 24</b></p>				

Feature	Tolerance $t$ for product grades			Tolerance $t$ based on dimensions	Notes
	A	B	C		
<p><b>3.2.1.1.2 Internal</b></p> <p>a 3 x simultaneously.</p> <p><b>Figure 25</b></p>					
<p><b>3.2.1.2 Tolerances of position</b></p> <p>a The datum A shall be as close to the head as possible but within 0,5d distance of the head and shall be either wholly plain or wholly threaded but shall not include the thread run-out or underhead fillet.</p> <p>b MD means that tolerance applies in relation to the axis of the cylinder derived from the major thread diameter.</p> <p>c 3 x simultaneously.</p> <p><b>Figure 26</b></p>	2 IT13	2 IT14	2 IT15	s	<p>0,5d max.</p> <p>0,5d max.</p>
<p>a, b, c See Figure 26.</p> <p><b>Figure 27</b></p>	2 IT13	2 IT14	—	s	




Feature	Tolerance $t$ for product grades			Tolerance $t$ based on dimensions	Notes
	A	B	C		
 <p>a, b, c See Figure 26</p> <p><b>Figure 28</b></p>	2 IT13	—	—	$d$	
 <p>a, b, c See Figure 26.</p> <p><b>Figure 29</b></p>	2 IT13	—	—	$d$	
 <p>a, b, c See Figure 26.</p> <p><b>Figure 30</b></p>	2 IT13	—	—	$d$	




Feature	Tolerance $t$ for product grades			Tolerance $t$ based on dimensions	Notes
	A	B	C		
 <p>b, c See Figure 26.</p> <p><b>Figure 31</b></p>	2 IT12	—	—	$d$	
 <p>a, b See Figure 26</p> <p><b>Figure 32</b></p>	2 IT12	2 IT13	2 IT14	$d$	
 <p>a, b See Figure 26</p> <p><b>Figure 33</b></p>	2 IT12	2 IT13	2 IT14	$d$	
 <p>a, b See Figure 26.</p> <p><b>Figure 34</b></p>	2 IT12	2 IT13	2 IT14	$d$	




Feature	Tolerance <i>t</i> for product grades			Tolerance <i>t</i> based on dimensions	Notes
	A	B	C		
 <p>b See Figure 26.</p> <p><b>Figure 35</b></p>	2 IT12	—	—	<i>d</i>	
 <p>a, b See Figure 26.</p> <p>c For referee purposes coaxiality of cross recess shall be assessed by means of a penetration gauge point in accordance with ISO 4757.</p> <p><b>Figure 36</b></p>	2 IT13	—	—	<i>d</i>	
 <p>a, b See Figure 26.</p> <p>c See Figure 36.</p> <p><b>Figure 37</b></p>	2 IT13	—	—	<i>d</i>	



Feature	Tolerance $t$ for product grades			Tolerance $t$ based on dimensions	Notes
	A	B	C		
<p><b>3.2.2 Other features</b></p> <p><b>3.2.2.1 Tolerances of position and run-out</b></p>  <p>a, b See Figure 26.</p> <p><b>Figure 38</b></p>	2 IT13	2 IT14	2 IT15	$d_k$	
 <p>a, b See Figure 26.</p> <p><b>Figure 39</b></p>	2 IT13	2 IT14	—	$d_c$	
 <p><sup>c</sup> PD means that the tolerance applies in relation to the axis derived from the pitch diameter.</p> <p><b>Figure 40</b></p>	2 IT13	2 IT14	2 IT15	$d$	





Feature	Tolerance $t$ for product grades			Tolerance $t$ based on dimensions	Notes
	A	B	C		
 <p>c See Figure 40.</p> <p><b>Figure 44</b></p>	2 IT13	2 IT14	2 IT15	$d$	
 <p>c See Figure 40.</p> <p>d The gauge datum feature A shall be as close to the respective part of the shank as possible but shall avoid the thread run-out.</p> <p><b>Figure 45</b></p>	IT13	IT14	IT15	$d$	
 <p>c See Figure 40.</p> <p>d The gauge datum features A and B shall be as close to the respective part of the shank as possible but shall avoid the thread run-out.</p> <p><b>Figure 46</b></p>	IT13	IT14	—	$d$	


Feature	Tolerance $t$ for product grades			Tolerance $t$ based on dimensions	Notes
	A	B	C		
<p><b>3.2.2.2 Tolerances of straightness</b></p>  <p><math>d</math></p> <p><math>\leq 8</math> <math>t = 0,002l + 0,05</math></p> <p><math>&gt; 8</math> <math>t = 0,002\ 5l + 0,05</math></p> <p><math>d \leq 8: t = 2(0,002l + 0,05)</math>  <math>d &gt; 8: t = 2(0,002\ 5l + 0,05)</math></p> <p><sup>b</sup> See Figure 26.  <b>Figure 47</b></p>					
 <p><math>d</math></p> <p><math>\leq 8</math> <math>t = 0,002l + 0,05</math></p> <p><math>&gt; 8</math> <math>t = 0,002\ 5l + 0,05</math></p> <p><math>d \leq 8: t = 2(0,002l + 0,05)</math>  <math>d &gt; 8: t = 2(0,002\ 5l + 0,05)</math></p> <p><sup>b</sup> See Figure 26.  <b>Figure 48</b></p>					
 <p><math>d</math></p> <p><math>\leq 8</math> <math>t = 0,002l + 0,05</math></p> <p><math>&gt; 8</math> <math>t = 0,002\ 5l + 0,05</math></p> <p>—</p> <p><sup>b</sup> See Figure 26.  <b>Figure 49</b></p>					

Feature	Tolerance <i>t</i> for product grades			Tolerance <i>t</i> based on dimension <i>d</i>	Notes
	A	B	C		
 <p>b See Figure 26.</p> <p><b>Figure 50</b></p>			$d \leq 8: t = 2(0,002l + 0,05)$ $d > 8: t = 2(0,0025l + 0,05)$		
<p><b>3.2.2.3 Tolerance of total run-out</b></p>  <p>a, b See Figure 26.</p> <p>c Up to 0,8s diameter only.</p> <p><b>Figure 51</b></p>	0,04			1,6	<p>For product grades A and B tolerance <i>t</i> is calculated as follows:</p> <p><math>\leq M 39:</math>  <math>t = 1,2 d \cdot \tan 1^\circ</math>  <math>&gt; M 39:</math>  <math>t = 1,2 d \cdot \tan 0,5^\circ</math></p> <p>For product grade C tolerance <i>t</i> is twice as much.</p>
				2	
	0,08			2,5	
				3	
				3,5	
				4	
	0,15		0,3	5	
				6	
				7	
	0,17	0,34		8	
	0,21	0,42		10	
	0,25	0,50		12	
	0,29	0,58		14	
	0,34	0,68		16	
	0,38	0,76		18	
	0,42	0,84		20	
	0,46	0,92		22	
	0,50	1,00		24	
	0,57	1,14		27	
	0,63	1,26		30	
	0,69	1,38		33	
	0,76	1,52		36	
	0,82	1,64		39	
	0,44	0,88		42	
	0,47	0,94		45	
	0,50	1		48	
	0,55	1,1		52	
 <p>a, b See Figure 26.</p> <p>c Up to 0,8 d<sub>k</sub> diameter only.</p> <p><b>Figure 52</b></p>					

Feature	Tolerance <i>t</i> for product grades			Tolerance <i>t</i> based on dimension <i>d</i>	Notes
	A	B	C		
 <p>a, b See Figure 26. c Up to 0,8 <i>d<sub>k</sub></i> diameter only.</p> <p><b>Figure 53</b></p>	0,04	—	—	1,6	<p>See Figures 51 and 52</p> <p>In case of flange bolts, tolerances apply to type F and type U.</p>
	0,08	0,3	—	2	
			—	2,5	
			—	3	
			—	3,5	
			—	4	
			—	5	
			—	6	
	0,15	0,3	—	7	
			—	8	
 <p>a, b See Figure 26. c Line of highest points on any radial line.</p> <p><b>Figure 54</b></p>	0,17	0,34	—	10	
	0,21	0,42	—	12	
	0,25	0,50	—	14	
	0,29	0,58	—	16	
	0,34	0,68	—	18	
	0,38	0,76	—	20	
	0,42	0,84	—	22	
	0,46	0,92	—	24	
	0,50	1,00	—	27	
	0,57	1,14	—	30	
0,63	0,3	—	33		
		—	36		
		—	39		
		—	42		
		—	45		
		—	48		
		—	52		
		0,69	1,38	—	—
		0,76	1,52	—	—
		0,82	1,64	—	—
0,44	0,88	—	—		
0,47	0,94	—	—		
0,50	1	—	—		
0,55	1,1	—	—		

Feature	Tolerance $t$ for product grades			Tolerance $t$ based on dimensions	Notes
	A	B	C		
 <p>a, b See Figure 26. c See Figure 51.</p> <p><b>Figure 55</b></p>	<p>For <math>t</math> see Figures 51 to 54</p>			<p>Basis for <math>t</math> see Figures 51 to 54</p>	<p>For dog points only, not for pilot points</p>
 <p>a, b See Figure 26. c Up to <math>\varnothing 0,8d_p</math> only</p> <p><b>Figure 56</b></p>					

STANDARDSISO.COM : Click to view the full PDF of ISO 4759-1:2000


Feature	Tolerance $t$ for product grades			Tolerance $t$ based on dimensions	Notes
	A	B	C		
<p>3.2.2.4 Permissible deviation from the form of bearing face</p>  <p>c radial lines between <math>d_{a \max}</math> and <math>d_{w \min}</math>.</p> <p>d According to product standard.</p> <p><b>Figure 57</b></p>	$0,005 d$			$d$	





STANDARDSISO.COM : Click to view the full PDF of ISO 4759-1:2000




4 Tolerances for metric nuts




4.1 Dimensional tolerances



NOTE Symbols and designations of dimensions are specified in ISO 225.

Feature	Tolerance for product grades			Notes
	A	B	C	
<p><b>4.1.1 Tolerance level</b></p> <p>Bearing surface</p> <p>Other features</p>	close	close	wide	
<p><b>4.1.2 Internal thread</b></p>  <p>For all nuts of heights <math>m \geq 0,8d</math> the minor diameter shall be within the specified tolerances for a minimum of <math>0,5 m_{max}</math> (only for sizes <math>\geq M3</math>).</p> <p>For all nuts of heights <math>0,5d \leq m &lt; 0,8d</math> the minor diameter shall be within the specified tolerances for a minimum of <math>0,35 m_{max}</math></p> <p>For prevailing torque type nuts the minor diameter may exceed the specified tolerance for a maximum height of <math>0,35d</math> from the non-restricted end which does not contain the prevailing torque feature.</p> <p>a Profile varies for different types of prevailing torque type nuts.</p> <p><b>Figure 58</b></p>	6H	6H	7H	For certain products and coatings, other tolerance classes may be specified in the relevant product and coating standards.



Feature	Tolerance for product grades				Notes
	A		B		
<p><b>4.1.3 Driving features</b></p> <p><b>4.1.3.1 Width across flats</b></p>  <p><b>Figure 59</b></p>	<p>s</p> <p>Tolerance</p> <p>≤ 30 h13</p> <p>&gt; 30 h14</p>	<p>s</p> <p>Tolerance</p> <p>≤ 18 &gt; 18 ≤ 60 &gt; 60 ≤ 180 &gt; 180</p>	<p>Tolerance</p> <p>h14 h15 h16 h17</p>		
 <p><b>Figure 60</b></p>	See figure 59	See figure 59			
<p><b>4.1.3.2 Width across corners</b></p>  <p><b>Figure 61</b></p>		$e_{min} = 1,13 s_{min}$			
 <p><b>Figure 62</b></p>		$e_{min} = 1,3 s_{min}$			

Feature	Tolerance for product grades			Notes
	A	B	C	
<p><b>4.1.4 Other features</b></p> <p><b>4.1.4.1 Height of nuts</b></p>  <p><b>Figure 63</b></p>	<p><math>d \leq 12 \text{ mm}</math>: h14</p> <p><math>12 \text{ mm} &lt; d \leq 18 \text{ mm}</math>: h15</p> <p><math>d &gt; 18 \text{ mm}</math>: h16</p>			<p>h17</p> <p>For slotted nuts and castle nuts see 4.1.5.1</p>
<p>Prevailing torque type nuts (with non-metallic insert)</p>  <p>Prevailing torque type all metal hexagon nuts</p>  <p><b>Figure 64</b></p>	<p>Tolerance of <math>h</math>, see product standards</p>			

Feature	Tolerance for product grades			Notes
	A	B	C	
<p><b>4.1.4.2 Wrenching height</b></p>  <p><b>Figure 65</b></p>	$m_w^a \min = 0,8 m_{\min}$			<p><math>m_w</math> defines the length over which <math>e_{\min}</math> applies but excluding any chamfer or washer face specified in the appropriate product standard.</p> <p>The symbol <math>m_w</math> replaces the previously used <math>m'</math>.</p>
 <p><b>Figure 66</b></p>	$m_w^b \min = 0,8 \times \left[ m_{\min} - \left( x + \frac{d_w \min - e_{\min}}{2} \tan \delta_{\max} \right) \right]$ <p><math>x</math> is the greater of <math>c_{\min} \times 1,25</math> or <math>c_{\min} + 0,4</math></p> <p><math>\delta</math> is the flange angle</p> <p>Dimensions <math>m_w^a</math>, <math>m</math>, <math>d_w</math>, <math>e</math> and <math>\delta</math> are in accordance with ISO 225.</p> 			<p><sup>a</sup> The formulae for <math>m_w \min</math> only apply to the products illustrated.</p> <p><sup>b</sup> For gauging, see annex A of the product standards.</p>

Feature	Tolerance for product grades			Notes																							
	A	B	C																								
<p><b>4.1.4.3 Bearing face diameter and height of washer-faced portion</b></p>  <p>a Reference datum for <math>d_w</math></p> <p><b>Figure 67</b></p>	<p><math>d_w \text{ min} = s_{\text{min}} - \text{IT16}</math> for width across flats &lt; 21 mm  <math>d_w \text{ min} = 0,95 s_{\text{min}}</math> for width across flats <math>\geq 21</math> mm  <math>d_w \text{ max} = s_{\text{actual}}</math></p> <table border="1"> <thead> <tr> <th rowspan="2">Thread diameter</th> <th colspan="2">c</th> </tr> <tr> <th>min.</th> <th>max.</th> </tr> </thead> <tbody> <tr> <td><math>\geq 1,6</math> to 2,5</td> <td>0,10</td> <td>0,25</td> </tr> <tr> <td>&gt; 2,5 to 4</td> <td>0,15</td> <td>0,40</td> </tr> <tr> <td>&gt; 4 to 6</td> <td>0,15</td> <td>0,50</td> </tr> <tr> <td>&gt; 6 to 14</td> <td>0,15</td> <td>0,60</td> </tr> <tr> <td>&gt; 14 to 36</td> <td>0,2</td> <td>0,8</td> </tr> <tr> <td>&gt; 36</td> <td>0,3</td> <td>1,0</td> </tr> </tbody> </table>	Thread diameter	c		min.	max.	$\geq 1,6$ to 2,5	0,10	0,25	> 2,5 to 4	0,15	0,40	> 4 to 6	0,15	0,50	> 6 to 14	0,15	0,60	> 14 to 36	0,2	0,8	> 36	0,3	1,0			<p>Requirements apply to both sides of symmetrical parts.</p>
Thread diameter	c																										
	min.	max.																									
$\geq 1,6$ to 2,5	0,10	0,25																									
> 2,5 to 4	0,15	0,40																									
> 4 to 6	0,15	0,50																									
> 6 to 14	0,15	0,60																									
> 14 to 36	0,2	0,8																									
> 36	0,3	1,0																									
 <p><b>Figure 68</b></p>	<p><math>d_w \text{ min}</math> for hexagon nuts with flange in accordance with product standards</p>																										

STANDARDSISO.COM · Click to view the full PDF of ISO 4759-1:2000



Feature	Tolerance for product grades			Notes																			
	A	B	C																				
 <p><math>\alpha = 90^\circ</math> to <math>120^\circ</math></p> <p><b>Figure 69</b></p>	$d \leq 5 \text{ mm} : d_{a \text{ max}} = 1,15d$ $5 \text{ mm} < d \leq 8 \text{ mm} :$ $d_{a \text{ max}} = d + 0,75$ $d > 8 \text{ mm} : d_{a \text{ max}} = 1,08d$ for all sizes: $d_{a \text{ min}} = d$			Requirements apply to both sides of symmetrical parts.																			
<p><b>4.1.5 Special products</b></p> <p><b>4.1.5.1 Castle nuts, slotted nuts</b></p>  <p><b>Figure 70</b></p> <table border="1" data-bbox="542 1433 1228 1702"> <tbody> <tr> <td><math>d_e</math></td> <td>h14</td> <td>h15</td> <td>h16</td> </tr> <tr> <td><math>m</math></td> <td>h14</td> <td>h15</td> <td>h17</td> </tr> <tr> <td><math>n</math></td> <td>H14</td> <td>H14</td> <td>H15</td> </tr> <tr> <td><math>w</math></td> <td>h14</td> <td>h15</td> <td>h17</td> </tr> <tr> <td><math>m_w</math></td> <td colspan="3">see <math>m_w</math>-values for hexagon nuts style 1 (see ISO 4032)</td> </tr> </tbody> </table>	$d_e$	h14	h15	h16	$m$	h14	h15	h17	$n$	H14	H14	H15	$w$	h14	h15	h17	$m_w$	see $m_w$ -values for hexagon nuts style 1 (see ISO 4032)					
$d_e$	h14	h15	h16																				
$m$	h14	h15	h17																				
$n$	H14	H14	H15																				
$w$	h14	h15	h17																				
$m_w$	see $m_w$ -values for hexagon nuts style 1 (see ISO 4032)																						

## 4.2 Geometrical tolerances




In accordance with ISO 1101 and ISO 2692 the tolerances specified in Figures 71 to 83 do not necessarily imply the use of any particular method of production, measurement or gauging.


Where the nut thread is used as the datum the pitch diameter shall be the reference diameter.

The maximum material principle in accordance with ISO 2692 is used.

Feature	Tolerance <i>t</i> for product grades			Notes
	A	B	C	
<p><b>4.2.1 Driving features</b></p> <p><b>4.2.1.1 Tolerances of form</b></p>  <p><sup>a</sup> 3 × simultaneously.</p> <p><b>Figure 71</b></p>  <p><sup>a</sup> 2 × simultaneously.</p> <p><b>Figure 72</b></p>				


Feature	Tolerance $t$ for product grades			Tolerance $t$ based on dimensions	Notes
	A	B	C		
<p><b>4.2.1.2 Tolerances of position</b></p> <p>a 3 × simultaneously.</p> <p><b>Figure 73</b></p>	2 IT13	2 IT14	2 IT15	$s$	
<p>a 3 × simultaneously.</p> <p><b>Figure 74</b></p>	2 IT13	2 IT14	—	$s$	
<p>a 2 × simultaneously.</p> <p><b>Figure 75</b></p>	2 IT13	2 IT14	2 IT15	$s$	

Feature	Tolerance $t$ for product grades			Tolerance $t$ based on dimensions	Notes
	A	B	C		
<p><b>4.2.2 Other features</b></p> <p><b>4.2.2.1 Tolerances of position</b></p>  <p><b>Figure 76</b></p>	2 IT14	2 IT15	—	$d_c$	
 <p><b>Figure 77</b></p>	2 IT13	2 IT14	2 IT15	$d$	
 <p><b>Figure 78</b></p>	2 IT13	2 IT14	—	$d_k$	

Feature	Tolerance $t$ for product grades			Tolerance $t$ based on dimension $d$	Notes
	A	B	C		
<b>4.2.2.2 Tolerance of total run-out</b> 	0,04		—	1,6	For symmetrical parts the perpendicularity requirement shall apply for both faces.
				0,08	
0,15	0,3		2,5		
					10


a Up to  $0,8s$  diameter only.

**Figure 79**





a Up to  $\varnothing 0,8s$  only.

**Figure 80**



a Up to  $\varnothing 0,8d_k$  only.




**Figure 81**




Feature	Tolerance $t$ for product grades			Notes
	A	B	C	
 <p>a Line of highest points on any radial line.</p> <p><b>Figure 82</b></p>	<p>For <math>t</math> see values for Figures 79, 80 and 81.</p>			
<p><b>4.2.2.3 Permissible deviation from the shape of bearing face</b></p>  <p>a Radial lines between <math>d_{a \max}</math> and <math>d_{w \min}</math>.</p> <p>b According to product standard.</p> <p><b>Figure 83</b></p>	<p>0,005d</p>			




5 Tolerances for tapping screws


5.1 Dimensional tolerances — Product grade A

Symbols and designations of dimensions are specified in ISO 225.

Feature	Tolerance	Notes
5.1.1 Thread	see ISO 1478	
5.1.2 Driving features  5.1.2.1 External  5.1.2.1.1 Width across flats   Figure 84	h13	
5.1.2.1.2 Width across corners   Figure 85	$e_{min} = 1,12 s_{min}$	
5.1.2.1.3 Height of head   Figure 86	For tolerances see ISO 1479	For tapping screws with hexagon flange head and hexagon washer head see ISO 7053 and ISO 10509 respectively.

Feature	Tolerance	Notes								
<p>5.1.2.1.4 Wrenching height</p>  <p>Figure 87</p>	<p><math>k_w \text{ min.} = 0,7 k_{\text{min}}</math></p>	<p>For tapping screws with hexagon flange head and hexagon washer head see ISO 7053 and ISO 10509 respectively.</p> <p>The symbol <math>k_w</math> replaces the previously used <math>k'</math>.</p>								
<p>5.1.2.2 Internal</p> <p>5.1.2.2.1 Width of slots</p>  <p>Figure 88</p>	<table border="1"> <thead> <tr> <th><math>n</math></th> <th>Tolerance<sup>a</sup></th> </tr> </thead> <tbody> <tr> <td><math>\leq 1</math></td> <td>+ 0,20 + 0,06</td> </tr> <tr> <td><math>&gt; 1 \leq 3</math></td> <td>+ 0,31 + 0,06</td> </tr> <tr> <td><math>&gt; 3 \leq 6</math></td> <td>+ 0,37 + 0,07</td> </tr> </tbody> </table>	$n$	Tolerance <sup>a</sup>	$\leq 1$	+ 0,20 + 0,06	$> 1 \leq 3$	+ 0,31 + 0,06	$> 3 \leq 6$	+ 0,37 + 0,07	<p><sup>a</sup> Tolerance field</p> <p>C13 for <math>n \leq 1</math></p> <p>C14 for <math>n &gt; 1</math></p>
$n$	Tolerance <sup>a</sup>									
$\leq 1$	+ 0,20 + 0,06									
$> 1 \leq 3$	+ 0,31 + 0,06									
$> 3 \leq 6$	+ 0,37 + 0,07									
<p>5.1.2.2.2 Depth of slots</p>  <p>Figure 89</p>	<p>The depth of slots is specified in product standards.</p>									

Feature	Tolerance	Notes
<p>5.1.2.2.3 Cross recesses</p>	<p>See ISO 4757 for all dimensions except penetration depths. For penetration depths see appropriate product standard.</p>	
<p>5.1.2.2.4 Hexalobular recess</p>	<p>See ISO 10664 for all dimensions except penetration depths. For penetration depths see appropriate product standard.</p>	
<p>5.1.3 Other features</p> <p>5.1.3.1 Head diameters</p>  <p>Figure 90</p>	<p>h14</p>	<p>Combined control of diameter and height for countersunk head screws as specified in ISO 7721.</p>
<p>5.1.3.2 Head height</p>  <p>Figure 91</p>	<p>h14</p>	
 <p>Figure 92</p>	<p>For countersunk head screws <math>k</math> is defined in product standards only as a maximum.</p>	<p>Combined control of diameter and height for countersunk head screws as specified in ISO 7721.</p>

Feature	Tolerance	Notes																		
<p><b>5.1.3.3 Length</b></p>  <p style="text-align: center;">Type C</p> <p style="text-align: center;">Type R                      Type F</p> <p style="text-align: center;"><b>Figure 93</b></p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: center;">Types C and R</th> </tr> <tr> <th style="text-align: center;"><i>l</i></th> <th style="text-align: center;">Tolerance</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;"><math>\leq 25</math></td> <td style="text-align: center;"><math>\pm 0,8</math></td> </tr> <tr> <td style="text-align: center;"><math>&gt; 25</math></td> <td style="text-align: center;"><math>\pm 1,3</math></td> </tr> </tbody> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: center;">Type F</th> </tr> <tr> <th style="text-align: center;"><i>l</i></th> <th style="text-align: center;">Tolerance</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;"><math>\leq 19</math></td> <td style="text-align: center;">0 - 0,8</td> </tr> <tr> <td style="text-align: center;"><math>&gt; 19 \leq 38</math></td> <td style="text-align: center;">0 - 1,3</td> </tr> <tr> <td style="text-align: center;"><math>&gt; 38</math></td> <td style="text-align: center;">0 - 1,5</td> </tr> </tbody> </table>	Types C and R		<i>l</i>	Tolerance	$\leq 25$	$\pm 0,8$	$> 25$	$\pm 1,3$	Type F		<i>l</i>	Tolerance	$\leq 19$	0 - 0,8	$> 19 \leq 38$	0 - 1,3	$> 38$	0 - 1,5	
Types C and R																				
<i>l</i>	Tolerance																			
$\leq 25$	$\pm 0,8$																			
$> 25$	$\pm 1,3$																			
Type F																				
<i>l</i>	Tolerance																			
$\leq 19$	0 - 0,8																			
$> 19 \leq 38$	0 - 1,3																			
$> 38$	0 - 1,5																			




STANDARDSISO.COM : Click to view the full PDF of ISO 4759-1:2000




5.2 Geometrical tolerances — Product grade A

In accordance with ISO 1101 and ISO 2692 the tolerances of form and position indicated in Figures 94 to 104 do not necessarily imply the use of any particular method of production, measurement or gauging.




Where a tapping screw thread is indicated either as the datum or as the toleranced feature the axis shall be determined from the major diameter of the thread.




The maximum material principle in accordance with ISO 2692 is used.

Feature	Tolerance $t$	Tolerance $t$ based on dimension	Notes
<p><b>5.2.1 Driving features</b></p> <p><b>5.2.1.1 Tolerance of form</b></p>  <p><math>6 \times 120^\circ</math></p> <p><sup>a</sup> 3 × simultaneously.</p> <p><b>Figure 94</b></p>			
<p><b>5.2.1.2 Tolerances of position</b></p>  <p><math>2\ IT13</math></p> <p><math>s</math></p> <p><math>1P\ max.</math></p> <p><math>6 \times 120^\circ</math></p> <p><sup>a</sup> The datum A shall be as close to the head as possible but within 1 <math>P</math> distance of the head. It shall not include the thread run-out or underhead fillet.</p> <p><sup>b</sup> MD means that tolerance applies in relation to the axis of the cylinder derived from the major thread diameter according to ISO 1101.</p> <p><sup>c</sup> 3 × simultaneously.</p> <p><b>Figure 95</b></p>			

Feature	Tolerance $t$	Tolerance $t$ based on dimension	Notes
 <p>a, b See Figure 95.</p> <p><b>Figure 96</b></p>	<p>2 IT12</p>	<p><math>d</math></p>	
 <p>a, b See Figure 95.</p> <p><b>Figure 97</b></p>	<p>2 IT12</p>	<p><math>d</math></p>	
 <p>a, b See Figure 95.</p> <p><b>Figure 98</b></p>	<p>2 IT12</p>	<p><math>d</math></p>	

STANDARDSISO.COM : Click to view the full PDF of ISO 4759-1:2000

Feature	Tolerance $t$	Tolerance $t$ based on dimension	Notes
 <p>a, b See Figure 95.</p> <p>c For referee purposes assessment of co-axiality of cross recess features shall be by means of a penetration gauge point in accordance with ISO 4757.</p>	<p>2 IT13</p>	<p><math>d</math></p>	
<p><b>Figure 99</b></p>  <p>a, b See Figure 95.</p> <p>c See Figure 99.</p>	<p>2 IT13</p>	<p><math>d</math></p>	
<p><b>5.2.2 Other features</b></p> <p><b>5.2.2.1 Tolerance of position</b></p>  <p>a, b See Figure 95.</p>	<p>2 IT13</p>	<p><math>d_k</math></p>	

Feature	Tolerance $t$	Tolerance $t$ based on dimension	Notes																				
<p><b>5.2.2.2 Total run-out</b></p>  <p>a, b See Figure 95. c Up to 0,8s diameter only.</p> <p><b>Figure 102</b></p>  <p>a, b See Figure 95. c up to 0,8 d_k diameter only.</p> <p><b>Figure 103</b></p> <table border="1" data-bbox="772 918 1011 1265"> <thead> <tr> <th><math>d</math></th> <th><math>t</math></th> </tr> </thead> <tbody> <tr><td>ST2,2</td><td>0,08</td></tr> <tr><td>ST2,9</td><td>0,16</td></tr> <tr><td>ST3,5</td><td>0,16</td></tr> <tr><td>ST4,2</td><td>0,16</td></tr> <tr><td>ST4,8</td><td>0,3</td></tr> <tr><td>ST5,5</td><td>0,3</td></tr> <tr><td>ST6,3</td><td>0,3</td></tr> <tr><td>ST8</td><td>0,34</td></tr> <tr><td>ST9,5</td><td>0,42</td></tr> </tbody> </table>	$d$	$t$	ST2,2	0,08	ST2,9	0,16	ST3,5	0,16	ST4,2	0,16	ST4,8	0,3	ST5,5	0,3	ST6,3	0,3	ST8	0,34	ST9,5	0,42		<p><math>d</math></p> <p><math>d</math></p>	<p>Tolerance <math>t</math> calculated as follows: <math>t \approx 1,2 d \times \tan 2^\circ</math></p>
$d$	$t$																						
ST2,2	0,08																						
ST2,9	0,16																						
ST3,5	0,16																						
ST4,2	0,16																						
ST4,8	0,3																						
ST5,5	0,3																						
ST6,3	0,3																						
ST8	0,34																						
ST9,5	0,42																						
<p><b>5.2.2.3 Straightness</b></p>  <p>b See Figure 95.</p> <p><b>Figure 104</b></p>	<p><math>t = 0,003l + 0,05</math></p>	<p>—</p>	<p>for <math>l \leq 20d</math></p>																				

**Annex A**  
(informative)

**Tolerances**

Numerical values of IT tolerance grades are given in Table A.1 and the limit deviations for shafts and for holes are given in Tables A.2 and A.3 respectively. These tolerances are taken from ISO 286-1 and ISO 286-2.

**Table A.1 — Numerical values of standard tolerance grades IT for basic sizes up to 500 mm**

Nominal dimension		Standard tolerance grades					
>	≤	IT12	IT13	IT14	IT15	IT16	IT17
Tolerances							
	3	0,1	0,14	0,25	0,4	0,6	1
3	6	0,12	0,18	0,3	0,48	0,75	1,2
6	10	0,15	0,22	0,36	0,58	0,9	1,5
10	18	0,18	0,27	0,43	0,7	1,1	1,8
18	30	0,21	0,33	0,52	0,84	1,3	2,1
30	50	0,25	0,39	0,62	1	1,6	2,5
50	80	0,3	0,46	0,74	1,2	1,9	3
80	120	0,35	0,54	0,87	1,4	2,2	3,5
120	180	0,4	0,63	1	1,6	2,5	4
180	250	0,46	0,72	1,15	1,85	2,9	4,6
250	315	0,52	0,81	1,3	2,1	3,2	5,2
315	400	0,57	0,89	1,4	2,3	3,6	5,7
400	500	0,63	0,97	1,55	2,5	4	6,3

**Table A.2 — Limit deviations for shafts**

Nominal dimension		Limit deviations								
>	≤	h13	h14	h15	h16	h17	js14	js15	js16	js17
	3	0 -0,14	0 -0,25	0 -0,4	0 -0,6	0 -1	± 0,125	± 0,2	± 0,3	± 0,5
3	6	0 -0,18	0 -0,3	0 -0,48	0 -0,75	0 -1,2	± 0,15	± 0,24	± 0,375	± 0,6
6	10	0 -0,22	0 -0,36	0 -0,58	0 -0,9	0 -1,5	± 0,18	± 0,29	± 0,45	± 0,75
10	18	0 -0,27	0 -0,43	0 -0,7	0 -1,1	0 -1,8	± 0,215	± 0,35	± 0,55	± 0,9
18	30	0 -0,33	0 -0,52	0 -0,84	0 -1,3	0 -2,1	± 0,26	± 0,42	± 0,65	± 1,05
30	50	0 -0,39	0 -0,62	0 -1	0 -1,6	0 -2,5	± 0,31	± 0,5	± 0,8	± 1,25
50	80	0 -0,46	0 -0,74	0 -1,2	0 -1,9	0 -3,0	± 0,37	± 0,6	± 0,95	± 1,5
80	120	0 -0,54	0 -0,87	0 -1,4	0 -2,2	0 -3,5	± 0,435	± 0,7	± 1,1	± 1,75
120	180	0 -0,63	0 -1	0 -1,6	0 -2,5	0 -4	± 0,5	± 0,8	± 1,25	± 2
180	250	0 -0,72	0 -1,15	0 -1,85	0 -2,9	0 -4,6	± 0,575	± 0,925	± 1,45	± 2,3
250	315	0 -0,81	0 -1,3	0 -2,1	0 -3,2	0 -5,2	± 0,65	± 1,05	± 1,6	± 2,6
315	400	0 -0,89	0 -1,4	0 -2,3	0 -3,6	0 -5,7	± 0,7	± 1,15	± 1,8	± 2,85
400	500	0 -0,97	0 -1,55	0 -2,5	0 -4	0 -6,3	± 0,775	± 1,25	± 2	± 3,15


Table A.3 — Limit deviations for holes

Nominal dimension		Limit deviations												
>	≤	C13	C14	D9	D10	D11	D12	EF8	11	E12	H14	H15	JS9	K9
	3	+0,2 +0,06	+0,31 +0,06	+0,045 +0,02	+0,06 +0,02	+0,08 +0,02	+0,12 +0,02	+0,024 +0,01	+0,074 +0,014	+0,114 +0,014	+0,25 0	+0,4 0	±0,012 5	0 -0,025
3	6	+0,25 +0,07	+0,37 +0,07	+0,06 +0,03	+0,078 +0,03	+0,105 +0,03	+0,15 +0,03	+0,032 +0,014	+0,095 +0,02	+0,14 +0,02	+0,3 0	+0,48 0	±0,015	0 -0,03
6	10					+0,13 +0,04	+0,19 +0,04	+0,04 +0,018	+0,115 +0,025	+0,175 +0,025	+0,36 0	+0,58 0	±0,018	0 -0,036
10	18						+0,23 +0,05		+0,142 +0,032	+0,212 +0,032	+0,43 0	+0,7 0		
18	30						+0,275 +0,065				+0,52 0	+0,84 0		
30	50						+0,33 +0,08				+0,62 0	+1 0		
50	80						+0,4 +0,1				+0,74 0	+1,2 0		
80	120						+0,47 +0,12				+0,87 0	+1,4 0		
120	180										+1 0	+1,6 0		
180	250										+1,15 0	+1,85 0		
250	315										+1,3 0	+2,1 0		
315	400										+1,4 0	+2,3 0		
400	500										+1,55 0	+2,5 0		

STANDARDSISO.COM : Click to view the full PDF of ISO 4759-1:2000


**Annex B**  
(informative)

**Examples of dimensioned and toleranced fasteners**



- a Up to 0,8  $d_k$  diameter only.
- b 3 × simultaneously.

**Figure B.1 — Hexagon socket head cap screw with shank and cone point**



- a Line of highest points on any radial line.
- b Radial lines between  $d_{a \max}$  and  $d_{w \min}$ .
- c 3 x simultaneously.

Figure B.2 — Hexagon head bolt with flange and pilot point