

INTERNATIONAL STANDARD

ISO
4762

Fourth edition
2004-03-01

Hexagon socket head cap screws

Vis à tête cylindrique à six pans creux

STANDARDSISO.COM : Click to view the full PDF of ISO 4762:2004



Reference number
ISO 4762:2004(E)

© ISO 2004

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 4762:2004

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
1 Scope	1
2 Normative references	1
3 Dimensions	2
4 Requirements and reference International Standards	9
5 Designation	9
Annex A (informative) Masses	10

STANDARDSISO.COM : Click to view the full PDF of ISO 4762:2004

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 4762 was prepared by Technical Committee ISO/TC 2, *Fasteners*.

This fourth edition cancels and replaces the third edition (ISO 4762:1997), which has been technically revised.

STANDARDSISO.COM : Click to view the full PDF of ISO 4762:2004

Hexagon socket head cap screws

1 Scope

This International Standard specifies the characteristics of hexagon socket head cap screws with coarse pitch thread from M1,6 up to and including M64 and product grade A.

For approximate masses of screws see Annex A.

If, in special cases, specifications other than those listed in this International Standard are required, they should be selected from existing International Standards, e.g ISO 261, ISO 888, ISO 898-1, ISO 965-2, ISO 3506-1, ISO 8839 and ISO 4759-1.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 225, *Fasteners — Bolts, screws, studs and nuts — Symbols and designations of dimensions*

ISO 261, *ISO general-purpose metric screw threads — General plan*

ISO 888, *Bolts, screws and studs — Nominal lengths, and thread lengths for general purpose bolts*

ISO 898-1, *Mechanical properties of fasteners made of carbon steel and alloy steel — Part 1: Bolts, screws and studs*

ISO 965-2, *ISO general purpose metric screw threads — Tolerances — Part 2: Limits of sizes for general purpose external and internal screw threads — Medium quality*

ISO 965-3, *ISO general purpose metric screw threads — Tolerances — Part 3: Deviations for constructional screw threads*

ISO 3269, *Fasteners — Acceptance inspection*

ISO 3506-1, *Mechanical properties of corrosion-resistant stainless-steel fasteners — Part 1: Bolts, screws and studs*

ISO 4042, *Fasteners — Electroplated coatings*

ISO 4753, *Fasteners — Ends of parts with external ISO metric thread*

ISO 4759-1, *Tolerances for fasteners — Part 1: Bolts, screws, studs and nuts — Product grades A, B and C*

ISO 6157-1, *Fasteners — Surface discontinuities — Part 1: Bolts, screws and studs for general requirements*

ISO 6157-3, *Fasteners — Surface discontinuities — Part 3: Bolts, screws and studs for special requirements*

ISO 8839, *Mechanical properties of fasteners — Bolts, screws, studs and nuts made of non-ferrous metals*

ISO 8992, *Fasteners — General requirements for bolts, screws, studs and nuts*


ISO 10683, Fasteners — Non-electrolytically applied zinc flake coatings

ISO 23429, Gauging of hexagon sockets

3 Dimensions

See Figure 1 and Table 1.

Symbols and designations of dimensions are defined in ISO 225.



Maximum underhead fillet


$$l_{f, \max} = 1,7 r_{\max}$$

$$r_{\max} = \frac{d_{a, \max} - d_{s, \max}}{2}$$


r_{\min} , see Table 1

Figure 1


Permissible alternative form of socket



Top and bottom edge of the head



For broached sockets which are at the maximum limit of size the overcut resulting from drilling shall not exceed 1/3 of the length of any flat of the socket which is $e/2$.



- a A slight rounding or countersink at the mouth of the socket is permissible.
- b Point chamfered or for sizes M4 and below "as rolled" according to ISO 4753.
- c Incomplete thread $u \leq 2 P$.
- d d_s applies if values of $l_{s, \min}$ are specified.
- e Top edge of head may be rounded or chamfered as shown at the option of the manufacturer.
- f Bottom edge of head may be rounded or chamfered to d_w but in every case shall be free from burrs.

Figure 1 (continued)

STANDARDSISO.COM: Click to view the full PDF of ISO 4762:2004

Table 1 — Dimensions

Dimensions in millimetres

Thread (d)	M1,6		M2		M2,5		M3		M4		M5		M6		M8		M10		M12			
	l_s min.	l_g max.	l_s min.	l_g max.	l_s min.	l_g max.	l_s min.	l_g max.	l_s min.	l_g max.	l_s min.	l_g max.	l_s min.	l_g max.	l_s min.	l_g max.	l_s min.	l_g max.	l_s min.	l_g max.		
P^a	0,35		0,4		0,45		0,5		0,7		0,8		1		1,25		1,5		1,75			
b^b ref.	15		16		17		18		20		22		24		28		32		36			
d_k max. ^c	3,00		3,80		4,50		5,50		7,00		8,50		10,00		13,00		16,00		18,00			
d_k max. ^d	3,14		3,98		4,68		5,68		7,22		8,72		10,22		13,27		16,27		18,27			
d_k min.	2,86		3,62		4,32		5,32		6,78		8,28		9,78		12,73		15,73		17,73			
d_a max.	2		2,6		3,1		3,6		4,7		5,7		6,8		9,2		11,2		13,7			
d_s max.	1,60		2,00		2,50		3,00		4,00		5,00		6,00		8,00		10,00		12,00			
d_s min.	1,46		1,86		2,36		2,86		3,82		4,82		5,82		7,78		9,78		11,73			
$e^{e,f}$ min.	1,733		1,733		2,303		2,873		3,443		4,583		5,723		6,863		9,149		11,429			
l_t max.	0,34		0,51		0,51		0,51		0,6		0,6		0,68		1,02		1,02		1,45			
k max.	1,60		2,00		2,50		3,00		4,00		5,00		6,0		8,00		10,00		12,00			
k min.	1,46		1,86		2,36		2,86		3,82		4,82		5,7		7,64		9,64		11,57			
r min.	0,1		0,1		0,1		0,1		0,2		0,2		0,25		0,4		0,4		0,6			
nom.	1,5		1,5		2		2,5		3		4		5		6		8		10			
s^f max.	1,58		1,58		2,08		2,58		3,08		4,095		5,14		6,14		8,175		10,175			
s^f min.	1,52		1,52		2,02		2,52		3,02		4,020		5,02		6,02		8,025		10,025			
t min.	0,7		1		1,1		1,3		2		2,5		3		4		5		6			
v max.	0,16		0,2		0,25		0,3		0,4		0,5		0,6		0,8		1		1,2			
d_w min	2,72		3,48		4,18		5,07		6,53		8,03		9,38		12,33		15,33		17,23			
w min.	0,55		0,55		0,85		1,15		1,4		1,9		2,3		3,3		4		4,8			
l^g	Shank length l_s and grip length l_g																					
	nom.	l_s min.	l_g max.																			
	2,5	2,3	2,7																			
	3	2,8	3,2																			
	4	3,76	4,24																			
	5	4,76	5,24																			
	6	5,76	6,24																			
	8	7,71	8,29																			
	10	9,71	10,29																			
	12	11,65	12,35																			

Table 1 — Dimensions (continued)

Thread (d)		(M14) ^h	M16	M20	M24	M30	M36	M42	M48	M56	M64								
<i>P</i> ^a		2	2	2,5	3	3,5	4	4,5	5	5,5	6								
<i>b</i> ^b	ref.	40	44	52	60	72	84	96	108	124	140								
<i>d</i> _k	max. ^c	21,00	24,00	30,00	36,00	45,00	54,00	63,00	72,00	84,00	96,00								
	max. ^d	21,33	24,33	30,33	36,39	45,39	54,46	63,46	72,46	84,54	96,54								
	min.	20,67	23,67	29,67	35,61	44,61	53,54	62,54	71,54	83,46	95,46								
<i>d</i> _a	max.	15,7	17,7	22,4	26,4	33,4	39,4	45,6	52,6	63	71								
	max.	14,00	16,00	20,00	24,00	30,00	36,00	42,00	48,00	56,00	64,00								
<i>d</i> _s	min.	13,73	15,73	19,67	23,67	29,67	35,61	41,61	47,61	55,54	63,54								
<i>e</i> ^e , <i>f</i>	min.	13,716	15,996	19,437	21,734	25,154	30,854	36,571	41,131	46,831	52,531								
<i>l</i> _t	max	1,45	1,45	2,04	2,04	2,89	2,89	3,06	3,91	5,95	5,95								
	max.	14,00	16,00	20,00	24,00	30,00	36,00	42,00	48,00	56,00	64,00								
<i>k</i>	min.	13,57	15,57	19,48	23,48	29,48	35,38	41,38	47,38	55,26	63,26								
<i>r</i>	min.	0,6	0,6	0,8	0,8	1	1	1,2	1,6	2	2								
	nom.	12	14	17	19	22	27	32	36	41	46								
<i>s</i> ^f	max.	12,212	14,212	17,23	19,275	22,275	27,275	32,33	36,33	41,33	46,33								
	min.	12,032	14,032	17,05	19,065	22,065	27,065	32,08	36,08	41,08	46,08								
<i>t</i>	min.	7	8	10	12	15,5	19	24	28	34	38								
<i>v</i>	max.	1,4	1,6	2	2,4	3	3,6	4,2	4,8	5,6	6,4								
<i>d</i> _w	min	20,17	23,17	28,87	34,81	43,61	52,54	61,34	70,34	82,26	94,26								
<i>w</i>	min.	5,8	6,8	8,6	10,4	13,1	15,3	16,3	17,5	19	22								
<i>l</i> ^g	nom.	<i>l</i> _s min.	<i>l</i> _s max.	<i>l</i> _g min.	<i>l</i> _g max.	<i>l</i> _s min.	<i>l</i> _s max.	<i>l</i> _g min.	<i>l</i> _g max.	<i>l</i> _s min.	<i>l</i> _s max.	<i>l</i> _g min.	<i>l</i> _g max.	<i>l</i> _s min.	<i>l</i> _s max.	<i>l</i> _g min.	<i>l</i> _g max.		
																		<i>l</i> _s min.	<i>l</i> _s max.
	2,5	2,3	2,7																
	3	2,8	3,2																
	4	3,76	4,24																
	5	4,76	5,24																
	6	5,76	6,24																
	8	7,71	8,29																
	10	9,71	10,29																
	12	11,65	12,35																

Shank length *l*_s and grip length *l*_g

Table 1 — Dimensions (continued)

a	P is the pitch of the thread.
b	For lengths between the bold stepped lines in the unshaded area.
c	For plain heads.
d	For knurled heads.
e	$e_{\min} = 1,14 s_{\min}$
f	Combined gauging of socket dimensions e and s , see ISO 23429.
g	The range of commercial lengths is between the bold stepped lines. Lengths in the shaded area are threaded to the head within $3 P$. Lengths below the shaded area have values of l_g and l_s in accordance with the following formulae: $l_{g, \max} = l_{\text{nom}} - b$ $l_{s, \min} = l_{g, \max} - 5 P$
h	The size in brackets should be avoided if possible.

STANDARDSISO.COM : Click to view the full PDF of ISO 4762:2004