
**Fruits, vegetables and derived
products — Determination of benzoic acid
content — Spectrophotometric method**

*Fruits, légumes et produits dérivés — Détermination de la teneur en
acide benzoïque — Méthode spectrophotométrique*

STANDARDSISO.COM : Click to view the full PDF of ISO 5518:2007



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 5518:2007

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 5518 was prepared by Technical Committee ISO/TC 34, *Food products*, Subcommittee SC 3, *Fruit and vegetable products*.

This second edition cancels and replaces the first edition (ISO 5518:1978), which has been technically revised.

STANDARDSISO.COM : Click to view the full PDF of ISO 5518:2007

Introduction

A method for determining the benzoic acid content of fruits, vegetable and derivatives, described in 1959, was based on the technique of peak emergence. The advantage of this method was that it was specifically intended for benzoic acid, with one exception: *p*-chlorobenzoic acid.

However, it was necessary to make a modification, consisting of purifying the ethereal extract by chromic acid oxidation. This results in the elimination of the effects of colouring substances in certain vegetable products containing anthocyanins, and also all the oxybenzoic acids and sorbic acid which may be present if several antiseptics have been used. Moreover, purification increases the sensitivity of the method. This improved technique was also more rapid.

STANDARDSISO.COM : Click to view the full PDF of ISO 5518:2007

Fruits, vegetables and derived products — Determination of benzoic acid content — Spectrophotometric method

1 Scope

This International Standard specifies a method for determining the benzoic acid content of fruits, vegetables and derived products.

As chlorobenzoic acids are resistant to oxidation, the method cannot be applied in the presence of *p*-chlorobenzoic acid, as the absorption spectrum of this acid is close to that of benzoic acid. Neither can it be used in the presence of cinnamic acid, which is transformed into benzoic acid by chromic acid oxidation.

NOTE The cinnamic acid determined as benzoic acid in this method exists generally only in the form of traces in vegetables, and therefore has no effect on the result obtained, except in the case of cinnamon bark, which contains higher quantities.

2 Principle

The test sample is homogenized, followed by dilution and acidification of a test portion. The benzoic acid is extracted by diethyl ether, then this acid undergoes alkaline re-extraction and purification by oxidation using acidified potassium dichromate. The purified benzoic acid dissolved in diethyl ether is determined by spectrophotometry.

3 Reagents

Use only reagents of recognized analytical quality and distilled water or water of at least equivalent purity.

3.1 Tartaric acid [COOH(CHOH)₂COOH], crystalline.

3.2 Sodium hydroxide (NaOH), approximately 1 mol/l solution.

3.3 Potassium dichromate (K₂Cr₂O₇), solution containing 33 g/l to 34 g/l.

3.4 Dilute sulfuric acid (H₂SO₄), obtained by diluting 2 volumes of concentrated sulfuric acid ($\rho_{20} = 1,84$ g/ml) with 1 volume of water.

3.5 Diethyl ether [(CH₃CH₂)₂O], recently distilled.

3.6 Benzoic acid (C₆H₅COOH), standard solution in diethyl ether containing 0,100 g/l.

3.7 Sodium hydrogen carbonate (NaHCO₃), crystalline.

4 Apparatus

Usual laboratory apparatus and, in particular, the following.

4.1 Volumetric flasks, of capacities 50 ml and 1 000 ml.

4.2 Beakers, of capacities 50 ml and 100 ml.

4.3 Graduated pipettes, of capacities 10 ml, 20 ml and 50 ml.

4.4 Flasks, of capacity 250 ml, having ground-glass stoppers and made of borosilicate glass.

4.5 Separating funnels, of capacities 100 ml and 500 ml.

4.6 Evaporating dish, of diameter about 10 cm.

4.7 Water bath, capable of being controlled at a temperature of 70 °C to 80 °C.

4.8 Homogenizer or mortar, as appropriate.

4.9 Spectrophotometer for determination in the ultraviolet range, equipped with a monochromator allowing measurement to the nearest 0,5 nm, with silica cells of optical path length 10 mm or 20 mm (preferably 20 mm so as to increase sensitivity), equipped with ground glass covers.

4.10 Analytical balance.

5 Sampling

A representative sample should have been sent to the laboratory. It should not have been damaged or changed during transport or storage.

6 Procedure

6.1 Preparation of test sample

6.1.1 Liquid products (e.g. juices, pulpy fluid products, syrups)

Thoroughly mix the laboratory sample.

6.1.2 Thick products (e.g. marmalades, jams)

Homogenize the laboratory sample after having carefully mixed it.

6.1.3 Solid products (e.g. fruits, vegetables)

Cut a part of the laboratory sample into small pieces and remove seeds, stalks and carpellary cells, if necessary. Carefully homogenize approximately 40 g of the sample.

6.1.4 Frozen or deep-frozen products

After thawing the sample in a closed container and removing, if necessary, seeds, stalks and carpellary cells, mix the product with the liquid formed during the thawing process and proceed as described in 6.2.1, 6.2.2 or 6.2.3 as appropriate.

6.2 Preparation of test portion

6.2.1 Liquid products

Using a pipette (4.3), take 20 ml of the test sample (6.1), free from substances in suspension, dilute it with approximately 50 ml of water and transfer it to a 500 ml separating funnel (4.5) (separating funnel A).

The test portion may also be taken by mass by weighing, to the nearest 0,01 g, approximately 20 g of the test sample.

6.2.2 Pulpy and fluid products

Take 20 ml of the test sample (6.1). Place in a mortar (4.8) and dilute with 20 ml of water. After decanting, filter the liquid.

Twice successively, take up the residue in 20 ml of water and filter after decanting.

Collect all the filtrates directly in a 500 ml separating funnel (4.5) (separating funnel A).

The test portion may also be taken by mass by weighing, to the nearest 0,01 g, approximately 20 g of the test sample.

6.2.3 Thick or solid products

Weigh, to the nearest 0,01 g, approximately 10 g of the test sample (6.1) and, using 30 ml to 40 ml of water, transfer it to a 250 ml flask (4.4).

Add approximately 50 mg of sodium hydrogen carbonate (3.7) (see Note). Shake, then place the flask on the water bath (4.7), controlled at 70 °C to 80 °C, and leave for 15 min to 30 min. Filter the contents of the flask and rinse twice using 15 ml to 20 ml of water each time.

Collect all the filtrates in a 500 ml separating funnel (4.5) (separating funnel A). Allow to cool.

NOTE The addition of sodium hydrogen carbonate is intended to neutralize the benzoic acid, traces of which could be lost by volatilization.

6.3 Extraction of the benzoic acid

WARNING — Attention is drawn to the hazard derived from the use of diethyl ether, which is a highly flammable, explosive and harmful substance.

6.3.1 Introduce 1 g of the tartaric acid (3.1) into the separating funnel A (4.5) containing the diluted test portion (6.2), add 60 ml of the diethyl ether (3.5) and shake carefully.

Allow to separate, then collect the ethereal layer in a second 500 ml separating funnel (4.5) (separating funnel B).

Wash the aqueous phase in the first separating funnel (A) with 60 ml of the diethyl ether.

Allow to separate, then collect the ethereal layer in the separating funnel (B) containing the first layer collected.

Proceed similarly with a third extraction with 30 ml of the diethyl ether and combine the ethereal layer with the first two in the separating funnel (B).

6.3.2 Extract the benzoic acid from the ethereal solution by adding successively 10 ml and then 5 ml of the sodium hydroxide solution (3.2), and then twice 10 ml of water. After each addition, shake, then allow to separate and collect the aqueous phase.

Collect the aqueous phases in an evaporating dish (4.6). Place the dish on the water bath (4.7), controlled at 70 °C to 80 °C, and leave until the volume of the alkaline solution is reduced by approximately half, to remove the residual dissolved diethyl ether.

6.4 Purification of the benzoic acid

After cooling, pour the contents of the dish into a 250 ml flask (4.4) containing a mixture of 20 ml of the dilute sulfuric acid (3.4) and 20 ml of the potassium dichromate solution (3.3). Stopper the flask and leave for at least 1 h.

Other preservatives derived from benzoic acid may be present. In this case, leave the flask for at least 3 h to oxidize completely the three hydroxybenzoic acids and prevent any interference in the determination. The extension of the reaction time creates no problem as the benzoic acid resists this oxidizing mixture.

When the initial product also contains sorbic acid, it is necessary to prolong oxidation for 24 h so as to ensure the complete destruction of this acid.

6.5 Extraction of the purified benzoic acid

Extract the benzoic acid by treating the above solution (6.4) twice with 20 ml to 25 ml of the diethyl ether (3.5), collecting the ethereal solutions. Wash the ethereal solutions twice with several millilitres of water. After decanting very carefully, filter through a dry filter paper and collect the filtrate in a 50 ml volumetric flask (4.1). Then wash the filter with several millilitres of the diethyl ether, adding sufficient washing solvent to dilute to the mark.

6.6 Determination

Using the spectrophotometer (4.9), measure the absorbance of the ethereal solution (6.5) in relation to the absorbance of the pure diethyl ether at 267,5 nm, 272 nm and 276,5 nm (see Note).

The absorbance due to benzoic acid is given by the formula for the differential measure of emergence at 272 nm:

$$A_2 - \frac{A_1 + A_3}{2}$$

where

A_1 is the absorbance at 267,5 nm;

A_2 is the absorbance at 272 nm;

A_3 is the absorbance at 276,5 nm.

NOTE Examination of the absorption spectrum of the ethereal solution of purified benzoic acid allows characterization of this product by the presence of two peaks at 272 nm and 279 nm.

The benzoic acid extracted by the diethyl ether is determined by the measurement of the relative height of the peak at 272 nm with respect to the straight line which joins the points on the abscissa between 267,5 nm and 276,5 nm.

6.7 Number of determinations

Carry out two determinations on the same test sample (6.1).

6.8 Plotting the calibration curve

Into a series of six 50 ml volumetric flasks (4.1), introduce respectively 5 ml, 7,5 ml, 10 ml, 12,5 ml, 15 ml and 20 ml of the standard benzoic acid solution (3.6). Dilute to the mark with the diethyl ether (3.5).

The solutions obtained contain respectively 10 mg, 15 mg, 20 mg, 25 mg, 30 mg and 40 mg of benzoic acid per litre.