

---

---

**Motorcycle tyres and rims (metric series) —**

Part 3:

**Range of approved rim contours**

*Pneumatiques et jantes pour motocycles (séries millimétriques) —*

*Partie 3: Gamme des profils de jante homologués*

STANDARDSISO.COM : Click to view the full PDF of ISO 5751-3:2010



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 5751-3:2010



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 5751-3 was prepared by Technical Committee ISO/TC 31, *Tyres, rims and valves*, Subcommittee SC 10, *Cycle, moped, motorcycle tyres and rims*.

This sixth edition cancels and replaces the fifth edition (ISO 5751-3:2004), which has been technically revised.

ISO 5751 consists of the following parts, under the general title *Motorcycle tyres and rims (metric series)*:

- *Part 1: Design guides*
- *Part 2: Tyre dimensions and load-carrying capacities*
- *Part 3: Range of approved rim contours*

[STANDARDSISO.COM](https://standardsiso.com) : Click to view the full PDF of ISO 5751-3:2010

# Motorcycle tyres and rims (metric series) —

## Part 3: Range of approved rim contours

### 1 Scope

This part of ISO 5751 specifies the approved rim contours for motorcycle rims on which metric series motorcycle tyres are mounted.

NOTE See ISO 4249 for motorcycle tyres and rims (code-designated series) of rim diameter codes 13 and above, and ISO 6054 for those of codes 12 and below.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4249-3, *Motorcycle tyres and rims (code-designated series) — Part 3: Rims*

ISO 5751-2, *Motorcycle tyres and rims (metric series) — Part 2: Tyre dimensions and load-carrying capacities*

ISO 6054-2:1990, *Motorcycle tyres and rims (Code-designated series) — Diameter codes 4 to 12 — Part 2: Rims*

### 3 Approved rim contours

See Tables 1 and 2 for the range of permitted rims and approved rim contour codes, and for the coefficients and tyre nominal section widths used to calculate minimum and maximum rim widths.

Table 1 — Coefficients for approved rims

Series	Tyre construction	Coefficient,	
		minimum, $R_{\min}$	maximum, $R_{\max}$
100 to 80	Diagonal and bias-belted	0,50	0,70
	Radial	0,60	0,70
75	Diagonal and bias-belted	0,55	0,75
	Radial	0,65	0,75
70 to 60	Diagonal and bias-belted	0,60	0,80
	Radial	0,70	0,80
55 and 50	Diagonal and bias-belted	0,70	0,85
	Radial	0,75	0,85
45 to 30	Radial	0,85	0,95

Minimum rim width =  $S_N \times R_{\min}$   
Maximum rim width =  $S_N \times R_{\max}$   
where  $S_N$  is the tyre nominal section width (see Table 2).  
Calculated values shall be rounded to the nearest standardized rim widths as specified in ISO 4249-3.

The dimensions of rim contours, diameter details and complete marking of rims of nominal rim diameter shall be in accordance with

- ISO 4249-3 for codes 13 and above, and
- ISO 6054-2 for codes 12 and below.

The recommended rims correspond to the measuring rim widths ( $R_m$ ) specified in ISO 5751-2.

The design new tyre section width,  $S$ , and the maximum overall width in service,  $W_{\max}$ , specified in ISO 5751-2 will change 1 mm for each 0.1 code (2,5 mm) change in rim width from the recommended (measuring) rim width.

Table 2 — Approved rim contours

Tyre nominal section width $S_N$	Approved rims <sup>abc</sup>
<b>30, 35, 40 and 45 series</b>	
210	MT7.00; MT7.50; MT8.00
240	MT8.00; MT8.50; MT9.00
250	MT8.50; MT9.00; MT9.50
260	MT8.50; MT9.00; MT9.50
280	MT9.50; MT10.00; MT10.50
300	MT10.00; MT10.50; MT11.00
330	MT11.00; MT11.50; MT12.00; MT12.50
360	MT12.00; MT12.50; MT13.00; MT13.50
<b>55 and 50 series</b>	
130	MT3.75; MT4.00
140	MT4.00; MT4.25; MT4.50
150	MT4.50; MT5.00
160	MT4.50; MT5.00
170	MT5.00; MT5.50
180	(MT5.00); MT5.50; MT6.00
190	MT5.50; MT6.00
200	MT6.00; MT6.25; MT6.50
210	MT6.25; MT6.50; MT7.00
240	MT7.00; MT7.50; MT8.00
<b>60, 65 and 70 series</b>	
80	(MT1.85); (1.85); 2.15; MT2.15; 2.50; MT2.50
100	(2.50); (MT2.50); 2.75; MT2.75; MT3.00
110	(2.50); (MT2.50); (2.75); (MT2.75); MT3.00; MT3.50
120	(2.75); (MT2.75); (MT3.00); MT3.50; MT3.75
130	(MT3.00); MT3.50; MT3.75; MT4.00
140	(MT3.50); MT3.75; MT4.00; MT4.25; MT4.50
150	(MT3.50); (MT3.75); MT4.00; MT4.25; MT4.50
160	(MT3.75); (MT4.00); MT4.25; MT4.50; MT5.00
170	(MT4.00); MT4.25; MT4.50; MT5.00; MT5.50
180	(MT4.25); (MT4.50); MT5.00; MT5.50
190	(MT4.50); MT5.00; MT5.50; MT6.00
200	(MT4.75); (MT5.00); MT5.50; MT6.00; MT6.25
210	(MT5.00); (MT5.50); MT6.00; MT6.25; MT6.50
230	(MT5.50); (MT6.00); MT6.25; MT6.50; MT7.00
<b>75 series</b>	
140	(MT3.00); MT3.50; MT3.75; MT4.00; MT4.75

Table 2 (continued)

Tyre nominal section width $S_N$	Approved rims <sup>abc</sup>
<b>80, 90 and 100 series</b>	
50	1.20; 1.40
60	(1.20); 1.40; 1.50; MT1.50; 1.60; MT1.60
70	(1.40); (1.50); (MT1.50); 1.60; MT1.60; 1.85; MT1.85
80	(1.60); (MT1.60); 1.85; MT1.85; 2.15; MT2.15
90	(1.85); (MT1.85); 2.15; MT2.15; 2.50; MT2.50
100	(2.15); (MT2.15); 2.50; MT2.50; 2.75; MT2.75
110	(2.15); (MT2.15); 2.50; MT2.50; 2.75; MT2.75; 3.00; MT3.00
120	(2.50); (MT2.50); 2.75; MT2.75; 3.00; MT3.00
130 <sup>d</sup>	(2.50); (MT2.50); (2.75); (MT2.75); 3.00; MT3.00; MT3.50
140 <sup>d</sup>	(2.75); (MT2.75); (3.00); (MT3.00); MT3.50; MT3.75
150 <sup>d</sup>	(3.00); (MT3.00); MT3.50; MT3.75; MT4.00; MT4.25
160	(MT3.50); MT3.75; MT4.00; MT4.25; MT4.50
170	(MT3.50); (MT3.75); MT4.00; MT4.25; MT4.50
180	(MT3.50); (MT3.75); (MT4.00); MT4.25; MT4.50; MT5.00
a	Recommended rims are the measuring rims.
b	Care should be taken, especially when either tyres or rims, or both, are not marked with the suffix M/C, not to fit motorcycle tyres to rims designed for tyres for other types of service (e.g. passenger cars or agricultural machines). Cylindrical bead-seat rims are for tube-type tyres only.
c	Rims within parentheses are permitted for diagonal-ply and bias-belted tyres only.
d	For tyre sizes 130/90-16, 140/90-16 and 150/80-16, a 3.00D rim with a specified rim diameter of 405,6 mm ± 0,4 mm and with humps is permitted (see ISO 6054-2 for contour dimensions).