
INTERNATIONAL STANDARD



6122

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

**Surface active agents — Technical alkane sulphonates —
Determination of total alkane sulphonates content**

Agents de surface — Alcanesulfonates techniques — Détermination de la teneur en alcanesulfonates totaux

First edition — 1978-08-15

STANDARDSISO.COM : Click to view the full PDF of ISO 6122:1978

UDC 661.186.5 : 543.24

Ref. No. ISO 6122-1978 (E)

Descriptors : surfactants, alkane sulphonates, chemical analysis, determination of content, purity.

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been set up has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 6122 was developed by Technical Committee ISO/TC 91, *Surface active agents*, and was circulated to the member bodies in September 1977.

It has been approved by the member bodies of the following countries :

Australia	India	Romania
Austria	Iran	South Africa, Rep. of
Belgium	Italy	Spain
Brazil	Japan	Switzerland
Bulgaria	Kenya	Turkey
Chile	Mexico	United Kingdom
France	Netherlands	U.S.A.
Germany	New Zealand	U.S.S.R.
Hungary	Poland	

No member body expressed disapproval of the document.

Surface active agents – Technical alkane sulphonates – Determination of total alkane sulphonates content

1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies a method for the determination of total alkane sulphonates content (mono- + di-) of technical alkane sulphonates containing small quantities of paraffins.

It is applicable to all alkali metal salts of the products of sulphochlorination and sulphoxidation of paraffins.

2 REFERENCES

ISO 607, *Surface active agents and detergents – Methods of sample division.*¹⁾

ISO 894, *Surface active agents – Technical sodium primary alkylsulphates – Methods of analysis.*

3 DEFINITION

For the purpose of this International Standard, the following definition applies :

alkane sulphonate : Alkali metal salt of the sulphonic acids present in the products of sulphochlorination and sulphoxidation of pure straight-chain paraffins of which the chain consists of between 12 and 20 carbon atoms.

4 PRINCIPLE

Dispersion of a test portion of the technical alkane sulphonate in a sodium sulphate solution, and addition of a mixture of butan-1-ol and acetone to precipitate sodium sulphate decahydrate and part of the sodium chloride.

Filtration to obtain a mixture of alkane sulphonates (mono- + di-), which may be contaminated by a little sodium chloride.

Evaporation of solvent so that the small quantities of paraffins are eliminated, gravimetric determination of the alkane sulphonates content, and potentiometric determination of any sodium chloride present.

5 REAGENTS

During the analysis, use only reagents of recognized analytical grade and only distilled water or water of equivalent purity.

5.1 Acetone.

5.2 Butan-1-ol and acetone mixture (60 + 40) ($V_1 + V_2$).

5.3 Sodium sulphate, anhydrous, 200 g/l solution.

6 APPARATUS

Ordinary laboratory apparatus and

6.1 Boiling flask or crystallizing dish, glass, 250 ml.

6.2 Oven capable of being regulated at 120 ± 2 °C.

6.3 Magnetic stirrer.

7 SAMPLING

The laboratory sample shall be prepared and stored according to the instructions given in ISO 607.

8 PROCEDURE

8.1 Test portion

Weigh, to the nearest 0,001 g, into a 250 ml conical flask, a test portion which contains about 0,5 to 1 g of total alkane sulphonates.

8.2 Determination

Add to the test portion (8.1), 15 ml of the sodium sulphate solution (5.3) and heat the mixture to 50 °C, stirring with the magnetic stirrer (6.3).

¹⁾ At present at the stage of draft. (Revision of ISO/R 607.)