

INTERNATIONAL STANDARD

ISO 701

Second edition
1998-05-15

International gear notation — Symbols for geometrical data

Notation internationale des engrenages — Symboles géométriques

STANDARDSISO.COM : Click to view the full PDF of ISO 701:1998



Reference number
ISO 701:1998(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 701 was prepared by Technical Committee ISO/TC 60, *Gears*, Subcommittee SC 1, *Nomenclature and worm gears*.

This second edition of ISO 701 cancels and replaces the first edition (ISO 701:1976), which has been technically revised.

STANDARDSISO.COM : Click to view the full PDF of ISO 701:1998

© ISO 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet iso@iso.ch

Printed in Switzerland

Introduction

The symbols in this International Standard are defined for use in relation to the principal geometrical terms defined in ISO 1122-1:1998, *Vocabulary of gear terms — Part 1: Definitions related to geometry*.

Consequently, it is important:

- that these symbols be used in national standards and, where appropriate, in other national documents in order to facilitate the understanding of documents which are exchanged between countries;
- to use for geometrical data only those combinations of letters which are given in the tables of this International Standard, in order to avoid any risk of confusion with symbols relating to other gear data, which may be determined later.

STANDARDSISO.COM : Click to view the PDF of ISO 701:1998

STANDARDSISO.COM : Click to view the full PDF of ISO 701:1998

International gear notation — Symbols for geometrical data

1 Scope

This International Standard specifies geometrical symbols for use in notation of gear data. It comprises two lists:

- the principal symbols, consisting of a single basic letter (see table 1); and
- subscripts to be used as necessary to qualify principal symbols (see tables 2, 3 and 4).

2 Symbols

2.1 Derivation of geometrical symbols

The principal rules are as follows:

- a) symbols consist of a principal symbol which can be followed by one or more subscripts and possibly a superscript;
- b) the principal symbol is either a single uppercase or lowercase letter. The letter should be a Latin or Greek letter in italics;
- c) a numerical subscript is an integer, a decimal number or a roman numeral, printed in roman characters. No symbol contains more than one numerical subscript;
- d) all subscripts are written on the same line below the line of the principal symbol;
- e) barred notations (barred above or below), superscripts other than exponents, pre-subscripts, pre-superscripts, second order subscripts, second order superscripts and dashes should be avoided.

2.2 Principal geometrical symbols

The most frequently used geometrical symbols are listed in table 1.

2.3 Principal subscripts

The same character as a subscript may have different meanings, each depending on the symbol to which the subscript is assigned. General subscripts are presented in table 2. Abbreviated subscripts of two or three letters are presented in table 3. Numerical subscripts are presented in table 4; their use with a principal symbol is for a reference value.

2.4 Sequence of subscripts

When more than one subscript is used, it is recommended to use the sequence given in table 5.

Table 1 — Principal geometrical symbols

Symbols	Designation
a	Centre distance
b	Facewidth
c	Tip and root clearance
d	Diameter, reference diameter
e	Space width
g	Length of path of contact
h	Tooth depth (total, addendum, dedendum)
i	Total transmission ratio
j	Backlash
M	Measurement over rolls or balls
m	Module
p	Pitch, lead
q	Diametral quotient of a worm
R	Cone distance
r	Radius
s	Tooth thickness
u	Gear ratio
W	Span measurement over k teeth
x	Profile shift coefficient
y	Centre distance modification coefficient
z	Number of teeth
α	(alpha) Pressure angle
β	(beta) Helix angle
γ	(gamma) Lead angle
δ	(delta) Cone angle
ε	(epsilon) Contact or overlap ratio
η	(eta) Spacewidth half angle
θ	(theta) Tooth angle of bevel gear
ρ	(rho) Radius of curvature
Σ	(sigma) Shaft angle
ψ	(psi) Tooth thickness half-angle

Table 2 — Principal subscripts

Subscript	Refers to
a	tip
b	base
e	external
f	root
i	internal
k	sector
m	mean
n	normal direction
P	basic rack tooth profile
r	radial
t	transverse plane
u	usable
w	operating configuration
x	axial direction
y	arbitrary point
z	lead
α	(alpha) flank profile
β	(beta) helix direction
γ	(gamma) total

Table 3 — Abbreviated subscripts

Subscript	Refers to
act	actual
max	maximum
min	minimum
pr	protuberance

Table 4 — Numerical subscripts

Subscript	Refers to
0	tool
1	pinion
2	wheel
3	master gear
...	other gear

Table 5 — Sequence of subscripts

Subscript	Refers to
a, b, m, f	cylinder or cone
e, i	external, internal
pr	protuberance
n, r, t, x	plan or direction
max, min	abbreviation
0, 1, 2, 3,...	gear

3 Examples

Table 6 — Examples of symbols

Symbols	Designation
u	gear ratio
m_n	normal module
α_{wt}	transverse operating angle
d_1	reference diameter of pinion
d_{w2}	operating diameter of wheel
R_2	cone distance of the wheel