

---

# International Standard



# 7041

---

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

---

## Prevaling torque type hexagon nuts (with non-metallic insert), style 2 — Property classes 9 and 12

*Écrous hexagonaux à freinage interne, à couple préalable (avec anneau non métallique), style 2 — Classes de qualité 9 et 12*

First edition — 1983-08-01

STANDARDSISO.COM : Click to view the full PDF of ISO 7041:1983

---

UDC 621.882.31

Ref. No. ISO 7041-1983 (E)

Descriptors : fasteners, nuts (fasteners), hexagonal nuts, specifications, dimensions, designation.

Price based on 3 pages

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been authorized has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 7041 was developed by Technical Committee ISO/TC 2, *Fasteners*, and was circulated to the member bodies in December 1981.

It has been approved by the member bodies of the following countries:

Australia	Hungary	Norway
Brazil	India	Poland
Belgium	Ireland	Romania
Canada	Italy	South Africa, Rep. of
China	Japan	Spain
Czechoslovakia	Korea, Dem. P. Rep. of	Sri Lanka
Denmark	Korea, Rep. of	Sweden
Egypt, Arab Rep. of	Mexico	Switzerland
Finland	Netherlands	USA
Germany, F.R.	New Zealand	

The member bodies of the following countries expressed disapproval of the document on technical grounds:

United Kingdom  
USSR

# Prevailing torque type hexagon nuts (with non-metallic insert), style 2 — Property classes 9 and 12

## 1 Scope and field of application

This International Standard specifies the characteristics of prevailing torque type hexagon nuts, style 2, with non-metallic annular insert and thread sizes from M 5 to M 36 inclusive, in product grades A ( $d < M 16$ ) and B ( $d > M 16$ ), and property classes 9 and 12.

NOTE — The dimensions of the nuts correspond to those given in ISO 4033 plus prevailing torque feature.

If other specifications are required, it is recommended that they should be selected from existing International Standards, for example ISO 261, ISO 898, ISO 965, ISO 2320, ISO 4759/1.

## 2 References

ISO 225, *Fasteners — Bolts, screws, studs and nuts — Symbols and designations of dimensions.*

ISO 261, *ISO general purpose metric screw threads — General plan.*

ISO 898, *Mechanical properties of fasteners.*

ISO 965, *ISO general purpose metric screw threads — Tolerances.*

ISO 2320, *Prevailing torque type steel hexagon nuts — Mechanical and performance properties.*

ISO 3269, *Fasteners — Acceptance inspection.*<sup>1)</sup>


ISO 4033, *Hexagon nuts, style 2 — Product grades A and B.*

ISO 4042, *Threaded components — Electroplated coatings components.*<sup>1)</sup>

ISO 4759/1, *Tolerances for fasteners — Part 1: Bolts, screws and nuts with thread diameters  $> 1,6$  and  $< 150$  mm and product grades A, B and C.*

<sup>1)</sup> At present at the stage of draft.

3 Dimensions



Dimensions in millimetres

Thread size $d$		M 5	M 6	M 8	M 10	M 12	(M 14) <sup>1)</sup>	M 16	M 20	M 24	M 30	M 36
$P$ <sup>2)</sup>		0,8	1	1,25	1,5	1,75	2	2	2,5	3	3,5	4
$d_a$	min.	5	6	8	10	12	14	16	20	24	30	36
	max.	5,75	6,75	8,75	10,8	13	15,1	17,3	21,6	25,9	32,4	38,9
$d_w$	min.	6,9	8,9	11,6	14,6	16,6	19,6	22,5	27,7	33,2	42,7	51,1
$e$	min.	8,79	11,05	14,38	17,77	20,03	23,35	26,75	32,95	39,55	50,85	60,79
$h$	max.	7,2	8,5	10,2	12,8	16,1	18,3	20,7	25,1	29,5	35,6	42,6
$m$ <sup>3)</sup>	min.	4,8	5,4	7,14	8,94	11,57	13,4	15,7	19	22,6	27,3	33,1
$m'$ <sup>4)</sup>	min.	2,7	3	4,3	5,6	7,7	8,9	10,5	12,7	15,1	18,2	22,1
$s$	max.	8	10	13	16	18	21	24	30	36	46	55
	min.	7,78	9,78	12,73	15,73	17,73	20,67	23,67	29,16	35	45	53,8

1) The size in brackets should be avoided if possible.

2)  $P$  = pitch of the thread.

3) Also minimum thread height.

4) Minimum wrenching height.