
**Oilseed meals — Determination of oil
content — Extraction method with
hexane (or light petroleum)**

*Tourteaux de graines oléagineuses — Détermination de la teneur en
huile — Méthode par extraction à l'hexane (ou à l'éther de pétrole)*

STANDARDSISO.COM : Click to view the full PDF of ISO 734:2015



STANDARDSISO.COM : Click to view the full PDF of ISO 734:2015



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	1
5 Reagents	1
6 Apparatus	1
7 Sampling	2
8 Preparation of test sample	2
9 Procedure	3
9.1 Number of determinations.....	3
9.2 Test portion.....	3
9.3 Pre-drying.....	3
9.4 Determination.....	3
9.4.1 Preparation of the flask.....	3
9.4.2 First extraction.....	3
9.4.3 Second extraction.....	3
9.4.4 Elimination of solvent and weighing of the extract.....	4
10 Expression of results	4
11 Precision	5
11.1 Interlaboratory test.....	5
11.2 Repeatability.....	5
11.3 Reproducibility.....	5
12 Test report	5
Annex A (informative) Results of an interlaboratory test	6
Bibliography	7

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 34, *Food products*, Subcommittee SC 2, *Oleaginous seeds and fruits and oilseed meals*.

This second edition cancels and replaces ISO 734-1:2006, which has been renumbered and editorially revised.

Introduction

A method for the determination of the oil content of oilseeds has been specified in ISO 659. It is therefore necessary to provide for control of oil production by establishing a reference method for the determination of the oil content of oilseed meals in the same way.

STANDARDSISO.COM : Click to view the full PDF of ISO 734:2015

STANDARDSISO.COM : Click to view the full PDF of ISO 734:2015

Oilseed meals — Determination of oil content — Extraction method with hexane (or light petroleum)

1 Scope

This International Standard specifies a method for the determination of the hexane extract (or light-petroleum extract), called “oil content”, of meals (excluding compounded products) obtained by the extraction of oil from oilseeds by pressure or solvents.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 771, *Oilseed residues — Determination of moisture and volatile matter content*

ISO 5502, *Oilseed residues — Preparation of test samples*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

oil content

all of the substances extracted under the operating conditions specified in this International Standard, and expressed as a mass fraction, in percent, of the product as received

Note 1 to entry: The oil content may also be expressed relative to dry matter.

4 Principle

A test portion of the product is extracted in a suitable apparatus, with technical hexane or, failing this, light petroleum. The solvent is eliminated and the extract obtained is weighed.

5 Reagents

Use only reagents of recognized analytical grade, unless otherwise specified.

5.1 Technical hexane, *n*-hexane or light petroleum, essentially composed of hydrocarbons with six carbon atoms.

Less than 5 % shall distil below 50 °C and more than 95 % between 50 °C and 70 °C.

For any of these solvents, the residue on complete evaporation shall not exceed 2 mg per 100 ml.

6 Apparatus

Usual laboratory apparatus and, in particular, the following.

6.1 Mechanical grinder, easy to clean and allowing the meals to be ground, without heating and without appreciable change in moisture, volatile matter and oil content, to obtain particles which pass completely through a sieve of aperture size 1 mm.

6.2 Mechanical microgrinder, of the Dangoumau type¹⁾ capable of producing a fineness of grinding of oilseed meals of less than 160 µm, with the exception of the "shell" whose particles may reach 400 µm.

In laboratories where a microgrinder is not available, microgrinding of the ground sample (see 9.4.3) may be replaced by trituration with a pestle and mortar, in the presence of about 10 g of sand that has been washed with hydrochloric acid and then calcined. However, grinding in a mortar cannot be applied in the case of multiple analyses because operator fatigue prevents sufficiently efficient grinding of numerous samples, and the extraction of oil from a coarsely ground sample can never be complete.

6.3 Extraction thimble and cotton wool, or filter paper, free from matter soluble in hexane or light petroleum.

6.4 Suitable extraction apparatus, fitted with a flask of capacity 200 ml to 250 ml.

NOTE Straight-through extractors, for example the Butt, Smalley, Twisselmann and Bolton-Williams²⁾ are suitable. The use of other extractors is conditional upon the results of a test on a standard material of known oil content to confirm the suitability of the apparatus.

6.5 Electric heating bath (e.g. sand bath, water bath) or **hot plate**.

6.6 Electrically heated oven, with thermostatic control, permitting ventilation or obtaining reduced pressure, capable of being maintained at 103 °C ± 2 °C.

6.7 Desiccator, containing an efficient desiccant.

6.8 Pumice stone, in small particles, previously dried in an oven at 103 °C ± 2 °C and cooled in a desiccator.

6.9 Analytical balance, capable of weighing to an accuracy of ±0,001 g.

7 Sampling

A representative sample should have been sent to the laboratory. It should not have been damaged or changed during transport or storage.

Sampling is not part of the method specified in this International Standard. A recommended sampling method is given in ISO 5500.

8 Preparation of test sample

8.1 Prepare the test sample in accordance with ISO 5502.

1) The Dangoumau mechanical microgrinder is an example of suitable apparatus available commercially. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by ISO of this apparatus.

2) The Butt, Smalley, Twisselmann or Bolton-Williams straight-through extractors are examples of suitable apparatus available commercially. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by ISO of this apparatus.

8.2 If necessary, grind the test sample in the previously well-cleaned mechanical mill (6.1). First, use about one-twentieth of the sample to complete the cleaning of the mill, and reject these grindings. Then grind the rest, collect the grindings, mix carefully and carry out the analysis without delay.

9 Procedure

9.1 Number of determinations

If it is required to check whether the repeatability (11.2) is met, carry out two single determinations in accordance with 9.2 to 9.4.4.

9.2 Test portion

9.2.1 Weigh, to the nearest 0,001 g, about 10 g of the test sample (8.2).

9.2.2 Transfer this test portion to the extraction thimble (6.3) and close the latter with a wad of cotton wool (6.3). If a filter paper is used, wrap the test portion in it.

9.3 Pre-drying

If the test portion is very moist [moisture and volatile matter content more than 10 % (mass fraction)], leave the filled thimble for some time in an oven, maintained at a temperature not higher than 80 °C, to reduce the moisture and volatile matter content to less than 10 % (mass fraction).

As an alternative to the pre-drying procedure described above, the test portion (9.2.1) may be mixed in a suitable vessel with 2 g to 3 g of analytical quality anhydrous sodium sulfate per 5 g of grindings. Continue as indicated in 9.2.2 and 9.4.

9.4 Determination

9.4.1 Preparation of the flask

Weigh, to the nearest 1 mg, the flask of the extraction apparatus (6.4) containing one or two particles of pumice stone (6.8).

9.4.2 First extraction

Place the thimble (6.3) containing the test portion in the extraction apparatus (6.4). Pour into the flask the necessary quantity of solvent (5.1). Fit the flask to the extraction apparatus on the electric heating bath or hot plate (6.5). Carry out the heating so that the rate of reflux is at least 3 drops per second (boiling moderately, not violently).

After extracting for 4 h, allow to cool. Remove the thimble from the extraction apparatus and place it in a current of air in order to expel the greater part of the residual solvent.

9.4.3 Second extraction

Empty the thimble into the microgrinder (6.2) and grind as finely as possible. Put the mixture back into the thimble and put the latter back into the extraction apparatus. Re-extract for a further 2 h, using the same flask containing the first extract.

The solution obtained in the extraction flask shall be clear. If it is not, filter it through a filter paper, collecting the filtrate in another previously dried and tared flask, then wash the first flask and filter paper several times with the same solvent.

9.4.4 Elimination of solvent and weighing of the extract

Expel the greater part of the solvent from the flask by distillation on the electric heating bath or the hot plate (6.5). Expel the last traces of solvent by heating the flask for about 20 min in the electrically heated oven (6.6) set at 103 °C.

In the case of meals rich in volatile acids (meals from copra, palm kernel, etc.), drying of the extract should be carried out at atmospheric pressure, and at 80 °C maximum.

Assist the removal of solvent either by blowing air or, preferably, an inert gas (such as nitrogen or carbon dioxide) into the flask for short periods, or by reducing the pressure in the flask.

In the case of drying or semi-drying oilseed meals, it is preferable to remove the residual solvent by drying under reduced pressure.

Allow the flask to cool in the dessicator (6.7), for at least 1 h, to ambient temperature and then weigh to the nearest 1 mg.

Heat again for about 10 min under the same conditions. Allow to cool and reweigh.

The difference between the two weighings shall not exceed 10 mg. If it does, repeat the operations of heating for 10 min, cooling and weighing until the difference between two successive weighings does not exceed 10 mg. Note the final mass of the flask.

10 Expression of results

10.1 The oil content, w , expressed as a mass fraction, in percent, of the product as received, is equal to Formula (1):

$$w = \frac{m_1}{m_0} \times 100\% \quad (1)$$

where

m_0 is the mass, in grams, of the test portion (9.2.1);

m_1 is the mass, in grams, of the extract after drying (see 9.4.4).

Express the result to one decimal place.

10.2 On request, the oil content may be expressed as a mass fraction, in percent, of the dry matter, w_D . It is then equal to Formula (2):

$$w_D = w \times \frac{100}{100 - w_M} \% \quad (2)$$

where

w is the mass fraction, in percent, of oil in the product as received (calculated according to 10.1);

w_M is the mass fraction, in percent, of moisture and volatile matter, determined as specified in ISO 771.

11 Precision

11.1 Interlaboratory test

Details of an interlaboratory test on the precision of the method are summarized in [Annex A](#). The values derived from this interlaboratory test may not be applicable to concentration ranges and matrices other than those given.

11.2 Repeatability

The absolute difference between two independent single test results, obtained using the same method on identical test material in the same laboratory by the same operator using the same equipment within a short interval of time, will in not more than 5 % of cases be greater than the value of the repeatability limit r given in [Table 1](#).

11.3 Reproducibility

The absolute difference between two single test results, obtained using the same method on identical test material in different laboratories by different operators using different equipment, will in not more than 5 % of cases exceed the value of the reproducibility limit R given in [Table 1](#).

Table 1 — Repeatability and reproducibility limits

Sample	Mean value oil content % (mass fraction)	r % (mass fraction)	R % (mass fraction)
Rapeseed meal	0 to 5	0,3	1,1
Soya and sunflower meals	0 to 5	0,2	0,7

12 Test report

The test report shall specify the following:

- all information necessary for the complete identification of the sample;
- the sampling method used, if known;
- the test method used, with reference to this International Standard, i.e. ISO 734;
- all operating details not specified in this International Standard, or regarded as optional, together with details of any incidents which may have influenced the test result(s);
- the test result(s) obtained and the solvent used, indicating clearly whether the result represents the oil content of the product as received or the oil content in relation to the dry matter;
- if the repeatability has been checked, the final quoted result obtained.