
Quantities and units —
Part 10:
Atomic and nuclear physics

Grandeurs et unités —

Partie 10: Physique atomique et nucléaire

STANDARDSISO.COM : Click to view the full PDF of ISO 80000-10:2019



STANDARDSISO.COM : Click to view the full PDF of ISO 80000-10:2019



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
Bibliography.....	41
Alphabetical index.....	42

STANDARDSISO.COM : Click to view the full PDF of ISO 80000-10:2019

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 12, *Quantities and units*, in collaboration with Technical Committee IEC/TC 25, *Quantities and units*.

This second edition cancels and replaces the first edition (ISO 80000-10:2009), which has been technically revised.

The main changes compared to the previous edition are as follows:

- the table giving the quantities and units has been simplified;
- some definitions and the remarks have been stated physically more precisely;
- definitions in this document have been brought in line with their equivalent ones in ICRU 85a.

A list of all parts in the ISO 80000 and IEC 80000 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

0 Special remarks

0.1 Quantities

Numerical values of physical constants in this document are quoted in the consistent values of the fundamental physical constants published in CODATA recommended values. The indicated values are the last known before publication. The user is advised to refer to the CODATA website for the latest values, <https://physics.nist.gov/cuu/Constants/index.html>.

The symbol \hbar is the reduced Planck constant, it is equal to $\frac{h}{2\pi}$, where h is the Planck constant.

0.2 Special units

1 eV is the energy acquired by an electron in passing a potential difference of 1 V in vacuum.

0.3 Stochastic and non-stochastic quantities

Differences between results from repeated observations are common in physics. These can arise from imperfect measurement systems, or from the fact that many physical phenomena are subject to inherent fluctuations. Quantum-mechanical issues aside, one often needs to distinguish between a *stochastic* quantity, the values of which follow a probability distribution, and a *non-stochastic* quantity with its unique, expected value (expectation) of such distributions. In many instances the distinction is not significant because the probability distribution is very narrow. For example, the measurement of an electric current commonly involves so many electrons that fluctuations contribute negligibly to inaccuracy in the measurement. However, as the limit of zero electric current is approached, fluctuations can become manifest. This case, of course, requires a more careful measurement procedure, but perhaps more importantly illustrates that the significance of stochastic variations of a quantity can depend on the magnitude of the quantity. Similar considerations apply to ionizing radiation; fluctuations can play a significant role, and in some cases need to be considered explicitly. Stochastic quantities, such as the energy imparted and the specific energy imparted (item 10-81.2) but also the number of particle traversals across microscopic target regions and their probability distributions, have been introduced as they describe the discontinuous nature of the ionizing radiations as a determinant of radiochemical and radiobiological effects. In radiation applications involving large numbers of ionizing particles, e.g. in medicine, radiation protection and materials testing and processing, these fluctuations are adequately represented by the expected values of the probability distributions. “Non-stochastic quantities” such as particle fluence (item 10-43), absorbed dose (item 10-81.1) and kerma (item 10-86.1) are based on these expected values.

This document contains definitions based on a differential quotient of the type dA/dB in which the quantity A is of a stochastic nature, a situation common in ionizing radiation metrology. In these cases, quantity A is understood as the expected or mean value whose element ΔA falls into element ΔB . The differential quotient dA/dB is the limit value of the difference quotient $\Delta A/\Delta B$ for $\Delta B \rightarrow 0$. In the remarks of the definitions falling in this category, a reference to this paragraph is made.

STANDARDSISO.COM : Click to view the full PDF of ISO 80000-10:2019

Quantities and units —

Part 10: Atomic and nuclear physics

1 Scope

This document gives names, symbols, definitions and units for quantities used in atomic and nuclear physics. Where appropriate, conversion factors are also given.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

The names, symbols, and definitions for quantities and units used in atomic and nuclear physics are given in [Table 1](#).

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

Table 1 — Quantities and units used in atomic and nuclear physics

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-1.1	atomic number, proton number	Z	number of protons in an atomic nucleus	1 A nuclide is a species of atom with specified numbers of protons and neutrons. Nuclides with the same value of Z but different values of N are called isotopes of an element. The ordinal number of an element in the periodic table is equal to the atomic number. The atomic number equals the quotient of the charge (IEC 80000-6) of the nucleus and the elementary charge (ISO 80000-1).
10-1.2	neutron number	N	number of neutrons in an atomic nucleus	1 Nuclides with the same value of N but different values of Z are called isotones. N - Z is called the neutron excess number.
10-1.3	nucleon number, mass number	A	number of nucleons in an atomic nucleus	1 A = Z + N Nuclides with the same value of A are called isobars.
10-2	rest mass, proper mass	m(X) m _x	for particle X, mass (ISO 80000-4) of that particle at rest in an inertial frame	kg u Da EXAMPLE m(H ₂ O) for a water molecule, m _e for an electron. Rest mass is often denoted m ₀ . 1 u is equal to 1/12 times the mass of a free carbon 12 atom, at rest and in its ground state. 1 Da = 1 u
10-3	rest energy	E ₀	energy E ₀ (ISO 80000-5) of a particle at rest: E ₀ = m ₀ c ₀ ² where m ₀ is the rest mass (item 10-2) of that particle, and c ₀ is speed of light in vacuum (ISO 80000-1)	J Nm kg m ² s ⁻²

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Definition		
10-4.1	atomic mass	rest mass (item 10-2) of an atom X in the ground state $m(X)$ m_x	kg u Da	$\frac{m(X)}{m_u}$ is called the relative atomic mass. 1 u is equal to 1/12 times the mass of a free carbon 12 atom, at rest and in its ground state. 1 Da = 1 u
10-4.2	nuclidic mass	rest mass (item 10-2) of a nuclide X in the ground state $m(X)$ m_x	kg u Da	1 u is equal to 1/12 times the mass of a free carbon 12 atom, at rest and in its ground state. 1 Da = 1 u
10-4.3	unified atomic mass constant	1/12 of the mass (ISO 80000-4) of an atom of the nuclide ^{12}C in the ground state at rest m_u	kg u Da	1 u is equal to 1/12 times the mass of a free carbon 12 atom, at rest and in its ground state. 1 Da = 1 u
10-5.1	elementary charge	one of the fundamental constants in the SI system (ISO 80000-1), equal to the charge of the proton and opposite to the charge of the electron e	C s A	
10-5.2	charge number, ionization number	for a particle, quotient of the electric charge (IEC 80000-6) and the elementary charge (ISO 80000-1) c	1	A particle is said to be electrically neutral if its charge number is equal to zero. The charge number of a particle can be positive, negative, or zero. The state of charge of a particle may be presented as a superscript to the symbol of that particle, e.g. H^+ , He^{++} , Al^{3+} , Cl^- , S^{--} , N^{3-} .

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-6	Bohr radius	a_0	<p>radius (ISO 80000-3) of the electron orbital in the hydrogen atom in its ground state in the Bohr model of the atom:</p> $a_0 = \frac{4\pi\epsilon_0\hbar^2}{m_e e^2}$ <p>where</p> <ul style="list-style-type: none"> ϵ_0 is the electric constant (IEC 80000-6), \hbar is the reduced Planck constant (ISO 80000-1), m_e is the rest mass (item 10-2) of electron, and e is the elementary charge (ISO 80000-1) 	<p>The radius of the electron orbital in the H atom in its ground state is a_0 in the Bohr model of the atom.</p> <p>ångström (Å), 1 Å: = 10^{-10} m</p>
10-7	Rydberg constant	R_∞	<p>spectroscopic constant that determines the wave numbers of the lines in the spectrum of hydrogen:</p> $R_\infty = \frac{e^2}{8\pi\epsilon_0 a_0 h c_0}$ <p>where</p> <ul style="list-style-type: none"> e is the elementary charge (ISO 80000-1), ϵ_0 is the electric constant (IEC 80000-6), a_0 is the Bohr radius (item 10-6), h is the Planck constant (ISO 80000-1), and c_0 is the speed of light in vacuum (ISO 80000-1) 	<p>The quantity $R_y = R_\infty h c_0$ is called the Rydberg energy.</p>

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-8	Hartree energy	E_H E_h	energy (ISO 80000-5) of the electron in a hydrogen atom in its ground state: $E_H = \frac{e^2}{4\pi\epsilon_0 a_0}$ where e is the elementary charge (ISO 80000-1), ϵ_0 is the electric constant (IEC 80000-6), and a_0 is the Bohr radius (item 10-6)	The energy of the electron in an H atom in its ground state is E_H .
10-9.1	magnetic dipole moment <atomic physics>	μ	$m^2 A$	For an atom or nucleus, this energy is quantized and can be written as: $W = g \mu_x M B$ where g is the appropriate g factor (item 10-14.1 or item 10-14.2), μ_x is mostly the Bohr magneton or nuclear magneton (item 10-9.2 or item 10-9.3), M is magnetic quantum number (item 10-13.4), and B is magnitude of the magnetic flux density. See also IEC 80000-6.
10-9.2	Bohr magneton	μ_B	$m^2 A$	magnitude of the magnetic moment of an electron in a state with orbital angular momentum quantum number $l=1$ (item 10-13.3) due to its orbital motion: $\mu_B = \frac{e\hbar}{2m_e}$ where e is the elementary charge (ISO 80000-1), \hbar is the reduced Planck constant (ISO 80000-1), and m_e is the rest mass (item 10-2) of electron

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-9.3	nuclear magneton	μ_N	absolute value of the magnetic moment of a nucleus: $\mu_N = \frac{e\hbar}{2m_p}$ where e is the elementary charge (ISO 80000-1), \hbar is the reduced Planck constant (ISO 80000-1), and m_p is the rest mass (item 10-2) of proton	$m^2 A$ Subscript N stands for nucleus. For the neutron magnetic moment, subscript n is used. The magnetic moments of protons and neutrons differ from this quantity by their specific g factors (item 10-14.2).
10-10	spin	\mathbf{s}	vector (ISO 80000-2) quantity expressing the internal angular momentum (ISO 80000-4) of a particle or a particle system	$kg\ m^2\ s^{-1}$ Spin is an additive vector quantity.
10-11	total angular momentum	\mathbf{J}	vector (ISO 80000-2) quantity in a quantum system composed of the vectorial sum of angular momentum \mathbf{L} (ISO 80000-4) and spin \mathbf{s} (item 10-10)	$J\ s$ $eV\ s$ $kg\ m^2\ s^{-1}$ In atomic and nuclear physics, orbital angular momentum is usually denoted by \mathbf{l} or \mathbf{L} . The magnitude of \mathbf{J} is quantized so that: $J^2 = \hbar^2 j(j+1)$ where j is the total angular momentum quantum number (item 10-13.6). Total angular momentum and magnetic dipole moment have the same direction. j is not the magnitude of the total angular momentum \mathbf{J} but its projection onto the quantization axis, divided by \hbar .

Table 1 (continued)

Item No.	Quantity			Unit	Remarks
	Name	Symbol	Definition		
10-12.1	gyromagnetic ratio, magnetogyric ratio, gyromagnetic coefficient	γ	proportionality constant between the magnetic dipole moment and the angular momentum: $\boldsymbol{\mu} = \gamma \mathbf{J}$ where $\boldsymbol{\mu}$ is the magnetic dipole moment (item 10-9.1), and \mathbf{J} is the total angular momentum (item 10-11)	$1 \text{ A}\cdot\text{m}^2/(\text{J}\cdot\text{s}) = 1 \text{ A}\cdot\text{s}/\text{kg} = 1 \text{ T}^{-1}\cdot\text{s}^{-1}$ The systematic name is "gyromagnetic coefficient", but "gyromagnetic ratio" is more usual. The gyromagnetic ratio of the proton is denoted by γ_p . The gyromagnetic ratio of the neutron is denoted by γ_n .	
10-12.2	gyromagnetic ratio of the electron, magnetogyric ratio of the electron, gyromagnetic coefficient of the electron	γ_e	proportionality constant between the magnetic dipole moment and the angular momentum of the electron $\boldsymbol{\mu} = \gamma_e \mathbf{J}$ where $\boldsymbol{\mu}$ is the magnetic dipole moment (item 10-9.1), and \mathbf{J} is the total angular momentum (item 10-11)	$1 \text{ A}\cdot\text{m}^2/(\text{J}\cdot\text{s}) = 1 \text{ A}\cdot\text{s}/\text{kg} = 1 \text{ T}^{-1}\cdot\text{s}^{-1}$ $\text{A s}/\text{kg}$ $\text{kg}^{-1} \text{ s A}$	

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-13.1	quantum number	N, L, M, J, S, F	1	<p>Electron states determine the binding energy $E = E(n, l, m, j, s, f)$ in an atom.</p> <p>Upper case letters N, L, M, J, S, F are usually used for the whole system.</p> <p>The spatial probability distribution of an electron is given by $\psi ^2$, where ψ is its wave function. For an electron in an H atom in a non-relativistic approximation, the wave function can be presented as:</p> $\psi(r, \vartheta, \phi) = R_{nl}(r) \cdot Y_l^m(\vartheta, \phi)$ <p>where</p> <p>r, ϑ, ϕ are spherical coordinates (ISO 80000-2) with respect to the nucleus and to a given (quantization) axis, $R_{nl}(r)$ is the radial distribution function, and $Y_l^m(\vartheta, \phi)$ are spherical harmonics.</p> <p>In the Bohr model of one-electron atoms, n, l, and m define the possible orbits of an electron about the nucleus.</p>
10-13.2	principal quantum number	n	1	<p>In the Bohr model, $n = 1, 2, \dots, \infty$ is related to the binding energy of an electron and the radius of spherical orbits (principal axis of the elliptic orbits).</p> <p>For an electron in an H atom, the semi-classical radius of its orbit is $r_n = a_0 n^2$ and its binding energy is $E_n = -E_H/n^2$.</p>

STANDARDSISO.COM : Click to view the full PDF of ISO 80000-10:2019

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol Definition		
10-13.3	orbital angular momentum quantum number	l l_i L atomic quantum number related to the orbital angular momentum l of a one-electron state	1	$ l ^2 = \hbar^2 l(l-1)$, $l=0, 1, \dots, n-1$ where l is the orbital angular momentum and \hbar is the reduced Planck constant (ISO 80000-1). If reference is made to a specific particle i , the symbol l_i is used instead of l ; if reference is made to the whole system, the symbol L is used instead of l . An electron in an H atom for $l=0$ appears as a spherical cloud. In the Bohr model, it is related to the form of the orbit.
10-13.4	magnetic quantum number	m m_i M atomic quantum number related to the z component l_z, j_z or s_z , of the orbital, total, or spin angular momentum	1	$l_z = m_l \hbar$, $j_z = m_j \hbar$, and $s_z = m_s \hbar$, with the ranges from $-l$ to l , from $-j$ to j , and $\pm 1/2$, respectively. m_i refers to a specific particle i . M is used for the whole system. Subscripts l, s, j , etc., as appropriate, indicate the angular momentum involved. \hbar is the reduced Planck constant (ISO 80000-1).
10-13.5	spin quantum number	s characteristic quantum number s of a particle, related to its spin (item 10-10), \mathbf{s} : $s^2 = \hbar^2 s(s+1)$ where \hbar is the reduced Planck constant (ISO 80000-1)	1	Spin quantum numbers of fermions are odd multiples of $1/2$, and those of bosons are integers.

Table 1 (continued)

Item No.	Quantity			Unit	Remarks
	Name	Symbol	Definition		
10-13.6	total angular momentum quantum number	j i J	quantum number in an atom describing the magnitude of total angular momentum J (item 10-11)	1	j_i refers to a specific particle i ; J is used for the whole system. The quantum number J and the magnitude of total angular momentum J (item 10-11) are different quantities. The two values of j are $l \pm 1/2$. (See item 10-13.3.)
10-13.7	nuclear spin quantum number	I	quantum number related to the total angular momentum (item 10-11), I , of a nucleus in any specified state, normally called nuclear spin: $J^2 = \hbar^2 I(I+1)$ where \hbar is the reduced Planck constant (ISO 80000-1)	1	Nuclear spin is composed of spins of the nucleons (protons and neutrons) and their (orbital) motions. In principle there is no upper limit for the nuclear spin quantum number. It has possible values $I = 0, 1, 2, \dots$ for even A and $I = \frac{1}{2}, \frac{3}{2}, \dots$ for odd A . In nuclear and particle physics, J is often used.
10-13.8	hyperfine structure quantum number	F	quantum number of an atom describing the inclination of the nuclear spin with respect to a quantization axis given by the magnetic field produced by the orbital electrons	1	The interval of F is $ I-J , I-J +1, \dots, I+J$. This is related to the hyperfine splitting of the atomic energy levels due to the interaction between the electron and nuclear magnetic moments.
10-14.1	Landé factor, g factor of atom	g	quotient of the magnetic dipole moment of an atom, and the product of the total angular momentum quantum number and the Bohr magneton: $g = \frac{\mu}{J \cdot \mu_B}$ where μ is magnitude of magnetic dipole moment (item 10-9.1), J is total angular momentum quantum number (item 10-13.6), and μ_B is the Bohr magneton (item 10-9.2)	1	These quantities are also called g values. The Landé factor can be calculated from the expression: $g(L, S, J) = 1 + (g_e - 1) \frac{J(J+1) + S(S+1) - L(L+1)}{2J(J+1)}$ where g_e is the g factor of the electron.

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-14.2	g factor of nucleus or nuclear particle	g	quotient of the magnetic dipole moment of an atom, and the product of the nuclear spin quantum number and the nuclear magneton: $g = \frac{\mu}{I \cdot \mu_N}$ where μ is magnitude of magnetic dipole moment (item 10-9.1), I is nuclear spin quantum number (item 10-13.7), and μ_N is the nuclear magneton (item 10-9.3)	1 The g factors for nuclei or nucleons are known from measurements.
10-15.1	Larmor angular frequency	ω_L	angular frequency (ISO 80000-3) of the electron angular momentum (ISO 80000-4) vector precession about the axis of an external magnetic field: $\omega_L = \frac{eB}{2m_e}$ where e is the elementary charge (ISO 80000-1), m_e is the rest mass (item 10-2) of electron, and B is magnetic flux density (IEC 80000-6)	rad s ⁻¹ s ⁻¹
10-15.2	Larmor frequency	ν_L	quotient of Larmor angular frequency (ISO 80000-3) and 2π	s ⁻¹
10-15.3	nuclear precession angular frequency	ω_N	frequency (ISO 80000-3) by which the nucleus angular momentum vector (ISO 80000-4) precesses about the axis of an external magnetic field: $\omega_N = \gamma B$ where γ is the gyromagnetic ratio (item 10-12.1), and B is magnetic flux density (IEC 80000-6)	rad s ⁻¹ s ⁻¹

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-16	cyclotron angular frequency	ω_c	<p>quotient of the product of the electric charge of a particle and the magnitude of the magnetic flux density of the magnetic field, and the particle mass:</p> $\omega_c = \frac{ q B}{m}$ <p>where</p> <p>q is the electric charge (IEC 80000-6) of the particle,</p> <p>m is the mass (ISO 80000-4) of the particle, and</p> <p>B is the absolute value of the magnetic flux density (IEC 80000-6)</p>	<p>The quantity $\nu_c = \omega_c/2\pi$ is called the cyclotron frequency.</p>
10-17	gyroradius, Larmor radius	r_g r_L	<p>radius (ISO 80000-3) of circular movement of a particle with mass (ISO 80000-4) and velocity v (ISO 80000-3), and electric charge q (IEC 80000-6), moving in a magnetic field with magnetic flux density B (IEC 80000-6):</p> $r_g = \frac{m \mathbf{v} \times \mathbf{B} }{qB^2}$	
10-18	nuclear quadrupole moment	Q	<p>z component of the diagonalized tensor of nuclear quadrupole moment:</p> $Q = \left(\frac{1}{e}\right) \int (3z^2 - r^2) \rho(x, y, z) dV$ <p>in the quantum state with the nuclear spin in the field direction (z), where</p> <p>e is the elementary charge (ISO 80000-1),</p> $r^2 = x^2 + y^2 + z^2,$ <p>$\rho(x, y, z)$ is the nuclear electric charge density (IEC 80000-6), and</p> <p>dV is the volume element $dx dy dz$</p>	<p>The electric nuclear quadrupole moment is eQ.</p> <p>This value is equal to the z component of the diagonalized tensor of quadrupole moment.</p>

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-19.1	nuclear radius	<p>R</p> <p>conventional radius (ISO 80000-3) of sphere in which the nuclear matter is included</p>	m	<p>This quantity is not exactly defined. It is given approximately for nuclei in their ground state by:</p> $R = r_0 A^{1/3}$ <p>where</p> $r_0 \approx 1,2 \times 10^{-15} \text{ m},$ <p>and A is the nucleon number (item 10-1.3).</p> <p>Nuclear radius is usually expressed in femtometres, $1 \text{ fm} = 10^{-15} \text{ m}$.</p>
10-19.2	electron radius	<p>r_e</p> <p>radius of a sphere such that the relativistic electron energy is distributed uniformly:</p> $r_e = \frac{e^2}{4\pi\epsilon_0 m_e c_0^2}$ <p>where</p> <p>e is the elementary charge (ISO 80000-1),</p> <p>ϵ_0 is the electric constant (IEC 80000-6),</p> <p>m_e is the rest mass (item 10-2) of electron, and</p> <p>c_0 is the speed of light in vacuum (ISO 80000-1)</p>	m	<p>This quantity corresponds to the electrostatic energy E of a charge distributed inside a sphere of radius r_e as if all the rest energy (item 10-3) of the electron were attributed to the energy of electromagnetic origin, using the relation $E = m_e c_0^2$.</p>
10-20	Compton wavelength	<p>λ_c</p> <p>quotient of the Planck constant and the product of the mass of the particle and the speed of light in vacuum:</p> $\lambda_c = \frac{h}{m c_0}$ <p>where</p> <p>h is the Planck constant (ISO 80000-1),</p> <p>m is the rest mass (item 10-2) of a particle, and</p> <p>c_0 is the speed of light in vacuum (ISO 80000-1)</p>	m	<p>The wavelength of electromagnetic radiation scattered from free electrons (Compton scattering) is larger than that of the incident radiation by a maximum of $2\lambda_c$.</p>

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-21.1	mass excess	Δ	<p>difference between the mass of an atom, and the product of its mass number and the unified mass constant:</p> $\Delta = m_a - A \cdot m_u$ <p>where</p> <p>m_a is the rest mass (item 10-2) of the atom,</p> <p>A is its nucleon number (item 10-1.3), and</p> <p>m_u is the unified atomic mass constant (item 10-4.3)</p>	<p>The mass excess is usually expressed in daltons, 1 Da = 1 u.</p> <p>See item 10-2.</p>
10-21.2	mass defect	B	<p>sum of the product of the proton number and the hydrogen atomic mass, and the neutron rest mass, minus the rest mass of the atom:</p> $B = Z m(^1\text{H}) + N m_n - m_a$ <p>where</p> <p>Z is the proton number (item 10-1.1) of the atom,</p> <p>$m(^1\text{H})$ is atomic mass (item 10-4.1) of ^1H,</p> <p>N is neutron number (item 10-1.2),</p> <p>m_n is the rest mass (item 10-2) of the neutron, and</p> <p>m_a is the rest mass (item 10-2) of the atom</p>	<p>The mass excess is usually expressed in daltons, 1 Da = 1 u.</p> <p>If the binding energy of the orbital electrons is neglected, Bc_0^2 is equal to the binding energy of the nucleus.</p>
10-22.1	relative mass excess	Δ_r	<p>quotient of mass excess and the unified atomic mass constant:</p> $\Delta_r = \Delta / m_u$ <p>where</p> <p>Δ is mass excess (item 10-21.1), and</p> <p>m_u is the unified atomic mass constant (item 10-4.3)</p>	1

Table 1 (continued)

Item No.	Quantity		Unit	Remarks	
	Name	Symbol			
10-22.2	relative mass defect	B_r	quotient of mass defect and the unified atomic mass constant: $B_r = B/m_u$ where B is mass defect (item 10-21.2), and m_u is the unified atomic mass constant (item 10-4.3)	1	
10-23.1	packing fraction	f	quotient of relative mass excess and the nucleon number: $f = \Delta_r/A$ where Δ_r is relative mass excess (item 10-22.1), and A is the nucleon number (item 10-1.3)	1	
10-23.2	binding fraction	b	quotient of relative mass defect and the nucleon number: $b = B_r/A$ where B_r is relative mass defect (item 10-22.2), and A is the nucleon number (item 10-1.3)	1	
10-24	decay constant, disintegration constant	λ	quotient of $-dN/N$ and dt , where dN/N is the mean fractional change in the number of nuclei in a particular energy state due to spontaneous transformations in a time interval of duration (ISO 80000-3) dt : $\lambda = -\frac{1}{N} \frac{dN}{dt}$	s^{-1}	For exponential decay, this quantity is constant. For more than one decay channel, $\lambda = \sum \lambda_a$ where λ_a denotes the decay constant for a specified final state and the sum is taken over all final states.
10-25	mean duration of life, mean life time <atomic and nuclear physics>	τ	reciprocal of the decay constant λ (item 10-24): $\tau = \frac{1}{\lambda}$	s	Mean duration of life is the expected value of the duration of life of an unstable particle or an excited state of a particle when the number of decay events in a short time interval follows a Poisson distribution.

Table 1 (continued)

Item No.	Quantity			Unit	Remarks
	Name	Symbol	Definition		
10-26	level width	Γ	quotient of the reduced Planck constant and the mean life: $\Gamma = \frac{\hbar}{\tau}$ where \hbar is the reduced Planck constant (ISO 80000-1), and τ is mean duration of life (item 10-25)	eV J kg m ² s ⁻²	Level width is the uncertainty of the energy of an unstable particle or an excited state of a system due to the Heisenberg principle. The term energy level refers to the configuration of the distribution function of the density of states. Energy levels may be considered as discrete, like those in an atom, or may have a finite width, like e.g. this item or like e.g. the valence or conduction band in solid state physics. Energy levels are applicable to both real and virtual particles, e.g. electrons and phonons, respectively.
10-27	activity	A	differential quotient of N with respect to time, where N is the mean change in the number of nuclei in a particular energy state due to spontaneous nuclear transformations in a time interval of duration (ISO 80000-3) dt : $A = -\frac{dN}{dt}$	Bq s ⁻¹	For exponential decay, $A = \lambda N$, where λ is the decay constant (item 10-24). The becquerel (Bq) is a special name for second to the power minus one, to be used as the coherent SI unit of activity. In report 85a of the ICRU a definition with an equivalent meaning is given as: The activity, A , of an amount of a radionuclide in a particular energy state at a given time is the quotient of $-dN$ by dt , where dN is the mean change in the number of nuclei in that energy state due to spontaneous nuclear transformations in the time interval dt : $A = -\frac{dN}{dt}$ See also section 0.3.
10-28	specific activity, massic activity	a	quotient of the activity A (item 10-27) of a sample and the mass m (ISO 80000-4) of that sample: $a = A/m$	Bq/kg kg ⁻¹ s ⁻¹	

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-29	activity density, volumic activity, activity concentration	c_A	quotient of the activity A (item 10-27) of a sample and the volume V (ISO 80000-3) of that sample: $c_A = A/V$	Bq/m ³ m ⁻³ s ⁻¹
10-30	surface-activity density	a_S	quotient of the activity A (item 10-27) of a sample and the total area S (ISO 80000-3) of the surface of that sample: $a_S = A/S$	Bq/m ² m ⁻² s ⁻¹
10-31	half life	$T_{1/2}$	mean duration (ISO 80000-3) required for the decay of one half of the atoms or nuclei	s
10-32	alpha disintegration energy	Q_α	sum of the kinetic energy (ISO 80000-4) of the α -particle produced in the disintegration process and the recoil energy (ISO 80000-5) of the product atom in a reference frame in which the emitting nucleus is at rest before its disintegration	eV J kg m ² s ⁻²
10-33	maximum beta-particle energy	E_β	maximum kinetic energy (ISO 80000-4) of the emitted beta particle produced in the nuclear disintegration process	eV J kg m ² s ⁻²
10-34	beta disintegration energy	Q_β	sum of the maximum beta-particle kinetic energy (item 10-33) and the recoil energy (ISO 80000-5) of the atom produced in a reference frame in which the emitting nucleus is at rest before its disintegration	eV J kg m ² s ⁻²
10-35	internal conversion factor	α	quotient of the number of internal conversion electrons and the number of gamma quanta emitted by the radioactive atom in a given transition, where a conversion electron represents an orbital electron emitted through the radioactive decay	1

Table 1 (continued)

Item No.	Quantity			Unit	Remarks
	Name	Symbol	Definition		
10-36	particle emission rate	\dot{N}	differential quotient of N with respect to time, where N is the number of particles being emitted from an infinitesimally small volume element in the time interval of duration dt (ISO 80000-3), and dt : $\dot{N} = \frac{dN}{dt}$	1	Usually the kind of particles is specified, e.g. neutron emission rate or alpha particle emission rate.
10-37.1	reaction energy	Q	in a nuclear reaction, sum of the kinetic energies (ISO 80000-4) and photon energies (ISO 80000-5) of the reaction products minus the sum of the kinetic and photon energies of the reactants	eV J kg m ² s ⁻²	For exothermic nuclear reactions, $Q > 0$. For endothermic nuclear reactions, $Q < 0$.
10-37.2	resonance energy	E_r E_{res}	kinetic energy (ISO 80000-4) of an incident particle, in the reference frame of the target, corresponding to a resonance in a nuclear reaction	eV J kg m ² s ⁻²	The energy of the resonance corresponds to the difference of the energy levels involved of the nucleus.
10-38.1	cross section <atomic physics>	σ	for a specified target entity and for a specified reaction or process produced by incident charged or uncharged particles of a given type and energy, the quotient of the mean number of such reactions or processes and the incident-particle fluence (item 10-43)	m ² b	The type of process is indicated by subscripts, e.g. absorption cross section σ_a , scattering cross section σ_s , fission cross section σ_f . 1 barn (b) = 10 ⁻²⁸ m ²
10-38.2	total cross section <atomic physics>	σ_{tot} σ_T	sum of all cross sections (item 10-38.1) corresponding to the various reactions or processes between an incident particle of specified type and energy (ISO 80000-5) and a target entity	m ² b	In the case of a narrow unidirectional beam of incident particles, this is the effective cross section for the removal of an incident particle from the beam. See the Remarks for item 10-52. 1 barn (b) = 10 ⁻²⁸ m ²
10-39	direction distribution of cross section <atomic physics>	σ_Ω	differential quotient of σ with respect to Ω , where σ is the cross section (item 10-38.1) for ejecting or scattering a particle into a specified direction, and Ω is the solid angle (ISO 80000-3) around that direction: $\sigma_\Omega = d\sigma/d\Omega$	m ² sr ⁻¹ m ²	Quantities listed under items 10-39, 10-40 and 10-41 are sometimes called differential cross sections. The type of interaction needs to be specified.

Table 1 (continued)

Item No.	Quantity			Unit	Remarks
	Name	Symbol	Definition		
10-40	energy distribution of cross section <atomic physics>	σ_E	differential quotient of σ with respect to energy, where σ is the cross section (item 10-38.1) for a process in which the energy E (ISO 80000-5) of the ejected or scattered particle is between E and $E+dE$: $\sigma_E = d\sigma/dE$	m^2/J $kg^{-1} s^2$	
10-41	direction and energy distribution of cross section <atomic physics>	$\sigma_{\Omega,E}$	partial differential quotient of σ with respect to solid angle and energy, where σ is the cross section (item 10-38.1) for ejecting or scattering a particle into a solid angle $d\Omega$ around a specified direction and with an energy between E and $E+dE$: $\sigma_{\Omega,E} = \frac{\partial^2 \sigma}{\partial \Omega \partial E}$	$m^2/(J sr)$ $kg^{-1} s^2$	
10-42.1	volumic cross section, macroscopic cross section <atomic physics>	Σ	product of the number density n_a of the atoms and of the cross section (item 10-38.1) σ_a for a given type of atoms: $\Sigma = n_a \sigma_a$	m^{-1}	When the target particles of the medium are at rest, $\Sigma = 1/l$, where l is the mean free path (item 10-71).
10-42.2	volumic total cross section, macroscopic total cross section <atomic physics>	Σ_{tot} Σ_T	product of the number density n_a of the atoms and the cross section (item 10-38.1) σ_{tot} for a given type of atoms: $\Sigma_{tot} = n_a \sigma_{tot}$	m^{-1}	See the Remarks for item 10-49.
10-43	particle fluence	Φ	differential quotient of N with respect to a , where N is the number of particles incident on a sphere of cross-sectional area a (item 10-38.1): $\Phi = \frac{dN}{da}$	m^{-2}	The word "particle" is usually replaced by the name of a specific particle, for example <i>proton</i> fluence. If a flat area of size dA is passed perpendicularly by a number of dN particles, the corresponding particle fluence is: $\Phi = \frac{dN}{dA}$

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-43 (cont.)				<p>A plane area of size dA crossed at an angle α with respect to the surface normal by a number of dN particles results in the particle fluence:</p> $\Phi = \frac{dN}{\cos(\alpha)dA}$ <p>In report 85a of the ICRU a definition with an equivalent meaning is given as:</p> <p>The fluence, Φ, is the quotient of dN and $d\alpha$, where dN is the number of particles incident on a sphere of cross-sectional area $d\alpha$:</p> $\Phi = \frac{dN}{d\alpha}$ <p>See also section 0.3.</p>
10-44	particle fluence rate	$\dot{\Phi}$ differential quotient of fluence Φ (item 10-43) with respect to time (ISO 80000-3): $\dot{\Phi} = \frac{d\Phi}{dt}$	$m^{-2} s^{-1}$	<p>The word "particle" is usually replaced by the name of a specific particle, for example proton fluence rate.</p> <p>The distribution function expressed in terms of speed and energy, $\dot{\Phi}_v$ and $\dot{\Phi}_E$, are related to by:</p> $\dot{\Phi} = \int \dot{\Phi}_v dv = \int \dot{\Phi}_E dE$

STANDARDSISO.COM : Click to view the full PDF of ISO 80000-10:2019

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-44 (cont.)				<p>This quantity has also been termed particle flux density. Because the word “density” has several connotations, the term “fluence rate” is preferred. For a radiation field composed of particles of velocity v, the fluence rate is equal to $n \cdot v$ where n is the particle number density. See Remarks for item 10-43.</p> <p>In report 85a of the ICRU a definition with an equivalent meaning is given as:</p> <p>The fluence rate, $\dot{\Phi}$, is the quotient of $d\Phi$ and dt, where $d\Phi$ is the increment of the fluence in the time interval dt:</p> $\dot{\Phi} = \frac{d\Phi}{dt}$ <p>See also section 0.3.</p>
10-45	radiant energy <ionizing radiation>	R	<p>eV J kg m² s⁻²</p>	<p>For particles of energy E (excluding rest energy), the radiant energy, R, is equal to the product $N \cdot E$ where N is the number of the particles that are emitted, transferred, or received</p> <p>The distributions, N_E and R_E, of the particle number and the radiant energy with respect to energy are given by $N_E = dN/dE$ and $R_E = dR/dE$, respectively, where dN is the number of particles with energy between E and $E+dE$, and dR is their radiant energy. The two distributions are related by $R_E = E \cdot N_E$.</p>

Table 1 (continued)

Item No.	Quantity			Unit	Remarks
	Name	Symbol	Definition		
10-46	energy fluence	ψ	differential quotient of radiant energy R (item 10-45) incident on a sphere of cross-sectional area (item 10-38.1) a with respect to that area: $\psi = \frac{dR}{da}$	eV/m ² J/m ² kg s ⁻²	In report 85a of the ICRU a definition with an equivalent meaning is given as: The energy fluence, Ψ , is the quotient of dR and da , where dR is the radiant energy incident on a sphere of cross-sectional area da : $\Psi = \frac{dR}{da}$ See also section 0.3.
10-47	energy fluence rate	$\dot{\psi}$	differential quotient of the energy fluence Ψ (item 10-46) with respect to time (ISO 80000-3): $\dot{\psi} = \frac{d\Psi}{dt}$	W/m ² kg s ⁻³	In report 85a of the ICRU a definition with an equivalent meaning is given as: The energy-fluence rate, $\dot{\Psi}$, is the quotient of $d\Psi$ by dt , where $d\Psi$ is the increment of the energy fluence in the time interval dt : $\dot{\Psi} = \frac{d\Psi}{dt}$ See also section 0.3.

STANDARDSISO.COM Click to view the full PDF of ISO 80000-10:2019

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-48	particle current density	<p>J</p> <p>S</p> <p>vector whose component in direction of an area normal is given by:</p> $J_n = \int \Phi_{\Omega}(\theta, \alpha) \cos(\theta) d\Omega$ <p>where</p> <p>$\Phi_{\Omega}(\theta, \alpha)$ is the directional distribution of the particle fluence rate (item 10-44), and</p> <p>θ and α are polar and azimuthal angles, respectively</p>	m ⁻² s ⁻¹	<p>Usually the word "particle" is replaced by the name of a specific particle, for example proton current.</p> <p>Symbol S is recommended when there is a possibility of confusion with the symbol J for electric current density. For neutron current, the symbol J is generally used. The distribution functions expressed in terms of speed and energy, J_v and J_E, are related to J by:</p> $J = \int J_v dv = \int J_E dE .$ <p>The directional distribution of the particle fluence rate is also denoted as particle radiance.</p>
10-49	linear attenuation coefficient <ionizing radiation>	<p>μ</p> <p>μ_I</p> <p>for uncharged particles of a given type and energy the differential quotient n with respect to l, where n is the fraction of N incoming particles that experience interactions in traversing a distance (ISO 80000-3) l in a given material:</p> $\mu = \frac{dn}{dl} = \frac{1}{N} \frac{dN}{dl}$ <p>where dN is the number of particles that experience interactions in traversing dl</p>	m ⁻¹	<p>μ is equal to the macroscopic total cross section Σ_{tot} for the removal of particles from the beam.</p> <p>Using the relation $\mu_m = \mu/\rho$ between the linear attenuation coefficient μ, the mass attenuation coefficient μ_m (item 10-50) and the density ρ, the definition given for the mass attenuation coefficient in report 85a of the ICRU can be applied to the linear attenuation coefficient resulting in:</p>

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-49 (cont.)				The linear attenuation coefficient, μ , of a material, for uncharged particles of a given type and energy, is the quotient of dN/N by dI , where dN/N is the mean fraction of the particles that experience interactions in traversing a distance dI in the material: $\mu = \frac{1}{dI} \frac{dN}{N}$ This definition has an equivalent meaning as the one given in column 4 of this item. See also section 0.3.
10-50	mass attenuation coefficient <ionizing radiation>	μ_m	$\text{kg}^{-1} \text{m}^2$	quotient of the linear attenuation coefficient μ (item 10-49) and the mass density ρ (ISO 80000-4) of the medium: $\mu_m = \mu/\rho$
10-51	molar attenuation coefficient	μ_c	$\text{m}^2 \text{mol}^{-1}$	quotient of linear attenuation coefficient μ (item 10-49) and the amount c (ISO 80000-9) of the medium: $\mu_c = \mu/c$
10-52	atomic attenuation coefficient	μ_a	m^2	quotient of the linear attenuation coefficient μ (item 10-49) and the number density (item 10-62.1), n , of atoms in the substance: $\mu_a = \mu/n$
10-53	half-value thickness	$d_{1/2}$	m	thickness (ISO 80000-3) of the attenuating layer that reduces the quantity of interest of a unidirectional beam of infinitesimal width to half of its initial value

Table 1 (continued)

Item No.	Quantity			Unit	Remarks
	Name	Symbol	Definition		
10-54	total linear stopping power	S	for charged particles of a given type and energy E_0 the differential quotient of E with respect to x , where E is the mean energy (ISO 80000-4) lost by the charged particles in traversing a distance (ISO 80000-3) x in the given material:	eV/m J/m kg m s ⁻²	The total linear stopping power is sometimes also called stopping power. Both electronic losses and radiative losses are included. The quotient of the total linear stopping power of a substance and that of a reference substance is called the relative linear stopping power. See also item 10-85. Using the relation $S_m = S/\rho$ between the total mass stopping power S_m (item 10-55), the total linear stopping power S , and the density ρ , the definition given for the mass stopping in report 85a of the ICRU can be applied to that of the total linear stopping power resulting in: The linear stopping power, S , of a material, for charged particles of a given type and energy, is the quotient of dE by dl , where dE is the mean energy lost by the charged particles in traversing a distance dl in the material: $S = -\frac{dE}{dx}$ This definition has an equivalent meaning as the one given in column 4 of this item. See also section 0.3.
	linear stopping power	S_l	$S = -\frac{dE}{dx}$		
10-55	total mass stopping power	S_m	quotient of the total linear stopping power S (item 10-54) and the mass density ρ (ISO 80000-4) of the material:	eV m ² /kg J m ² /kg m ⁴ s ⁻²	The quotient of total mass stopping power of a material and that of a reference material is called relative mass stopping power.
	mass stopping power	$S_m = S/\rho$			

Table 1 (continued)

Item No.	Quantity			Unit	Remarks
	Name	Symbol	Definition		
10-56	mean linear range	R	mean total rectified path length (ISO 80000-3) travelled by a particle in the course of slowing down to rest in a given material averaged over a group of particles having the same initial energy (ISO 80000-5)	m	
10-57	mean mass range	R_p R_m	product of the mean linear range (item 10-56) R and the mass density ρ (ISO 80000-4) of the material: $R_p = R\rho$	kg m ⁻²	
10-58	linear ionization	N_{il}	differential quotient of q with respect to l , where q is the average total charge (IEC 80000-6) of all positive ions produced by an ionizing charged particle over a path l (ISO 80000-3), divided by the elementary charge, e (ISO 80000-1): $N_{il} = \frac{1}{e} \frac{dq}{dl}$	m ⁻¹	Ionization due to secondary ionizing particles is included.
10-59	total ionization	N_i	quotient of the total mean charge of all positive ions produced by an ionizing charged particle along its entire path and along the paths of any secondary charged particles, and the elementary charge, e (ISO 80000-1)	1	$N_i = \int N_{il} dl$ See item 10-58.
10-60	average energy loss per elementary charge produced	W_i	quotient of the initial kinetic energy E_k (ISO 80000-4) of an ionizing charged particle and the total ionization N_i (item 10-59) produced by that particle: $W_i = E_k/N_i$	eV J kg m ² s ⁻²	The name "average energy loss per ion pair formed" is usually used, although it is ambiguous. In the practical dosimetry of ionizing radiation the term W/e , the quotient of W , the average energy deposited in dry air per ion pair formed, and e , the elementary charge, is used as the factor which, when multiplied with the electric charge of one sign carried by all ion pairs formed in dry air of given mass, gives the energy deposited in this amount of dry air in the form of excitations and ionizations.

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol Definition		
10-60 (cont.)				In ICRU Report 85a, the mean energy expended in a gas per ion pair formed, W , is the quotient of E by N , where N is the mean total liberated charge of either sign, divided by the elementary charge when the initial kinetic energy E of a charged particle introduced into the gas is completely dissipated in the gas. Thus, $W = E/N$. It follows from the definition of W that the ions produced by bremsstrahlung or other secondary radiation emitted by the initial and secondary charged particles are included in N .
10-61	mobility	μ μ_m	$m^2/(V s)$ $kg^{-1} s^2 A$	
10-62.1	particle number density	n	m^{-3}	n is the general symbol for the number density of particles. The distribution functions expressed in terms of speed and energy, n_v and n_E , are related to n by: $n = \int n_v dv = \int n_E dE .$ The word "particle" is usually replaced by the name of a specific particle, for example <i>neutron</i> number density.
10-62.2	ion number density, ion density	n^+ n^-	m^{-3}	quotient of the number of positive and negative ions, N^+ and N^- , respectively, in the volume V (ISO 80000-3), and that volume: $n^+ = N^+/V, n^- = N^-/V$

Table 1 (continued)

Item No.	Quantity			Unit	Remarks
	Name	Symbol	Definition		
10-63	Recombination coefficient	α	coefficient in the law of recombination: $-\frac{dn^+}{dt} = -\frac{dn^-}{dt} = \alpha \cdot n^+ \cdot n^-$ where n^+ and n^- are the ion number densities (item 10-62.2) of positive and negative ions, respectively, recombined during a time interval of duration dt (ISO 80000-3)	$m^3 s^{-1}$	The widely used term “recombination factor” is not correct because “factor” should only be used for quantities with dimension 1. The terms $\frac{dn^+}{dt}$, $\frac{dn^-}{dt}$ are differential quotients.
10-64	diffusion coefficient, diffusion coefficient for particle number density	D D_n	proportionality constant between the particle current density J (item 10-48) and the gradient of the particle number density n (item 10-62.1): $J = -D \cdot \nabla n$	$m^2 s^{-1}$	The word “particle” is usually replaced by the name of a specific particle, for example <i>neutron</i> number density. For a particle of a given speed v : $D_n(v) = -\frac{J_{v,x}}{\partial n_v / \partial x}$
10-65	diffusion coefficient for fluence rate	D_ϕ D	proportionality constant between the particle current density J (item 10-48) and the gradient of the particle fluence rate ϕ (item 10-44): $J = -D \cdot \nabla \phi$	m	For a particle of a given speed v : $D_\psi(v) = -\frac{J_{v,x}}{\partial \psi_v / \partial x}$ and $v \cdot D_\psi(v) = -D_n(v)$
10-66	particle source density	S	quotient of the mean rate of production of particles in a volume, and that volume (ISO 80000-3)	$m^{-3} s^{-1}$	The word “particle” is usually replaced by the name of a specific particle, for example <i>proton</i> source density. The distribution functions expressed in terms of speed and energy, S_v and S_E , are related to S by: $S = \int S_v dv = \int S_E dE$

Table 1 (continued)

Item No.	Quantity			Unit	Remarks
	Name	Symbol	Definition		
10-67	slowing-down density	q	differential quotient of n with respect to time, where n is the number density of particles that are slowed down in a time interval of duration (ISO 80000-3) t : $q = -\frac{dn}{dt}$	$m^{-3} s^{-1}$	
10-68	resonance escape probability	p	in an infinite medium, the probability that a neutron slowing down will traverse all or some specified portion of the range of resonance energies (item 10-37.2) without being absorbed	1	
10-69	lethargy	u	for a neutron of kinetic energy E (ISO 80000-4) : $u = \ln(E_0/E)$, where E_0 is a reference energy	1	Lethargy is also referred to as logarithmic energy decrement.
10-70	average logarithmic energy decrement	ζ	average value of the increase in lethargy (item 10-69) in elastic collisions between neutrons and nuclei whose kinetic energy (ISO 80000-4) is negligible compared with that of the neutrons	1	
10-71	mean free path <atomic physics>	l λ	average distance (ISO 80000-3) that particles travel between two successive specified reactions or processes	m	See the Remarks for item 10-42.1.
10-72.1	slowing-down area	L_s^2 L_{sl}^2	in an infinite homogenous medium, one-sixth of the mean square of the distance (ISO 80000-3) between the neutron source and the point where a neutron reaches a given energy (ISO 80000-5)	m^2	
10-72.2	diffusion area	L^2	in an infinite homogenous medium, one-sixth of the mean square distance (ISO 80000-3) between the point where a neutron enters a specified class and the point where it leaves this class	m^2	The class of neutrons must be specified, e.g. thermal.
10-72.3	migration area	M^2	sum of the slowing-down area (item 10-72.1) from fission energy to thermal energy (ISO 80000-5) and the diffusion area (item 10-72.2) for thermal neutrons	m^2	
10-73.1	slowing-down length	L_s L_{sl}	square root of the slowing down area L_s^2 (item 10-72.1): $L_s = \sqrt{L_s^2}$	m	

Table 1 (continued)

Item No.	Quantity			Unit	Remarks
	Name	Symbol	Definition		
10-73.2	diffusion length <atomic physics>	L	square root of the diffusion area L^2 (item 10-72.2): $L = \sqrt{L^2}$	m	
10-73.3	migration length	M	square root of the migration area M^2 (item 10-72.3): $M = \sqrt{M^2}$	m	
10-74.1	neutron yield per fission	ν	average number of fission neutrons, both prompt and delayed, emitted per fission event	1	
10-74.2	neutron yield per absorption	η	average number of fission neutrons, both prompt and delayed, emitted per neutron absorbed in a fissionable nuclide or in a nuclear fuel, as specified	1	ν/η is equal to the quotient of the macroscopic cross section for fission and that for absorption, both for neutrons in the fuel material.
10-75	fast fission factor	ϕ	in an infinite medium, the quotient of the mean number of neutrons produced by fission due to neutrons of all energies (ISO 80000-5) and the mean number of neutrons produced by fissions due to thermal neutrons only	1	The class of neutrons must be specified, e.g. thermal.
10-76	thermal utilization factor	f	in an infinite medium, the quotient of the number of thermal neutrons absorbed in a fissionable nuclide or in a nuclear fuel, as specified, and the total number of thermal neutrons absorbed	1	
10-77	non-leakage probability	A	probability that a neutron will not escape from the reactor during the slowing-down process or while it diffuses as a thermal neutron	1	
10-78.1	multiplication factor	k	quotient of the total number of fission or fission-dependent neutrons produced in the duration of a time interval and the total number of neutrons lost by absorption and leakage in that duration	1	
10-78.2	infinite multiplication factor	k_{∞}	multiplication factor (item 10-78.1) for an infinite medium or for an infinite repeating lattice	1	For a thermal reactor, $k_{\infty} = \eta \cdot \epsilon \cdot p \cdot f$
10-79	reactor time constant	T	duration (ISO 80000-3) required for the neutron fluence rate (item 10-44) in a reactor to change by the factor e when the fluence rate is rising or falling exponentially	s	Also called reactor period.

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-80.1	energy imparted	ϵ	<p>sum of all energy deposits in a given volume:</p> $\epsilon = \sum_i \epsilon_i$ <p>where the summation is performed over all energy (ISO 80000-5) deposits ϵ_i of interaction i in that volume</p>	<p>Energy imparted is a stochastic quantity. ϵ_i is given by:</p> $\epsilon_i = \epsilon_{in} - \epsilon_{out} + Q$ <p>where ϵ_{in} is the energy (ISO 80000-5) of the incident ionizing particle, excluding rest energy (item 10-3), ϵ_{out} is the sum of the energies (ISO 80000-5) of all ionizing particles leaving the interaction, excluding rest energy (item 10-3), and Q is the change in the rest energies (item 10-3) of the nucleus and of all particles involved in the interaction.</p> <p>$Q > 0$ means decrease of rest energy; $Q < 0$ means increase of rest energy.</p> <p>Stochastic quantities such as the energy imparted and the specific energy imparted (item 10-81.2) and their probability distributions have been introduced as they describe the discontinuous nature of the ionizing radiations as a determinant of radiochemical and radiobiological effects. In radiation applications involving large numbers of ionizing particles, e.g. in medicine, radiation protection and materials testing and processing, these fluctuations are adequately represented by the expectation values of the probability distributions. Non-stochastic quantities such as particle fluence (item 10-43), absorbed dose (item 10-81.1) and kerma (item 10-86.1) are based on these expectation values.</p>

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-80.2	mean energy imparted	$\bar{\epsilon}$ expectation value of the energy imparted (item 10-80.1): $\bar{\epsilon} = R_{in} - R_{out} + \sum Q$ where R_{in} is the radiant energy (item 10-45) of all those charged and uncharged ionizing particles that enter the volume, R_{out} is the radiant energy of all those charged and uncharged ionizing particles that leave the volume, and $\sum Q$ is the sum of all changes of the rest energy (item 10-3) of nuclei and elementary particles that occur in that volume	eV J kg m ² s ⁻²	Sometimes, it has been called the integral absorbed dose. $Q > 0$ means decrease of rest energy; $Q < 0$ means increase of rest energy.
10-81.1	absorbed dose	D differential quotient of $\bar{\epsilon}$ with respect to m , where $\bar{\epsilon}$ is the mean energy (ISO 80000-5) imparted by ionizing radiation to matter of mass (ISO 80000-4) m : $D = \frac{d\bar{\epsilon}}{dm}$	Gy J/kg m ² s ⁻²	The gray is a special name for joule per kilogram, to be used as the coherent SI unit for absorbed dose. 1 Gy = 1 J/kg $\bar{\epsilon} = \int D dm$ where dm is the element of mass of the irradiated matter. In the limit of a small domain, the mean specific energy $\bar{\epsilon} = \frac{\Delta\bar{\epsilon}}{\Delta m}$ is equal to the absorbed dose D . The absorbed dose can also be expressed in terms of the volume of the mass element by: $D = \frac{d\bar{\epsilon}}{dm} = \frac{d\bar{\epsilon}}{\rho dV}$

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-81.1 (cont.)				<p>where ρ is the mass density of the mass element.</p> <p>In report 85a of the ICRU a definition with an equivalent meaning is given as: The absorbed dose, D, is the quotient of $d\bar{\epsilon}$ by dm, where $d\bar{\epsilon}$ is the mean energy imparted by ionizing radiation to matter of mass dm:</p> $D = \frac{d\bar{\epsilon}}{dm}$
10-81.2	specific energy imparted	z $z = \frac{\epsilon}{m}$	<p>Gy J/kg $m^2 s^{-2}$</p>	<p>z is a stochastic quantity.</p> <p>In the limit of a small domain, the mean specific energy \bar{z} is equal to the absorbed dose D.</p> <p>The specific energy imparted can be due to one or more (energy-deposition) events.</p>
10-82	quality factor <ionizing radiation>	Q	1	<p>Q is determined by the linear energy transfer (item 10-85) for $\Delta \rightarrow \infty$, L_∞ (often denoted as L or LET), of charged particles passing through a small volume element at this point (the value of L_∞ refers to water, not to tissue; the difference, however, is small). The relationship between L and Q is given in ICRP Publication 103 (ICRP, 2007).</p>

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-83.1	dose equivalent	<p>H</p> <p>product of the absorbed dose D (item 10-81.1) to tissue at the point of interest and the quality factor Q (item 10-82) at that point:</p> $H = DQ$	<p>Sv</p> <p>J/kg</p> <p>$m^2 s^{-2}$</p>	<p>The sievert (Sv) is a special name for joule per kilogram, and is the coherent SI unit for dose equivalent.</p> <p>1 Sv = 1 J/kg</p> <p>The dose equivalent at a point in tissue is given by:</p> $H = \int_0^{\infty} Q(L) D_L dL$ <p>where $D_L = dD/dL$ is the distribution of D in L at the point of interest. See ICRP Publication 103 (ICRP, 2007).</p> <p>The quantities measured with radiation protection dosimeters are based on the definition $H = Q D$. If various radiation qualities i have to be simultaneously accounted for, the definition is:</p> $H = \sum_i Q_i D_i$

STANDARDSISO.COM : Click to view the full PDF of ISO 80000-10:2019

Table 1 (continued)

Item No.	Quantity		Unit	Remarks
	Name	Symbol		
10-83.1 (cont.)				In ICRU 51 this quantity is denoted as "dose equivalent". In order to quantify the radiation exposition of the human body and to specify dose limits, use is made of a quantity defined in ICRP 103, the "equivalent dose to a tissue or organ": $H_T = w_T \sum_R w_R D_{T,R}$. The weighting factors w_T for various tissues and organs T and w_R for various radiation qualities R have been numerically laid down in ICRP 103. $D_{T,R}$ is the mean absorbed dose to tissue within a tissue or organ T, imparted by radiation with radiation quality R.
10-83.2	dose equivalent rate	\dot{H}	Sv/s W/kg $m^2 s^{-3}$	1 Sv/s = 1 W/kg See the remarks for item 10-83.1.
10-84	absorbed-dose rate	\dot{D}	Gy/s W/kg $m^2 s^{-3}$	1 Gy/s = 1 W/kg See the remarks for item 10-81.1. In report 85a of the ICRU a definition with an equivalent meaning is given as: The absorbed-dose rate, \dot{D} , is the quotient of dD by dt , where dD is the increment of absorbed dose in the time interval dt : $\dot{D} = \frac{dD}{dt}$