

First edition  
2007-06-01

Corrected version  
2007-08-15

---

---

**Quantities and units —**  
**Part 8:**  
**Acoustics**

*Grandeurs et unités —*  
*Partie 8: Acoustique*

STANDARDSISO.COM : Click to view the full PDF of ISO 80000-8:2007

---

---

Reference number  
ISO 80000-8:2007(E)



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 80000-8:2007



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 80000-8 was prepared by Technical Committee ISO/TC 12, *Quantities, units, symbols, conversion factors*, in collaboration with IEC/TC 25, *Quantities and units, and their letter symbols*.

This first edition cancels and replaces the second edition of ISO 31-7:1992 and ISO 31-7:1992/Amd.1:1998. The major technical changes from the previous standards are the following:

- the presentation of *numerical statements* has been changed;
- the *special remarks* in the Introduction have been changed;
- the *normative references* have been changed;
- some quantities have been added to the list of quantities and some quantities have been deleted.

This corrected version of ISO 80000-8:2007 incorporates the following corrections.

- 0.3.1 e) The sentence was reworded.
- 8-3.b In the definition, the sign “=” was replaced by the sign “:=” after “dec”.
- 8-18 In the definition and in the remarks, the subscript “*f*” was deleted.  
In the definition, “frequency-weighted” was deleted.
- 8-22 In the definition and in the remarks, the subscript “*ft*” was deleted.  
In the definition, “frequency- and time-weighted” was deleted.  
In the remarks, “, or both” was added at the end of the first line.  
In the remarks, “and/or specific frequency bands” was changed to “or specific frequency bands or both” in the second line.
- 8-23 In the definition, “is” was added after “reference value”.
- 8-24 In the definition, “is” was added after “reference value”.

ISO 80000 consists of the following parts, under the general title *Quantities and units*:

- *Part 1: General*
- *Part 2: Mathematical signs and symbols to be used in the natural sciences and technology*
- *Part 3: Space and time*
- *Part 4: Mechanics*

## ISO 80000-8:2007(E)

- *Part 5: Thermodynamics*
- *Part 7: Light*
- *Part 8: Acoustics*
- *Part 9: Physical chemistry and molecular physics*
- *Part 10: Atomic and nuclear physics*
- *Part 11: Characteristic numbers*
- *Part 12: Solid state physics*

IEC 80000 consists of the following parts, under the general title *Quantities and units*:

- *Part 6: Electromagnetism*
- *Part 13: Information science and technology*
- *Part 14: Telebiometrics related to human physiology*

STANDARDSISO.COM : Click to view the full PDF of ISO 80000-8:2007

## Introduction

### 0.1 Arrangements of the tables

The tables of quantities and units in this International Standard are arranged so that the quantities are presented on the left-hand pages and the units on the corresponding right-hand pages.

All units between two full lines on the right-hand pages belong to the quantities between the corresponding full lines on the left-hand pages.

Where the numbering of an item has been changed in the revision of a part of ISO 31, the number in the preceding edition is shown in parentheses on the left-hand page under the new number for the quantity; a dash is used to indicate that the item in question did not appear in the preceding edition.

### 0.2 Tables of quantities

The names in English and in French of the most important quantities within the field of this International Standard are given together with their symbols and, in most cases, their definitions. These names and symbols are recommendations. The definitions are given for identification of the quantities in the International System of Quantities (ISQ), listed on the left hand pages of the table, they are not intended to be complete.

The scalar, vectorial or tensorial character of quantities is pointed out, especially when this is needed for the definitions.

In most cases only one name and only one symbol for the quantity are given; where two or more names or two or more symbols are given for one quantity and no special distinction is made, they are on an equal footing. When two types of italic letters exist (for example as with  $\vartheta$  and  $\theta$ ;  $\varphi$  and  $\phi$ ;  $a$  and  $\alpha$ ;  $g$  and  $g$ ) only one of these is given. This does not mean that the other is not equally acceptable. It is not recommended to give such variants different meanings. A symbol within parentheses implies that it is a reserve symbol, to be used when, in a particular context, the main symbol is in use with a different meaning.

In this English edition, the quantity names in French are printed in an italic font, and are preceded by *fr.* The gender of the French name is indicated by (m) for masculine and (f) for feminine, immediately after the noun in the French name.

### 0.3 Tables of units

#### 0.3.1 General

The names of units for the corresponding quantities are given together with the international symbols and the definitions. These unit names are language-dependent, but the symbols are international and the same in all languages. For further information, see the SI Brochure (8<sup>th</sup> edition 2006) from BIPM and ISO 80000-1<sup>1)</sup>.

The units are arranged in the following way:

- a) The coherent SI units are given first. The SI units have been adopted by the General Conference on Weights and Measures (Conférence Générale des Poids et Mesures, CGPM). The use of coherent SI units

1) To be published.

is recommended; decimal multiples and submultiples formed with the SI prefixes are recommended, even though not explicitly mentioned.

- b) Some non-SI units are then given, being those accepted by the International Committee for Weights and Measures (Comité International des Poids et Mesures, CIPM), or by the International Organization of Legal Metrology (Organisation Internationale de Métrologie Légale, OIML), or by ISO and IEC, for use with the SI.

Such units are separated from the SI units in the item by use of a broken line between the SI units and the other units.

- c) Non-SI units currently accepted by the CIPM for use with the SI are given in small print (smaller than the text size) in the “Conversion factors and remarks” column.
- d) Non-SI units that are not recommended are given only in annexes in some parts of this International Standard. These annexes are informative, in the first place for the conversion factors, and are not integral parts of the standard. These deprecated units are arranged in two groups:
- 1) units in the CGS system with special names;
  - 2) units based on the foot, pound, second, and some other related units.
- e) Other non-SI units are given for information, especially regarding the conversion factors, in informative annexes in some parts of this International Standard.

### 0.3.2 Remark on units for quantities of dimension one, or dimensionless quantities

The coherent unit for any quantity of dimension one, also called a dimensionless quantity, is the number one, symbol 1. When the value of such a quantity is expressed, the unit symbol 1 is generally not written out explicitly.

EXAMPLE 1 Refractive index  $n = 1,53 \times 1 = 1,53$

Prefixes shall not be used to form multiples or submultiples of this unit. Instead of prefixes, powers of 10 are recommended.

EXAMPLE 2 Reynolds number  $Re = 1,32 \times 10^3$

Considering that plane angle is generally expressed as the ratio of two lengths and solid angle as the ratio of two areas, in 1995 the CGPM specified that, in the SI, the radian, symbol rad, and steradian, symbol sr, are dimensionless derived units. This implies that the quantities plane angle and solid angle are considered as derived quantities of dimension one. The units radian and steradian are thus equal to one; they may either be omitted, or they may be used in expressions for derived units to facilitate distinction between quantities of different kinds but having the same dimension.

## 0.4 Numerical statements in this International Standard

The sign = is used to denote “is exactly equal to”, the sign  $\approx$  is used to denote “is approximately equal to”, and the sign := is used to denote “is by definition equal to”.

Numerical values of physical quantities that have been experimentally determined always have an associated measurement uncertainty. This uncertainty should always be specified. In this International Standard, the magnitude of the uncertainty is represented as in the following example.

EXAMPLE  $l = 2,347\ 82(32)\ \text{m}$

In this example,  $l = a(b)\ \text{m}$ , the numerical value of the uncertainty  $b$  indicated in parentheses is assumed to apply to the last (and least significant) digits of the numerical value  $a$  of the length  $l$ . This notation is used when  $b$  represents the standard uncertainty (estimated standard deviation) in the last digits of  $a$ . The numerical example given above may be interpreted to mean that the best estimate of the numerical value of the length  $l$  (when  $l$  is expressed in the unit metre) is 2,347 82, and that the unknown value of  $l$  is believed to lie between  $(2,347\ 82 - 0,000\ 32)\ \text{m}$  and  $(2,347\ 82 + 0,000\ 32)\ \text{m}$ , with a probability determined by the standard uncertainty 0,000 32 m and the normal probability distribution of the values of  $l$ .

## 0.5 Special remarks

### 0.5.1 General

In the explanations in the “Definition” column for quantities, it is assumed that systems are linear and that non-linear effects and effects due to anisotropy and superimposed flow are sufficiently small, that they may be neglected. Root-mean-square values may be indicated by the subscript “eff”.

### 0.5.2 Remark on logarithmic quantities and their units

Quantities are independent of the choice of units in which the values of the quantities are expressed. Derived units are expressed in terms of base units according to the equations between the corresponding quantities. In strict quantity calculus, it is therefore a circular definition if a unit is included in the definition of a quantity. This could, however, be done if the unit is defined elsewhere. In most practical applications in acoustics, logarithmic quantities are defined as expressed in the unit decibel, dB. This practice is applied in ISO 80000-8. For the fundamental definitions of logarithmic quantities, see ISO 80000-3:2006, items 3-21 and 3-22.

STANDARDSISO.COM : Click to view the full PDF of ISO 80000-8:2007

[STANDARDSISO.COM](http://STANDARDSISO.COM) : Click to view the full PDF of ISO 80000-8:2007

# Quantities and units —

## Part 8: Acoustics

### 1 Scope

ISO 80000-8 gives names, symbols and definitions for quantities and units of acoustics. Where appropriate, conversion factors are also given.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 16, *Acoustics — Standard tuning frequency (Standard musical pitch)*

ISO 80000-3:2006, *Quantities and units — Part 3: Space and time*

ISO 80000-4:2006, *Quantities and units — Part 4: Mechanics*

IEC 60027-1, *Letter symbols to be used in electrical technology — Part 1: General*

IEC 61672-1, *Electroacoustics — Sound level meters — Part 1: Specifications*

### 3 Names, symbols, and definitions

The names, symbols and definitions for quantities and units of acoustics are given on the following pages.

ACOUSTICS			QUANTITIES	
Item No.	Name	Symbol	Definition	Remarks
8-1 (7-1)	period duration, period <i>fr période</i> (f)	$T$	duration of one cycle of a periodic phenomenon	See also ISO 80000-3:2006, item 3-12.
8-2 (7-2)	frequency <i>fr fréquence</i> (f)	$f, (v)$	$f = 1/T$ where $T$ is period (item 8-1)	For the standard tuning frequency (standard musical pitch), see ISO 16. See also ISO 80000-3:2006, item 3-15.1.
8-3 (7-3)	logarithmic frequency interval <i>fr intervalle</i> (m) <i>logarithmique de fréquence</i>	$G$	$G = \text{lb}(f_2/f_1)$ where $f_1$ and $f_2 \geq f_1$ are frequencies (item 8-2) of two tones	$\text{lb}(f_2/f_1) = \log_2(f_2/f_1)$
8-4 (7-4)	angular frequency <i>fr pulsation</i> (f)	$\omega$	$\omega = 2\pi f$ where $f$ is frequency (item 8-2)	See also ISO 80000-3:2006, item 3-16.
8-5 (7-5)	wavelength <i>fr longueur</i> (f) <i>d'onde</i>	$\lambda$	for a sinusoidal wave and in a direction perpendicular to the wavefront, distance between two successive points where at a given instant the phase (item 8-25.2, remark) differs by $2\pi$	See also ISO 80000-3:2006, item 3-17.
8-6 (7-6)	wavenumber, repetency <i>fr nombre</i> (m) <i>d'onde</i>	$\sigma$	$\sigma = 1/\lambda$ where $\lambda$ is wavelength (item 8-5)	The vector $k$ , corresponding to item 8-7, is generally called wave vector. Also the vector $\sigma$ is sometimes called wave vector.
8-7 (7-7)	angular wavenumber, angular repetency <i>fr nombre</i> (m) <i>d'onde angulaire</i>	$k$	$k = \omega/c = 2\pi/\lambda$ where $\omega$ is angular frequency (item 8-4), $c$ is phase speed of sound (item 8-14.1), $2\pi$ is the phase difference, and $\lambda$ is wavelength (item 8-5)	
8-8 (7-8)	density, mass density <i>fr masse</i> (f) <i>volumique</i>	$\rho$	$\rho = m/V$ where $m$ is mass (ISO 80000-4:2006, item 4-1) and $V$ is volume (ISO 80000-3:2006, item 3-4)	

UNITS			ACOUSTICS	
Item No.	Name	Inter-national symbol	Definition	Conversion factors and remarks
8-1.a	second	s		
8-2.a	hertz	Hz	1 Hz := 1 s <sup>-1</sup>	1 Hz is the frequency of a periodic phenomenon, the period of which is 1 s.
8-3.a	octave	oct	1 oct := lb 2 = 1	1 oct is the logarithmic frequency interval between $f_1$ and $f_2$ when $f_2/f_1 = 2$ .
8-3.b	decade	dec	1 dec := lb 10 = (lb 10) oct $\approx$ 3,32 oct = 3,32	1 dec is the logarithmic frequency interval between $f_1$ and $f_2$ when $f_2/f_1 = 10$ .
8-4.a	radian per second	rad/s		
8-4.b	second to the power minus one	s <sup>-1</sup>		
8-5.a	metre	m		
8-6.a	metre to the power minus one	m <sup>-1</sup>		
8-7.a	radian per metre	rad/m		
8-7.b	metre to the power minus one	m <sup>-1</sup>		
8-8.a	kilogram per cubic metre	kg/m <sup>3</sup>		

(continued)

ACOUSTICS			QUANTITIES	
Item No.	Name	Symbol	Definition	Remarks
8-9.1 (7-9.1)	static pressure <i>fr pression (f) statique</i>	$p_s$	pressure that would exist in the absence of sound waves	
8-9.2 (7-9.2)	sound pressure <i>fr pression (f) acoustique (instantanée)</i>	$p$	difference between instantaneous total pressure and static pressure	The symbols for any of the quantities 8-9.2 to 8-13 inclusive are often used without modification for their root-mean-square (r.m.s.) values. See also IEC 60027-1.
8-10 (7-10)	sound particle displacement <i>fr élancement (f) (instantanée) d'une particule</i>	$\delta$ ( $\xi, \eta, \zeta$ )	instantaneous displacement of a particle in a medium from what would be its position in the absence of sound waves	
8-11 (7-11)	sound particle velocity <i>fr vitesse (f) acoustique (instantanée) d'une particule</i>	$v, u$ ( $u, v, w$ )	$v = \frac{\partial \delta}{\partial t}$ where $\delta$ is sound particle displacement (item 8-10) and $t$ is time	
8-12 (7-12)	sound particle acceleration <i>fr accélération (f) acoustique (instantanée) d'une particule</i>	$a$	$a = \frac{\partial v}{\partial t}$ where $v$ is sound particle velocity (item 8-11) and $t$ is time	
8-13 (7-13)	sound volume velocity, sound volume flow rate <i>fr flux (m) de vitesse acoustique (instantanée)</i>	$q, (q_V)$	surface integral of the normal component of the sound particle velocity (item 8-11) over the cross-section (through which the sound propagates)	
8-14.1 (7-14.1)	phase speed of sound <i>fr vitesse (f) de phase du son, (célérité) (f) du son</i>	$c$	$c = \frac{\omega}{k} (= \lambda f)$ where $\omega$ is angular frequency (item 8-4) and $k$ is angular wavenumber (item 8-7)	
8-14.2 (7-14.1)	group speed of sound <i>fr vitesse (f) de groupe du son</i>	$c_g$	$c_g = \frac{d\omega}{dk}$ where $\omega$ is angular frequency (item 8-4) and $k$ is angular wavenumber (item 8-7)	Group speed of sound is the travel speed of the energy of a sound wave.

UNITS			ACOUSTICS	
Item No.	Name	Inter-national symbol	Definition	Conversion factors and remarks
8-9.a	pascal	Pa		
8-10.a	metre	m		
8-11.a	metre per second	m/s		
8-12.a	metre per second squared	m/s <sup>2</sup>		
8-13.a	cubic metre per second	m <sup>3</sup> /s		
8-14.a	metre per second	m/s		

(continued)

ACOUSTICS			QUANTITIES	
Item No.	Name	Symbol	Definition	Remarks
8-15 (7-15)	sound energy density <i>fr énergie (f) volumique acoustique</i>	$w$	time-averaged sound energy in a given volume divided by that volume	
8-16 (7-16)	sound power <i>fr puissance (f) acoustique</i>	$P, P_a$	through a surface, product of the sound pressure, $p$ (item 8-9.2), and the component of the particle velocity, $u_n$ (item 8-11), at a point on the surface in the direction normal to the surface, integrated over that surface (item 8-16.2)	
8-17.1 (7-17)	sound intensity <i>fr intensité (f) acoustique</i>	$i$	$i = p \cdot v$ where $p$ is sound pressure (item 8-9.2) and $v$ is sound particle velocity (item 8-11)	Intensity is sometimes known as energy flux density.
8-17.2 (—)	time-averaged sound intensity <i>fr intensité (f) acoustique moyenne</i>	$I$	$I = \frac{1}{t_2 - t_1} \int_{t_1}^{t_2} i(t) dt$ where $t_1$ and $t_2$ are the starting and ending times for the integral and $i$ is sound intensity (item 8-17.1)	
8-18 (—)	sound exposure <i>fr exposition (f) sonore, exposition (f) au bruit</i>	$E$	$E = \int_{t_1}^{t_2} p^2 dt$ where $t_1$ and $t_2$ are the starting and ending times for the integral and $p$ is sound pressure (item 8-9.2)	Because of practical limitations of the measuring instruments, $p^2$ is always understood to denote the square of a frequency-weighted and frequency-band-limited sound pressure. If specific frequency weightings as specified in IEC 61672-1 are applied, this should be indicated by appropriate subscripts to the symbol $E$ .
8-19 (7-20.2)	characteristic impedance of a medium <i>fr impédance (f) acoustique caractéristique d'un milieu</i>	$Z_c$	at a point in a non-dissipative medium and for a plane progressive wave, the quotient of the sound pressure (item 8-9.2) by the component of the sound particle velocity (item 8-11) in the direction of the wave propagation	$Z_c = \rho c$ where $\rho$ is the density (item 8-8) of the medium and $c$ the phase speed of sound (item 8-14.1).

UNITS			ACOUSTICS	
Item No.	Name	Inter-national symbol	Definition	Conversion factors and remarks
8-15.a	joule per cubic metre	J/m <sup>3</sup>		
8-16.a	watt	W		
8-17.a	watt per square metre	W/m <sup>2</sup>		
8-18.a	pascal squared second	Pa <sup>2</sup> .s		
8-19.a	pascal second per metre	Pa·s/m		

(continued)

ACOUSTICS			QUANTITIES	
Item No.	Name	Symbol	Definition	Remarks
8-20 (7-18)	acoustic impedance <i>fr impédance (f) acoustique</i>	$Z_a$	at a surface, the complex quotient of the average sound pressure (item 8-9.2) over that surface by the sound volume flow rate (item 8-13) through that surface	
8-21 (7-19)	mechanical surface impedance <i>fr impédance (f) mécanique (de surface)</i>	$Z_m$	at a surface, the complex quotient of the total force on the surface by the component of the average sound particle velocity (item 8-11) at the surface in the direction of the force	$Z_m = Z_a \cdot A^2$ where $A$ is the area of the surface considered and $Z_a$ is the acoustic impedance (item 8-20).
8-22 (7-21)	sound pressure level <i>fr niveau (m) de pression acoustique</i>	$L_p$	$L_p = 10 \lg \frac{p^2}{p_0^2}$ dB  where $p$ is sound pressure (item 8-9.2) and the reference value in airborne acoustics is $p_0 = 20 \mu\text{Pa}$	Because of practical limitations of the measuring instruments, $p^2$ is always understood to denote the square of a frequency-weighted, frequency-band-limited or time-weighted sound pressure or both. If specific frequency and time weightings as specified in IEC 61672-1 or specific frequency bands or both are applied, this should be indicated by appropriate subscripts.  For a general definition of the level of a field quantity, see also ISO 80000-3:2006, item 3-21. For media other than air, other reference values may be used.
8-23 (7-22)	sound power level <i>fr niveau (m) de puissance acoustique</i>	$L_W$	$L_W = 10 \lg \frac{P}{P_0}$ dB  where $P$ is sound power (item 8-16) and the reference value is $P_0 = 1 \text{ pW}$	For a general definition of the level of a power quantity, see also ISO 80000-3:2006, item 3-22.
8-24 (—)	sound exposure level <i>fr niveau (m) d'exposition sonore, niveau d'exposition au bruit</i>	$L_E$	$L_E = 10 \lg \frac{E}{E_0}$ dB  where $E$ is sound exposure (item 8-18) and the reference value is $E_0 = 400 \mu\text{Pa}^2 \cdot \text{s}$	If specific frequency weightings as specified in IEC 61672-1 are applied, this should be indicated by appropriate subscripts.

UNITS			ACOUSTICS	
Item No.	Name	International symbol	Definition	Conversion factors and remarks
8-20.a	pascal second per cubic metre	Pa·s/m <sup>3</sup>		
8-21.a	newton second per metre	N·s/m		
8-22.a	bel	B	1 B is the sound pressure level when $p/p_0 = \sqrt{10}$	In practical applications and consistent with the definition of sound pressure level, the submultiple decibel, dB, is used instead of the bel, B.  NOTE The addition of a postscript to indicate the frequency weighting, e.g. dB(A), is incorrect. This information should be carried by the quantity symbol, e.g. $L_A$ .
8-23.a	bel	B	1 B is the sound power level when $P/P_0 = 10$	In practical applications and consistent with the definition of sound power level, the submultiple decibel, dB, is used instead of the bel, B.
8-24.a	bel	B	1 B is the sound exposure level when $E/E_0 = 10$	In practical applications and consistent with the definition of sound exposure level, the submultiple decibel, dB, is used instead of the bel, B.

(continued)