

INTERNATIONAL STANDARD

ISO
8362-3

First edition
1989-11-15

Injection containers for injectables and accessories —

Part 3 : Aluminium caps for injection vials

*Réipients et accessoires pour produits
injectables —*

Partie 3 : Capsules en aluminium pour flacons



Reference number
ISO 8362-3 : 1989 (E)

Contents

	Page
Foreword	iii
Introduction	iv
1 Scope	1
2 Normative reference	1
3 Dimensions and designation	1
4 Requirements	3
5 Packaging	3
6 Marking	3

STANDARDSISO.COM : Click to view the full PDF of ISO 8362-3:1989

© ISO 1989

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization

Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 8361-3 was prepared by Technical Committee ISO/TC 76, *Transfusion, infusion and injection equipment for medical use*.

ISO 8362 consists of the following parts, under the general title *Injection containers for injectables and accessories* :

- *Part 1: Injection vials made of glass tubing*
- *Part 2: Closures for injection vials*
- *Part 3: Aluminium caps for injection vials*
- *Part 4: Injection vials made of moulded glass*

Introduction

The materials from which injection containers (including the elastomeric closures) are made are suitable primary packaging materials for storing injectable products until they are administered. However, in this part of ISO 8362, aluminium caps are not considered as primary packaging materials in direct contact with pharmaceutical preparations.

STANDARDSISO.COM : Click to view the full PDF of ISO 8362-3:1989

Injection containers for injectables and accessories —

Part 3 : Aluminium caps for injection vials

1 Scope

This part of ISO 8362 specifies aluminium caps for injection vials as described in ISO 8362-1 and ISO 8362-4.

2 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this part of ISO 8362. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this part of ISO 8362 are encouraged to investigate the possibility of applying the most recent edition of the


standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 8872 : 1988, *Aluminium caps for transfusion, infusion and injection bottles — General requirements and test methods.*

3 Dimensions and designation


3.1 Dimensions

The dimensions of aluminium caps shall be as shown in figure 1 and as given in table 1.



a) Type A – Aluminium cap with centre hole

b) Type B – Aluminium cap with two-bridge tab



c) Type C – Aluminium cap with three-bridge tab

d) Type D – Aluminium cap with complete tear-off tab

NOTE – The width and the number of bridges for types B, C and D depend on the degree of resistance intended.

Figure 1 – Dimensions and configuration of aluminium caps