

INTERNATIONAL  
STANDARD

**ISO**  
**8590**

Second edition  
1994-08-01

---

---

**Cinematography — Audio records on  
70 mm motion-picture release prints with  
magnetic stripes — Recorded  
characteristic**

*Cinématographie — Enregistrements sonores sur copies d'exploitation  
sur film cinématographique 70 mm à pistes magnétiques —  
Caractéristique d'enregistrement*



Reference number  
ISO 8590:1994(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 8590 was prepared by Technical Committee ISO/TC 36, *Cinematography*.

This second edition cancels and replaces the first edition (ISO 8590:1985), of which it constitutes a technical revision.

STANDARDSISO.COM : Click to view the full PDF of ISO 8590:1994

© ISO 1994

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization  
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

# Cinematography — Audio records on 70 mm motion-picture release prints with magnetic stripes — Recorded characteristic

## 1 Scope

This International Standard specifies the recorded characteristic of audio records on 70 mm motion-picture release prints with magnetic striping when reproduced at the nominal speed of 24 frames per second.

## 2 Recorded characteristic

With a constant amplitude sine-wave applied to the input of the recording system, the relative characteristic in effective values of the short-circuit magnetic flux versus frequency shall decrease with increasing frequency proportionately to the impedance of a combination of capacitance and resistance having time constants,  $t_1$  and  $t_h$ , of 35  $\mu\text{s}$  and 3 180  $\mu\text{s}$ . The characteristic defined above is obtained by the following formula:

$$L_{\phi} = C_0 - 10 \log_{10} \left[ \frac{1 + (2\pi t_h)^2 f^2}{1 + \frac{1}{(2\pi t_1)^2 f^2}} \right]$$

where

$L_{\phi}$  is the recorded relative magnetic flux level, in decibels;

$f$  is the frequency, in hertz;

$t_1$  is a time constant with a value of 3 180  $\mu\text{s}$ ;

$t_h$  is a time constant with a value of 35  $\mu\text{s}$ ;

$C_0$  is a constant calculated to make  $L_{\phi} = 0$  at the reference frequency of 1 000 Hz.

### NOTES

1 A frequency response curve may be conveniently defined as proportional to the impedance curve of a resistance-capacitance network having stated time constants. Such a network is not intended as a recommended electrical circuit.

2 It has been shown that a low-frequency time constant of infinity should be used for best headroom versus frequency of the medium. It is recognized, however, that it is necessary for the immediate future to continue to add low-frequency pre-emphasis of 3 180  $\mu\text{s}$  because much theatre equipment cannot meet the tolerances of this International Standard when using a time constant of infinity.

**Table 1 — Approximate values of the recorded relative magnetic flux**

Frequency, <i>f</i> Hz	$L_{\phi}$ dB	Tolerances dB
20	8,8	+3,0 -10,0
25	7,19	+3,0 -8,0
31,5	5,66	+3,0 -6,0
40	4,29	+2,0 -4,0
50	3,21	
63	2,32	+1,5 -3,0
80	1,63	+1,3 -2,0
100	1,16	
125	0,84	
160	0,59	
200	0,45	
250	0,35	
315	0,28	
400	0,23	
500	0,19	
630	0,14	+1,0 -1,0
800	0,08	
1 000	0	
1 250	- 0,12	
1 600	- 0,31	
2 000	- 0,57	
2 500	- 0,95	
3 150	- 1,51	
4 000	- 2,29	
5 000	- 3,25	
6 300	- 4,46	+1,3 -1,0
8 000	- 5,93	+1,5 -2,0
10 000	- 7,47	+2,0 -2,5
12 500	- 9,13	+2,0 -3,5
16 000	- 11,07	

STANDARD.SISO.COM · Click to view the full PDF of ISO 8590:1994




Figure 1 — Approximate values of the recorded relative magnetic flux




Figure 2 — Tolerances

This page intentionally left blank

STANDARDSISO.COM : Click to view the full PDF of ISO 8590:1994