

INTERNATIONAL
STANDARD

ISO
8674

Second edition
1999-08-15

**Hexagon nuts, style 2, with metric fine pitch
thread — Product grades A and B**

Écrous hexagonaux, style 2, à filetage métrique à pas fin — Grades A et B

STANDARDSISO.COM : Click to view the full PDF of ISO 8674:1999



Reference number
ISO 8674:1999(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 8674 was prepared by Technical Committee ISO/TC 2, *Fasteners*.

This second edition cancels and replaces the first edition (ISO 8674:1988) which has been technically revised.

STANDARDSISO.COM : Click to view the full PDF of ISO 8674:1999

© ISO 1999

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet iso@iso.ch

Printed in Switzerland

Introduction

This International Standard is part of the complete ISO product standard series on external hexagon drive fasteners. The series comprises:

- a) hexagon head bolts (ISO 4014 to ISO 4016 and ISO 8765);
- b) hexagon head screws (ISO 4017, ISO 4018 and ISO 8676);
- c) hexagon nuts (ISO 4032 to ISO 4036, ISO 8673 to ISO 8675);
- d) hexagon bolts with flange (ISO 4162 and ISO 15071);
- e) hexagon nuts with flange (ISO 4161 and ISO 10663);
- f) structural bolts and nuts (ISO 4775, ISO 7411 to ISO 7414 and ISO 7417).

STANDARDSISO.COM : Click to view the full PDF of ISO 8674:1999

Hexagon nuts, style 2, with metric fine pitch thread — Product grades A and B

1 Scope

This International Standard specifies the characteristics of hexagon nuts, style 2, with metric fine pitch thread, with nominal thread diameters d from 8 mm up to and including 36 mm, with product grade A for sizes d up to and including 16 mm and product grade B for sizes d over 16 mm.

If, in special cases, specifications other than those listed in this International Standard are required, they should be selected from existing International Standards, for example ISO 724, ISO 898-6, ISO 965-1 and ISO 4759-1.

Coarse thread hexagon nuts, style 2, according to ISO 4033 should be the first choice.

NOTE For hexagon nuts, style 1, with fine pitch thread, see ISO 8673.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 225:1983, *Fasteners — Bolts, screws, studs and nuts — Symbols and designations of dimensions.*

ISO 724:1993, *ISO general-purpose metric screw threads — Basic dimensions.*

ISO 898-6:1994, *Mechanical properties of fasteners — Part 6: Nuts with specified proof load values — Fine pitch thread.*

ISO 965-1:1998, *ISO general purpose metric screw threads — Tolerances — Part 1: Principles and basic data.*

ISO 3269:—¹⁾, *Fasteners — Acceptance inspection.*

ISO 4042:1999, *Fasteners — Electroplated coatings.*

ISO 4759-1:—²⁾, *Tolerances for fasteners — Part 1: Bolts, screws, studs and nuts — Product grades A, B and C.*

ISO 6157-2:1995, *Fasteners — Surface discontinuities — Part 2: Nuts.*

ISO 8839:1986, *Mechanical properties of fasteners — Bolts, screws, studs and nuts made of non-ferrous metals.*

ISO 8992:1986, *Fasteners — General requirements for bolts, screws, studs and nuts.*

ISO 10683:—³⁾, *Fasteners — Non-electrolytically applied zinc flake coatings.*

¹⁾ To be published. (Revision of ISO 3269:1988)


²⁾ To be published. (Revision of ISO 4759-1:1978)

³⁾ To be published.

3 Dimensions

See Figure 1, Tables 1 and 2.

Symbols and descriptions of dimensions are defined in ISO 225.



a Washer-face form to be ordered separately.

b $\beta = 15^\circ$ to 30°

c $\theta = 90^\circ$ to 120°

Figure 1

STANDARDSISO.COM : Click to view the full PDF of ISO 8674:1999

Table 1 — Preferred threads

Dimensions in millimetres

Thread ($d \times P$)		M8 × 1	M10 × 1	M12 × 1,5	M16 × 1,5	M20 × 1,5	M24 × 2	M30 × 2	M36 × 3
c	max.	0,60	0,60	0,60	0,8	0,8	0,8	0,8	0,8
	min.	0,15	0,15	0,15	0,2	0,2	0,2	0,2	0,2
d_a	max.	8,75	10,8	13	17,3	21,6	25,9	32,4	38,9
	min.	8,00	10,0	12	16,0	20,0	24,0	30,0	36,0
d_w	min.	11,63	14,63	16,63	22,49	27,7	33,25	42,75	51,11
e	min.	14,38	17,77	20,03	26,75	32,95	39,55	50,85	60,79
m	max.	7,50	9,30	12,00	16,4	20,3	23,9	28,6	34,7
	min.	7,14	8,94	11,57	15,7	19,0	22,6	27,3	33,1
m_w	min.	5,71	7,15	9,26	12,56	15,2	18,08	21,84	26,48
s	nom. = max.	13,00	16,00	18,00	24,00	30,00	36	46	55,0
	min.	12,73	15,73	17,73	23,67	29,16	35	45	53,8

Table 2 — Non-preferred threads

Dimensions in millimetres

Thread ($d \times P$)		M10 × 1,25	M12 × 1,25	M14 × 1,5	M18 × 1,5	M20 × 2	M22 × 1,5	M27 × 2	M33 × 2
c	max.	0,60	0,60	0,60	0,8	0,8	0,8	0,8	0,8
	min.	0,15	0,15	0,15	0,2	0,2	0,2	0,2	0,2
d_a	max.	10,8	12	15,1	19,5	21,6	23,7	29,1	35,6
	min.	10,0	13	14,0	18,0	20,0	22,0	27,0	33,0
d_w	min.	14,63	16,63	19,64	24,85	27,7	31,35	38	46,55
e	min.	17,77	20,03	23,36	29,56	32,95	37,29	45,2	55,37
m	max.	9,30	12,00	14,1	17,6	20,3	21,8	26,7	32,5
	min.	8,94	11,57	13,4	16,9	19,0	20,5	25,4	30,9
m_w	min.	7,15	9,26	10,72	13,52	15,2	16,4	20,32	24,72
s	nom. = max.	16,00	18,00	21,00	27,00	30,00	34	41	50
	min.	15,73	17,73	20,67	26,16	29,16	33	40	49

4 Specifications and reference standards

See Table 3.

Table 3 — Specification and reference standards

Material		Steel
General requirements	International Standard	ISO 8992
Thread	Tolerance	6H
	International Standards	ISO 724, ISO 965-1
Mechanical properties	Property class ^a	$d \leq 16$ mm: 8, 12 $d \leq 36$ mm: 10
	International Standard	ISO 898-6
Tolerances	Product grade	$d \leq 16$ mm: A $d > 16$ mm: B
	International Standard	ISO 4759-1
Finish and/or coating		As processed Requirements for electroplating are covered in ISO 4042. Requirements for non-electrolytically applied zinc flake coatings are covered in ISO 10683. If different electroplating requirements are desired or if requirements are needed for other finishes, they should be negotiated between customer and supplier. Limits for surface discontinuities are covered in ISO 6157-2.
Acceptability		For acceptance procedure, see ISO 3269.
^a For other property classes see ISO 898-6.		

5 Designation

EXAMPLE:

A hexagon nut, style 2, with thread M16 × 1,5 and property class 12 is designated as follows:

Hexagon nut ISO 8674 - M16 × 1,5 - 12