

INTERNATIONAL STANDARD

ISO
9158

First edition
1988-03-15



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION
ORGANISATION INTERNATIONALE DE NORMALISATION
МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ

Road vehicles — Nozzle spouts for unleaded gasoline

Véhicules routiers — Pistolets de remplissage pour essence sans plomb

STANDARDSISO.COM : Click to view the full PDF of ISO 9158:1988

Reference number
ISO 9158 : 0000 (E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 9158 was prepared by Technical Committee ISO/TC 22, *Road vehicles*.

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its latest edition, unless otherwise stated.

STANDARDSISO.COM : Click to view the full PDF of ISO 9158:1988

Road vehicles — Nozzle spouts for unleaded gasoline

1 Scope and field of application

This International Standard specifies the dimensions of nozzle spouts on pumps for refuelling road vehicles, and their filling rates.

It applies to nozzle spouts for unleaded gasoline for road vehicles.

2 Reference

ISO 4130, *Road vehicles — Three-dimensional reference systems and fiducial marks — Definitions.*

3 Requirements

The nozzle spout shall conform to the dimensions given in the figure. The shape is at the manufacturer's discretion.

The flow rate, q_V , for unleaded gasoline shall be

$$q_V \leq 50 \text{ l/min.}$$

The figure shows a nozzle spout with a spring for safe hooking in the tank filler opening. The dimensions apply also to nozzle spouts with cams or depressions for safe hooking.