

---

---

**Agricultural irrigation equipment —  
Irrigation valves —**

Part 3:  
**Check valves**

*Matériel agricole d'irrigation — Vannes d'irrigation —  
Partie 3: Clapets antiretour*

STANDARDSISO.COM : Click to view the full PDF of ISO 9635-3:2006



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 9635-3:2006

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 9635-3 was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 18, *Irrigation and drainage equipment and systems*.

This first edition of ISO 9635-3, together with ISO 9635-1, ISO 9635-2, ISO 9635-4 and ISO 9635-5, cancels and replaces ISO 9635:1990, of which it constitutes a technical revision.

ISO 9635 consists of the following parts, under the general title *Agricultural irrigation equipment — Irrigation valves*:

- *Part 1: General requirements*
- *Part 2: Isolating valves*
- *Part 3: Check valves*
- *Part 4: Air valves*
- *Part 5: Control valves*

[STANDARDSISO.COM](http://STANDARDSISO.COM) : Click to view the full PDF of ISO 9635-3:2006

# Agricultural irrigation equipment — Irrigation valves —

## Part 3: Check valves

### 1 Scope

This part of ISO 9635 specifies construction and performance requirements and test methods for check valves, intended for operation in irrigation systems with water at temperatures not exceeding 60 °C, which can contain fertilizers and other chemicals of the types and concentrations used in agriculture.

It is applicable to hydraulically operated check irrigation valves of DN 15 (1/2 inch) diameter or greater, designed to operate in the fully open and fully closed positions, but which can also operate for extended time periods in any intermediate position.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9635-1:2006, *Agricultural irrigation equipment — Irrigation valves — Part 1: General requirements*

ISO 9644:1993, *Agricultural irrigation equipment — Pressure losses in irrigation valves — Test method*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 9635-1 and the following apply.

#### 3.1

##### check valve

valve which automatically opens by fluid flow in a defined direction and which automatically closes to prevent fluid flow in the reverse direction

[EN 1267]

#### 3.2

##### flow coefficient

$K_v$

coefficient equal to the flow rate, in cubic metres per hour, of water at a temperature between 5 °C and 50 °C, passing through the valve and causing a loss of static head of 1 bar

NOTE 1  $Q = K_v \sqrt{\Delta p}$ , where  $Q$  is the flow rate in cubic metres per hour (m<sup>3</sup>/h), and  $p$  is the pressure in kilopascals per square centimetre (kPa/cm<sup>2</sup>).

NOTE 2 1 bar = 0,1 MPa = 10<sup>5</sup> Pa; 1 MPa = 1 N/mm<sup>2</sup>.

NOTE 3 Adapted from EN 736-3.

## 4 Design requirements

Check valves shall be designed in accordance with ISO 9635-1:2006, Clause 4.

Check valves may be equipped with a device to assist closure or balance the weight of the obturator. However, such valves are not considered to have a mechanically operated obturator.

The manufacturer shall indicate in the relevant technical documentation the orientations in which the check valves fulfil the requirements of this standard.

It is recommended that the valves be designed to permit integral repair and maintenance without removing the valve body from the line.

## 5 Performance requirements

### 5.1 Mechanical strength

#### 5.1.1 Resistance of shell and all pressure-containing components to internal pressure

Requirements and testing shall be in accordance with ISO 9635-1:2006, 5.1.1.

#### 5.1.2 Resistance of obturator to differential pressure

Requirements and testing shall be in accordance with ISO 9635-1:2006, 5.1.2.

The test shall be performed with the pressure applied to the downstream side of the obturator.

After testing, the obturator shall not be jammed nor wedged. After completion of the test, the differential pressure and flow rate necessary to fully open the obturator shall not exceed the initial values by more than 10 %.

#### 5.1.3 Resistance of valve to bending

Requirements and testing shall be in accordance with ISO 9635-1:2006, 5.1.3.

The test shall be performed with the pressure applied to the downstream side of the obturator.

The bending moment,  $M$ , to be applied during the test shall be in accordance with Table 1, as a function of DN.

Table 1 — Bending moments

DN	Bending moment $M$ N · m
50	1 050
65	1 400
80	1 500
100	2 200
125	3 200
150	4 800
200	7 200
250	11 000
300	15 000
350	19 000
400	24 000
450	28 000
500	33 000

## 5.2 Watertightness and air-tightness

### 5.2.1 Watertightness and air-tightness of shell and all pressure-containing components

#### 5.2.1.1 Internal pressure

Requirements and testing shall be in accordance with ISO 9635-1:2006, 5.2.1.1.

#### 5.2.1.2 External pressure

Requirements and testing shall be in accordance with ISO 9635-1:2006, 5.2.1.2.

### 5.2.2 Seat tightness

#### 5.2.2.1 Seat tightness at high differential pressure

Requirements and testing shall be in accordance with ISO 9635-1:2006, 5.2.2.1. For a type test, the test duration shall not be less than 10 min.

The test shall be performed with the pressure applied to the downstream side of the obturator.

#### 5.2.2.2 Seat tightness at low differential pressure

Requirements and testing shall be in accordance with ISO 9635-1:2006, 5.2.2.2. For a type test, the test duration shall not be less than 10 min.

The test shall be performed with the pressure applied to the downstream side of the obturator.

### 5.3 Hydraulic characteristics

Requirements shall be in accordance with ISO 9635-1:2006, 5.3. The characteristic given by the manufacturer shall be the head loss as a function of flow or the  $K_v$  value.

When measured in accordance with ISO 9644:1993, Clause 4, the head loss shall not be more than 1,1 times the value indicated by the manufacturer.

### 5.4 Resistance to chemicals and fertilizers

Requirements and testing shall be in accordance with ISO 9635-1:2006, 5.4.

### 5.5 Endurance

Check valves shall keep their functional capacity after a significant number of operations (opening/closing cycles).

The flow rate should be high enough to deflect the obturator to a fully open position.

In order to verify this requirement, the check valve shall be tested in accordance with Annex A, comprising 2 500 opening/closing cycles. Following this, it shall still pass the leak-tightness tests in accordance with 5.2.1 and 5.2.2, and no breakage of any part shall be detected by visual inspection after dismantling of the valve. Testing is not required for check valves greater than DN 300.

## 6 Conformity assessment

### 6.1 General

Requirements shall be in accordance with ISO 9635-1:2006, 6.1.

### 6.2 Type tests

Requirements shall be in accordance with ISO 9635-1:2006, 6.2. The type tests to be performed shall be those according to Table 2. They shall be carried out with the valve in the horizontal position, or in the position indicated by the manufacturer, depending on the possibilities of use of the check valve.

### 6.3 Control of production process and quality system

Requirements shall be in accordance with ISO 9635-1:2006, 6.3.

NOTE The production control tests given in Table 2 are for information only.

Table 2 — Requirements and testing

Subclause of ISO 9635-1:2006	Corresponding requirement	Type tests <sup>a</sup>	Production tests (informative)
4.1	Materials	See drawings and part lists	—
4.2	DN	See drawings	—
4.3	Pressures	See technical documentation	—
4.4	Temperatures	See materials	—
4.5	Design of shell obturator	See test report or calculation report	—
4.6	End types and interchangeability	See drawings and marking	—
4.7	Operating direction	See drawings	—
4.8	Maximum water velocity	See Clause 4	—
4.9	All materials, including lubricants, in contact with water intended for human consumption	See test reports in accordance with national regulations	—
4.10	Internal corrosion and ageing resistance	See drawings, part lists and technical documentation	Visual inspection of coatings
4.11	External corrosion and ageing resistance	See drawings, part lists and technical documentation	Visual inspection of coatings
5.1.1	Resistance of shell and of all pressure-containing components to internal pressure	See 5.1.1	See 5.1.1
5.1.2	Resistance of obturator to differential pressure	See 5.1.2	—
5.1.3	Resistance of valves to bending	See 5.1.3	—
5.2.1.1	Leak-tightness to internal pressure	See 5.2.1.1	See 5.2.1.1
5.2.1.2	Leak-tightness to external pressure	See 5.2.1.2	—
5.2.2.1	Seat tightness at high differential pressure	See 5.2.2.1	See 5.2.2.1
5.2.2.2	Seat tightness at low differential pressure	See 5.2.2.2	—
5.3	Hydraulic or airflow characteristics	See 5.3	—
5.4	Resistance to chemicals and fertilizers	See 5.4	—
5.5	Endurance	See 5.5	—

<sup>a</sup> References to subclauses in this column are to this part of ISO 9635.

## 7 Marking

Requirements shall be in accordance with ISO 9635-1:2006, Clause 7. In addition, the direction of flow shall be marked.

## 8 Packaging

Requirements shall be in accordance with ISO 9635-1:2006, Clause 8.