
INTERNATIONAL STANDARD



990

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION · МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ · ORGANISATION INTERNATIONALE DE NORMALISATION

Potassium hydroxide for industrial use — Method of assay

First edition — 1973-04-15

STANDARDSISO.COM : Click to view the full PDF of ISO 990:1973

UDC 661.312.1 : 543.241

Ref. No. ISO 990-1973 (E)

Descriptors : potassium hydroxide, chemical analysis, determination of content, alkalinity, volumetric analysis.

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 990 was drawn up by Technical Committee ISO/TC 47, *Chemistry*, and circulated to the Member Bodies in September 1971.

It has been approved by the Member Bodies of the following countries:

Austria	India	South Africa, Rep. of
Belgium	Ireland	Spain
Chile	Israel	Sweden
Czechoslovakia	Italy	Switzerland
Egypt, Arab Rep. of	Netherlands	Thailand
France	New Zealand	United Kingdom
Germany	Poland	U.S.S.R.
Hungary	Romania	

No Member Body expressed disapproval of the document.

This International Standard ~~cancels~~ and replaces ISO Recommendation R 990-1969.

Potassium hydroxide for industrial use – Method of assay

1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies a method of assay of potassium hydroxide for industrial use. This assay can be expressed conventionally as a percentage by mass of KOH in three different ways :

A – Total alkalinity (KOH equiv.);

B – Caustic alkalinity (KOH c.) corresponding to the total alkalinity less the alkalinity due to carbonates;

C – Actual potassium hydroxide (KOH) corresponding to the total alkalinity less the alkalinity due to carbonates and any sodium hydroxide which may be present.

2 REFERENCES

ISO/R 991, *Potassium hydroxide for industrial use – Determination of carbon dioxide content, expressed as potassium carbonate – Gas-volumetric method.*

ISO 1550, *Potassium hydroxide for industrial use – Determination of sodium content – Flame emission spectrophotometric method.*

ISO 2466, *Potassium hydroxide for industrial use – Sampling – Test sample – Preparation of the main solution for carrying out certain determinations.*

3 PRINCIPLE

Titration of the total alkalinity with standard volumetric hydrochloric acid solution in the presence of methyl orange as indicator. Calculation of the three amounts, A, B and C defined in section 1.

4 REAGENTS

Distilled water, or water of equivalent purity, shall be used in the test.

4.1 Hydrochloric acid, N standard volumetric solution.

4.2 Methyl orange, 0,5 g/l solution.

5 APPARATUS

Ordinary laboratory apparatus and

5.1 Pipette, 50 ml, accurate to $\pm 0,05$ ml. (See ISO/R 648, *One-mark pipettes*, class A.)

5.2 Burette, 50 ml, class A (see ISO/R 385), with tapered point permitting a delivery of 30 drops per millilitre.

6 PROCEDURE

6.1 Test portion

Transfer 50,0 ml of the main solution A¹⁾, by means of the pipette (5.1), to a 500 ml conical flask.

6.2 Titration

Add to the conical flask containing the test portion (6.1), about 50 ml of water, 5 drops of the methyl orange solution (4.2) and titrate with the standard volumetric hydrochloric acid solution (4.1) contained in the burette (5.2) until the colour changes from yellow to orange.

7 EXPRESSION OF RESULTS

7.1 Total alkalinity (KOH equiv.)

The total alkalinity (A), expressed as potassium hydroxide (KOH), is given, as a percentage by mass, by the formula

$$A = V \times \frac{1\,000}{50} \times \frac{100}{m} \times 0,056\,11 = 112,22 \frac{V}{m}$$

where

V is the volume, in millilitres, of the standard volumetric hydrochloric acid solution (4.1) used for the titration;

m is the mass, in grams, of the test portion used for the preparation of the main solution A.¹⁾

The result should be expressed to one place of decimals.

1) See 4.3 of ISO 2466.