

First edition
1996-05-15

AMENDMENT 2
1997-12-15

**Information technology — Generic coding
of moving pictures and associated audio
information: Video**

AMENDMENT 2: 4:2:2 Profile

*Technologies de l'information — Codage générique des images animées et
des informations sonores associées: Vidéo*

AMENDEMENT 2: Profil 4:2:2

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Amendment 2 to International Standard ISO/IEC 13818-2:1996 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*, in collaboration with ITU-T. The identical text is published as ITU-T Rec. H.262/Amd.2.

© ISO/IEC 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

**INFORMATION TECHNOLOGY – GENERIC CODING OF MOVING PICTURES
AND ASSOCIATED AUDIO INFORMATION: VIDEO**

**AMENDMENT 2
4:2:2 Profile**

1) Clause 8

Replace Table 8-4 by:

Table 8-4 – Escape profile_and_level_indication identification

profile_and_level_indication	Name
10000110 to 11111111	(Reserved)
10000101	4:2:2 profile @ Main level
10000000 to 10000100	(Reserved)

Add the following text as a Note after Table 8-4:

NOTE – On 4:2:2 Profile: The ITU-T Rec. H.262 | ISO/IEC 13818-2 compression algorithm exploits temporal redundancy, spatial redundancy, and human psycho-visual properties and is not a lossless algorithm. For sequences with substantial spatial and temporal redundancies, or without many sharp lines/edges, the quality of the sequences obtained after decompression will be higher than that obtained for sequences with lower redundancy, or with a large number of sharp lines/edges.

The 4:2:2 profile can provide higher video quality, better chroma resolution and allows a higher bit rate (at Main level, up to 50 Mbit/s) than MP@ML. It also provides the capability to encode all active lines of video.

Although it is not part of the hierarchy of profiles and levels, the 4:2:2 profile @ Main level decoder is required to decode all the bit streams decodable by MP@ML decoders.

The 4:2:2 profile does not support scalability. This allows implementation architectures to be similar to those of MP@ML.

This profile can be used for applications requiring multiple generations of encoding and decoding. In the case of multiple generations without picture manipulation or change in picture coding type between generations, the quality remains nearly constant after the first generation. Use of picture manipulation or change in picture coding type between generations causes some degradation in quality. Nevertheless, the resulting quality is acceptable for a broad range of applications.

The 4:2:2 profile permits all I-picture encoding. This enables fast recovery from transmission errors and can simplify editing applications. This profile allows the high bit rates required to maintain high quality while using only I-picture coding. The 4:2:2 profile also allows the use of P- and B-picture coding types which can further improve quality or reduce bit rate for the same quality.

See Annex J for more information on the picture quality of the 4:2:2 profile.

2) Subclause 8.2

Replace Table 8-5 by:

Table 8-5 – Syntactic constraints of profiles

Syntactic Element	Profile					
	Simple	Main	SNR	Spatial	High	4:2:2
chroma_format	4:2:0	4:2:0	4:2:0	4:2:0	4:2:2 or 4:2:0	4:2:2 or 4:2:0
frame_rate_extension_n	0	0	0	0	0	0
frame_rate_extension_d	0	0	0	0	0	0
aspect_ratio_information	0001, 0010, 0011	0001, 0010, 0011	0001, 0010, 0011	0001, 0010, 0011	0001, 0010, 0011	0001, 0010, 0011
picture_coding_type	I, P	I, P, B				
repeat_first_field	Constrained			Unconstrained		Constrained
sequence_scalable_extension()	No	No	Yes	Yes	Yes	No
scalable_mode	–	–	SNR	SNR or Spatial	SNR or Spatial	–
picture_spatial_scalable_extension()	No	No	No	Yes	Yes	No
intra_dc_precision	8, 9, 10	8, 9, 10	8, 9, 10	8, 9, 10	8, 9, 10, 11	8, 9, 10, 11
Slice structure	Restricted 6.1.2.2					

Replace Table 8-6 by:

Table 8-6 – Maximum number of bits in a macroblock

chroma_format	Maximum number of bits
4:2:0	4608
4:2:2	6144
4:2:2 (in 4:2:2 Profile)	Unconstrained
4:4:4	9216

3) Subclause 8.2.1

After the following bullet in 8.2.1:

- if vertical_size > 480 lines frame_rate shall be “25Hz”

add the following text:

Additionally, the following constraints exist for 4:2:2 profile @ Main level only:

- if vertical_size > 512 lines,
then if picture_coding_type=011 (i.e. B-picture), repeat_first_field shall be 0;
- if vertical_size > 512 lines frame_rate shall be “25Hz”.

4) Subclause 8.5

Replace Table 8-11 by:

Table 8-11 – Upper bounds for sampling density

Level	Spatial resolution layer		Profile					
			Simple	Main	SNR	Spatial	High	4:2:2
High	Enhancement	Samples/line Lines/frame Frames/sec		1920 1152 60			1920 1152 60	
	Lower	Samples/line Lines/frame Frames/sec		–			960 576 30	
High-1440	Enhancement	Samples/line Lines/frame Frames/sec		1440 1152 60			1440 1152 60	
	Lower	Samples/line Lines/frame Frames/sec		–			720 576 30	
Main	Enhancement	Samples/line Lines/frame Frames/sec	720 576 30	720 576 30	720 576 30		720 576 30	720 608 ^{a)} 30
	Lower	Samples/line Lines/frame Frames/sec		–	–		352 288 30	–
Low	Enhancement	Samples/line Lines/frame Frames/sec		352 288 30	352 288 30			
	Lower	Samples/line Lines/frame Frames/sec		–	–			

^{a)} 512 lines/frame for 525/60, 608 lines/frame for 625/50
 NOTE – In the case of single layer or SNR scaled coding, the limits specified by “Enhancement layer” apply.

Replace Table 8-12 by:

Table 8-12 – Upper bounds for luminance sample rate (samples/sec)

Level	Spatial resolution layer	Profile					
		Simple	Main	SNR	Spatial	High	4:2:2
High	Enhancement		62 668 800			62 668 800 (4:2:2) 83 558 400 (4:2:0)	
	Lower		–			14 745 600 (4:2:2) 19 660 800 (4:2:0)	
High-1440	Enhancement		47 001 600		47 001 600	47 001 600 (4:2:2) 62 668 800 (4:2:0)	
	Lower		–		10 368 000	11 059 200 (4:2:2) 14 745 600 (4:2:0)	
Main	Enhancement	10 368 000	10 368 000	10 368 000		11 059 200 (4:2:2) 14 745 600 (4:2:0)	11 059 200
	Lower	–	–	–		– 3 041 280 (4:2:0)	–
Low	Enhancement		3 041 280	3 041 280			
	Lower		–	–			

NOTE – In the case of single layer or SNR scaled coding, the limits specified by “Enhancement layer” apply.

Replace Table 8-13 by:

Table 8-13 – Upper bounds for bit rates (Mbit/s)

Level	Profile					
	Simple	Main	SNR	Spatial	High	4:2:2
High		80			100 all layers 80 middle + base layer 25 base layer	
High-1440		60		60 all layers 40 middle + base layers 15 base layer	80 all layers 60 middle + base layers 20 base layer	
Main	15	15	– 15 both layers 10 base layer		20 all layers 15 middle + base layer 4 base layer	50
Low		4	– 4 both layers 3 base layer			

Replace Table 8-14 by:

Table 8-14 – VBV buffer size requirements (bits)

Level	Layer	Profile					
		Simple	Main	SNR	Spatial	High	4:2:2
High	Enhancement 2 Enhancement 1 Base		9 781 248			12 222 464 9 781 248 3 047 424	
High-1440	Enhancement 2 Enhancement 1 Base		7 340 032			7 340 032 4 882 432 1 835 008	
Main	Enhancement 2 Enhancement 1 Base	1 835 008	1 835 008	– 1 835 008 1 212 416		2 441 216 1 835 008 475 136	9 437 184
Low	Enhancement 2 Enhancement 1 Base		475 136	– 475 136 360 448			

Replace Table 8-15 by:

Table 8-15 – Forward compatibility between different profiles and levels

Profile and Level indication in bitstream	Decoder											
	HP@HL	HP@H-14	HP@ML	Spatial@H-14	SNR@ML	SNR@LL	MP@HL	MP@H-14	MP@ML	MP@LL	SP@ML	4:2:2@ML
HP@HL	X											
HP@H-14	X	X										
HP@ML	X	X	X									
Spatial@H-14	X	X		X								
SNR@ML	X	X	X	X	X							
SNR@LL	X	X	X	X	X	X						
MP@HL	X						X					
MP@H-14	X	X		X			X	X				
MP@ML	X	X	X	X	X		X	X	X			X ^{b)}
MP@LL	X	X	X	X	X	X	X	X	X	X	X ^{a)}	X ^{b)}
SP@ML	X	X	X	X	X		X	X	X		X	X ^{b)}
ISO/IEC 11172	X	X	X	X	X	X	X	X	X	X	X	X ^{b)}
4:2:2@ML												X

X Indicates that the decoder shall be able to decode the bit stream including all relevant lower layers.

a) SP@ML decoders are required to decode MP@LL bitstreams.

b) A 4:2:2 profile@Main level decoder shall be able to decode Main profile@Main level, Main profile@Low level and Simple profile@Main level bit streams, as well as ISO/IEC 11172-2 constrained system parameter bit streams.

5) Annex E

Replace Table E.2 by:

Table E.2 – Sequence header

#	Status							Type	Comments
	4:2:2								
	HIGH								
	SPATIAL								
	SNR								
	MAIN								
	SIMPLE								
#	Syntactic elements								
01	horizontal_size_value	x	x	x	x	x	x	D	Table 8-11
02	vertical_size_value	x	x	x	x	x	x	D	Table 8-11
03	aspect_ratio_information	x	x	x	x	x	x	P	
04	frame_rate_code	x	x	x	x	x	x	D	Table 8-11
05	(pel rate) NOTE – This is not a syntactic element.							D	Table 8-12; pel rate is a product of pels/line, lines/frame and frames/sec
06	bit_rate_value	x	x	x	x	x	x	D	Table 8-13
07	vbv_buffer_size_value	x	x	x	x	x	x	D	Table 8-14
08	constrained_parameters_flag	x	x	x	x	x	x	I	Set to "1" if ISO/IEC 11172-2 constrained, Set to "0" if ITU-T Rec. H.262 ISO/IEC 13818-2
09	load_intra_quantiser_matrix	x	x	x	x	x	x	I	
10	intra_quantiser_matrix[64]	x	x	x	x	x	x	I	
11	load_non_intra_quantiser_matrix	x	x	x	x	x	x	I	
12	non_intra_quantiser_matrix[64]	x	x	x	x	x	x	I	
13	sequence_extension()	x	x	x	x	x	x	I	Always present if ITU-T Rec. H.262 ISO/IEC 13818-2
14	sequence_display_extension()	x	x	x	x	x	x	P	
15	sequence_scalable_extension()	o	o	x	x	x	o	I	Table 8-9 for maximum number of scalable layers
16	user_data()	x	x	x	x	x	x	I	Decoder may skip this data

Replace Table E.3 by:

Table E.3 – Sequence extension

#	Syntactic elements	Status						Type	Comments
		4:2:2							
		SIMPLE				MAIN			
		SNR		SPATIAL		HIGH			
01	profile_and_level_indication	x	x	x	x	x	x	D	Profile: one of 8 values Level: one of 16 values Escape bit: one of 2 values
02	progressive_sequence	x	x	x	x	x	x	I	
03	chroma_format	x	x	x	x	x	x	I	Table 8-5
04	horizontal_size_extension	x	x	x	x	x	x	D	Input picture size related
05	vertical_size_extension	x	x	x	x	x	x	D	Input picture size related
06	bit_rate_extension	x	x	x	x	x	x	D	Input picture size related
07	vbv_buffer_size_extension	x	x	x	x	x	x	D	Input picture size related
08	low_delay	x	x	x	x	x	x	I	
09	frame_rate_extension_n	x	x	x	x	x	x	I	Set to "0" for all defined profiles
10	frame_rate_extension_d	x	x	x	x	x	x	I	Set to "0" for all defined profiles

Replace Table E.4 by:

Table E.4 – Sequence display extension elements

#	Syntactic elements	Status						Type	Comments
		4:2:2							
		SIMPLE				MAIN			
		SNR		SPATIAL		HIGH			
01	video_format	x	x	x	x	x	x	P	
02	colour_description	x	x	x	x	x	x	P	Input format related
03	colour primaries	x	x	x	x	x	x	P	
04	transfer_characteristics	x	x	x	x	x	x	P	
05	matrix_coefficients	x	x	x	x	x	x	P	
06	display_horizontal_size	x	x	x	x	x	x	P	Input format related
07	display_vertical_size	x	x	x	x	x	x	P	Input format related

Replace Table E.5 by:

Table E.5 – Sequence scalable extension

#	Status							Type	
	Syntactic elements	SIMPLE	MAIN	SNR	SPATIAL	HIGH	4:2:2		Comments
01	scalable_mode	o	o	x	x	x	o	I	SNR Profile: SNR Scalability Spatial and High Profile: SNR or Spatial Scalability
02	layer_id	o	o	x	x	x	o	I	
	if (spatial scalable)								
03	lower_layer_prediction_horizontal_size	o	o	o	x	x	o	D	Table 8-12 for luminance sampling density
04	lower_layer_prediction_vertical_size	o	o	o	x	x	o	D	Table 8-12 for luminance sampling density
05	horizontal_subsampling_factor_m	o	o	o	x	x	o	I	
06	horizontal_subsampling_factor_n	o	o	o	x	x	o	I	
07	vertical_subsampling_factor_m	o	o	o	x	x	o	I	
08	vertical_subsampling_factor_n	o	o	o	x	x	o	I	
	if (temporal scalable)								
09	picture_mux_enable	o	o	o	o	o	o	I	
10	mux_to_progressive_sequence	o	o	o	o	o	o	I	
11	picture_mux_order	o	o	o	o	o	o	I	
12	picture_mux_factor	o	o	o	o	o	o	I	

STANDARDSISO.COM: Click to view the full PDF of ISO/IEC 13818-2/Amd2:1997

Replace Table E.6 by:

Table E.6 – Group of pictures header

#	Status							Type	
	Syntactic elements	SIMPLE	MAIN	SNR	SPATIAL	4:2:2	HIGH		Comments
01	time_code	x	x	x	x	x	x	I	Decoder may skip this data
02	closed_gop	x	x	x	x	x	x	I	
03	broken_link	x	x	x	x	x	x	I	

STANDARDSISO.COM: Click to view the full PDF of ISO/IEC 13818-2:1995/Amd.2:1997

Replace Table E.7 by:

Table E.7 – Picture header

#	Syntactic elements	Status						Type	
		4:2:2	HIGH	SPATIAL	SNR	MAIN	SIMPLE	Comments	
01	temporal_reference	x	x	x	x	x	x	I	
02	picture_coding_type	x	x	x	x	x	x	I	Simple Profile: I, P at Main level. I, P, B at Low level Main, SNR, Spatial and High Profile: I, P, B
03	vbv_delay	x	x	x	x	x	x	I	
04	full_pel_forward_vector	x	x	x	x	x	x	I	Set to "0" for ITU-T Rec. H.262 ISO/IEC 13818-2
05	forward_f_code	x	x	x	x	x	x	I	Set to "111" for ITU-T Rec. H.262 ISO/IEC 13818-2
06	full_pel_backward_vector	x	x	x	x	x	x	I	Set to "0" for ITU-T Rec. H.262 ISO/IEC 13818-2
07	backward_f_code	x	x	x	x	x	x	I	Set to "111" for ITU-T Rec. H.262 ISO/IEC 13818-2
08	extra_information_picture	x	x	x	x	x	x	I	
09	picture_coding_extension()	x	x	x	x	x	x	I	
10	quant_matrix_extension()	x	x	x	x	x	x	I	
11	picture_display_extension()	x	x	x	x	x	x	P	
12	picture_spatial_scalable_extension()	o	o	o	x	x	o	I	
13	picture_temporal_scalable_extension()	o	o	o	o	o	x	I	

Replace Table E.8 by:

Table E.8 – Picture coding extension

#	Syntactic elements	Status						Type	Comments
		SIMPLE	MAIN	SNR	SPATIAL	HIGH	4:2:2		
01	f_code[0][0] (forward horizontal)	x	x	x	x	x	x	D	Low Level [1:7] Main Level [1:8] High-1440 and High Level [1:9]
02	f_code[0][1] (forward vertical)	x	x	x	x	x	x	D	Low Level [1:4] Main, High-1440 and High Level [1:5]
03	f_code[1][0] (backward horizontal)	x	x	x	x	x	x	D	Low Level [1:7] Main Level [1:8] High-1440 and High Level [1:9]
04	f_code[1][1] (backward vertical)	x	x	x	x	x	x	D	Low level [1:4] Main, H-14 and High Level [1:5]
05	intra_dc_precision	x	x	x	x	x	x	I	Simple, Main, SNR and Spatial Profile: [8:10] High Profile: [8:11] 4:2:2 Profile: [8:11]
06	picture_structure	x	x	x	x	x	x	I	
07	top_field_first	x	x	x	x	x	x	I	
08	frame_pred_frame_dct	x	x	x	x	x	x	I	
09	concealment_motion_vectors	x	x	x	x	x	x	I	
10	q_scale_type	x	x	x	x	x	x	I	
11	intra_vlc_format	x	x	x	x	x	x	I	
12	alternate_scan	x	x	x	x	x	x	I	
13	repeat_first_field	x	x	x	x	x	x	I	
14	chroma_420_type	x	x	x	x	x	x	P	
15	progressive_frame	x	x	x	x	x	x	P	
16	composite_display_flag	x	x	x	x	x	x	P	
17	v_axis	x	x	x	x	x	x	P	
18	field_sequence	x	x	x	x	x	x	P	
19	sub_carrier	x	x	x	x	x	x	P	
20	burst_amplitude	x	x	x	x	x	x	P	
21	sub_carrier_phase	x	x	x	x	x	x	P	

Replace Table E.9 by:

Table E.9 – Quant matrix extension

#	Syntactic elements	Status						Type	Comments
		4:2:2	HIGH	SPATIAL	SNR	MAIN	SIMPLE		
01	load_intra_quantiser_matrix	x	x	x	x	x	x	I	
02	intra_quantiser_matrix[64]	x	x	x	x	x	x	I	
03	load_non_intra_quantiser_matrix	x	x	x	x	x	x	I	
04	non_intra_quantiser_matrix[64]	x	x	x	x	x	x	I	
05	load_chroma_intra_quantiser_matrix	o	o	o	o	x	x	I	
06	chroma_intra_quantiser_matrix[64]	o	o	o	o	x	x	I	
07	load_chroma_non_intra_quantiser_matrix	o	o	o	o	x	x	I	
08	chroma_non_intra_quantiser_matrix[64]	o	o	o	o	x	x	I	

Replace Table E.10 by:

Table E.10 – Picture display extension

#	Syntactic elements	Status						Type	Comments
		4:2:2	HIGH	SPATIAL	SNR	MAIN	SIMPLE		
01	frame_centre_horizontal_offset	x	x	x	x	x	x	P	Input format related
02	frame_centre_vertical_offset	x	x	x	x	x	x	P	Input format related

Replace Table E.11 by:

Table E.11 – Picture temporal scalable extension

#	Status							Type	
	Syntactic elements	SIMPLE	MAIN	SNR	SPATIAL	HIGH	4:2:2		Comments
01	reference_select_code	o	o	o	o	o	o	I	
02	forward_temporal_reference	o	o	o	o	o	o	I	
03	backward_temporal_reference	o	o	o	o	o	o	I	

Replace Table E.12 by:

Table E.12 – Picture spatial scalable extension

#	Status							Type	
	Syntactic elements	SIMPLE	MAIN	SNR	SPATIAL	HIGH	4:2:2		Comments
01	lower_layer_temporal_reference	o	o	o	x	x	o	I	
02	lower_layer_horizontal_offset	o	o	o	x	x	o	D	Input format related
03	lower_layer_vertical_offset	o	o	o	x	x	o	D	Input format related
04	spatial_temporal_weight_code_table_index	o	o	o	x	x	o	I	
05	lower_layer_progressive_frame	o	o	o	x	x	o	I	
06	lower_layer_deinterlaced_field_select	o	o	o	x	x	o	I	

Replace Table E.13 by:

Table E.13 – Slice layer

#	Syntactic elements	Status						Type	Comments
		4:2:2	HIGH	SPATIAL	SNR	MAIN	SIMPLE		
01	slice_vertical_position_extension	x	x	x	x	x	x	D	Input format related
02	priority_breakpoint	o	o	o	o	o	o	I	Only required for data partitioning
03	quantiser_scale_code	x	x	x	x	x	x	I	
04	slice_extension_flag	x	x	x	x	x	x	I	
05	intra_slice	x	x	x	x	x	x	I	Decoder may skip this data
06	slice_picture_id_enable	x	x	x	x	x	x	I	Decoder may skip this data
07	slice_picture_id	x	x	x	x	x	x	I	Decoder may skip this data
08	extra_bit_slice	x	x	x	x	x	x	I	Decoder may skip this data
09	macroblock()	x	x	x	x	x	x	I	

Replace Table E.14 by:

Table E.14 – Macroblock layer

#	Syntactic elements	Status						Type	Comments
		4:2:2	HIGH	SPATIAL	SNR	MAIN	SIMPLE		
01	macroblock_escape	x	x	x	x	x	x	I	
02	macroblock_address_increment	x	x	x	x	x	x	I	
03	macroblock_modes()	x	x	x	x	x	x	I	
04	quantiser_scale_code	x	x	x	x	x	x	I	
05	motion_vectors(0)	x	x	x	x	x	x	I	Forward motion vector
06	motion_vectors(1)	o	x	x	x	x	x	I	Backward motion vector
07	coded_block_pattern()	x	x	x	x	x	x	I	
08	block(i)	x	x	x	x	x	x	I	

Replace Table E.15 by:

Table E.15 – Macroblock modes

#	Syntactic elements	Status						Type	Comments
		4:2:2	HIGH	SPATIAL	SNR	MAIN	SIMPLE		
01	macroblock_type	x	x	x	x	x	x	I	
02	spatial_temporal_weight_code	o	o	o	x	x	o	I	
03	frame_motion_type	x	x	x	x	x	x	I	01: Field-based prediction 10: Frame-based prediction 11: Dual-prime
04	field_motion_type	x	x	x	x	x	x	I	01: Field-based prediction 10: 16 x 8 MC 11: Dual-prime
05	dct_type	x	x	x	x	x	x	I	

Replace Table E.16 by:

Table E.16 – Motion vectors

#	Syntactic elements	Status						Type	Comments
		4:2:2	HIGH	SPATIAL	SNR	MAIN	SIMPLE		
01	motion_vertical_field_select	x	x	x	x	x	x	I	
02	motion_vector()	x	x	x	x	x	x	I	

Replace Table E.17 by:

Table E.17 – Motion vector

#	Syntactic elements	Status						Type	Comments
		4:2:2	HIGH	SPATIAL	SNR	MAIN	SIMPLE		
01	motion_horizontal_code	x	x	x	x	x	x	I	
02	motion_horizontal_r	x	x	x	x	x	x	I	
03	dmv_horizontal	x	x	x	x	x	x	I	
04	motion_vertical_code	x	x	x	x	x	x	I	
05	motion_vertical_r	x	x	x	x	x	x	I	
06	dmv_vertical	x	x	x	x	x	x	I	

Replace Table E.18 by:

Table E.18 – Coded block pattern

#	Syntactic elements	Status						Type	Comments
		4:2:2	HIGH	SPATIAL	SNR	MAIN	SIMPLE		
01	coded_block_pattern_420	x	x	x	x	x	x	I	
02	coded_block_pattern_1	o	o	o	o	x	x	I	4:2:2
03	coded_block_pattern_2	o	o	o	o	o	o	I	4:4:4

Replace Table E.19 by:

Table E.19 – Block layer

#	Status							Type	
	Syntactic elements	SIMPLE	MAIN	SNR	SPATIAL	HIGH	4:2:2		Comments
01	DCT coefficients	x	x	x	x	x	x	I	
02	End of block	x	x	x	x	x	x	I	

Withd@wn
 STANDARDISO.COM: Click to view the full PDF of ISO/IEC 13818-2:1995/Amd2:1997

6) New annex

Add the following Annex J:

Annex J

4:2:2 Profile test results

(This annex does not form an integral part of this Recommendation | International Standard)

J.1 Introduction

This annex provides guidance to users regarding the applicability of the 4:2:2 Profile at Main Level to applications which may require:

- higher quality than Main Profile at Main Level;
- better chroma resolution than Main Profile at Main Level;
- post processing after compression and decompression;
- multiple generations of compression and decompression;
- short Group of Pictures (GOP) for editability;
- capability to pass all active video;
- capability to pass vertical blanking interval information.

It should be noted that application of this Profile is an area of ongoing progress. Results presented here reflect varying degrees of algorithm refinement, so further improvement can be expected.

J.1.1 Test sequences

The test sequences were generated using computer simulation of the ITU-T Rec. H.262 | ISO/IEC 13818-2 compression and decompression. For 525/60, the test material included:

- Gwen;
- Trailblazers;
- Mobile and Calendar;
- Dissolve.

For 625/50, the test material included:

- Balls of Wool;
- Cactus and Comb;
- Basketball;
- Wall;
- Renata and Butterfly;
- Mobile and Calendar.

“Gwen” is a chroma key test sequence with a woman in the foreground keyed over a forest scene in the background. “Gwen” is a difficult sequence to chroma key but an easy sequence to compress. Both “Cactus and Comb” and “Balls of Wool” are chroma key sequences which were used with a coloured background. “Trailblazers” is a rapid motion basketball sequence shot with an unshuttered CCD camera. “Basketball” is also a rapid motion sports sequence. Both are typical program material and moderately difficult to compress. “Wall” consists of a woman standing in front of a wall made of many small stones. “Renata” consists of a woman in front of a complex background with a dissolve to a

complex image of butterflies. “Mobile and Calendar” is a particularly difficult compression test sequence with saturated colours and complex motion. “Dissolve” consists of two segments of “Mobile and Calendar” with a one second fade between the two segments and is also difficult to compress.

Test sequences were supplied by:

- ITU-R;
- Portland Trailblazers;
- SMPTE;
- Tektronix.

J.1.2 Test procedures

MPEG has conducted experiments to verify the performance of the 4:2:2 Profile. The results of those experiments are presented here. There are separate tests for 525/60 and 625/50. The 525/60 tests explore a broad range of data rates and GOP structures, while the 625/50 tests include more variety of test material but less combinations of data rate, GOP structure, and number of generations. The parameters chosen for the experiments are for example only, and do not cover the entire range of allowed parameter values. The examples are not intended as specific recommendations. Each application should use the combination of parameters that is most appropriate, depending on its requirements for quality, editability, and cost.

The tests include both a single generation and eight generations of cascaded compression and decompression. For the eight generation tests, separate tests were done with no shifts, with two spatial shifts, and with two temporal shifts. Spatial shifting means that the picture was shifted horizontally and vertically by two pixels and two spatial lines between the first and second generations and then back between the fifth and sixth generations. Spatial shifting represents the effects of picture repositioning which might occur in a DVE. Temporal shifting means that the GOP structure was shifted one frame between the first and second generations and again between the fifth and sixth generations. Temporal shifting represents the effect of multiple generations which have different GOP alignment.

Chroma key experiments were done by processing the foreground with blue screen through compression and decompression. After decompression the component digital signal was chroma keyed to add the background. The background image was not compressed.

Mixed environment tests for 525/60 used ITU-T Rec. H.262 | ISO/IEC 13818-2 4:2:2 compression and decompression cascaded with a compressed digital VTR using 2:1 intra-field compression. The tests used a total of eight generations of compression. The four odd number generations were MPEG and the four even number generations were compressed digital VTR. There were no shifts between generations.

Mixed environment tests for 625/50 used only MPEG compression. The tests used a total of three generations of compression. The first and third generations were ITU-T Rec. H.262 | ISO/IEC 13818-2 4:2:2 compression with IBBP-GOP structure at 20 Mbits/s, while the second generation was ITU-T Rec. H.262 | ISO/IEC 13818-2 4:2:2 compression with I-only GOP structure at 50 Mbits/s. A temporal shift of one frame was included between the second and third generations.

Compression and decompression processing were contributed by:

- CCETT;
- FTZ;
- IRT;
- JVC;
- Sony;
- Technical University of Braunschweig/BTS;
- Tektronix.

Editing and duplication of test tapes were contributed by:

- RAI;
- Tektronix.

J.1.3 Subjective assessment

The subjective assessment used the DSCQS method described in ITU-R Rec. BT.500-6. Both expert and non-expert viewing sessions were conducted at a number of sites around the world. All of the expert viewing results were combined, and all of the non-expert viewing results were combined. Both expert and non-expert results are presented here. Only subjective test results are presented, as signal to noise ratio is not regarded as a reliable measure of picture quality in these cases.

Expert subjective assessment viewing sessions were conducted by:

- NHK;
- SMPTE.

Non-expert subjective assessment viewing sessions were conducted by:

- CCETT;
- JVC/MPT/NHK/NTV;
- RAI;
- Technical University of Braunschweig/BTS.

J.1.4 Test results

Test results are presented in the following order (see Tables J.1 and J.2):

- 525/60 Homogeneous Environment;
- 525/60 Non-Homogeneous Environment;
- 625/50 Homogeneous Environment;
- 625/50 Non-Homogeneous Environment.

The tables of test results are organized with higher data rates presented first and lower data rates presented last. Within a given bit rate, results are organized by GOP structure, number of generations, and type of shifting. The mean and confidence interval are given for each test sequence.

These tests used the continuous quality scale specified in ITU-R Rec. BT.500-6. The subjective assessments were done on a continuous 0 to 100 scale. The mean differences between original and compressed sequence ratings were calculated, on a 0 to 100 scale, with differences inferior or equal to 0 representing no degradation through compression and 100 being the worst possible rating.

Hereinafter the average of the differences between original and compressed sequence ratings, calculated over the subjects, will be referred to as diff-grade.

The results presented here are based on the following quality definitions:

- **transparency**: diff-grade for all test sequences does not exceed 12% of the scale;
- **near transparency**: the diff-grade of the 25% of the test sequences is between 12% and 18%, while all the other diff-grades do not exceed 12% of the scale;
- **good quality in most of the material**: the mean diff-grades calculated over the test sequences do not exceed 18%, while the diff-grades of 25% of the test sequences exceed 18% of the scale;
- **difficulties in some materials**: all other cases.