
**Identification cards — Contactless
integrated circuit cards — Proximity
cards —**

**Part 4:
Transmission protocol**

AMENDMENT 2: Bit rates of $fc/8$, $fc/4$ and $fc/2$, protocol activation of PICC Type A and frame size from 512 bytes to 4 096 bytes

*Cartes d'identification — Cartes à circuit(s) intégré(s) sans contact —
Cartes de proximité —*

Partie 4: Protocole de transmission

*AMENDEMENT 2: Débits binaires de $fc/8$, $fc/4$ et $fc/2$, activation de
protocole de la PICC type A et taille de trame comprise entre 512 octets
et 4 096 octets*



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 2 to ISO/IEC 14443-4:2008 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Cards and personal identification*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 14443-4:2008/Amd.2:2012(E)

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 14443-4:2008/Amd 2:2012

Identification cards — Contactless integrated circuit cards — Proximity cards —

Part 4: Transmission protocol

AMENDMENT 2: Bit rates of $fc/8$, $fc/4$ and $fc/2$, protocol activation of PICC Type A and frame size from 512 bytes to 4 096 bytes

Page 4, Clause 5

Replace the second, third and fourth dashes with the following:

“

- The SAK byte shall be checked to get information if the PICC is compliant with ISO/IEC 14443-4. The SAK byte is defined in ISO/IEC 14443-3.
- The PICC may be set to HALT state, using the HALTA command as defined in ISO/IEC 14443-3, if e.g. no ISO/IEC 14443-4 protocol is used at PCD.

NOTE The PCD cannot continue the activation sequence in that case.


- If the PICC is compliant to ISO/IEC 14443-4, the RATS may be sent by the PCD as next command after receiving the SAK.

”

Page 5, Figure 1

Replace Figure 1 with the following figure:

“



”

Page 6, 5.1

Replace the second dash of 5.1 with the following:

“

- A PCD setting FSDI = 'D'-'F' is not compliant with this standard. Until the RFU values 'D' - 'F' are assigned by ISO/IEC, a PICC receiving value of FSDI = 'D' - 'F' should interpret it as FSDI = 'C' (FSD = 4096 bytes).

NOTE This PCD recommendation is added for PCD's compatibility with future PICCs when ISO/IEC defines the behavior for the RFU values of 'D' - 'F'.

”

Replace Table 1 with the following:

“

Table 1 — FSDI to FSD conversion

FSDI	'0'	'1'	'2'	'3'	'4'	'5'	'6'	'7'	'8'	'9'	'A'	'B'	'C'	'D' - 'F'
FSD (bytes)	16	24	32	40	48	64	96	128	256	512	1024	2048	4096	RFU

”

Page 8, 5.2.3

Replace the fourth dash with the following:

“

- A PICC setting FSCI = 'D'-'F' is not compliant with this standard. Until the RFU values 'D'-'F' are assigned by ISO/IEC, a PCD receiving value of FSCI = 'D' - 'F' should interpret it as FSCI = 'C' (FSC = 4096 bytes).

NOTE This PICC recommendation is added for PICC's compatibility with future PCDs when ISO/IEC defines the behavior for the RFU values of 'D' - 'F'.

”

Page 24, after 8.2

Add a new Clause 9 as follows:

9 Activation of bit rates and framing options in the PROTOCOL state

S(PARAMETERS) blocks shall be used to negotiate bit rates and communication parameters when the PICC is in PROTOCOL state.

- The information field shall contain tags and values as defined in Tables 4 and 5 and Figures 23 and 24.

The following rules shall be applied to negotiate those parameters:

- The PCD shall send an S(PARAMETERS) block to request parameters.
- If the PICC supports S(PARAMETERS) blocks, the PICC shall respond with an S(PARAMETERS) block containing values for all supported parameters. If the PICC does not support S(PARAMETERS) it shall stay mute.

After the PICC has sent its response and has indicated its parameters the PCD may activate one bit rate for each communication direction with following rules:

- The PCD shall send an S(PARAMETERS) block to activate selected communication parameters.
- The PICC shall acknowledge the activated parameters with an S(PARAMETERS) block and then shall activate the negotiated parameters.
- The PCD shall activate the negotiated parameters.

NOTE 1 S(PARAMETERS) block is defined in ISO/IEC 14443-4:2008/Amd.1:2012.

Table 4 — S(PARAMETERS) tag definition

Tag (Hex)	Description	Length	Value
'A0'	S(PARAMETERS) block information	L	Function Tags Identifier (see Table 5)

NOTE 2 The length field is in accordance with the full range of BER-TLV (see ISO/IEC 7816-4:2005).

Table 5 — Function tags identifier definition

Tag (Hex)	Description	Length (Hex)	Value		
'A1'	Bit rates Request	'0'	—		
'A2'	Bit rates Indication	L	Tag (Hex)	Length (Hex)	Value
			'80'	'02'	supported bit rates from PCD to PICC 1 st byte is specified in Figure 23 2 nd byte set to '00', other values are RFU
			'81'	'02'	supported bit rates from PICC to PCD 1 st byte is specified in Figure 23 2 nd byte set to '00', other values are RFU
			'82'	'01'	supported framing options PICC to PCD (see Figure 24)
'A3'	Bit rates Activation	L	Tag (Hex)	Length (Hex)	Value
			'83'	'02'	selected bit rate from PCD to PICC ^a 1 st byte is specified in Figure 23 2 nd byte set to '00', other values are RFU
			'84'	'02'	selected bit rate from PICC to PCD ^a 1 st byte is specified in Figure 23 2 nd byte set to '00', other values are RFU
			'85'	'01'	selected framing options PICC to PCD (see Figure 24) ^b
'A4'	Bit rates Acknowledgement	'0'	—		
<p>^a The PCD shall set only one bit. The PCD shall not activate simultaneously a bit rate higher than $fc/16$ for PCD to PICC communication and a bit rate of $fc/128$ for PICC to PCD communication in Type A.</p> <p>^b The PCD shall not set both b1 (start bit and stop bit suppression) and b2 (SOF and EOF suppression). When the PCD sets b1 (start bit and stop bit suppression):</p> <ul style="list-style-type: none"> — The PICC shall use a SOF low time of 10 etu and a SOF high time of 2 etu. — The PICC shall use an EOF low time of 10 etu. — The PICC shall apply no character separation. 					

NOTE 3 Only relevant objects should be sent. It is even possible to send an empty parent object with no children objects (i.e. 'A0 00'), although it is also possible to send an empty S(PARAMETERS) block (i.e. not even the parent object sent).