

---

---

**Information technology — Programming  
languages — Fortran —**

**Part 2:  
Varying length character strings**

*Technologies de l'information — Langages de programmation — Fortran —  
Partie 2: Chaînes de caractères de longueur variable*

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 1539-2:2000

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 1539-2:2000

© ISO/IEC 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 734 10 79  
E-mail [copyright@iso.ch](mailto:copyright@iso.ch)  
Web [www.iso.ch](http://www.iso.ch)

Printed in Switzerland

# CONTENTS

1	Scope .....	1
2	Normative References .....	2
3	Requirements .....	3
3.1	The Name of the Module .....	3
3.2	The Type .....	3
3.3	Extended Meanings for Intrinsic Operators .....	3
3.3.1	Assignment .....	3
3.3.2	Concatenation .....	4
3.3.3	Comparisons .....	4
3.4	Extended Meanings for Generic Intrinsic Procedures .....	5
3.4.1	ADJUSTL (string) .....	5
3.4.2	ADJUSTR (string) .....	5
3.4.3	CHAR (string [, length]) .....	5
3.4.4	IACHAR (c) .....	6
3.4.5	ICHAR (c) .....	6
3.4.6	INDEX (string, substring [, back]) .....	6
3.4.7	LEN (string) .....	7
3.4.8	LEN_TRIM (string) .....	7
3.4.9	LGE (string_a, string_b) .....	7
3.4.10	LGT (string_a, string_b) .....	7
3.4.11	LLE (string_a, string_b) .....	8
3.4.12	LLT (string_a, string_b) .....	8
3.4.13	REPEAT (string, ncopies) .....	9
3.4.14	SCAN (string, set [, back]) .....	9
3.4.15	TRIM (string) .....	9
3.4.16	VERIFY (string, set [, back]) .....	10
3.5	Additional Generic Procedure for Type Conversion .....	10
3.5.1	VAR_STR (char) .....	10
3.6	Additional Generic Procedures for Input/Output .....	11
3.6.1	GET (string [, maxlen, iostat]) or GET (unit, string [, maxlen, iostat]) or GET (string, set [, separator, maxlen, iostat]) or GET (unit, string, set [, separator, maxlen, iostat]) .....	11
3.6.2	PUT (string [, iostat]) or PUT (unit, string [, iostat]) .....	12
3.6.3	PUT_LINE (string [, iostat]) or PUT_LINE (unit, string [, iostat]) .....	12
3.7	Additional Generic Procedures for Substring Manipulation .....	12
3.7.1	EXTRACT (string [, start, finish]) .....	13
3.7.2	INSERT (string, start, substring) .....	13
3.7.3	REMOVE (string [, start, finish]) .....	13
3.7.4	REPLACE (string, start, substring) or REPLACE (string, start, finish, substring) or REPLACE (string, target, substring [,every, back]) .....	14

3.7.5 SPLIT (string, word, set [, separator, back]) .....	15
Annex A (informative). Module ISO_VARYING_STRING .....	16
Annex B (informative). Two examples .....	17
B.1 Word count .....	17
B.2 Vocabulary list .....	18

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 1539-2:2000

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO/IEC 1539 may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 1539-2 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 22, *Programming languages, their environments and system software interfaces*.

This second edition cancels and replaces the first edition (ISO/IEC 1539-2:1994), which has been technically revised. The following summarises the changes made to the facilities provided by this part of ISO/IEC 1539:

The assignment, concatenation, and comparison operations are extended to describe elemental semantics.

CHAR is extended to describe pure semantics.

ADJUSTL, ADJUSTR, EXTRACT, IACHAR, ICHAR, INDEX, INSERT, LEN, LEN\_TRIM, LGE, LGT, LLE, LLT, REMOVE, REPEAT, REPLACE, SCAN, SPLIT, TRIM, VAR\_STR, and VERIFY are all extended to describe elemental semantics.

ISO/IEC 1539 consists of the following parts, under the general title *Information technology — Programming languages — Fortran*:

- *Part 1: Base language*
- *Part 2: Varying length character strings*

Annexes A and B of this part of ISO/IEC 1539 are for information only.

## Introduction

This part of ISO/IEC 1539 has been prepared by ISO/IEC JTC1/SC22/WG5, the technical working group for the Fortran language. This part of ISO/IEC 1539 is an auxiliary standard to ISO/IEC 1539-1 : 1997, which defines the latest revision of the Fortran language, and is the first part of the multipart Fortran family of standards; this part of ISO/IEC 1539 is the second part. The revised language defined by ISO/IEC 1539-1 : 1997 is informally known as Fortran 95.

This part of ISO/IEC 1539 defines the interface and semantics for a module that provides facilities for the manipulation of character strings of arbitrary and dynamically variable length. Annex A refers to a possible implementation, in Fortran 95, of a module that conforms to this part of ISO/IEC 1539. It should be noted, however, that this is purely for purposes of demonstrating the feasibility and portability of this standard. The actual code is not intended in any way to prescribe the method of implementation, nor is there any implication that this is in any way an optimal portable implementation. The module is merely a fairly straightforward demonstration that a portable implementation is possible.

This standard is a development from a previous version known as ISO/IEC 1539-2: 1994 that takes account of the improvements introduced in Fortran 95. The most significant improvements in Fortran 95 for the present standard were the introduction of pure and elemental procedures. Since pure and elemental functions can be used in specification expressions, their introduction in this standard enhances the usability of the standard for the end user. The ability to define many of the functions specified in this standard to be elemental improves the compatibility of these functions with similar intrinsic functions defined by the main standard.

The improvements in type initialization provided in Fortran 95 have also enabled the sample implementation referred to in Annex A to be written in such a way that significant leakage of memory is less likely to occur.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 1539-2:2000

# Information technology – Programming languages – Fortran – Part 2: Varying length character strings

## 1 Scope

This part of ISO/IEC 1539 defines facilities in Fortran for the manipulation of character strings of dynamically variable length. This part of ISO/IEC 1539 provides an auxiliary standard for the version of the Fortran language specified by ISO/IEC 1539-1: 1997 and informally known as Fortran 95.

A program that conforms with 1539-2: 1994 also conforms with this standard.

This part of ISO/IEC 1539 is an auxiliary standard to that defining Fortran 95 in that it defines additional facilities to those defined intrinsically in the primary language standard. A processor conforming to the Fortran 95 standard is not required also to conform to this part of ISO/IEC 1539. However, conformance to this part of ISO/IEC 1539 assumes conformance to the primary Fortran 95 standard.

This part of ISO/IEC 1539 prescribes the name of a Fortran module, the name of a derived data type to be used to represent varying-length strings, the interfaces for the procedures and operators to be provided to manipulate objects of this type, and the semantics that are required for each of the entities made accessible by this module.

This part of ISO/IEC 1539 does not prescribe the details of any implementation. Neither the method used to represent the data entities of the defined type nor the algorithms used to implement the procedures or operators whose interfaces are defined by this part of ISO/IEC 1539 are prescribed. A conformant implementation may use any representation and any algorithms, subject only to the requirement that the publicly accessible names and interfaces conform to this part of ISO/IEC 1539, and that the semantics are as required by this part of ISO/IEC 1539 and those of ISO/IEC 1539-1 : 1997.

It should be noted that a processor is not required to implement this part of ISO/IEC 1539 in order to be a standard conforming Fortran processor, but if a processor implements facilities for manipulating varying

length character strings, it is recommended that this be done in a manner that is conformant with this part of ISO/IEC 1539.

A processor conforming to this part of ISO/IEC 1539 may extend the facilities provided for the manipulation of varying length character strings as long as such extensions do not conflict with this part of ISO/IEC 1539 or with ISO/IEC 1539-1 : 1997.

A module, written in standard conforming Fortran, is referenced in Annex A. This module illustrates one way in which the facilities described in this part of ISO/IEC 1539 could be provided. This module is both conformant with the requirements of this part of ISO/IEC 1539 and, because it is written in standard conforming Fortran, it provides a portable implementation of the required facilities. This module is referenced for information only and is not intended to constrain implementations in any way. This module is a demonstration that at least one implementation, in standard conforming and hence portable Fortran, is possible.

It should be noted that this part of ISO/IEC 1539 defines facilities for dynamically varying length strings of characters of default kind only. Throughout this part of ISO/IEC 1539 all references to intrinsic type CHARACTER should be read as meaning characters of default kind. Similar facilities could be defined for non-default kind characters by a separate, if similar, module for each such character kind.

This part of ISO/IEC 1539 has been designed, as far as is reasonable, to provide for varying length character strings the facilities that are available for intrinsic fixed length character strings. All the intrinsic operations and functions that apply to fixed length character strings have extended meanings defined by this part of ISO/IEC 1539 for varying length character strings. Also a small number of additional facilities are defined that are appropriate because of the essential differences between the intrinsic type and the varying length derived data type.

## 2 Normative References

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO/IEC 1539. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO/IEC 1539 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO/IEC 646 : 1991 *Information technology – ISO 7-bit Coded character set for information interchange.*

ISO/IEC 1539-1 : 1997 *Information technology – Programming languages – Fortran – Part 1: Base language.*

## 3 Requirements

### 3.1 The Name of the Module

The name of the module shall be

ISO\_VARYING\_STRING

Programs shall be able to access the facilities defined by this part of ISO/IEC 1539 by the inclusion of USE statements of the form

USE ISO\_VARYING\_STRING

### 3.2 The Type

The type shall have the name

VARYING\_STRING

Entities of this type shall represent values that are strings of characters of default kind. These character strings may be of any non-negative length and this length may vary dynamically during the execution of a program. There shall be no arbitrary upper length limit other than that imposed by the size of the processor and the complexity of the programs it is able to process. The characters representing the value of the string have positions 1,2,...,N, where N is the length of the string. The internal structure of the type shall be PRIVATE to the module.

### 3.3 Extended Meanings for Intrinsic Operators

The meanings for the intrinsic operators of:

*assignment* =

*concatenation* //

*comparisons* ==, /=, <, <=, >=, >

shall be extended to accept any combination of operands of type VARYING\_STRING and type CHARACTER. Note that the equivalent comparison operator forms .EQ., .NE., .LT., .LE., .GE., and .GT. also have their meanings extended in this manner.

#### 3.3.1 Assignment

An elemental assignment of the form

*var* = *expr*

shall be defined with the following type combinations:

VARYING\_STRING and VARYING\_STRING

VARYING\_STRING and CHARACTER

CHARACTER and VARYING\_STRING

**Action.** The characters that are the value of the expression *expr* become the value of the variable *var*. There are two cases:

*Case(i):* Where the variable is of type VARYING\_STRING, the length of the variable becomes that of the

expression.

*Case(ii):* Where the variable is of type CHARACTER, the rules of intrinsic assignment to a Fortran character variable apply. Namely, if the expression string is longer than the declared length of the character variable, only the left-most characters are assigned. If the character variable is longer than that of the string expression, it is padded on the right with blanks.

### 3.3.2 Concatenation

The elemental concatenation operation

```
string_a // string_b
```

shall be defined with the following type combinations:

```
VARYING_STRING and VARYING_STRING
VARYING_STRING and CHARACTER
CHARACTER and VARYING_STRING
```

The values of the operands are unchanged by the operation.

**Result Characteristics.** Of type VARYING\_STRING.

**Result Value.** The result value is a new string whose characters are the same as those produced by concatenating the operand character strings in the order given.

### 3.3.3 Comparisons

Elemental comparisons of the form

```
string_a == string_b
string_a /= string_b
string_a < string_b
string_a <= string_b
string_a > string_b
string_a >= string_b
```

shall be defined for operands with the following type combinations:

```
VARYING_STRING and VARYING_STRING
VARYING_STRING and CHARACTER
CHARACTER and VARYING_STRING
```

The values of the operands are unchanged by the operation. Note that the equivalent operator forms `.EQ.`, `.NE.`, `.LT.`, `.LE.`, `.GE.`, and `.GT.` also have their meanings extended in this manner.

**Result Characteristics.** Of type default LOGICAL.

**Result Value.** The result value is true if `string_a` stands in the indicated relation to `string_b` and is false otherwise. The collating sequence used for the inequality comparisons is that defined by the processor for characters of default kind. If `string_a` and `string_b` are of different lengths, the comparison is done as if the shorter string were padded on the right with blanks.

### 3.4 Extended Meanings for Generic Intrinsic Procedures

The generic intrinsic procedures ADJUSTL, ADJUSTR, CHAR, IACHAR, ICHAR, INDEX, LEN, LEN\_TRIM, LGE, LGT, LLT, LLE, REPEAT, SCAN, TRIM, and VERIFY shall have their meanings extended to include the appropriate argument type combinations involving VARYING\_STRING and CHARACTER. Detailed descriptions of the extensions are given in this section.

#### 3.4.1 ADJUSTL (string)

**Description.** Adjusts to the left, removing any leading blanks and inserting trailing blanks.

**Class.** Elemental function.

**Argument.** *string* shall be of type VARYING\_STRING.

**Result Characteristics.** Of type VARYING\_STRING.

**Result Value.** The result value is the same as *string* except that any leading blanks have been deleted and the same number of trailing blanks inserted.

#### 3.4.2 ADJUSTR (string)

**Description.** Adjusts to the right, removing any trailing blanks and inserting leading blanks.

**Class.** Elemental function.

**Argument.** *string* shall be of type VARYING\_STRING.

**Result Characteristics.** Of type VARYING\_STRING.

**Result Value.** The result value is the same as *string* except that any trailing blanks have been deleted and the same number of leading blanks inserted.

#### 3.4.3 CHAR (string [, length])

**Description.** Converts a varying string value to default CHARACTER.

**Class.** Pure transformational function.

**Arguments.**

*string* shall be scalar and of type VARYING\_STRING.

*length* (optional) shall be scalar and of type default INTEGER.

**Result Characteristics.** Scalar of type default CHARACTER. If *length* is absent, the result has the same length as *string*. If *length* is present, the result has the length specified by the argument *length*.

**Result Value.**

*Case(i):* If *length* is absent, the result is a copy of the characters in the argument *string*.

*Case(ii):* If *length* is present, the result is a copy of the characters in the argument *string* that may have been truncated or padded. If *string* is longer than *length*, the result is truncated on the right. If *string* is shorter than *length*, the result is padded on the right with blanks. If *length* is less than one, the result is of zero length.

**Note.** This function is elemental in Fortran 95, where it has the form CHAR(*i* [, *kind*]), with *i* of type integer.

### 3.4.4 IACHAR (c)

**Description.** Returns the position of a character in the collating sequence defined by the International Standard ISO 646 : 1991.

**Class.** Elemental function.

**Argument.** *c* shall be of type VARYING\_STRING and of length exactly one.

**Result Characteristics.** Of type default INTEGER.

**Result Value.** The result value is the position of the character *c* in the collating sequence defined by the International Standard ISO 646 : 1991 for default characters. If the character *c* is not defined in the standard set, the result is processor dependent but is always equal to IACHAR ( CHAR ( *c* ) ).

### 3.4.5 ICHAR (c)

**Description.** Returns the position of a character in the processor defined collating sequence.

**Class.** Elemental function.

**Argument.** *c* shall be of type VARYING\_STRING and of length exactly one.

**Result Characteristics.** Of type default INTEGER.

**Result Value.** The result value is the position of the character *c* in the processor defined collating sequence for default characters. That is, the result value is ICHAR ( CHAR ( *c* ) ).

### 3.4.6 INDEX (string, substring [, back])

**Description.** Returns an integer that is the starting position of a substring within a string.

**Class.** Elemental function.

**Arguments.**

*string* and *substring* shall be of one of the type combinations:

VARYING\_STRING and VARYING\_STRING  
 VARYING\_STRING and CHARACTER  
 CHARACTER and VARYING\_STRING

*back* (optional) shall be of type default LOGICAL.

**Result Characteristics.** Of type default INTEGER.

**Result Value.**

*Case(i):* If *back* is absent or is present with the value false, the result is the minimum positive value of *I* such that

EXTRACT (*string*, *I*, *I*+LEN (*substring*)-1) == *substring*,

(where EXTRACT is defined in Section 3.7) or zero if there is no such value.

*Case(ii):* If *back* is present with the value true, the result is the maximum value of *I* less than or equal to LEN (*string*)-LEN (*substring*)+1 such that

EXTRACT (*string*, *I*, *I*+LEN (*substring*)-1) == *substring*,

or zero if there is no such value.

### 3.4.7 LEN (string)

**Description.** Returns the length of a character string.

**Class.** Elemental function.

**Argument.** *string* shall be of type VARYING\_STRING.

**Result Characteristics.** Of type default INTEGER.

**Result Value.** The result value is the number of characters in *string*.

**Note.** This function is not elemental for *string* of type CHARACTER.

### 3.4.8 LEN\_TRIM (string)

**Description.** Returns the length of a string not counting any trailing blanks.

**Class.** Elemental function.

**Argument.** *string* shall be of type VARYING\_STRING.

**Result Characteristics.** Of type default INTEGER.

**Result Value.** The result value is the position of the last non-blank character in *string*. If the argument *string* contains only blank characters or is of zero length, the result is zero.

### 3.4.9 LGE (string\_a, string\_b)

**Description.** Compares the lexical ordering of two strings based on the ISO 646 : 1991 collating sequence.

**Class.** Elemental function.

**Arguments.**

*string\_a* and *string\_b* shall be of one of the type combinations:

VARYING\_STRING and VARYING\_STRING

VARYING\_STRING and CHARACTER

CHARACTER and VARYING\_STRING

**Result Characteristics.** Of type default LOGICAL.

**Result Value.** The result value is true if *string\_a* is lexically greater than or equal to *string\_b*, and is false otherwise. The collating sequence used to establish the ordering of characters is that of the International Standard ISO 646 : 1991. If *string\_a* and *string\_b* are of different lengths, the comparison is done as if the shorter string were padded on the right with blanks. If either argument contains a character *c* not defined by the standard, the result value is processor dependent and based on the collating value for IACHAR(*c*). Zero length strings are considered to be lexically equal.

### 3.4.10 LGT (string\_a, string\_b)

**Description.** Compares the lexical ordering of two strings based on the ISO 646 : 1991 collating sequence.

**Class.** Elemental function.

**Arguments.**

*string\_a* and *string\_b* shall be of one of the type combinations:

VARYING\_STRING and VARYING\_STRING  
 VARYING\_STRING and CHARACTER  
 CHARACTER and VARYING\_STRING

**Result Characteristics.** Of type default LOGICAL.

**Result Value.** The result value is true if `string_a` is lexically greater than `string_b`, and is false otherwise. The collating sequence used to establish the ordering of characters is that of the International Standard ISO 646 : 1991. If `string_a` and `string_b` are of different lengths, the comparison is done as if the shorter string were padded on the right with blanks. If either argument contains a character `c` not defined by the standard, the result value is processor dependent and based on the collating value for `IACHAR(c)`. Zero length strings are considered to be lexically equal.

### 3.4.11 LLE (`string_a`, `string_b`)

**Description.** Compares the lexical ordering of two strings based on the ISO 646 : 1991 collating sequence.

**Class.** Elemental function.

**Arguments.**

`string_a` and `string_b` shall be of one of the type combinations:

VARYING\_STRING and VARYING\_STRING  
 VARYING\_STRING and CHARACTER  
 CHARACTER and VARYING\_STRING

**Result Characteristics.** Of type default LOGICAL.

**Result Value.** The result value is true if `string_a` is lexically less than or equal to `string_b`, and is false otherwise. The collating sequence used to establish the ordering of characters is that of the International Standard ISO 646 : 1991. If `string_a` and `string_b` are of different lengths, the comparison is done as if the shorter string were padded on the right with blanks. If either argument contains a character `c` not defined by the standard, the result value is processor dependent and based on the collating value for `IACHAR(c)`. Zero length strings are considered to be lexically equal.

### 3.4.12 LLT (`string_a`, `string_b`)

**Description.** Compares the lexical ordering of two strings based on the ISO 646 : 1991 collating sequence.

**Class.** Elemental function.

**Arguments.**

`string_a` and `string_b` shall be of one of the type combinations:

VARYING\_STRING and VARYING\_STRING  
 VARYING\_STRING and CHARACTER  
 CHARACTER and VARYING\_STRING

**Result Characteristics.** Of type default LOGICAL.

**Result Value.** The result value is true if `string_a` is lexically less than `string_b`, and is false otherwise. The collating sequence used to establish the ordering of characters is that of the International Standard ISO 646 : 1991. If `string_a` and `string_b` are of different lengths, the comparison is done as if the shorter string were padded on the right with blanks. If either argument contains a character `c` not defined by the standard, the result value is processor dependent and based on the collating value for `IACHAR(c)`. Zero

length strings are considered to be lexically equal.

### 3.4.13 REPEAT (string, ncopies)

**Description.** Concatenates several copies of a string.

**Class.** Elemental function.

**Arguments.**

*string* – shall be of type VARYING\_STRING,

*ncopies* – shall be of type default INTEGER.

**Result Characteristics.** Of type VARYING\_STRING.

**Result Value.** The result value is the string produced by repeated concatenation of the argument *string*, producing a string containing *ncopies* copies of *string*. If the value of *ncopies* is not positive, the result is of zero length.

**Note.** This function is not elemental for *string* of type CHARACTER.

### 3.4.14 SCAN (string, set [, back])

**Description.** Scans a string for any one of the characters in a set of characters.

**Class.** Elemental function.

**Arguments.**

*string* and *set* shall be of one of the type combinations:

VARYING\_STRING and VARYING\_STRING  
 VARYING\_STRING and CHARACTER  
 CHARACTER and VARYING\_STRING

*back* (optional) shall be of type default LOGICAL.

**Result Characteristics.** Of type default INTEGER.

**Result Value.**

*Case(i):* If *back* is absent or is present with the value false and if *string* contains at least one character that is in *set*, the value of the result is the position of the left-most character of *string* that is in *set*.

*Case(ii):* If *back* is present with the value true and if *string* contains at least one character that is in *set*, the value of the result is the position of the right-most character of *string* that is in *set*.

*Case(iii):* The value of the result is zero if no character of *string* is in *set* or if the length of either *string* or *set* is zero.

### 3.4.15 TRIM (string)

**Description.** Removes trailing blanks from a string.

**Class.** Elemental function.

**Argument.** *string* shall be of type VARYING\_STRING.

**Result Characteristics.** Of type VARYING\_STRING.

**Result Value.** The result value is the same as `string` except that any trailing blanks have been deleted. If the argument `string` contains only blank characters or is of zero length, the result is a zero-length string.

**Note.** This function is not elemental for `string` of type CHARACTER.

### 3.4.16 VERIFY (`string`, `set` [, `back`])

**Description.** Verifies that a string contains only characters from a given set by scanning for any character not in the set.

**Class.** Elemental function.

**Arguments.**

`string` and `set` shall be of one of the type combinations:

VARYING\_STRING and VARYING\_STRING  
VARYING\_STRING and CHARACTER  
CHARACTER and VARYING\_STRING

`back` (optional) shall be of type default LOGICAL.

**Result Characteristics.** Of type default INTEGER.

**Result Value.**

*Case(i):* If `back` is absent or is present with the value `false` and if `string` contains at least one character that is not in `set`, the value of the result is the position of the left-most character of `string` that is not in `set`.

*Case(ii):* If `back` is present with the value `true` and if `string` contains at least one character that is not in `set`, the value of the result is the position of the right-most character of `string` that is not in `set`.

*Case(iii):* The value of the result is zero if each character of `string` is in `set` or if the length of `string` is zero.

## 3.5 Additional Generic Procedure for Type Conversion

An additional generic procedure shall be added to convert intrinsic fixed-length character values into varying-length string values.

### 3.5.1 VAR\_STR (`char`)

**Description.** Converts an intrinsic fixed-length character value into the equivalent varying-length string value.

**Class.** Elemental function.

**Argument.** `char` shall be of type default CHARACTER and may be of any length.

**Result Characteristics.** Of type VARYING\_STRING.

**Result Value.** The result value is the same string of characters as the argument.

### 3.6 Additional Generic Procedures for Input/Output

The following additional generic procedures shall be provided to support input and output of varying-length string values with formatted sequential files.

GET – input part or all of a record into a string

PUT – append a string to an output record

PUT\_LINE – append a string to an output record and end the record

- 3.6.1 GET (string [, maxlen, iostat]) or  
GET (unit, string [, maxlen, iostat]) or  
GET (string, set [, separator, maxlen, iostat]) or  
GET (unit, string, set [, separator, maxlen, iostat])**

**Description.** Reads characters from an external file into a string.

**Class.** Subroutine.

**Arguments.**

`string` shall be scalar and of type `VARYING_STRING`. It is an `INTENT(OUT)` argument.

`maxlen` (optional) shall be scalar and of type default `INTEGER`. It is an `INTENT(IN)` argument.

`unit` shall be scalar and of type default `INTEGER`. It is an `INTENT(IN)` argument that specifies the input unit to be used. The unit shall be connected to a formatted file for sequential read access. If the argument `unit` is omitted, the default input unit is used.

`set` shall be scalar and either of type `VARYING_STRING` or of type `CHARACTER`. It is an `INTENT(IN)` argument.

`separator` (optional) shall be scalar and of type `VARYING_STRING`. It is an `INTENT(OUT)` argument.

`iostat` (optional) shall be scalar and of type default `INTEGER`. It is an `INTENT(OUT)` argument.

**Action.** The `GET` procedure causes characters from the connected file, starting with the next character in the current record if there is a current record or the first character of the next record if not, to be read and stored in the variable `string`. The end of record always terminates the input but input may be terminated before this. If `maxlen` is present, its value indicates the maximum number of characters that will be read. If `maxlen` is less than or equal to zero, no characters will be read and `string` will be set to zero length. If `maxlen` is absent, a maximum of `HUGE(1)` is used. If the argument `set` is provided, this specifies a set of characters the occurrence of any of which will terminate the input. This terminal character, although read from the input file, will not be included in the result string. The file position after the data transfer is complete, is after the last character that was read. If the argument `separator` is present, the actual character found which terminates the transfer is returned in `separator`. If the transfer is terminated other than by the occurrence of a character in `set`, a zero length string is returned in `separator`. If the transfer is terminated by the end of record being reached, the file is positioned after the record just read. If present, the argument `iostat` is used to return the status resulting from the data transfer. A zero value is returned if a valid read operation occurs and the end-of-record is not reached, a positive value if an error occurs, and a negative value if an end-of-file or end-of-record condition occurs. Note, the negative value returned for an end-of-file condition shall be different from that returned for an end-of-record condition. If `iostat` is absent and an error or end-of-file condition occurs, the program execution is terminated.

**3.6.2 PUT (string [, iostat]) or PUT (unit, string [, iostat])**

**Description.** Writes a string to an external file.

**Class.** Subroutine.

**Arguments.**

`string` shall be scalar and either of type `VARYING_STRING` or type `CHARACTER`. It is an `INTENT(IN)` argument.

`unit` shall be scalar and of type default `INTEGER`. It is an `INTENT(IN)` argument that specifies the output unit to be used. The unit shall be connected to a formatted file for sequential write access. If the argument `unit` is omitted, the default output unit is used.

`iostat` (optional) shall be scalar and of type default `INTEGER`. It is an `INTENT(OUT)` argument.

**Action.** The `PUT` procedure causes the characters of `string` to be appended to the current record, if there is a current record, or to the start of the next record if there is no current record. The last character transferred becomes the last character of the current record, which is the last record of the file. If present, the argument `iostat` is used to return the status resulting from the data transfer. A zero value is returned if a valid write operation occurs, and a positive value if an error occurs. If `iostat` is absent and anything other than a valid write operation occurs, the program execution is terminated.

**3.6.3 PUT\_LINE (string [, iostat]) or PUT\_LINE (unit, string [, iostat])**

**Description.** Writes a string to an external file and ends the record.

**Class.** Subroutine.

**Arguments.**

`string` shall be scalar and either of type `VARYING_STRING` or type `CHARACTER`. It is an `INTENT(IN)` argument.

`unit` shall be scalar and of type default `INTEGER`. It is an `INTENT(IN)` argument that specifies the output unit to be used. The unit shall be connected to a formatted file for sequential write access. If the argument `unit` is omitted, the default output unit is used.

`iostat` (optional) shall be scalar and of type default `INTEGER`. It is an `INTENT(OUT)` argument.

**Action.** The `PUT_LINE` procedure causes the characters of `string` to be appended to the current record, if there is a current record, or to the start of the next record if there is no current record. Following completion of the data transfer, the file is positioned after the record just written, which becomes the previous and last record of the file. If present, the argument `iostat` is used to return the status resulting from the data transfer. A zero value is returned if a valid write operation occurs, and a positive value if an error occurs. If `iostat` is absent and anything other than a valid write operation occurs, the program execution is terminated.

**3.7 Additional Generic Procedures for Substring Manipulation**

The following additional generic procedures shall be provided to support the manipulation of scalar substrings of scalar varying-length strings.

`EXTRACT` – extract a section from a string

`INSERT` – insert a substring into a string

`REMOVE` – remove a section of a string

`REPLACE` – replace a substring in a string

SPLIT – split a string into two at the occurrence of a separator

### 3.7.1 EXTRACT (string [, start, finish])

**Description.** Extracts a specified substring from a string.

**Class.** Elemental function.

**Arguments.**

string shall be either of type VARYING\_STRING or type default CHARACTER

start (optional) shall be of type default INTEGER.

finish (optional) shall be of type default INTEGER.

**Result Characteristics.** Of type VARYING\_STRING.

**Result Value.** The result value is a copy of the characters of the argument string between positions start and finish, inclusive. If start is absent or less than one, the value one is used for start. If finish is absent or greater than LEN(string), the value LEN(string) is used for finish. If finish is less than start, the result is a zero-length string.

### 3.7.2 INSERT (string, start, substring)

**Description.** Inserts a substring into a string at a specified position.

**Class.** Elemental function.

**Arguments.**

string shall be either type VARYING\_STRING or type default CHARACTER.

start shall be type default INTEGER.

substring shall be either type VARYING\_STRING or type default CHARACTER.

**Result Characteristics.** Of type VARYING\_STRING.

**Result Value.** The result value is a copy of the characters of the argument string with the characters of substring inserted into the copy of string before the character at the character position start. If start is greater than LEN(string), the value LEN(string)+1 is used for start and substring is appended to the copy of string. If start is less than one, the value one is used for start and substring is inserted before the first character of the copy of string.

### 3.7.3 REMOVE (string [, start, finish])

**Description.** Removes a specified substring from a string.

**Class.** Elemental function.

**Arguments.**

string shall be either of type VARYING\_STRING or type default CHARACTER

start (optional) shall be of type default INTEGER.

finish (optional) shall be of type default INTEGER.

**Result Characteristics.** Of type VARYING\_STRING.

**Result Value.** The result value is a copy of the characters of string with the characters between positions start and finish, inclusive, removed. If start is absent or less than one, the value one is used for

start. If finish is absent or greater than `LEN(string)`, the value `LEN(string)` is used for finish. If finish is less than start, the characters of `string` are delivered unchanged as the result.

**3.7.4 REPLACE (string, start, substring) or  
REPLACE (string, start, finish, substring) or  
REPLACE (string, target, substring [,every, back])**

**Description.** Replaces a subset of the characters in a string by a given substring. The subset may be specified either by position or by content.

**Class.** Elemental function.

**Arguments.**

`string` shall be either of type `VARYING_STRING` or type default `CHARACTER`.

`start` shall be of type default `INTEGER`.

`finish` shall be of type default `INTEGER`.

`substring` shall be either of type `VARYING_STRING` or type default `CHARACTER`.

`target` shall be either of type `VARYING_STRING` or type default `CHARACTER`. It shall not be of zero length.

`every` (optional) shall be of type default `LOGICAL`.

`back` (optional) shall be of type default `LOGICAL`.

**Result Characteristics.** Of type `VARYING_STRING`.

**Result Value.** The result value is a copy of the characters in `string` modified as per one of the cases below.

*Case(i):* For a reference of the form

`REPLACE(string, start, substring)`

the characters of the argument `substring` are inserted into the copy of `string` beginning with the character at the character position `start`. The characters in positions from `start` to `MIN(start+LEN(substring)-1, LEN(string))` are deleted. If `start` is greater than `LEN(string)`, the value `LEN(string)+1` is used for `start` and `substring` is appended to the copy of `string`. If `start` is less than one, the value one is used for `start`.

*Case(ii):* For a reference of the form

`REPLACE(string, start, finish, substring)`

the characters in the copy of `string` between positions `start` and `finish`, including those at `start` and `finish`, are deleted and replaced by the characters of `substring`. If `start` is less than one, the value one is used for `start`. If `finish` is greater than `LEN(string)`, the value `LEN(string)` is used for `finish`. If `finish` is less than `start`, the characters of `substring` are inserted before the character at `start` and no characters are deleted.

*Case(iii):* For a reference of the form

`REPLACE(string, target, substring, every, back)`

the copy of `string` is searched for occurrences of `target`. The search is done in the backward direction if the argument `back` is present with the value `true`, and in the forward direction otherwise. If `target` is found, it is replaced by `substring`. If `every` is present with the value `true`, the search and

replace is continued from the character following `target` in the search direction specified until all occurrences of `target` in the copy string are replaced; otherwise only the first occurrence of `target` is replaced.

### 3.7.5 SPLIT (`string`, `word`, `set` [, `separator`, `back`])

**Description.** Splits a string into two substrings with the substrings separated by the occurrence of a character from a specified separator set.

**Class.** Elemental subroutine.

#### Arguments.

`string` shall be of type `VARYING_STRING`. It is an `INTENT(INOUT)` argument.

`word` shall be of type `VARYING_STRING`. It is an `INTENT(OUT)` argument.

`set` shall be either of type `VARYING_STRING` or type default `CHARACTER`. It is an `INTENT(IN)` argument.

`separator` (optional) shall be of type `VARYING_STRING`. It is an `INTENT(OUT)` argument.

`back` (optional) shall be of type default `LOGICAL`. It is an `INTENT(IN)` argument.

**Action.** The effect of the procedure is to divide the `string` at the first occurrence of a character that is in `set`. The `string` is searched in the forward direction unless `back` is present with the value `true`, in which case the search is in the backward direction. The characters passed over in the search are returned in the argument `word` and the remainder of the string, not including the separator character, is returned in the argument `string`. If the argument `separator` is present, the actual character found which separates the word from the remainder of the string is returned in `separator`. If no character from `set` is found or `set` is of zero length, the whole string is returned in `word`, `string` is returned as zero length, and `separator` (if present) is returned as zero length. The effect of the procedure is such that, on return, either

`word//separator//string`

is the same as the initial string for a forward search, or

`string//separator//word`

is the same as the initial string for a backward search.

## **Annex A (informative). Module ISO\_VARYING\_STRING**

A sample implementation of the module ISO\_VARYING\_STRING is available from [ftp.nag.co.uk/sc22wg5/ISO\\_VARYING\\_STRING](ftp.nag.co.uk/sc22wg5/ISO_VARYING_STRING) and is written in Fortran 95, conformant with the language as specified in the standard ISO/IEC 1539-1: 1997. It is intended to be a portable implementation of a module conformant with this part of ISO/IEC 1539 family of standards. It is not intended to be prescriptive of how facilities consistent with this part of ISO/IEC 1539 should be provided. This module is intended primarily to demonstrate that portable facilities consistent with the interfaces and semantics required by this part of ISO/IEC 1539 could be provided within the confines of the Fortran language. It is also included as a guide for users of processors which do not have supplier-provided facilities implementing this part of ISO/IEC 1539.

This module uses a derived type with a pointer component. On a processor without automatic garbage collection, it is possible that a program using this module might prematurely run out of memory.

It should be noted that while every care has been taken by the technical working group to ensure that this module is a correct implementation of this part of ISO/IEC 1539 in valid Fortran code, no guarantee is given or implied that this code will produce correct results, or even that it will execute on any particular processor. Neither is there any implication that this illustrative module is in any way an optimal implementation of this standard; it is merely one fairly straightforward portable module that is known to provide a functionally conformant implementation on a few processors.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 1539-2:2000