

---

---

**Information technology —  
JPEG 2000 image coding system:  
Motion JPEG 2000 —**

**AMENDMENT 1: Additional profiles for  
archiving applications**

*Technologies de l'information — Système de codage d'images  
JPEG 2000: Images JPEG 2000 animées —*

*AMENDEMENT 1: Profils additionnels pour réaliser des applications*

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 15444-3:2007/Amd 1:2010

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



**COPYRIGHT PROTECTED DOCUMENT**

© ISO/IEC 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO/IEC 15444-3:2007 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*, in collaboration with ITU-T. The identical text is published as ITU-T Rec. T.802 (01/2005) Amd.1.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 15444-3:2007/Amd 1:2010

INTERNATIONAL STANDARD  
RECOMMENDATION ITU-T

## Information technology – JPEG 2000 image coding system: Motion JPEG 2000

## Amendment 1

## Additional profiles for archiving applications

## 1) Clause 2 – Normative references

Add the following items to the list of the normative references:

- ISO/IEC 14496-3:2009, *Information technology – Coding of audio-visual objects – Part 3: Audio*.
- ISO/IEC 26428-1:2008, *Digital cinema (D-cinema) distribution master – Part 1: Image characteristics*.

## 2) Annex A

## 2.1) Clause A.1

In A.1, replace the following sentence:

This Recommendation | International Standard defines two profiles:

with

This Recommendation | International Standard defines four profiles:

In A.1, append the following numeration:

- 3) Motion Picture Archive Preservation Format. The brand 'mpap' indicates the Motion JPEG 2000 motion picture archive preservation format profile, as defined below.
- 4) Motion Picture Archive Access Format. The brand 'mpaa' indicates the Motion JPEG 2000 motion picture archive access format profile, as defined below.

## 2.2) New clauses A.3 and A.4

Add the following clauses:

**A.3 Motion JPEG 2000 motion picture archive preservation format profile**

For the preservation of motion picture content, the following profile is defined:

- 1) At least a single video track, using only JPEG 2000 visual samples is present.
- 2) Audio tracks may be present, as specified in Table A.1.
- 3) If more than one video track (e.g., different international versions or scenes) or more than one group of multi-channel audio tracks are present, the tracks shall be distinguished and selected by the `alternate_group` field. In addition, Edit Boxes (`edts`) and Edit List Boxes (`elst`) are permitted in order to create compositions of the different tracks.
- 4) The image codestream profile shall have `Rsiz=7` (as specified in ITU-T T.800 | ISO/IEC 15444-1, clause A.10).
- 5) All color spaces are allowed, as long as they can be described with the metadata in the Colour Specification Box (`colr`) (as specified in ITU-T T.800 | ISO/IEC 15444-1, Annex I).
- 6) There is no restriction on frame rates.
- 7) The file shall be self-contained; no data references are used, and therefore all media data shall be contained within the single file.
- 8) The presentation shall be described by a single Movie Box (`moov`) only, i.e., fragments are disallowed.

- 9) The media data in the Media Data Box(es) shall be placed within the box(es) in temporal order.
- 10) If more than one track is present, the media data for the tracks shall be interleaved, with a granularity no greater than the greater of (a) the duration of a single 'sample' (in file format terms) or (b) one second.
- 11) The transformation matrices used are restricted to uniform scaling and rotation by multiples of 90°.

**Table A.1 – Audio format specification for archive preservation format**

<b>Supported data format</b>	'raw ' (optional MPEG-4 SLS).
<b>Supported sample rates</b>	Each Motion JPEG 2000 decoder shall support sample rates of 48 kHz, 44.1 kHz, 32 kHz and 96 kHz (as recommended in [2]). A Motion JPEG 2000 encoder can use any desired sample rate. However, without any further agreements outside the scope of this Recommendation   International Standard, correct decoding can be assumed only if the values recommended above are being used.
<b>Supported word lengths</b>	Each Motion JPEG 2000 decoder shall be able to correctly decode word lengths of 16 and 24 bits. A Motion JPEG 2000 encoder can use any desired word length. However, without any further agreements outside the scope of this Recommendation   International Standard, correct decoding can be assumed only if a word length of 16 or 24 bits is being used.
<b>Channel format</b>	Discrete (i.e., no matrix encoding).

Audio data shall be stored in a lossless manner. For this purpose the 'raw ' audio format shall be used.

All audio channels shall be organized as discrete channels. As an option, audio data can also be represented as MPEG-4 Scalable Lossless Coding (SLS) specified in ISO/IEC 14496-3 as a compressed but lossless audio format.

Metadata should be stored together with image and other media data in the same file. Metadata can consist of any combination of structural, descriptive and historical metadata. In all cases, there should be a minimum set of structural metadata stored. For image data this should consist of all information relevant to the employed JPEG 2000 encoding parameters and contain at least image size, frame rate, colour space, sub-sampling information, number and meaning of components and bit depth. For audio data this should consist at least of bit depth, sample rate, number and meaning of audio channels for each multi-channel audio representation and audio encoding standard.

Descriptive and historical metadata should be stored in an XML [9] representation.

#### **A.4 Motion JPEG 2000 motion picture archive access format profile**

The profile optimized for access to and exchange of archived motion picture content has the following characteristics:

- 1) At least a single video track, using only JPEG 2000 visual samples, shall be present.
- 2) Audio tracks may be present, as specified in Table A.2.
- 3) If more than one video track (e.g., different international versions or scenes) or more than one group of multi-channel audio tracks are present, the tracks shall be distinguished and selected by the alternate group field. In addition, Edit Boxes (edt<sub>s</sub>) and Edit List Boxes (elst) are permitted in order to create compositions of the different tracks.
- 4) The image codestream profile shall have R<sub>siz</sub>=5 or R<sub>siz</sub>=6 (as specified in ITU-T T.800 | ISO/IEC 15444-1, clause A.10).
- 5) The 'X'Y'Z' color space as defined in ISO/IEC 26428-1 shall be used and signalled in the Colour Specification Box (colr) (as specified in ITU-T T.800 | ISO/IEC 15444-1, Annex I).
- 6) There is no restriction on frame rates. If distribution to digital cinema is intended, then frame rates of 24 frames per second (fps) or 48 frames per second (fps) are recommended.
- 7) The file shall be self-contained; no data references are used, and therefore all media data shall be contained within the single file.
- 8) The presentation shall be described by a single Movie Box (moov) only, i.e., fragments are disallowed.
- 9) The media data in the Media Data Box(es) is placed within the box(es) in temporal order.
- 10) If more than one track is present, the media data for the tracks is interleaved, with a granularity no greater than the greater of (a) the duration of a single 'sample' (in file format terms) or (b) one second.
- 11) The transformation matrices used are restricted to uniform scaling and rotation by multiples of 90°.

**Table A.2 – Audio format specification for archive access format**

<b>Supported data format</b>	'raw ' (optional MPEG-4 SLS).
<b>Supported sample rates</b>	Either 48 kHz or 96 kHz.
<b>Supported word lengths</b>	Either 16 bits or 24 bits.
<b>Channel format</b>	Discrete (i.e., no matrix encoding), a maximum of 16 channels per multi-channel representation.

Audio data shall be stored in a lossless manner. For this purpose the 'raw ' audio format shall be used.

All audio channels shall be organized as discrete channels. As an option, audio data can also be represented as MPEG-4 Scalable Lossless Coding (SLS) specified in ISO/IEC 14496-3 as a compressed but lossless audio format.

NOTE – Metadata should be stored together with image and other media data in the same file. Metadata can consist of any combination of structural, descriptive and historical metadata. In all cases there should be a minimum set of structural metadata stored. For image data this should consist of all information relevant to the employed JPEG 2000 encoding parameters and contain at least image size, frame rate, colour space, sub-sampling information, number and meaning of components and bit depth. For audio data this should consist at least of bit depth, sample rate, number and meaning of audio channels for each multi-channel audio track and audio encoding standard. Descriptive and historical metadata should be stored in an XML [9] representation.

### 3) Annex B

Add the following clause:

#### B.4 Digital cinema archives

In this section practical guidelines for the use and application of motion picture archive formats are given. In the following paragraphs procedures are described that are meant to help in creating Archive Package files and how to use them to disseminate archived cinematic content to end users and to exchange archived materials between two or more archiving institutions. Implementations should be strict when writing, and tolerant when reading the described formats.

##### B.4.1 Ingesting into cinematic archives

Several ways exist to convert cinematic content to the motion picture archive formats. The content may come directly from various stages of an uncompressed digital production process or it can be a compressed digital distribution format, e.g., a Digital Cinema Package (DCP) [10].

It is also possible to ingest images originating from scanned film material as well as access copies that were created through transferring original film images to some other type of analogue or digital media, e.g., analogue or digital video tapes, digital versatile disk (DVD), etc.

- a) Ingesting uncompressed digitally produced material:

Digitally produced material includes images that were recorded with an electronic camera and did not undergo any further processing, as well as the results of different processing steps during post-production to the final cinematic product. This also includes scanned films that were subject of a digital restoration process. Common formats for this type of imagery are DPX [3], TIFF [4] or TGA [5] sequences. This type of material may also have its origin on a digital video tape format that has been ingested into a computer system. This type of material should be compressed using the JPEG 2000 profile for long-term storage of cinematic content. To be able to preserve the material in its original quality, lossless compression with the 5-3 reversible filter should be used. The original colour space and bit depth should not be changed.

- b) Ingesting compressed Digital Cinema Packages (DCPs):

The Digital Cinema Package as described in the different parts of SMPTE 429 [10] can be regarded as the digital equivalent to the release print on film material. Archival institutions in some cases may only be able to acquire a DCP of a certain production and not the uncompressed material originally used to create the DCP. The DCP should be converted without decoding and re-encoding of the contained JPEG 2000 images to the motion picture preservation storage format or the motion picture access format. All structural information of the DCP should be preserved in the metadata section to be able to exactly reconstruct the original DCP.

Direct archival of encrypted DCPs is discouraged because of the risks of loss of the encryption keys. Instead, the content of encrypted DCPs should be decrypted and stored as described above in order to ensure future accessibility. Security should be enforced by other means (e.g., physical security of storage media).

c) Ingesting scanned film material:

The formats standardized in this Recommendation | International Standard can also be used to store cinematic content that is scanned from original film material. However, the choice of format and profile will usually depend on the preservation strategy for the original film. For digital long-term preservation, the original film material should be scanned at the highest reasonable spatial resolution and bit depth. These digital images should then be stored using the motion picture preservation format with the 5-3 reversible transform. Image data should be stored in the colour space the film scanner used. All available technical data of the film scanner should be stored as metadata. It is also possible to store additional image components (colour channels), e.g., infrared for scratch removal. This package can then be also used as a starting point for digital restoration procedures. For ingesting digitally restored images originating from film material, see item a).

In many cases, it is desirable to keep the original film as long-term preservation element and to create digitized versions to facilitate access to the cinematic content. Depending on the requirements of the archival institutions there are two main routes. For lower requirements, the film should be scanned and encoded according to the specifications for the motion picture access format. For higher requirements, the specifications for the motion picture preservation format should be used with parameters appropriate for the prospective use.

#### B.4.2 Disseminating cinematic archives

In the context of this Recommendation | International Standard, dissemination means the delivery of archived cinematic content to end users. This does not necessarily mean that end users are required to have software and systems to decode and interpret the formats described in this Recommendation | International Standard. To create a format that can be utilized by end users, a conversion process is necessary. The details and target formats of this conversion process largely depend on the requirements of each user group. Possible user groups may be digital cinemas, television and movie production companies, schools and universities, scientists, and others.

There may be a number of dissemination formats in consideration of the end user's many different requirements, like, e.g.:

- Digital Cinema Package (DCP) format as specified in [10] and related documents;
- MPEG-4/Part-10 (H.264/AVC) as specified in ITU-T H.264 | ISO/IEC 14496-10;
- MPEG-2 as specified in ITU-T H.262 | ISO/IEC 13818-2;
- etc.

Usually the motion picture access format is used as a starting point for the dissemination process because the compressed image data can be directly converted into a Digital Cinema Package. It is also possible to create small-sized preview movies easily from this format by decoding only the lower resolution layers.

In special cases also the motion picture preservation format may be used as a starting point for the creation of a dissemination package. The high quality contained in this format is, e.g., needed to create uncompressed image sequences for digital restoration or re-mastering procedures.

#### B.4.3 Exchange of content between cinematic archives

To exchange cinematic content between different archival institutions, both motion picture formats specified in this Recommendation | International Standard can be used, depending on the requirements of the institutions. Generally, the motion picture access format should be preferred due to its stricter parameter set.

It is also possible to create new packages for exchange that, e.g., contain only a subset of the image, audio, metadata or other content of the source format.

#### B.4.4 General procedures and archive management

The archival system used to handle and store the formats described in this Recommendation | International Standard should adhere to the OAIS Reference model (ISO 14721:2003).