
**Information technology — JPEG 2000
image coding system: Reference
software**

*Technologies de l'information — Système de codage d'image
JPEG 2000: Logiciel de référence*

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 15444-5:2003

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 15444-5:2003

© ISO/IEC 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

CONTENTS

	<i>Page</i>
1 Scope	1
2 Normative references	1
2.1 Identical Recommendations International Standards	1
2.2 Additional references	1
3 Definitions	2
4 Abbreviations and symbols	4
4.1 Abbreviations	4
4.2 Symbols	5
5 Conventions	5
6 General description	6
7 Copyright and licensing	6
8 Platform requirements	6
8.1 JasPer requirements	6
8.2 JJ2000 requirements	6
9 Reference code structure	7
9.1 JasPer executables	7
9.2 JJ2000 executables	7
10 Intellectual Property	7
11 Software availability and updates	8
Annex A JASPER – C reference software – software description	9
A.1 Introduction	9
A.2 Software updates	9
A.3 Version numbering	9
A.4 Software overview	9
A.5 JasPer library	10
A.6 JasPer demo application programs	10
A.7 Software requirements	11
A.8 Building the software	11
A.9 Using the software	11
Annex B JJ2000 – Java™ reference software – software description	12
B.1 Introduction	12
B.2 Software updates	12
B.3 Software architecture	12
B.4 Installing and running the software	13
Electronic attachment:	
JASPER reference software	
JJ2000 reference software	

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO/IEC 15444 may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 15444-5 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*, in collaboration with ITU-T. The identical text is published as ITU-T Rec. T.804.

ISO/IEC 15444 consists of the following parts, under the general title *Information technology — JPEG 2000 image coding system*:

- *Part 1: Core coding system*
- *Part 2: Extensions*
- *Part 3: Motion JPEG 2000*
- *Part 4: Conformance testing*
- *Part 5: Reference software*
- *Part 6: Compound image file format*
- *Part 9: Interactivity tools, APIs and protocols*
- *Part 12: ISO base media file format*

**INTERNATIONAL STANDARD
ITU-T RECOMMENDATION**

**Information technology –
JPEG 2000 image coding system: Reference software**

1 Scope

ITU-T Rec. T.800 | ISO/IEC 15444-1 defines a set of lossless and lossy compression methods for coding continuous-tone, bi-level, greyscale or colour digital still images. This Recommendation | International Standard provides two independently created software reference implementations of ITU-T Rec. T.800 | ISO/IEC 15444-1, in order to assist implementers of ITU-T Rec. T.800 | ISO/IEC 15444-1 in testing and understanding its content.

The reference software is informative only. This Recommendation | International Standard does not define any additional part of the JPEG 2000 image coding system.

Each version of the reference software contains source code, which may be compiled to provide the following functionality:

- transcoding from selected, widely available image formats into a JPEG 2000 codestream;
- transcoding from selected, widely available image formats into the JP2 file format;
- selection of a wide range of JPEG 2000 encoding options (as documented in each reference software);
- decoding from a JPEG 2000 codestream to a range of selected widely available image formats;
- partial processing of a JP2 file to extract a JPEG 2000 codestream for decoding to a range of selected widely available image formats;
 - NOTE – The reference software does not implement a conforming JP2 file reader. See clause 9.
- some additional tools to help with evaluation and testing.

The reference software is intended for use as a testing and validation tool for other implementations of JPEG 2000, and to help in the understanding of ITU-T Rec. T.800 | ISO/IEC 15444-1. Although components of the reference software may find application in software intended for product development, this was not an objective of the development of this software, and prospective implementors are cautioned against making any estimations of performance or resource usage based on the reference software.

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of the Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

2.1 Identical Recommendations | International Standards

- ITU-T Recommendation T.800 (2002) | ISO/IEC 15444-1:2002, *Information technology – JPEG 2000 Image Coding System: Core coding system*.

2.2 Additional references

- ISO/IEC 9899:1999, *Programming languages – C*.
- ISO/IEC 9945-1:1996, *Information technology – Portable Operating System Interface (POSIX) – Part 1: System Application Program Interface (API) (C language)*.
- ISO/IEC 9945-2:1993, *Information technology – Portable Operating System Interface (POSIX) – Part 2: Shell and utilities*.

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply:

- 3.1 bit endian:** The bits of a value representation occur in order from most significant to least significant.
- 3.2 bit:** A contraction of the term "binary digit"; a unit of information represented by a zero or a one.
- 3.3 bit-plane:** A two-dimensional array of bits. In this Recommendation | International Standard, a bit-plane refers to all the bits of the same magnitude in all coefficients or samples. This could refer to a bit-plane in a component, tile-component, code-block, region of interest, or other.
- 3.4 bit stream:** The actual sequence of bits resulting from the coding of a sequence of symbols. It does not include the markers or marker segments in the main and tile-part headers or the EOC marker. It does include any packet headers and in stream markers and marker segments not found within the main or tile-part headers.
- 3.5 box:** A portion of the file format defined by a length and unique box type. Boxes of some types may contain other boxes.
- 3.6 box contents:** Refers to the data wrapped within the box structure. The contents of a particular box are stored within the DBox field within the Box data structure.
- 3.7 byte:** Eight bits.
- 3.8 channel:** One logical component of the image. A channel may be a direct representation of one component from the codestream, or may be generated by the application of a palette to a component from the codestream.
- 3.9 code-block:** A rectangular grouping of coefficients from the same subband of a tile-component.
- 3.10 coder:** An embodiment of either an encoding or decoding process.
- 3.11 codestream:** A collection of one or more bit streams and the main header, tile-part headers, and the EOC required for their decoding and expansion into image data. This is the image data in a compressed form with all of the signalling needed to decode.
- 3.12 coefficient:** The values that are the result of a transformation.
- 3.13 component:** A two-dimensional array of samples. An image typically consists of several components, for instance representing red, green and blue.
- 3.14 compressed image data:** Part or all of a bit stream. Can also refer to a collection of bit streams in part or all of a codestream.
- 3.15 decoder:** An embodiment of a decoding process, and optionally a colour transformation process.
- 3.16 decoding process:** A process which takes as its input all or part of a codestream and outputs all or part of a reconstructed image.
- 3.17 discrete wavelet transformation (DWT):** A transformation that iteratively transforms one signal into two or more filtered and decimated signals corresponding to different frequency bands. This transformation operates on spatially discrete samples.
- 3.18 encoder:** An embodiment of an encoding process.
- 3.19 encoding process:** A process, that takes as its input all or part of a source image data and outputs a codestream.
- 3.20 file format:** A codestream and additional support data and information not explicitly required for the decoding of codestream. Examples of such support data include text fields providing titling, security and historical information, data to support placement of multiple codestreams within a given data file, and data to support exchange between platforms or conversion to other file formats.
- 3.21 header:** Either a part of the codestream that contains only markers and marker segments (main header and tile-part header) or the signalling part of a packet (packet header).
- 3.22 image:** The set of all components.
- 3.23 image area:** A rectangular part of the reference grid, registered by offsets from the origin and the extent of the reference grid.
- 3.24 image area offset:** The number of reference grid points down and to the right of the reference grid origin where the origin of the image area can be found.

- 3.25 image data:** The components and component samples making up an image. Image data can refer to either the source image data or the reconstructed image data.
- 3.26 irreversible:** A transformation, progression, system, quantization, or other process that, due to systemic or quantization error, disallows lossless recovery. An irreversible process can only lead to lossy compression.
- 3.27 JP2:** The name of the file format defined by ITU-T Rec. T.800 | ISO/IEC 15444-1.
- 3.28 JPEG:** Used to refer globally to the encoding and decoding process of the following Recommendations | International Standards:
- ITU-T Recommendation T.81 (1992) | ISO/IEC 10918-1:1994, Information technology – Digital compression and coding of continuous-tone still images: Requirements and guidelines.
 - ITU-T Recommendation T.83 (1994) | ISO/IEC 10918-2:1995, Information technology – Digital compression and coding of continuous-tone still images: Compliance testing.
 - ITU-T Recommendation T.84 (1996) | ISO/IEC 10918-3:1997, Information technology – Digital compression and coding of continuous-tone still images: Extensions.
 - ITU-T Recommendation T.84 (1996)/Amd. 1 (1999), Information technology – Digital compression and coding of continuous-tone still images: Extensions – Amendment 1: Provisions to allow registration of new compression types and versions in the SPIFF header.
 - ITU-T Recommendation T.86 (1998) | ISO/IEC 10918-4, Information technology – Digital compression and coding of continuous-tone still images: Registration of JPEG Profiles, SPIFF Profiles, SPIFF Tags, SPIFF colour Spaces, APPn Markers, SPIFF Compression types and Registration authorities (REGAUT).
- 3.29 JPEG 2000:** Used to refer globally to the encoding and decoding processes in this Recommendation | International Standard and their embodiment in applications.
- 3.30 layer:** A collection of compressed image data from coding passes of one, or more, code-blocks of a tile-component. Layers have an order for encoding and decoding that must be preserved.
- 3.31 lossless:** A descriptive term for the effect of the overall encoding and decoding processes in which the output of the decoding process is identical to the input to the encoding process. Distortion free restoration can be assured. All of the coding processes or steps used for encoding and decoding are reversible.
- 3.32 lossy:** A descriptive term for the effect of the overall encoding and decoding processes in which the output of the decoding process is not identical to the input to the encoding process. There is distortion (measured mathematically). At least one of the coding processes or steps used for encoding and decoding is irreversible.
- 3.33 marker:** A two-byte code in which the first byte is hexadecimal FF (0xFF) and the second byte is a value between 1 (0x01) and hexadecimal FE (0xFE).
- 3.34 marker segment:** A marker and associated (not empty) set of parameters.
- 3.35 packet:** A part of the bit stream comprising a packet header and the compressed image data from one layer of one precinct of one resolution level of one tile-component.
- 3.36 packet header:** Portion of the packet that contains signalling necessary for decoding that packet.
- 3.37 precinct:** A one rectangular region of a transformed tile-component, within each resolution level, used for limiting the size of packets.
- 3.38 precision:** Number of bits allocated to a particular sample, coefficient, or other binary numerical representation.
- 3.39 progression:** The order of a codestream where the decoding of each successive bit contributes to a "better" reconstruction of the image. What metrics make the reconstruction "better" is a function of the application. Some examples of progression are increasing resolution or improved sample fidelity.
- 3.40 quantization:** A method of reducing the precision of the individual coefficients to reduce the number of bits used to entropy code them. This is equivalent to division while compressing and multiplying while decompressing. Quantization can be achieved by an explicit operation with a given quantization value or by dropping (truncating) coding passes from the codestream.
- 3.41 raster order:** A particular sequential order of data of any type within an array. The raster order starts with the top left data point and moves to the immediate right data point, and so on, to the end of the row. After the end of the row is reached, the next data point in the sequence is the left-most data point immediately below the current row. This order is continued to the end of the array.

- 3.42 reconstructed image:** An image, that is the output of a decoder.
- 3.43 reconstructed sample:** A sample reconstructed by the decoder. This always equals the original sample value in lossless coding but may differ from the original sample value in lossy coding.
- 3.44 reference grid:** A regular rectangular array of points used as a reference for other rectangular arrays of data. Examples include components and tiles.
- 3.45 reference tile:** A rectangular sub-grid of any size associated with the reference grid.
- 3.46 region of interest (ROI):** A collection of coefficients that are considered of particular relevance by some user defined measure.
- 3.47 resolution level:** Equivalent to decomposition level with one exception: the LL subband is also a separate resolution level.
- 3.48 reversible:** A transformation, progression, system, or other process that does not suffer systemic or quantization error and, therefore, allows lossless signal recovery.
- 3.49 sample:** One element in the two-dimensional array that comprises a component.
- 3.50 source image:** An image used as input to an encoder.
- 3.51 subband:** A group of transform coefficients resulting from the same sequence of low-pass and high-pass filtering operations, both vertically and horizontally.
- 3.52 subband coefficient:** A transform coefficient within a given subband.
- 3.53 tile:** A rectangular array of points on the reference grid, registered with and offset from the reference grid origin and defined by a width and height. The tiles which overlap are used to define tile-components.
- 3.54 tile-component:** All the samples of a given component in a tile.
- 3.55 tile index:** The index of the current tile ranging from zero to the number of tiles minus one.
- 3.56 transformation:** A mathematical mapping from one signal space to another.

4 Abbreviations and symbols

4.1 Abbreviations

For the purposes of this Recommendation | International Standard, the following abbreviations apply.

CCITT	International Telegraph and Telephone Consultative Committee, now ITU-T
ICC	International Colour Consortium
ICT	Irreversible Colour transformation
IEC	International Electrotechnical Commission
ISO	International Organization for Standardization
ITTF	Information Technology Task Force
ITU	International Telecommunication Union
ITU-T	International Telecommunication Union – Telecommunication Standardization Sector (formerly the CCITT)
JPEG	Joint Photographic Experts Group – The joint ISO/ITU committee responsible for developing standards for continuous-tone still picture coding. It also refers to the standards produced by this committee: ITU-T Rec. T.81 ISO/IEC 10918-1, ITU-T Rec. T.83 ISO/IEC 10918-2, ITU-T Rec. T.84 ISO/IEC 10918-3 and ITU-T Rec. T.87 ISO/IEC 14495-1.
JURA	JPEG Utilities Registration Authority
1D-DWT	One-dimensional Discrete Wavelet Transformation
FDWT	Forward Discrete Wavelet Transformation
IDWT	Inverse Discrete Wavelet Transformation
LSB	Least Significant Bit
MSB	Most Significant Bit

PCS	Profile Connection Space
RCT	Reversible Colour Transformation
ROI	Region of Interest
SNR	Signal to Noise Ratio
UCS	Universal Character Set
URI	Uniform Resource Identifier
URL	Uniform Resource Locator
UTF-8	UCS Transformation Format 8
UUID	Universal Unique Identifier
XML	Extensible Markup Language
W3C	World-Wide Web Consortium

4.2 Symbols

For the purposes of this Recommendation | International Standard, the following symbols apply.

0x----	Denotes a hexadecimal number
\nnn	A three-digit number preceded by a backslash indicates the value of a single byte within a character string, where the three digits specify the octal value of that byte
COC	Coding style component marker
COD	Coding style default marker
COM	Comment marker
CRG	Component registration marker
EPH	End of packet header marker
EOC	End of codestream marker
PLM	Packet length, main header marker
PLT	Packet length, tile-part header marker
POC	Progression order change marker
PPM	Packed packet headers, main header marker
PPT	Packed packet headers, tile-part header marker
QCC	Quantization component marker
QCD	Quantization default marker
RGN	Region of interest marker
SIZ	Image and tile size marker
SOC	Start of codestream marker
SOP	Start of packet marker
SOD	Start of data marker
SOT	Start of tile-part marker
TLM	Tile-part lengths marker

5 Conventions

The source files provided are supplied in the form of an individual zip file for each source tree. File locations given in this Recommendation | International Standard are expressed relative to the top level of the corresponding source tree. A Unix style file structure and delimiters are assumed.

Basic instructions are provided within the reference software for the installation and compilation of the sources under a variety of operating systems and platforms. No support can be provided by ISO | ITU-T beyond that offered in this Recommendation | International Standard and through links on the official JPEG web site, <http://www.jpeg.org>.

6 General description

Two independent and separate software source trees are provided. These are:

- **JASPER.ZIP**, provided as indicated in the file **COPYRIGHT**, contained within the zip file. This is written in the C programming language, and should compile and run on any platform with a C language implementation conforming to ISO/IEC 9899:1999, and supporting a subset of the POSIX C API, ISO/IEC 9945-1:1996.
- **JJ2000.ZIP**, provided as indicated in the file **COPYRIGHT**, contained within the zip file. This is written in the Java™ programming language, and executes under versions of the Java Virtual Machine (JVM) from version 1.1.1 onwards.

The supplied executables are described briefly in clause 8, and in more detail with some information about the supplied source code in Annex A (JasPer) and Annex B (JJ2000).

Both distributions have been tested as meeting the coding and decoding requirements for codestreams identified in ITU-T Rec. T.800 | ISO/IEC 15444-1. Formal compliance is beyond the scope of this Recommendation | International Standard.

7 Copyright and licensing

These software modules were originally developed by the parties indicated in the file **COPYRIGHT** within each package forming a part of this Recommendation | International Standard, in the course of development of ITU-T Rec. T.800 | ISO/IEC 15444-1. These software modules are separate and discrete implementations of ITU-T Rec. T.800 | ISO/IEC 15444-1. ISO/IEC draws the attention of the users of these software modules to the license terms and conditions specified in the file **LICENSE** in each implementation. Those intending to use these software modules in hardware or software products are advised that their use may infringe existing patents. In particular, the original developers of these software modules and their respective companies, the editors and their companies, and ISO/IEC have disclaimed liability for any proposed use of these software modules or modifications thereof. No licensing is implied for their use in whole or in part in products that fail to conform to ITU-T Rec. T.800 | ISO/IEC 15444-1. The original software authors retain full rights to use the code within this Recommendation | International Standard for their own purposes, to assign or donate the code to a third party and to inhibit third parties from using the code for products that fail to conform to ITU-T Rec. T.800 | ISO/IEC 15444-1.

The two distributions have differing copyright and licensing restrictions, which reflect the different requirements and operating environments of those organizations that have contributed to the development of the software.

8 Platform requirements

Both reference software implementations have been successfully built on a variety of operating platforms and with a selection of compilers. They have been written with portability and comprehensibility in mind. Platforms for which there is specific installation documentation are indicated below:

8.1 JasPer requirements

JasPer has been successfully compiled in the following environments:

- Red Hat Linux 7.0, GNU C 2.96, GNU Make 3.79.1.
- SunOS/SPARC 5.5.1, GNU C 2.7.2.1, SunOS make.
- SunOS/SPARC 5.7, GNU C 2.95, SunOS make.
- Windows 2000 Professional, Microsoft Visual C 6.0.
- Windows 98 Second Edition, Cygwin 1.1.8.2, GNU Bash 2.04, GNU C 2.95, GNU Make 3.79.1.

8.2 JJ2000 requirements

JJ2000 has been tested on versions of the Java™ Virtual Machine from version 1.1.1 and later, on a variety of platforms including Sun Solaris, Microsoft Windows 95/98/NT/2000, Linux, and MacOS, using Sun's Java Development Kit (JDK), Sun's Java Runtime Environment (JRE) and Microsoft's Java Virtual Machine (JVM). Detailed instructions on how to set up and run the JJ2000 executables are included in the file **README** in the top level of the JJ2000 source tree.

9 Reference code structure

Both sets of reference software offer the capability to encode and decode codestreams that conform to the syntax defined in ITU-T Rec. T.800 | ISO/IEC 15444-1.

Both sets of reference software include a partial implementation of the JP2 file format defined in ITU-T Rec. T.800 | ISO/IEC 15444-1. However, neither implementation is a conforming JP2 file reader as defined in ITU-T Rec. T.800 | ISO/IEC 15444-1. Several features are missing from the reference software that are required of a conforming file reader. These include support for palettized colour, component mapping and Restricted ICC Profiles.

For transcoding to other image formats or for display, both sets of reference software allow the user to assume that the decoded codestream components are in an RGB colour space or greyscale. In general, additional information is required in order to determine the true nature of the component data. Support for such information is provided by the JP2 file format but is not processed by the reference software.

The executable files described below are available by compiling the reference software as indicated in the **INSTALL** file held in the top level of each respective source tree. In both cases, more than 30 optional different command line parameters may be defined, which can demonstrate aspects of the encoding for JPEG 2000 codestreams defined in ITU-T Rec. T.800 | ISO/IEC 15444-1.

9.1 JasPer executables

The JasPer reference software distribution provides three executables:

- **JASPER**, the transcoder which can be used to convert to and from a variety of image file formats including JPEG, Portable BitMap (PNM/PGM/PPM), Windows BMP, and Sun Rasterfile. The transcoder acts as both encoder and decoder for JPEG 2000 files.
NOTE – JASPER is not a conforming JP2 file reader. See the beginning of clause 9.
- **IMGCMP**, provided as a test utility to measure differences between images and provide various measures of the comparative differences, such as SNR.
- **IMGINFO**, provided as a simple command line utility to analyse JPEG 2000 files.

9.2 JJ2000 executables

The JJ2000 software distributions provide two executables:

- **JJ2KEncoder**, which acts as an encoder from PGM, PPM and PGX to JPEG 2000 (both codestream and JP2 file format).
NOTE – PGX is a non-standard format, defined in the JJ2000 documentation, that (unlike PGM) supports arbitrary bit-depths and signed sample values.
- **JJ2KDecoder**, which takes a JPEG 2000 codestream or JP2 file and decodes it to PGM, PPM, or PGX format. It can also take a number of optional parameters that emulate some of the partial decoding features that might be anticipated in a client server environment with restricted bandwidth communications. It is also capable of rendering the image to a screen display if no output file specification is provided, offering simple viewing capabilities for JPEG 2000 codestreams and JP2 files.
NOTE – JJ2KDecoder is not a conforming JP2 file reader. See the beginning of clause 9.

10 Intellectual Property

There is the possibility that, for some of the processes specified in ITU-T Rec. T.800 | ISO/IEC 15444-1, conformance or compliance may require use of an invention covered by patent rights. By publication of this Recommendation | International Standard, no position is taken with respect to the validity of these claims or of any patent rights in connection therewith. Information regarding such patents can be obtained from the organizations identified in Table L.1 in ITU-T Rec. T.800 | ISO/IEC 15444-1, which summarizes the formal patent and intellectual property rights statements that have been received in connection with the processes defined in ITU-T Rec. T.800 | ISO/IEC 15444-1.

11 Software availability and updates

The reference software sources released with this Recommendation | International Standard are the latest tested versions available at the date on which the text was released for final approval. Later versions of the software and implementation or fault reports and fixes may be made available after the publication of this Recommendation | International Standard. These may be found at the URLs contained in the documentation for each version of the reference software, or through links which may be maintained at <http://www.jpeg.org/software>.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 15444-5:2003

Annex A

JASPER – C reference software – software description

(This annex forms an integral part of this Recommendation | International Standard)

A.1 Introduction

JasPer is a collection of software (i.e., a library and application programs) for the coding and manipulation of images. This software is written in the C programming language. Of particular relevance to this standard, the JasPer software provides an implementation of the image codec specified in ITU-T Rec. T.800 | ISO/IEC 15444-1. Support for several other popular image codecs are also included in order to facilitate the transcoding of image data to and from JPEG 2000 codestreams and the JP2 file format. The JasPer software was developed with the objective of providing a license and royalty free JPEG 2000 implementation to anyone wishing to use the JPEG 2000 standard, although no warranty is provided as to any potential infringement of intellectual property (see the document **LICENSE** included with the software). Users of the software are advised to satisfy themselves as to the validity of any claims made for intellectual property which are made against ITU-T Rec. T.800 | ISO/IEC 15444-1 before using this software.

NOTE – Jasper is not a conforming JP2 file reader. See the beginning of clause 9.

In addition to this annex, readers interested in the JasPer software should also read the JasPer Software Reference Manual, which is included in the JasPer software distribution archive. This manual contains detailed information about the JasPer software, and includes release-specific details that have been deliberately omitted from this annex.

A.2 Software updates

The JasPer software release accompanying this Recommendation | International Standard represents the most recent version available at the time this Recommendation | International Standard was published. The development of the JasPer software is expected to continue. As new features and functionality are added, new releases of the software may become available. The most recent version of the JasPer software can be downloaded from the Internet via the URL given in clause 11. Further information and news about the JasPer software may also be made available via the same URL.

A.3 Version numbering

As the JasPer software is expected to evolve over time, it is important to be able to identify particular releases of the software. Each release of the JasPer software has a version identifier. For the purposes of this annex, a version identifier is comprised of three integers separated by dots. In order, the three integers correspond to the major, minor, and micro version numbers for the software. For example, the version identifier "1.500.0" corresponds to a major version of 1, a minor version of 500, and a micro version of 0. In instances where the micro version is zero, the version identifier may be truncated after the minor version number. For example, the version identifier "1.500" is completely valid and an abbreviation for "1.500.0".

Given two different releases of the JasPer software, the most recent can be identified by comparing the version identifiers, as follows:

- 1) if the major version numbers differ, the release with the higher major version number is newer;
- 2) if the major version numbers are equal and the minor version numbers differ, the release with the higher minor version number is newer; or
- 3) if the major version numbers are equal and the minor version numbers are equal, the release with the higher micro version is newer.

A.4 Software overview

The JasPer software consists of a library, and several demonstration application programs that utilize this library. The code is written in the C programming language in conformance with ISO/IEC 9899:1999. This language was chosen due to the availability of C development environments for most of today's computing platforms. In total, the software consists of about 30K lines of code.

In the clauses that follow, a brief overview of the JasPer software is provided. No mention is made of details that are likely to change between software releases. These are described within documents included in the relevant software distribution, to avoid introducing inconsistencies between this Recommendation | International Standard and the documentation accompanying the relevant JasPer software release.

A.5 JasPer library

At the core of the JasPer software is the JasPer library, named libjasper. The library consists of two distinct categories of code:

- 1) base/core code; and
- 2) codec drivers.

The base code provides generic routines for manipulating images and provides a framework for constructing codec drivers. The codec drivers provide a means for encoding/decoding images in specific formats. The library has been designed to be extensible, so that adding support for new image formats should be straightforward.

Currently, codec drivers are provided for the following image formats:

- 1) Partial support (non-conforming) for JPEG 2000 JP2 file (JP2);
- 2) JPEG 2000 code stream (JPC);
- 3) JPEG JFIF (JPG);
- 4) Portable Bitmap (PNM);
- 5) Windows BMP (BMP); and
- 6) Sun Rasterfile (RAS).

In addition, support is also provided for a number of non-standard formats, which offer features that are not available through any of the above formats (for example unusual image geometries). These formats are documented in the JasPer Software Reference Manual. The JPG codec driver requires that the IJG JPEG library be available on the system used to compile the software. The IJG JPEG library is free software and can be obtained from the Internet via the URL:

<http://www.ijg.org>

For licensing reasons, the IJG JPEG library is not distributed with the JasPer software.

The JP2 and JPC codecs provided are the main element of relevance to this Recommendation | International Standard. The JPG codec within JasPer provides support for the original JPEG format, and can be used to convert JPEG-formatted data into JPEG 2000.

The JasPer library provides the following key classes:

- 1) An image class – This class is used to represent an image, and also provides access to codec drivers for encoding/decoding image data in various formats.
- 2) A sequence/matrix class – This class provides matrix and two-dimensional sequence classes.
- 3) A I/O stream class – This class provides I/O streams similar to that of the standard C library, but with additional functionality required by other code in JasPer.
- 4) A fixed-point number class – This (templated) class is used for performing fixed-point arithmetic.
- 5) A tag-value parser class – This class facilitates the parsing of tag-value pairs. A tag-value pair is a string of the form "tag=value". Such pairs are used by some interfaces within JasPer in order to pass parameters.
- 6) A command line option class – This class allows the parsing of command lines. This code is similar to the getopt function available on most UNIX systems.

A.6 JasPer demo application programs

Three demonstration application programs are included that utilize the JasPer library. These application programs are:

- 1) **jasper** – This is a simple transcoder application. It converts image data from one format to another.
- 2) **imgcmp** – This is a image comparison utility. It can be used to quantify the difference between two images (using various distortion metrics).
- 3) **imginfo** – This program outputs basic information about the type and geometry of an image.

The **jasper** program is the main reference software provided and can be used as a JPEG 2000 encoder and/or decoder. The **imgcmp** utility is useful for analyzing image coding performance.