

---

---

**Information technology —  
Telecommunications and information  
exchange between systems — Private  
Integrated Services Network —  
Specification, functional model and  
information flows — Message waiting  
indication supplementary service**

*Technologies de l'information — Télécommunications et échange  
d'information entre systèmes — Réseau privé à intégration de services —  
Spécifications, modèle fonctionnel et flux d'informations — Service  
supplémentaire d'indication d'attente de message*

## Contents

Foreword	iv
Introduction	v
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Definitions	1
4.1 External definitions	1
4.2 Other definitions	2
5 List of acronyms	2
6 SS-MWI stage 1 specification	2
6.1 Description	2
6.1.1 General description	2
6.1.2 Qualifications on applicability to telecommunication services	2
6.2 Procedures	2
6.2.1 Provision / withdrawal	2
6.2.2 Normal procedures	2
6.2.3 Exceptional procedures	3
6.3 Interactions with other Supplementary Services / Additional Network Features	3
6.3.1 Advice of Charge (AOC)	3
6.3.2 Call Deflection (CD)	3
6.3.3 Call Forwarding Unconditional (CFU)	3
6.3.4 Call Forwarding Busy (CFB)	3
6.3.5 Call Forwarding No Reply (CFNR)	3
6.3.6 Call Interception (CINT)	3
6.3.7 Call Intrusion (CI)	3
6.3.8 Call Offer (CO)	4
6.3.9 Call Transfer (CT)	4
6.3.10 Calling/Connected Line Identification Restriction (CLIR)	4
6.3.11 Calling/Connected Name Identification Restriction (CNIR)	4
6.3.12 Calling Line Identification Presentation (CLIP)	4
6.3.13 Calling Name Identification Presentation (CNIP)	4
6.3.14 Connected Line Identification Presentation (COLP)	4
6.3.15 Connected Name Identification Presentation (CONP)	4
6.3.16 Completion of Calls to Busy Subscribers (CCBS)	4
6.3.17 Completion of Calls on No Reply (CCNR)	4
6.3.18 Do Not Disturb (DND)	4
6.3.19 Do Not Disturb Override (DNDO)	4

© ISO/IEC 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

<b>6.3.20</b> Path Replacement (PR)	4
<b>6.3.21</b> Recall (RE)	4
<b>6.3.22</b> Route Restriction Class (RRC)	4
<b>6.4</b> Interworking considerations	4
<b>6.5</b> Overall SDL	4
<b>7</b> SS-MWI stage 2 specification	8
<b>7.1</b> Functional model	8
<b>7.1.1</b> Functional model description	8
<b>7.1.2</b> Description of Functional Entities	8
<b>7.1.3</b> Relationship of functional model to Basic Call functional model	8
<b>7.2</b> Information flows	8
<b>7.2.1</b> Definition of information flows	8
<b>7.2.2</b> Relationship of information flows to Basic Call information flows	11
<b>7.2.3</b> Information flow sequences	11
<b>7.3</b> Functional Entity actions	13
<b>7.3.1</b> Functional Entity actions of FE1	13
<b>7.3.2</b> Functional Entity actions of FE2	13
<b>7.4</b> Functional Entity behaviour	14
<b>7.4.1</b> Behaviour of FE1	14
<b>7.4.2</b> Behaviour of FE2	15
<b>7.5</b> Allocation of Functional Entities to physical equipment	16
<b>7.6</b> Interworking considerations	16

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 15505:1997

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 15505 was prepared by ECMA (as ECMA-241) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

STANDARDSISO.COM : Click to view the full PDF on ISO/IEC 15505:1997

## Introduction

This International Standard is one of a series of standards defining services and signalling protocols applicable to Private Integrated Services Networks. The series uses the ISDN concepts as developed by ITU-T and is also within the framework of standards for open systems interconnection as defined by ISO.

This International Standard specifies the Message Waiting Indication supplementary service.

This International Standard is based upon the practical experience of ECMA member companies and the results of their active and continuous participation in the work of ISO/IEC JTC 1, ITU-T, ETSI and other international and national standardization bodies. It represents a pragmatic and widely based consensus.

There is currently no equivalent service specified by ITU-T or ETSI for public ISDNs.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 15505:1997

This page intentionally left blank

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 15505:1997

# Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Specification, functional model and information flows — Message waiting indication supplementary service

## 1 Scope

This International Standard specifies supplementary service Message Waiting Indication (SS-MWI), which is related to various basic services supported by Private Integrated Services Networks (PISNs). Basic services are specified in ISO/IEC 11574.

This supplementary service MWI enables a Served User to be sent a Message Waiting Indication and also enables this Message Waiting Indication to be cancelled.

Service specifications are produced in three stages, according to the method described in CCITT Rec. I.130. This International Standard contains the stage 1 and stage 2 specifications of SS-MWI. The stage 1 specification (clause 6) specifies the supplementary service as seen by users of PISNs. The stage 2 specification (clause 7) specifies the functional entities involved in the supplementary service and the information flows between them.

## 2 Conformance

In order to conform to this International Standard, a stage 3 standard shall specify signalling protocols and equipment behaviour that are capable of being used in a PISN which supports the supplementary service specified in this International Standard. This means that, to claim conformance, a stage 3 standard is required to be adequate for the support of those aspects of clause 6 (stage 1) and clause 7 (stage 2) which are relevant to the interface or equipment to which the stage 3 standard applies.

## 3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO/IEC 11574:1994, *Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Circuit-mode 64 kbit/s bearer services — Service description, functional capabilities and information flows.*

ISO/IEC 11579-1:1994, *Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Part 1: Reference configuration for PISN Exchanges (PINX).*

ITU-T Rec. I.112:1993, *Vocabulary of terms for ISDNs.*

CCITT Rec. I.130:1988, *Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN.*

ITU-T Rec. I.210:1993, *Principles of telecommunication services supported by an ISDN and the means to describe them.*

ITU-T Rec. Z.100:1993, *Specification and description language.*

## 4 Definitions

For the purposes of this International Standard, the following definitions apply.

### 4.1 External definitions

This International Standard uses the following terms defined in other documents:

- Basic Service (ITU-T Rec. I.210)
- Private Integrated Services Network Exchange (PINX) (ISO/IEC 11579-1)
- Private Integrated Services Network (PISN) (ISO/IEC 11579-1)
- Service (ITU-T Rec. I.112)
- Signalling (ITU-T Rec. I.112)

- Supplementary Service (ITU-T Rec. I.210)
- User (ISO/IEC 11574)

## 4.2 Other definitions

**4.2.1 Served User** : The user to whom the Message Waiting Indication is sent on initiative of the Message Centre.

**4.2.2 Message Centre** : The entity which activates or deactivates the Message Waiting Indication as a result of the storage or retrieval of messages.

**4.2.3 Message Waiting Indication** : An indication to the Served User when messages are waiting for the Served User.

Note - The indication may be a lamp, special tone, display etc. This is outside the scope of this International Standard.

## 5 List of acronyms

ANF	Additional Network Feature
FE	Functional Entity
ISDN	Integrated Services Digital Network
MWI	Message Waiting Indication
PISN	Private Integrated Services Network
PINX	Private Integrated Services Network Exchange
SDL	Specification and Description Language
SS	Supplementary Service

## 6 SS-MWI stage 1 specification

### 6.1 Description

#### 6.1.1 General description

The supplementary service MWI enables a Served User to be sent a Message Waiting Indication and also enables this Message Waiting Indication to be cancelled.

Note - The Message Waiting Indication is sent on activation by the Message Centre.

Note - The Message Waiting Indication is cancelled on deactivation by the Message Centre.

A Served User can receive separate MWIs for each of the basic services for which there is a message waiting.

Note - A basic service for which there is a message waiting would usually be the basic service used to retrieve that message.

#### 6.1.2 Qualifications on applicability to telecommunication services

This supplementary service does not apply directly to any basic telecommunication service. However, a MWI relates to a basic service for which there are messages waiting. It can relate to any of the basic services defined in ISO/IEC 11574.

### 6.2 Procedures

#### 6.2.1 Provision / withdrawal

SS-MWI may be provided or withdrawn after pre-arrangement with the service provider or may be generally available to all users.

#### 6.2.2 Normal procedures

##### 6.2.2.1 Activation, deactivation and interrogation

The PISN shall provide activation / deactivation by the Message Centre. In addition, the PISN may provide interrogation by the Served User.

To activate SS-MWI, the Message Centre shall supply the PISN number and the basic service for which there is a message waiting and may, as an implementation option, add any combination of the following pieces of information: the identity of the Message Centre; the number of messages waiting for the Served User for that basic service; the address of the user that left a message; the time when a message was left; the priority of the highest priority message waiting for that basic service. After activation, SS-MWI may be activated again whenever the number of waiting messages changes.

To deactivate SS-MWI, the Message Centre shall supply the PISN number and the basic service for which there is no longer a message waiting.

As a result of activation, a MWI shall be sent to the Served User. The MWI may include information on messages waiting, if provided by the Message Centre. As a result of deactivation, the MWI at the Served User, for the basic service concerned, shall be cancelled.

When the Message Centre activates or deactivates SS-MWI at the Served User, it shall be provided with an indication of acceptance.

When the Served User interrogates SS-MWI for a particular basic service, the Message Centre shall provide the Served User with an indication of whether SS-MWI is activated for that basic service and may add, as an implementation option, any of the following information:

- the identity of the Message Centre;
- the number of messages waiting;
- the address of the user that left a message;
- the time when a message was left;
- the priority of the highest priority message waiting.

When the Served User interrogates SS-MWI for all basic services, the Message Centre shall provide the Served User with a list of basic services for which SS-MWI is active and, as an implementation option, for each basic service, any of the additional information listed above.

#### **6.2.2.2 Invocation and operation**

Not applicable.

#### **6.2.3 Exceptional procedures**

##### **6.2.3.1 Activation, deactivation and interrogation**

If the Served User cannot accept activation or deactivation, then the Message Centre shall be informed and may also be given the reason. If the PISN cannot accept interrogation, then the Served User shall be informed and may also be given a reason.

##### **6.2.3.2 Invocation and operation**

None.

#### **6.3 Interactions with other Supplementary Services / Additional Network Features**

Interactions with other supplementary services and ANFs for which PISN standards were available at the time of publication of this International Standard are specified below.

##### **6.3.1 Advice of Charge (AOC)**

No interaction.

##### **6.3.2 Call Deflection (CD)**

No interaction.

##### **6.3.3 Call Forwarding Unconditional (CFU)**

No interaction.

##### **6.3.4 Call Forwarding Busy (CFB)**

No interaction.

##### **6.3.5 Call Forwarding No Reply (CFNR)**

No interaction.

##### **6.3.6 Call Interception (CINT)**

No interaction.

##### **6.3.7 Call Intrusion (CI)**

No interaction.

**6.3.8 Call Offer (CO)**

No interaction.

**6.3.9 Call Transfer (CT)**

No interaction.

**6.3.10 Calling/Connected Line Identification Restriction (CLIR)**

No interaction.

**6.3.11 Calling/Connected Name Identification Restriction (CNIR)**

No interaction.

**6.3.12 Calling Line Identification Presentation (CLIP)**

No interaction.

**6.3.13 Calling Name Identification Presentation (CNIP)**

No interaction.

**6.3.14 Connected Line Identification Presentation (COLP)**

No interaction.

**6.3.15 Connected Name Identification Presentation (CONP)**

No interaction.

**6.3.16 Completion of Calls to Busy Subscribers (CCBS)**

No interaction.

**6.3.17 Completion of Calls on No Reply (CCNR)**

No interaction.

**6.3.18 Do Not Disturb (DND)**

No interaction.

**6.3.19 Do Not Disturb Override (DNDO)**

No interaction.

**6.3.20 Path Replacement (PR)**

No interaction.

**6.3.21 Recall (RE)**

No interaction.

**6.3.22 Route Restriction Class (RRC)**

No interaction.

**6.4 Interworking considerations**

A PISN may be able to accept MWIs from a Message Centre in another network. In this case, the PISN may also be able to interrogate that Message Centre.

A PISN may be able to send MWIs to a Served User in another network. In this case, the PISN may also be able to accept interrogation requests from that Served User.

**6.5 Overall SDL**

Figure 1 contains the dynamic description of SS-MWI using the Specification and Description Language (SDL) defined in ITU-T Rec. Z.100 (1993). The SDL process represents the behaviour of the network in providing SS-MWI.

Input signals from the left and output signals to the left represent primitives from and to the Message Centre.

Input signals from the right and output signals to the right represent primitives from and to the Served User.




Figure 1 (part 1) - SS-MWI Overall SDL

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 15505:1997




Figure 1 (part 2) - SS-MWI Overall SDL

STANDARDSISO.COM: Click to view the full PDF of ISO/IEC 15505:1997




Figure 1 (part 3) - SS-MWI Overall SDL

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 15505:1997

## 7 SS-MWI stage 2 specification

### 7.1 Functional model

#### 7.1.1 Functional model description

The functional model shall comprise the following Functional Entities (FEs):

FE1 Message Centre's control entity;

FE2 Served User's control entity.

The following relationship shall exist between these FEs:

ra between FE1 and FE2.

Figure 2 shows these FEs and this relationship.




Figure 2 - Functional model for SS-MWI

#### 7.1.2 Description of Functional Entities

##### 7.1.2.1 Message Centre control entity, FE1

This Functional Entity:

- sends an activation / deactivation request to FE2 on initiative of the Message Centre;
- receives the result of the activation / deactivation request from FE2 and informs the Message Centre of the result;
- receives the interrogation request from FE2;
- checks if the interrogation request is allowed to be performed;
- sends the status of the Message Waiting Indication to FE2, in the case of interrogation.

##### 7.1.2.2 Served User's control entity, FE2

This Functional Entity:

- receives the activation / deactivation request from FE1;
- checks if the activation / deactivation request is allowed to be performed;
- sends the result of the activation / deactivation request to FE1;
- sends the interrogation request to FE1;
- receives the status of the Message Waiting Indication from FE1, in the case of interrogation;
- sends/cancels MWIs to/at the Served User.

#### 7.1.3 Relationship of functional model to Basic Call functional model

Not applicable.

### 7.2 Information flows

#### 7.2.1 Definition of information flows

In the tables listing the elements in information flows, the column headed "Request" indicates which of these elements are mandatory (M) and which are optional (O) in a request/indication information flow, and the column headed "Confirm" (confirmed information flows only) indicates which of these elements are mandatory (M) and which are optional (O) in a response/confirmation information flow.

### 7.2.1.1 ra\_MWI\_Activate

ra\_MWI\_Activate is a confirmed information flow across ra from FE1 to FE2 used to activate SS-MWI.

Table 1 lists the elements within the ra\_MWI\_Activate information flow.

**Table 1 - Content of ra\_MWI\_Activate**

Element	Request	Confirm	NOTE
Served User's number	M		1
Basic Service	M		2
Number of messages	O		3
Priority	O		4
Message Centre identity	O		5
Originating number	O		6
Timestamp	O		7
Result		M	8

Note 1 - This is the Served User's PISN number.

Note 2 - This indicates a particular basic service.

Note 3 - This indicates the number (non-zero) of messages waiting for the Served User. If this field is omitted, then there is one or more than one message waiting.

Note 4 - This indicates the priority of the highest priority message waiting.

Note 5 - This identifies the Message Centre at which messages are waiting.

Note 6 - This indicates the PISN number of the user that left a message.

Note 7 - This indicates the time when a message was left.

Note 8 - This indicates acceptance or the reason for rejection.

**7.2.1.2 ra\_MWI\_Deactivate**

ra\_MWI\_Deactivate is a confirmed information flow across ra from FE1 to FE2 used to deactivate SS-MWI.

Table 2 lists the elements within the ra\_MWI\_Deactivate information flow.

**Table 2 - Content of ra\_MWI\_Deactivate**

Element	Request	Confirm	NOTE
Served User's number	M		1
Basic Service	M		2
Message Centre identity	O		3
Result		M	4

Note 1 - This is the Served User's PISN number.

Note 2 - This indicates a particular basic service.

Note 3 - This identifies the Message Centre at which messages have been retrieved. This element is mandatory if included in a previous ra\_MWI\_Activate information flow.

Note 4 - This indicates acceptance or the reason for rejection.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 15505:1997

### 7.2.1.3 ra\_MWI\_Interrogate

ra\_MWI\_Interrogate is a confirmed information flow across ra from FE2 to FE1 used to interrogate SS-MWI.

Table 3 lists the elements within the ra\_MWI\_Interrogate information flow.

**Table 3 - Content of ra\_MWI\_Interrogate**

Element	Request	Confirm	NOTE
Served User's number	M		1
Basic Service	M	M	2
Number of messages		O	3
Priority		O	4
Message Centre identity	O	O	5
Originating number		O	6
Timestamp		O	7
Result		M	8

Note 1 - This is the Served User's PISN number.

Note 2 - In the request, this indicates a particular basic service or all basic services. The confirmation shall provide a list of zero or more basic services for which SS-MWI is activated.

Note 3 - This indicates the number (non-zero) of messages waiting for the Served User. If provided, and the request was for all basic services, it shall be repeated for each basic service for which SS-MWI is active.

Note 4 - This indicates the priority of the highest priority message waiting. If provided, and the request was for all basic services, it shall be repeated for each basic service for which SS-MWI is active.

Note 5 - This identifies the Message Centre interrogated.

Note 6 - This indicates the PISN number of the user that left a message.

Note 7 - This indicates the time when a message was left.

Note 8 - This indicates acceptance or the reason for rejection.

### 7.2.2 Relationship of information flows to Basic Call information flows

ra\_MWI\_Activate, ra\_MWI\_Deactivate and ra\_MWI\_Interrogate are sent independently of basic call information flows.


### 7.2.3 Information flow sequences

A stage 3 standard for SS-MWI shall provide signalling procedures in support of the information flow sequences specified in the figures. In addition, signalling procedures should be provided to cover other sequences arising from error situations, interactions with Basic Call, interactions with other supplementary services, different topologies, etc.

Within a column representing an SS-MWI Functional Entity, the numbers refer to Functional Entity actions listed in 7.3.

**7.2.3.1 Activation of SS-MWI**


Figure 3 shows in generic form the information flow sequence for activation of SS-MWI.



**Figure 3 - Information flow sequence for activation of SS-MWI**

**7.2.3.2 Deactivation of SS-MWI**

Figure 4 shows in generic form the information flow sequence for deactivation of SS-MWI.



**Figure 4 - Information flow sequence for deactivation of SS-MWI**

### 7.2.3.3 Interrogation of SS-MWI

Figure 5 shows in generic form the information flow sequence for interrogation of SS-MWI.




Figure 5 - Information flow sequence for interrogation of SS-MWI

## 7.3 Functional Entity actions

### 7.3.1 Functional Entity actions of FE1

- 101 Send ra\_MWI\_Activate req/ind to FE2 in order to activate SS-MWI at the Served User.
- 102 Receive ra\_MWI\_Activate con/res from FE2.
- 103 Send ra\_MWI\_Deactivate req/ind to FE2 in order to deactivate SS-MWI at the Served User.
- 104 Receive ra\_MWI\_Deactivate con/res from FE2.
- 105 Process ra\_MWI\_Interrogate and if SS-MWI is allowed to be interrogated, obtain the current status of the Message Waiting Indication and send it back to FE2.

### 7.3.2 Functional Entity actions of FE2

- 201 Process ra\_MWI\_Activate and if SS-MWI is allowed to be activated at the Served User, activate SS-MWI at the Served User and send back a confirmation of the activation to FE1.
- 202 Process ra\_MWI\_Deactivate and if SS-MWI is allowed to be deactivated at the Served User, deactivate SS-MWI at the Served User and send back a confirmation of the deactivation to FE1.
- 203 Send ra\_MWI\_Interrogate req/ind to FE1 in order to interrogate SS-MWI.
- 204 Receive ra\_MWI\_Interrogate con/res from FE1.