
Information technology — Digitally recorded media for information interchange and storage — Quality discrimination method for optical disks and operating method of storage systems for long-term data preservation

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 18630:2023



STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 18630:2023



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	2
4 Quality of optical disk.....	4
4.1 Types and quality indicators of optical disk (CD, DVD and BD).....	4
4.2 Lifetime estimation of optical disks.....	4
5 Recordable optical disk and drive used for long-term data preservation.....	5
5.1 General.....	5
5.2 Recordable optical disk used for long-term data preservation.....	5
5.3 Drive used for long-term data preservation.....	5
5.4 Combination of recordable optical disk and drive.....	5
6 Quality discrimination method for recordable optical disk.....	5
6.1 General.....	5
6.2 Test method.....	5
6.2.1 Preparation for test.....	5
6.2.2 Test parameters.....	5
6.2.3 Recording method of optical disk for test.....	6
6.2.4 Playback evaluation drive.....	6
6.3 Quality classification by data error testing.....	6
7 Quality test of recordable optical disk and operation of long-term storage systems.....	7
7.1 General.....	7
7.2 Initial quality test.....	7
7.3 Periodic quality test.....	8
8 Quality test of read-only optical disk and operation of long-term storage systems.....	10
8.1 General.....	10
8.2 Initial quality test.....	10
8.2.1 Preparation for test.....	10
8.2.2 Test parameters.....	10
8.2.3 Playback evaluation drive.....	10
8.2.4 Test operation.....	10
8.3 Periodic quality test.....	11
9 Handling and storage of optical disks.....	12
Annex A (normative) Defect management on BD recordable disk.....	13
Bibliography.....	15

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 23, *Digitally Recorded Media for Information Interchange and Storage*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Introduction

In the digital information society, there is no secure means for storing and accumulating rapidly growing digital information safely and on a permanent basis. There is therefore a concern that the world will face a critical situation and significant problem in the near future. Within this context, optical disks are increasingly being considered as a solution for archiving storage media with high capacity because of their unique features (such as low cost, high compatibility and low energy consumption) and more specifically, their data storage capability without power consumption.

On the other hand, the data storage performance of an optical disk often depends on the initial recording quality and storage environment conditions. Therefore, when an optical disk is used for long-term data storage, it is desirable to check its estimated lifetime and initial recording quality by using a combination of a good quality optical disk and a good quality recording drive.

For this reason, this document specifies quality discrimination criteria using the initial quality of recordable optical disks as an index. It also specifies a quality judgement method for storage systems for long-term data preservation, including the consistency of the recordable optical disks and recording drives to ensure the quality of recorded digital data. In this document, recordable (write-once) optical disks are adopted as long-term storage media to ensure the security of the stored digital data when giving greater importance to evidence, because physical overwriting and deletion by erroneous or intentional operation can be prevented.

This document is also applicable to read-only optical disks such as CD-ROM, DVD-ROM and BD-ROM, specifying the quality judgement method for long-term data preservation.

This document enables users to build data storage systems that use recordable and/or read-only optical disks for long-term data preservation. Optical disks with sufficient quality can be confirmed based on the results of the initial quality test. Through the periodic quality test described in this document, the possibility of data restoration from the optical disk can be continuously monitored. Using this document, manufacturers will be able to supply recordable and read-only optical disks incorporated with suitable recording and playback drives for building data storage systems for long-term data preservation.

In the future, it will be possible to build data storage systems using optical disks for storing and accumulating important digital information safely and on a permanent basis, for consumer use and professional use. The safe and secure progress of the digital information society towards greater sophistication can be expected.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 18630:2023

Information technology — Digitally recorded media for information interchange and storage — Quality discrimination method for optical disks and operating method of storage systems for long-term data preservation

1 Scope

This document specifies a quality discrimination method for optical disks and the operating method of storage systems for long-term digital data preservation using optical disks and optical disk drives (hereinafter referred to as "drives").

It is applicable to recordable (write-once) optical disks which can prevent physical overwriting and deletion by erroneous or intentional operation in contexts where greater importance is given to evidence. It is also applicable to read-only (ROM) optical disks.

This document specifies:

- combinations of recordable optical disks and drives used for long-term data preservation;
- quality discrimination criteria for recordable optical disks and the operation method of long-term storage systems;
- a quality test for read-only optical disks and the operation method of long-term storage systems;
- quality discrimination criteria for BD recordable disks when adopting defect management.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 10149, *Information technology — Data interchange on read-only 120 mm optical data disks (CD-ROM)*

ISO/IEC 12862, *Information technology — 120 mm (8,54 Gbytes per side) and 80 mm (2,66 Gbytes per side) DVD recordable disk for dual layer (DVD-R for DL)*

ISO/IEC 16448, *Information technology — 120 mm DVD — Read-only disk*

ISO/IEC 16449, *Information technology — 80 mm DVD — Read-only disk*

ISO/IEC 16963, *Information technology — Digitally recorded media for information interchange and storage — Test method for the estimation of lifetime of optical disks for long-term data storage*

ISO/IEC 17344, *Information technology — Data interchange on 120 mm and 80 mm optical disk using +R format — Capacity: 4,7 Gbytes and 1,46 Gbytes per side (recording speed up to 16X)*

ISO/IEC 23912, *Information technology — 80 mm (1,46 Gbytes per side) and 120 mm (4,70 Gbytes per side) DVD Recordable Disk (DVD-R)*

ISO/IEC 25434, *Information technology — Data interchange on 120 mm and 80 mm optical disk using +R DL format — Capacity: 8,55 Gbytes and 2,66 Gbytes per side (recording speed up to 16X)*

ISO/IEC 30190, *Information technology — Digitally recorded media for information interchange and storage — 120 mm Single Layer (25,0 Gbytes per disk) and Dual Layer (50,0 Gbytes per disk) BD Recordable disk*

ISO/IEC 30191, *Information technology — Digitally recorded media for information interchange and storage — 120 mm Triple Layer (100,0 Gbytes single sided disk and 200,0 Gbytes double sided disk) and Quadruple Layer (128,0 Gbytes single sided disk) BD Recordable disk*

ECMA-394, *Recordable Compact Disk Systems CD-R Multi-Speed*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

maximum C1 error

Max C1

maximum number of C1 errors per second averaged over any 10 s in one of the relevant areas on a CD, measured at the input of error correction decoder under the standard data transfer rate

Note 1 to entry: See ISO/IEC 10149, ISO/IEC 16963, and ECMA 394.

3.2

maximum PI SUM 8

Max PI SUM 8

maximum parity of inner code (PI) error count at any consecutive 8 *error correction code* (3.7) blocks in one of the relevant areas on a DVD, measured at the first pass of the decoder before correction

Note 1 to entry: See ISO/IEC 12862, ISO/IEC 16448, ISO/IEC 16449, ISO/IEC 17344, ISO/IEC 23912, and ISO/IEC 25434.

3.3

maximum random symbol error rate

Max RSER

maximum value of random symbol error rate in one of the relevant areas on a BD excluding burst errors of 40 bytes or more, measured at the input of error-correction decoder

Note 1 to entry: See ISO/IEC 30190, and ISO/IEC 30191.

Note 2 to entry: Maximum random symbol error rate shall be measured by averaging over any N consecutive *long distance code* (3.8) blocks to reduce the impact of burst errors, with the condition that all blocks are recorded in a continuously written sequence, in a discontinuously written sequence excluding disk defects. In this document, the number of N shall be 10 000, and when *defect management* (3.17) is applied, the number of N shall be 10 000 at maximum.

3.4

maximum burst error

Max BE

maximum sum of the lengths of burst errors with length greater than or equal to 40 bytes in one recording-unit block in one of the relevant areas on a BD

Note 1 to entry: See ISO/IEC 30190 and ISO/IEC 30191.

Note 2 to entry: The number of burst errors is not covered in this document.

3.5**error rate**

rate of data errors on the recorded disk measured before error correction is applied

3.6**uncorrectable error**

error in the read-out data that cannot be corrected by the error-correction decoders

[SOURCE: ISO/IEC 29121:2021, 3.18]

3.7**error correction code****ECC**

mathematical computation yielding check bytes used for the detection and correction of errors in data

3.8**long distance code****LDC**

error correction code (3.7) that increases the correction ability by increasing the code length and assigning more inspection symbols

Note 1 to entry: Long distance code is used in BD disks.

Note 2 to entry: See ISO/IEC 30190, and ISO/IEC 30191.

3.9**initial quality test**

verification test of the data quality recorded on an optical disk before storing

3.10**periodic quality test**

periodic test of the data quality recorded on an optical disk during preservation period

3.11**constant linear velocity****CLV**

rotation control method of optical disk that keeps the linear velocity constant

3.12**data migration**

process to copy data from one storage device or medium to another

3.13**lifetime**

time that information is retrievable in a *system* (3.15)

[SOURCE: ISO/IEC 29121:2021, 3.9]

3.14**preservation period**

period during which an optical disk has been stored since data was recorded

3.15**system**

combination of hardware, software, storage medium and documentation, used to record, retrieve and reproduce information

[SOURCE: ISO/IEC 16963:2017, 3.20]

**3.16
defect management
DM**

method for handling the defective areas on the BD recordable disk

[SOURCE: ISO/IEC 17345:2006, 4.10, modified — disk type ("BD recordable") has been added.]

**3.17
defective cluster**

cluster in a user-data area that has been registered in a defect list as unreliable or uncorrectable

Note 1 to entry: See ISO/IEC 30190, and ISO/IEC 30191.

[SOURCE: ISO/IEC 30190:2021, 3.6, modified — Note 1 to entry has been added.]

4 Quality of optical disk

4.1 Types and quality indicators of optical disk (CD, DVD and BD)

The types and quality indicators of typical CD, DVD and BD disks are shown in [Table 1](#).

Table 1 — Types and quality indicators of typical optical disks

Type of optical disk		Recording layer	Number of layers	Capacity	Typical quality indicator ^a
CD	CD-ROM	Read-only	1	640 MB / 700 MB	C1 error ^b
	CD-R	Write-once			
DVD	DVD-ROM	Read-only	1	4,7 Gbytes	PI SUM 8 ^c
	DVD-R	Write-once	2	8,5 Gbytes	
	+R				
BD	BD-ROM	Read-only	1	25 Gbytes	RSER ^d and burst error ^e
			2	50 Gbytes / 66 Gbytes	
			3	100 Gbytes	
	BD recordable disk	Write-once	1	25 Gbytes	
			2	50 Gbytes	
			3	100 Gbytes	
			4	128 Gbytes	
		3, both sides	200 Gbytes		

NOTE JIS Z 6017 is used as a method for long-term storage of digitized documents using writable CD, DVD and BD disks, and ISO/IEC 29121 is used for data migration methods.

^a The test parameters specified in [6.2.2](#) are used for the quality discrimination method for each type of optical disk.

^b C1 error is the number of errors as defined in ISO/IEC 10149.

^c PI SUM 8 is the PI error count as defined in ISO/IEC 16448.

^d RSER is the random symbol error rate as defined in ISO/IEC 30190.

^e Burst error is the sum of the lengths of burst errors as defined in ISO/IEC 30190.

4.2 Lifetime estimation of optical disks

The lifetime of an optical disk shall be estimated in accordance with the test method specified in ISO/IEC 16963, with the following conditions.

- Controlled storage-condition (temperature, $T = 25 \text{ °C}$ and relative humidity, $R_H = 50 \%$) as the ambient storage-condition for the lifetime estimation.

- 95 % lower confidence bound of B_5 Life [= $(B_5 \text{ Life})_L$] for the maximum-likelihood method with the least squares method, or the point estimates of the 5th percentile with variation (= B_{5V} Life) for the acceleration-factor method, as the lifetime estimation.

5 Recordable optical disk and drive used for long-term data preservation

5.1 General

This clause specifies the requirements for long-term data preservation using optical disks with regard to recordable optical disks and drives used for recording. By adopting a combination of high quality recordable optical disks and drives dedicated to long-term storage, deterioration of recorded data quality can be reduced during long-term data preservation.

5.2 Recordable optical disk used for long-term data preservation

Use the recordable optical disk which is designed for long-term data preservation, the lifetime of which is estimated by the test method specified in [4.2](#). It is also recommended that the disk be selected by screening inspection of defects at the shipment.

5.3 Drive used for long-term data preservation

Use the drive which is equipped with a control program that optimizes the recording characteristics according to the optical disk to be used.

The rotation control method of the optical disk during recording shall be a constant linear velocity (CLV), and the linear velocity shall be the speed specified or recommended by the combination of the recordable optical disk and the drive for recording.

5.4 Combination of recordable optical disk and drive

Adopt the combination of the recordable optical disk specified in [5.2](#) and the drive specified in [5.3](#) and confirm that the recording quality meets the criteria specified in [6.3](#). For when defect management is applied on a BD recordable disk specified by ISO/IEC 30190 or ISO/IEC 30191, the operating method and test parameters specified in [Annex A](#) shall be adopted to confirm the recording quality criteria in [6.3](#).

6 Quality discrimination method for recordable optical disk

6.1 General

This clause specifies the test method for quality discrimination and the quality criteria for recordable optical disks for long-term data preservation.

6.2 Test method

6.2.1 Preparation for test

Before conducting the test, the optical disk should be checked for dust, fingerprints and other stains. If there is dirt, remove it according to the handling method specified in [Clause 9](#). Microscopic observation can reveal physical deterioration such as detachment of the protective coating and small holes.

6.2.2 Test parameters

The data error parameters used in the test are as follows.

- For CD-R specified by ECMA-394, measure the maximum C1 error (Max C1).

- b) For DVD-R specified by ISO/IEC 12862 or ISO/IEC 23912, and + R disk specified by ISO/IEC 17344 or ISO/IEC 25434, measure the maximum PI SUM 8 (Max PI SUM 8).
- c) For BD recordable disks specified by ISO/IEC 30190 or ISO/IEC 30191, measure the maximum random symbol error rate (Max RSER) and the maximum burst error (Max BE). In the case that defect management is applied, measure the Max RSER and the Max BE after data replacement (see [Annex A](#)).

6.2.3 Recording method of optical disk for test

The optical disk used for the test shall be recorded by the drive for which combination quality is confirmed as shown in [5.3](#) and [5.4](#), using the optimum conditions determined by the optical disk manufacturer and the drive manufacturer.

It is recommended to record the entire user data area of the optical disk with arbitrary user data, but three zones may be specified for the inner radius, middle radius and outer radius, depending on the radial position of the optical disk (for example, 25 mm, 40 mm, and 55 mm, each 5 mm width, etc.). For multi-layer optical disks, record all recording layers.

6.2.4 Playback evaluation drive

The recorded optical disk shall be tested with a reference drive conforming to the specifications of ECMA-394 for CD-R, of ISO/IEC 12862 or ISO/IEC 23912 for DVD-R, of ISO/IEC 17344 or ISO/IEC 25434 for +R and of ISO/IEC 30190 or ISO/IEC 30191 for BD recordable disks, or a playback evaluation drive with equivalent data error detection performance. In the evaluation, the test is performed by installing a reference drive or a playback evaluation drive under the following environmental conditions:

- temperature: 15 °C to 30 °C;
- relative humidity: 20 % to 75 %.

The playback evaluation drive is required to confirm a certain correlation with the playback characteristics of the reference drive, by using a reference disk or a calibration disk that conforms to the reference disk prepared by the manufacturer. The same applies to a playback evaluation drive that doubles as a recording drive.

6.3 Quality classification by data error testing

The quality grade of the optical disk in [Table 2](#) is determined by combining the test results of data errors specified in [6.2.2](#) and the results of the lifetime estimation test specified in [4.2](#).

For the test of data errors, record data in accordance with [6.2.3](#) and use the playback evaluation drive specified in [6.2.4](#) as follows.

- a) Test the entire area where the data is recorded. If recording zones are specified in [6.2.3](#), test the recording areas of those zones. For multi-layer optical disks, inspect all recorded layers.
- b) The testing value shall be the maximum value in the test area(s).

Table 2 — Quality criteria of recordable optical disks

Quality grade	Type of optical disk			Estimate value of lifetime
	CD-R	DVD-R, +R	BD recordable disk	
	Test parameter			
	Max C1	Max PI SUM 8	Max RSER ^a and Max BE ^b	
Grade10	Less than 110	Less than 140	Less than $5,0 \times 10^{-4}$ and less than 800 bytes	10 years or more
Grade30	Less than 80	Less than 100	Less than $3,5 \times 10^{-4}$ and less than 800 bytes	30 years or more
Grade100	Less than 80	Less than 100	Less than $3,5 \times 10^{-4}$ and less than 800 bytes	100 years or more

^a RSER = random symbol error rate.
^b BE = burst error.

7 Quality test of recordable optical disk and operation of long-term storage systems

7.1 General

This clause specifies a quality test and operating method for storage systems for long-term data preservation using a recordable optical disk.

- Users shall use optical disks and drives that satisfy the provisions of [Clause 5](#) and a playback evaluation drive as specified in [6.2.4](#) to operate long-term storage systems.
- Even if the quality grade of the optical disk has been confirmed, when the storage period of a blank disk exceeds the disk supplier's recommendation, the recording characteristics can have changed due to the influence of the environment, so it is recommended not to use it.
- Before recording and playback, it is recommended to check that the recording surface of the optical disk is free of dirt and dust. If dirt or dust is present, it should be removed properly according to [Clause 9](#).
- When recording is intended in an environment that is a significantly different temperature and humidity from the environment in which the optical disk was stored, the angular deviation of the optical disk can change, so it is recommended to leave the optical disk for a sufficient time in the recording environment before recording.

7.2 Initial quality test

The recorded optical disk shall be measured for data errors specified in [6.2.2](#) using a playback evaluation drive as specified in [6.2.4](#) before storing. This initial quality is determined according to the quality grade from [Table 2](#).

The initial quality test shall be as follows.

- a) Test the entire area where the data was recorded. For multi-layer optical disks, test all recorded layers. The test result value shall be the maximum value within the test area of the optical disk.
- b) Inspect all recorded optical disks.
- c) If the test result does not meet the quality criteria specified in [Table 2](#) or an uncorrectable error occurs in the data area, recreate it.

If dirt, dust, etc. on the recording surface of the optical disk are properly removed according to [Clause 9](#) and it is confirmed that the quality criteria are met by retesting, there is no need to recreate.

- d) All test results (error distribution on optical disks, etc.), recording speed and inspection speed shall be recorded in the management ledger and used as judgment data for data migration during the preservation period.

7.3 Periodic quality test

The stored optical disk is periodically tested for data errors specified in [6.2.2](#) using a playback evaluation drive as specified in [6.2.4](#), and the quality shall be judged by [Table 3](#) or [Table 4](#) corresponding to the quality grade of the optical disk.

- a) For the disk to be inspected, test the entire area where the data was recorded. For multi-layer optical disks, test all recorded layers. The test result value shall be the maximum value within the test area.
- b) Perform a sampling test from the stored optical disks with the same recording conditions (lot). For lots whose sampling test results are Category 2 or Category 3, it is recommended to test all of them.
- c) If Category 3 occurs, take immediate measures, i.e. recreate it. In the case of Category 2, it will be recreated within one year.

If dirt, dust, etc. on the recording surface of the optical disk are properly removed according to [Clause 9](#) and it is confirmed that Category 1 is satisfied by re-inspection, there is no need to recreate it.

- d) The frequency of the periodic performance test should be approximately every 5 years, and should be determined according to the preservation plan of the data to be stored.

The periodic performance test interval can be changed according to the quality grade of the optical disk used. Regarding changes, it is recommended to conform to ISO/IEC 29121.

NOTE There is a complicated failure mechanism in the deterioration of the data quality recorded on the optical disk. The lifetime of an optical disk depends not only on storage temperature and humidity, but also on many other factors such as light exposure, corrosive gases, dirt, handling, and drives for playback. As a result, when the storage environment is harsh, it is necessary to increase the frequency of periodic quality tests. In other words, the frequency of periodic quality tests depends on both the quality of the optical disk and the storage environment.

- e) All test results (error distribution on optical disks, etc.), recording speed and inspection speed shall be recorded in the management ledger. When migrating data, record the work contents in the management ledger.

Table 3 — Data error classification for periodic quality test (Grade10)

Category		Media type		
		CD-R	DVD-R, +R	BD recordable disk
		Test parameter		
		Max C1	Max PI SUM 8	Max RSER ^a and Max BE ^b
1	In good condition	Less than 160	Less than 200	Less than $7,1 \times 10^{-4}$ and less than 1 200 bytes
2	Measures within one year	160 or more and less than 220	200 or more and less than 280	$7,1 \times 10^{-4}$ or more and less than $1,0 \times 10^{-3}$ and/or 1 200 bytes or more and less than 1 900 bytes
3	Immediate measures	220 or more	280 or more	$1,0 \times 10^{-3}$ or more and/or 1 900 bytes or more
^a RSER = random symbol error rate. ^b BE = burst error.				

Table 4 — Data error classification for periodic quality test (Grade30 and Grade100)

Category		Media type		
		CD-R	DVD-R, +R	BD recordable disk
		Test parameter		
		Max C1	Max PI SUM 8	Max RSER ^a and Max BE ^b
1	In good condition	Less than 110	Less than 140	Less than $5,0 \times 10^{-4}$ and less than 1 200 bytes
2	Measures within one year	110 or more and less than 220	140 or more and less than 280	$5,0 \times 10^{-4}$ or more and less than $1,0 \times 10^{-3}$ and/or 1 200 bytes or more and less than 1 900 bytes
3	Immediate measures	220 or more	280 or more	$1,0 \times 10^{-3}$ or more and/or 1 900 bytes or more
^a RSER = random symbol error rate. ^b BE = burst error.				

8 Quality test of read-only optical disk and operation of long-term storage systems

8.1 General

This clause specifies a quality test and operating method for storage systems for long-term data preservation using a read-only optical disk.

8.2 Initial quality test

8.2.1 Preparation for test

Before conducting the test, the optical disk should be checked for dust, fingerprints and other stains. If there is dirt, remove it according to the handling method specified in [Clause 9](#).

8.2.2 Test parameters

The data error parameters used in the test are as follows.

- a) For CD-ROM specified by ISO/IEC 10149, measure the maximum C1 error (Max C1).
- b) For DVD-ROM specified by ISO/IEC 16448 or ISO/IEC 16449, measure the maximum PI SUM 8 (Max PI SUM 8).
- c) For BD-ROM, measure the maximum random symbol error rate (Max RSER) and maximum burst error (Max BE).

NOTE ISO/IEC 30190, ISO/IEC 30191 and Reference [6] contain further information on the random symbol error rate and burst error.

8.2.3 Playback evaluation drive

The optical disk shall be tested with a reference drive conforming to the specifications of ISO/IEC 10149 for CD-ROM, ISO/IEC 16448 or ISO/IEC 16449 for DVD-ROM and ISO/IEC 30190 or ISO/IEC 30191 for BD-ROM, or a playback evaluation drive with equivalent data error detection performance. In the evaluation, the test is performed by installing a reference drive or a playback evaluation drive under the following environmental conditions:

- temperature: 15 °C to 30 °C;
- relative humidity: 20 % to 75 %.

The playback evaluation drive is required to confirm that there is a certain correlation with the playback characteristics of the reference drive, by using a reference disk or a calibration disk that conforms to the reference disk prepared by the manufacturer. The same applies to a playback evaluation drive that doubles as a recording drive.

8.2.4 Test operation

Before storing, the optical disk shall be measured for data errors as specified in [8.2.2](#) using the playback evaluation drive as specified in [8.2.3](#) and the initial quality shall be determined using [Table 5](#).

The initial quality test shall be as follows.

- a) Test the entire area where the data exist. For multi-layer optical disks, test all layers. The test result value shall be the maximum value within the test area of the optical disk.
- b) Inspect all optical disks to be stored.

- c) If Category 3 conditions occur (see [Table 5](#)), take immediate measures, i.e. obtain another copy of the same disk, or the data may be migrated to a recordable optical disk according to the means specified in [Clause 5](#), [Clause 6](#) and [Clause 7](#) when the data can be retrieved. In the case of Category 2 conditions, take measures within one year.

If dirt, dust, etc. on the recording surface of the optical disk are properly removed according to [Clause 9](#) and it is confirmed that Category 1 conditions are satisfied by re-testing, there is no need to take measures.

- d) All test results (error distribution on optical disks, etc.) and inspection speed shall be recorded in the management ledger as judgment data for taking measures during the preservation period. When migrating data to recordable optical disks, record the work contents in the management ledger.

Table 5 — Data error classification for quality test of read-only optical disk

Category		Media type		
		CD-ROM	DVD-ROM	BD-ROM
		Test parameter		
		Max C1 error	Max PI SUM 8	Max RSER ^a and Max BE ^b
1	In good condition	Less than 110	Less than 140	Less than $5,0 \times 10^{-4}$ and less than 1 200 bytes
2	Measures within one year	110 or more and less than 220	140 or more and less than 280	$5,0 \times 10^{-4}$ or more and less than $1,0 \times 10^{-3}$ and/or 1 200 bytes or more and less than 1 900 bytes
3	Immediate measures	220 or more	280 or more	$1,0 \times 10^{-3}$ or more and/or 1 900 bytes or more
^a RSER = random symbol error rate. ^b BE = burst error.				

8.3 Periodic quality test

The stored optical disk is periodically tested for data errors as specified in [8.2.2](#) using a playback evaluation drive as specified in [8.2.3](#). The disk quality is determined using [Table 5](#).

- a) For the disk to be inspected, test the entire area where the data exists. For multi-layer optical disks, test all layers. The test result value shall be the maximum value within the test area.
- b) If Category 3 conditions occur, take immediate measures, i.e. obtain another copy of the same disk, or the data may be migrated to a recordable optical disk according to the means specified in [Clause 5](#), [Clause 6](#) and [Clause 7](#) when the data can be retrieved. In the case of Category 2 conditions, take measures within one year.

If dirt, dust, etc. on the recording surface of the optical disk are properly removed according to [Clause 9](#) and it is confirmed that Category 1 conditions are satisfied by re-testing, there is no need to take measures.