

---

---

**Linux Standard Base (LSB) core  
specification 3.1 —**

Part 8:  
**Specification for S390X architecture**

*Spécifications 3.1 relatives au noyau de base normalisé Linux (LSB) —  
Partie 8: Spécifications pour l'architecture S390X*

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 23360-8:2006

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 23360-8:2006

© ISO/IEC 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

**Linux Standard Base Core Specification for S390X 3.1**

ISO/IEC 23360-8:2006(E)

Copyright © 2006 ISO/IEC

This standard includes material that has been provided by the Free Standards Group under the GNU Free Documentation License Version 1.1 published by the Free Software Foundation.

Portions of the text are copyrighted by the following parties:

- The Regents of the University of California
- Free Software Foundation
- Ian F. Darwin
- Paul Vixie
- BSDI (now Wind River)
- Andrew G Morgan
- Jean-loup Gailly and Mark Adler
- Massachusetts Institute of Technology

These excerpts are being used in accordance with their respective licenses.

Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.

UNIX is a registered trademark of The Open Group.

LSB is a trademark of the Free Standards Group in the United States and other countries.

AMD is a trademark of Advanced Micro Devices, Inc.

Intel and Itanium are registered trademarks and Intel386 is a trademark of Intel Corporation.

PowerPC is a registered trademark and PowerPC Architecture is a trademark of the IBM Corporation.

S/390 is a registered trademark of the IBM Corporation.

OpenGL is a registered trademark of Silicon Graphics, Inc.

## Contents

Foreword .....	vii
Introduction .....	viii
<b>I Introductory Elements .....</b>	<b>0</b>
1 Scope.....	1
1.1 General.....	1
1.2 Module Specific Scope.....	1
2 References .....	2
2.1 Normative References .....	2
2.2 Informative References/Bibliography .....	3
3 Requirements .....	6
3.1 Relevant Libraries .....	6
3.2 LSB Implementation Conformance .....	6
3.3 LSB Application Conformance.....	7
4 Definitions .....	9
5 Terminology .....	10
6 Documentation Conventions .....	12
<b>II Executable and Linking Format (ELF).....</b>	<b>13</b>
7 Introduction.....	14
8 Low Level System Information.....	15
8.1 Machine Interface.....	15
8.2 Function Calling Sequence.....	15
8.3 Operating System Interface .....	16
8.4 Process Initialization.....	17
8.5 Coding Examples .....	17
8.6 Debug Information.....	17
9 Object Format.....	18
9.1 Introduction .....	18
9.2 ELF Header .....	18
9.3 Sections .....	18
9.4 Symbol Table .....	19
9.5 Relocation.....	19
10 Program Loading and Dynamic Linking .....	20
10.1 Introduction .....	20
10.2 Program Loading .....	20
10.3 Dynamic Linking.....	20
<b>III Base Libraries .....</b>	<b>21</b>
11 Libraries .....	22
11.1 Program Interpreter/Dynamic Linker .....	22
11.2 Interfaces for libc .....	22
11.3 Data Definitions for libc .....	36
11.4 Interfaces for libm .....	48
11.5 Data Definitions for libm.....	52
11.6 Interfaces for libpthread.....	54
11.7 Data Definitions for libpthread .....	56
11.8 Interfaces for libgcc_s .....	57
11.9 Data Definitions for libgcc_s.....	57
11.10 Interface Definitions for libgcc_s.....	58
11.11 Interfaces for libdl .....	64
11.12 Data Definitions for libdl .....	65
11.13 Interfaces for libcrypt.....	65
<b>IV Utility Libraries.....</b>	<b>66</b>
12 Libraries .....	67

12.1 Interfaces for libz.....	67
12.2 Data Definitions for libz.....	67
12.3 Interfaces for libncurses.....	67
12.4 Data Definitions for libncurses.....	68
12.5 Interfaces for libutil.....	68
<b>V Package Format and Installation.....</b>	<b>70</b>
13 Software Installation .....	71
13.1 Package Dependencies .....	71
13.2 Package Architecture Considerations .....	71
<b>A Alphabetical Listing of Interfaces.....</b>	<b>72</b>
A.1 libgcc_s.....	72

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 23360-8:2006

## List of Tables

2-1 Normative References .....	2
2-2 Other References .....	4
3-1 Standard Library Names.....	6
9-1 ELF Special Sections .....	18
9-2 Additional Special Sections .....	18
11-1 libc Definition .....	22
11-2 libc - RPC Function Interfaces .....	22
11-3 libc - System Calls Function Interfaces .....	23
11-4 libc - Standard I/O Function Interfaces .....	25
11-5 libc - Standard I/O Data Interfaces .....	26
11-6 libc - Signal Handling Function Interfaces .....	26
11-7 libc - Signal Handling Data Interfaces .....	27
11-8 libc - Localization Functions Function Interfaces .....	27
11-9 libc - Localization Functions Data Interfaces .....	27
11-10 libc - Socket Interface Function Interfaces .....	28
11-11 libc - Wide Characters Function Interfaces.....	28
11-12 libc - String Functions Function Interfaces .....	30
11-13 libc - IPC Functions Function Interfaces .....	31
11-14 libc - Regular Expressions Function Interfaces .....	31
11-15 libc - Character Type Functions Function Interfaces .....	31
11-16 libc - Time Manipulation Function Interfaces .....	32
11-17 libc - Time Manipulation Data Interfaces .....	32
11-18 libc - Terminal Interface Functions Function Interfaces .....	32
11-19 libc - System Database Interface Function Interfaces.....	33
11-20 libc - Language Support Function Interfaces .....	33
11-21 libc - Large File Support Function Interfaces .....	34
11-22 libc - Standard Library Function Interfaces.....	34
11-23 libc - Standard Library Data Interfaces .....	36
11-24 libm Definition .....	48
11-25 libm - Math Function Interfaces.....	49
11-26 libm - Math Data Interfaces .....	52
11-27 libpthread Definition.....	54
11-28 libpthread - Realtime Threads Function Interfaces .....	54
11-29 libpthread - Posix Threads Function Interfaces .....	54
11-30 libpthread - Thread aware versions of libc interfaces Function Interfaces .....	56
11-31 libgcc_s Definition .....	57
11-32 libgcc_s - Unwind Library Function Interfaces.....	57
11-33 libdl Definition .....	64
11-34 libdl - Dynamic Loader Function Interfaces.....	64
11-35 libcrypt Definition.....	65
11-36 libcrypt - Encryption Function Interfaces .....	65
12-1 libz Definition.....	67
12-2 libncurses Definition .....	68
12-3 libutil Definition.....	68
12-4 libutil - Utility Functions Function Interfaces .....	69
A-1 libgcc_s Function Interfaces .....	72

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 23360-8 was prepared by the Free Standards Group and was adopted, under the PAS procedure, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 22, *Programming languages, their environments and system software interfaces*.

ISO/IEC 23360 consists of the following parts, under the general title *Linux Standard Base (LSB) core specification 3.1*:

- *Part 1: Generic specification*
- *Part 2: Specification for IA32 architecture*
- *Part 3: Specification for IA64 architecture*
- *Part 4: Specification for AMD64 architecture*
- *Part 5: Specification for PPC32 architecture*
- *Part 6: Specification for PPC64 architecture*
- *Part 7: Specification for S390 architecture*
- *Part 8: Specification for S390X architecture*

## Introduction

The LSB defines a binary interface for application programs that are compiled and packaged for LSB-conforming implementations on many different hardware architectures. Since a binary specification includes information specific to the computer processor architecture for which it is intended, it is not possible for a single document to specify the interface for all possible LSB-conforming implementations. Therefore, the LSB is a family of specifications, rather than a single one.

This document should be used in conjunction with the documents it references. This document enumerates the system components it includes, but descriptions of those components may be included entirely or partly in this document, partly in other documents, or entirely in other reference documents. For example, the section that describes system service routines includes a list of the system routines supported in this interface, formal declarations of the data structures they use that are visible to applications, and a pointer to the underlying referenced specification for information about the syntax and semantics of each call. Only those routines not described in standards referenced by this document, or extensions to those standards, are described in detail. Information referenced in this way is as much a part of this document as is the information explicitly included here.

The specification carries a version number of either the form  $x.y$  or  $x.y.z$ . This version number carries the following meaning:

- The first number ( $x$ ) is the major version number. All versions with the same major version number should share binary compatibility. Any addition or deletion of a new library results in a new version number. Interfaces marked as deprecated may be removed from the specification at a major version change.
- The second number ( $y$ ) is the minor version number. Individual interfaces may be added if all certified implementations already had that (previously undocumented) interface. Interfaces may be marked as deprecated at a minor version change. Other minor changes may be permitted at the discretion of the LSB workgroup.
- The third number ( $z$ ), if present, is the editorial level. Only editorial changes should be included in such versions.

Since this specification is a descriptive Application Binary Interface, and not a source level API specification, it is not possible to make a guarantee of 100% backward compatibility between major releases. However, it is the intent that those parts of the binary interface that are visible in the source level API will remain backward compatible from version to version, except where a feature marked as deprecated in one release may be removed from a future release.

Implementors are strongly encouraged to make use of symbol versioning to permit simultaneous support of applications conforming to different releases of this specification.

This is version 3.1 of the Linux Standard Base Core Specification. This specification is part of a family of specifications under the general title "Linux Standard Base (LSB) core specification 3.1". Developers of applications or implementations interested in using the LSB trademark should see the Free Standards Group Certification Policy for details.

# I Introductory Elements

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 23360-8:2006

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 23360-8:2006

# Linux Standard Base (LSB) core specification 3.1 —

## Part 8: Specification for S390X architecture

### 1 Scope

#### 1.1 General

The Linux Standard Base (LSB) defines a system interface for compiled applications and a minimal environment for support of installation scripts. Its purpose is to enable a uniform industry standard environment for high-volume applications conforming to the LSB.

These specifications are composed of two basic parts: A common specification ("LSB-generic" or "generic LSB"), ISO/IEC 23360-1, describing those parts of the interface that remain constant across all implementations of the LSB, and an architecture-specific part ("LSB-arch" or "archLSB") describing the parts of the interface that vary by processor architecture. Together, the LSB-generic and the relevant architecture-specific part of ISO/IEC 23360 for a single hardware architecture provide a complete interface specification for compiled application programs on systems that share a common hardware architecture.

ISO/IEC 23360-1, the LSB-generic document, is used in conjunction with an architecture-specific part. Whenever a section of the LSB-generic specification is supplemented by architecture-specific information, the LSB-generic document includes a reference to the architecture part. Architecture-specific parts of ISO/IEC 23360 may also contain additional information that is not referenced in the LSB-generic document.

The LSB contains both a set of Application Program Interfaces (APIs) and Application Binary Interfaces (ABIs). APIs may appear in the source code of portable applications, while the compiled binary of that application may use the larger set of ABIs. A conforming implementation provides all of the ABIs listed here. The compilation system may replace (e.g. by macro definition) certain APIs with calls to one or more of the underlying binary interfaces, and may insert calls to binary interfaces as needed.

The LSB is primarily a binary interface definition. Not all of the source level APIs available to applications may be contained in this specification.

#### 1.2 Module Specific Scope

This is the S390X architecture-specific Core part of the Linux Standard Base (LSB). It supplements the generic LSB Core module with those interfaces that differ between architectures.

Interfaces described in this part of ISO/IEC 23360 are mandatory except where explicitly listed otherwise. Core interfaces may be supplemented by other modules; all modules are built upon the core.

## 2 References

### 2.1 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

**Note:** Where copies of a document are available on the World Wide Web, a Uniform Resource Locator (URL) is given for informative purposes only. This may point to a more recent copy of the referenced specification, or may be out of date. Reference copies of specifications at the revision level indicated may be found at the Free Standards Group's Reference Specifications (<http://refspecs.freestandards.org>) site.

Table 2-1 Normative References

Name	Title	URL
ISO/IEC 23360-1	ISO/IEC 23360-1:2006, <i>Linux Standard Base (LSB) core specification 3.1 — Part 1: Generic Specification</i>	<a href="http://www.linuxbase.org/spec/">http://www.linuxbase.org/spec/</a>
Filesystem Hierarchy Standard	Filesystem Hierarchy Standard (FHS) 2.3	<a href="http://www.pathname.com/fhs/">http://www.pathname.com/fhs/</a>
ISO C (1999)	ISO/IEC 9899:1999, <i>Programming Languages — C</i>	
ISO POSIX (2003)	ISO/IEC 9945-1:2003, <i>Information technology — Portable Operating System Interface (POSIX) — Part 1: Base Definitions</i>  ISO/IEC 9945-2:2003, <i>Information technology — Portable Operating System Interface (POSIX) — Part 2: System Interfaces</i>  ISO/IEC 9945-3:2003, <i>Information technology — Portable Operating System Interface (POSIX) — Part 3: Shell and Utilities</i>  ISO/IEC 9945-4:2003, <i>Information technology — Portable Operating System Interface (POSIX) — Part 4: Rationale</i>	<a href="http://www.unix.org/version3/">http://www.unix.org/version3/</a>

Name	Title	URL
Large File Support	Large File Support	<a href="http://www.UNIX-systems.org/version2/whatsnew/lfs20mar.html">http://www.UNIX-systems.org/version2/whatsnew/lfs20mar.html</a>
LINUX for zSeries Application Binary Interface Supplement	LINUX for zSeries Application Binary Interface Supplement	<a href="http://oss.software.ibm.com/linux390/documentation-2.2.shtml">http://oss.software.ibm.com/linux390/documentation-2.2.shtml</a>
SUSv2	CAE Specification, January 1997, System Interfaces and Headers (XSH), Issue 5 (ISBN: 1-85912-181-0, C606)	<a href="http://www.opengroup.org/publications/catalog/un.htm">http://www.opengroup.org/publications/catalog/un.htm</a>
SVID Issue 3	American Telephone and Telegraph Company, System V Interface Definition, Issue 3; Morristown, NJ, UNIX Press, 1989. (ISBN 0201566524)	
SVID Issue 4	System V Interface Definition, Fourth Edition	
System V ABI	System V Application Binary Interface, Edition 4.1	<a href="http://www.caldera.com/developers/devspecs/gabi41.pdf">http://www.caldera.com/developers/devspecs/gabi41.pdf</a>
System V ABI Update	System V Application Binary Interface - DRAFT - 17 December 2003	<a href="http://www.caldera.com/developers/gabi/2003-12-17/contents.html">http://www.caldera.com/developers/gabi/2003-12-17/contents.html</a>
X/Open Curses	CAE Specification, May 1996, X/Open Curses, Issue 4, Version 2 (ISBN: 1-85912-171-3, C610), plus Corrigendum U018	<a href="http://www.opengroup.org/publications/catalog/un.htm">http://www.opengroup.org/publications/catalog/un.htm</a>
z/Architecture Principles of Operation	z/Architecture Principles of Operation	<a href="http://oss.software.ibm.com/linux390/documentation-2.2.shtml">http://oss.software.ibm.com/linux390/documentation-2.2.shtml</a>

## 2.2 Informative References/Bibliography

In addition, the specifications listed below provide essential background information to implementors of this specification. These references are included for information only.

Table 2-2 Other References

Name	Title	URL
DWARF Debugging Information Format, Revision 2.0.0	DWARF Debugging Information Format, Revision 2.0.0 (July 27, 1993)	<a href="http://refspecs.freestdards.org/dwarf/dwarf-2.0.0.pdf">http://refspecs.freestdards.org/dwarf/dwarf-2.0.0.pdf</a>
DWARF Debugging Information Format, Revision 3.0.0 (Draft)	DWARF Debugging Information Format, Revision 3.0.0 (Draft)	<a href="http://refspecs.freestdards.org/dwarf/">http://refspecs.freestdards.org/dwarf/</a>
IEC 60559/IEEE 754 Floating Point	IEC 60559:1989, <i>Binary floating-point arithmetic for microprocessor systems</i>	<a href="http://www.ieee.org/">http://www.ieee.org/</a>
ISO/IEC TR 14652	ISO/IEC TR 14652:2004, <i>Information technology — Specification method for cultural conventions</i>	
ITU-T V.42	International Telecommunication Union Recommendation V.42 (2002): Error-correcting procedures for DCEs using asynchronous-to-synchronous conversion ITUV	<a href="http://www.itu.int/rec/recommendation.asp?type=folders&amp;lang=e&amp;parent=T-REC-V.42">http://www.itu.int/rec/recommendation.asp?type=folders&amp;lang=e&amp;parent=T-REC-V.42</a>
Li18nux Globalization Specification	LI18NUNIX 2000 Globalization Specification, Version 1.0 with Amendment 4	<a href="http://www.li18nux.org/docs/html/LI18NUNIX-2000-amd4.htm">http://www.li18nux.org/docs/html/LI18NUNIX-2000-amd4.htm</a>
Linux Allocated Device Registry	LINUX ALLOCATED DEVICES	<a href="http://www.lanana.org/docs/device-list/devices.txt">http://www.lanana.org/docs/device-list/devices.txt</a>
PAM	Open Software Foundation, Request For Comments: 86.0, October 1995, V. Samar & R. Schemers (SunSoft)	<a href="http://www.opengroup.org/tech/rfc/mirror-rfc/rfc86.0.txt">http://www.opengroup.org/tech/rfc/mirror-rfc/rfc86.0.txt</a>
RFC 1321: The MD5 Message-Digest Algorithm	IETF RFC 1321: The MD5 Message-Digest Algorithm	<a href="http://www.ietf.org/rfc/rfc1321.txt">http://www.ietf.org/rfc/rfc1321.txt</a>
RFC 1831/1832 RPC & XDR	IETF RFC 1831 & 1832	<a href="http://www.ietf.org/">http://www.ietf.org/</a>
RFC 1833: Binding Protocols for ONC RPC Version 2	IETF RFC 1833: Binding Protocols for ONC RPC Version 2	<a href="http://www.ietf.org/rfc/rfc1833.txt">http://www.ietf.org/rfc/rfc1833.txt</a>

Name	Title	URL
RFC 1950: ZLIB Compressed Data Format Specification	IETF RFC 1950: ZLIB Compressed Data Format Specification	<a href="http://www.ietf.org/rfc/rfc1950.txt">http://www.ietf.org/rfc/rfc1950.txt</a>
RFC 1951: DEFLATE Compressed Data Format Specification	IETF RFC 1951: DEFLATE Compressed Data Format Specification version 1.3	<a href="http://www.ietf.org/rfc/rfc1951.txt">http://www.ietf.org/rfc/rfc1951.txt</a>
RFC 1952: GZIP File Format Specification	IETF RFC 1952: GZIP file format specification version 4.3	<a href="http://www.ietf.org/rfc/rfc1952.txt">http://www.ietf.org/rfc/rfc1952.txt</a>
RFC 2440: OpenPGP Message Format	IETF RFC 2440: OpenPGP Message Format	<a href="http://www.ietf.org/rfc/rfc2440.txt">http://www.ietf.org/rfc/rfc2440.txt</a>
RFC 2821: Simple Mail Transfer Protocol	IETF RFC 2821: Simple Mail Transfer Protocol	<a href="http://www.ietf.org/rfc/rfc2821.txt">http://www.ietf.org/rfc/rfc2821.txt</a>
RFC 2822: Internet Message Format	IETF RFC 2822: Internet Message Format	<a href="http://www.ietf.org/rfc/rfc2822.txt">http://www.ietf.org/rfc/rfc2822.txt</a>
RFC 791: Internet Protocol	IETF RFC 791: Internet Protocol Specification	<a href="http://www.ietf.org/rfc/rfc791.txt">http://www.ietf.org/rfc/rfc791.txt</a>
RPM Package Format	RPM Package Format V3.0	<a href="http://www.rpm.org/max-rpm/s1-rpm-file-format-rpm-file-format.html">http://www.rpm.org/max-rpm/s1-rpm-file-format-rpm-file-format.html</a>
SUSv2 Commands and Utilities	The Single UNIX Specification (SUS) Version 2, Commands and Utilities (XCU), Issue 5 (ISBN: 1-85912-191-8, C604)	<a href="http://www.opengroup.org/publications/catalog/un.htm">http://www.opengroup.org/publications/catalog/un.htm</a>
zlib Manual	zlib 1.2 Manual	<a href="http://www.gzip.org/zlib/">http://www.gzip.org/zlib/</a>

## 3 Requirements

### 3.1 Relevant Libraries

The libraries listed in Table 3-1 shall be available on S390X Linux Standard Base systems, with the specified runtime names. These names override or supplement the names specified in the generic LSB (ISO/IEC 23360-1) specification. The specified program interpreter, referred to as proginterp in this table, shall be used to load the shared libraries specified by DT\_NEEDED entries at run time.

Table 3-1 Standard Library Names

Library	Runtime Name
libm	libm.so.6
libdl	libdl.so.2
libcrypt	libcrypt.so.1
libz	libz.so.1
libncurses	libncurses.so.5
libutil	libutil.so.1
libc	libc.so.6
libpthread	libpthread.so.0
proginterp	/lib64/ld-lsb-s390x.so.3
libgcc_s	libgcc_s.so.1

These libraries will be in an implementation-defined directory which the dynamic linker shall search by default.

### 3.2 LSB Implementation Conformance

A conforming implementation is necessarily architecture specific, and must provide the interfaces specified by both the generic LSB Core specification (ISO/IEC 23360-1) and the relevant architecture specific part of ISO/IEC 23360.

**Rationale:** An implementation must provide *at least* the interfaces specified in these specifications. It may also provide additional interfaces.

A conforming implementation shall satisfy the following requirements:

- A processor architecture represents a family of related processors which may not have identical feature sets. The architecture specific parts of ISO/IEC 23360 that supplement this specification for a given target processor architecture describe a minimum acceptable processor. The implementation shall provide all features of this processor, whether in hardware or through emulation transparent to the application.
- The implementation shall be capable of executing compiled applications having the format and using the system interfaces described in this document.
- The implementation shall provide libraries containing the interfaces specified by this document, and shall provide a dynamic linking mechanism that allows

these interfaces to be attached to applications at runtime. All the interfaces shall behave as specified in this document.

- The map of virtual memory provided by the implementation shall conform to the requirements of this document.
- The implementation's low-level behavior with respect to function call linkage, system traps, signals, and other such activities shall conform to the formats described in this document.
- The implementation shall provide all of the mandatory interfaces in their entirety.
- The implementation may provide one or more of the optional interfaces. Each optional interface that is provided shall be provided in its entirety. The product documentation shall state which optional interfaces are provided.
- The implementation shall provide all files and utilities specified as part of this document in the format defined here and in other referenced documents. All commands and utilities shall behave as required by this document. The implementation shall also provide all mandatory components of an application's runtime environment that are included or referenced in this document.
- The implementation, when provided with standard data formats and values at a named interface, shall provide the behavior defined for those values and data formats at that interface. However, a conforming implementation may consist of components which are separately packaged and/or sold. For example, a vendor of a conforming implementation might sell the hardware, operating system, and windowing system as separately packaged items.
- The implementation may provide additional interfaces with different names. It may also provide additional behavior corresponding to data values outside the standard ranges, for standard named interfaces.

### 3.3 LSB Application Conformance

A conforming application is necessarily architecture specific, and must conform to both the generic LSB Core specification (ISO/IEC 23360-1) and the relevant architecture specific part of ISO/IEC 23360.

A conforming application shall satisfy the following requirements:

- Its executable files shall be either shell scripts or object files in the format defined for the Object File Format system interface.
- Its object files shall participate in dynamic linking as defined in the Program Loading and Linking System interface.
- It shall employ only the instructions, traps, and other low-level facilities defined in the Low-Level System interface as being for use by applications.
- If it requires any optional interface defined in this document in order to be installed or to execute successfully, the requirement for that optional interface shall be stated in the application's documentation.
- It shall not use any interface or data format that is not required to be provided by a conforming implementation, unless:
  - If such an interface or data format is supplied by another application through direct invocation of that application during execution, that application shall be in turn an LSB conforming application.

- The use of that interface or data format, as well as its source, shall be identified in the documentation of the application.
- It shall not use any values for a named interface that are reserved for vendor extensions.

A strictly conforming application shall not require or use any interface, facility, or implementation-defined extension that is not defined in this document in order to be installed or to execute successfully.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 23360-8:2006

## 4 Definitions

For the purposes of this document, the following definitions, as specified in the *ISO/IEC Directives, Part 2, 2004, 5th Edition*, apply:

can

be able to; there is a possibility of; it is possible to

cannot

be unable to; there is no possibility of; it is not possible to

may

is permitted; is allowed; is permissible

need not

it is not required that; no...is required

shall

is to; is required to; it is required that; has to; only...is permitted; it is necessary

shall not

is not allowed [permitted] [acceptable] [permissible]; is required to be not; is required that...be not; is not to be

should

it is recommended that; ought to

should not

it is not recommended that; ought not to

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 23360-8:2006

## 5 Terminology

For the purposes of this document, the following terms apply:

### archLSB

The architectural part of the LSB Specification which describes the specific parts of the interface that are platform specific. The archLSB is complementary to the gLSB.

### Binary Standard

The total set of interfaces that are available to be used in the compiled binary code of a conforming application.

### gLSB

The common part of the LSB Specification that describes those parts of the interface that remain constant across all hardware implementations of the LSB.

### implementation-defined

Describes a value or behavior that is not defined by this document but is selected by an implementor. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence of the value or behavior. An application that relies on such a value or behavior cannot be assured to be portable across conforming implementations. The implementor shall document such a value or behavior so that it can be used correctly by an application.

### Shell Script

A file that is read by an interpreter (e.g., awk). The first line of the shell script includes a reference to its interpreter binary.

### Source Standard

The set of interfaces that are available to be used in the source code of a conforming application.

### undefined

Describes the nature of a value or behavior not defined by this document which results from use of an invalid program construct or invalid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

### unspecified

Describes the nature of a value or behavior not specified by this document which results from use of a valid program construct or valid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

Other terms and definitions used in this document shall have the same meaning as defined in Chapter 3 of the Base Definitions volume of [ISO POSIX \(2003\)](#).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 23360-8:2006

## 6 Documentation Conventions

Throughout this document, the following typographic conventions are used:

`function()`

the name of a function

**command**

the name of a command or utility

CONSTANT

a constant value

*parameter*

a parameter

variable

a variable

Throughout this specification, several tables of interfaces are presented. Each entry in these tables has the following format:

name

the name of the interface

(symver)

An optional symbol version identifier, if required.

[*refno*]

A reference number indexing the table of referenced specifications that follows this table.

For example,

forkpty(GLIBC_2.0) [SUSv3]
----------------------------

refers to the interface named `forkpty()` with symbol version `GLIBC_2.0` that is defined in the `SUSv3` reference.

**Note:** Symbol versions are defined in the architecture specific parts of ISO/IEC 23360 only.

## II Executable and Linking Format (ELF)

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 23360-8:2006

## 7 Introduction

Executable and Linking Format (ELF) defines the object format for compiled applications. This specification supplements the information found in [System V ABI Update](#) and [LINUX for zSeries Application Binary Interface Supplement](#), and is intended to document additions made since the publication of that document.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 23360-8:2006

## 8 Low Level System Information

### 8.1 Machine Interface

#### 8.1.1 Processor Architecture

The z/Architecture is specified by the following documents

- [LINUX for zSeries Application Binary Interface Supplement](#)
- [z/Architecture Principles of Operation](#)

Only the non optional features of z/Architecture processor instruction set may be assumed to be present. An application should determine if any additional instruction set features are available before using those additional features. If a feature is not present, then a conforming application shall not use it.

Conforming applications shall not invoke the implementations underlying system call interface directly. The interfaces in the implementation base libraries shall be used instead.

**Rationale:** Implementation-supplied base libraries may use the system call interface but applications must not assume any particular operating system or kernel version is present.

Applications conforming to this specification must provide feedback to the user if a feature that is required for correct execution of the application is not present. Applications conforming to this specification should attempt to execute in a diminished capacity if a required instruction set feature is not present.

This specification does not provide any performance guarantees of a conforming system. A system conforming to this specification may be implemented in either hardware or software.

#### 8.1.2 Data Representation

LSB-conforming applications shall use the data representation as defined in Chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

##### 8.1.2.1 Byte Ordering

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

##### 8.1.2.2 Fundamental Types

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

##### 8.1.2.3 Aggregates and Unions

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

##### 8.1.2.4 Bit Fields

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 8.2 Function Calling Sequence

LSB-conforming applications shall use the function calling sequence as defined in Chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### **8.2.1 Registers**

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### **8.2.2 Stack Frame**

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### **8.2.3 Parameter Passing**

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### **8.2.4 Variable Argument Lists**

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### **8.2.5 Return Values**

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## **8.3 Operating System Interface**

LSB-conforming applications shall use the Operating System Interfaces as defined in Chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### **8.3.1 Virtual Address Space**

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### **8.3.2 Page Size**

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### **8.3.3 Virtual Address Assignments**

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### **8.3.4 Managing the Process Stack**

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### **8.3.5 Coding Guidelines**

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### **8.3.6 Processor Execution Mode**

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### **8.3.7 Exception Interface**

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### **8.3.8 Signal Delivery**

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

#### **8.3.8.1 Signal Handler Interface**

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 8.4 Process Initialization

LSB-conforming applications shall use the Process Initialization as defined in Chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 8.4.1 Registers

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 8.4.2 Process Stack

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 8.5 Coding Examples

LSB-conforming applications may implement fundamental operations using the Coding Examples as defined in Chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 8.5.1 Code Model Overview

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 8.5.2 Function Prolog and Epilog

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 8.5.3 Profiling

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 8.5.4 Data Objects

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 8.5.5 Function Calls

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 8.5.6 Dynamic Stack Space Allocation

See chapter 1 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 8.6 Debug Information

The LSB does not currently specify the format of Debug information.

## 9 Object Format

### 9.1 Introduction

LSB-conforming implementations shall support an object file, called Executable and Linking Format (ELF) as defined by the [System V ABI](#), [System V ABI Update](#), [LINUX for zSeries Application Binary Interface Supplement](#) and as supplemented by the generic LSB and this document.

### 9.2 ELF Header

#### 9.2.1 Machine Information

LSB-conforming applications shall use the Machine Information as defined in Chapter 2 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 9.3 Sections

See chapter 2 of the [LINUX for zSeries Application Binary Interface Supplement](#).

#### 9.3.1 Special Sections

The following sections are defined in the [LINUX for zSeries Application Binary Interface Supplement](#).

Table 9-1 ELF Special Sections

Name	Type	Attributes
.got	SHT_PROGBITS	SHF_ALLOC+SHF_WRITE
.plt	SHT_PROGBITS	SHF_ALLOC+SHF_EXECINSTR

.got

This section holds the global offset table

.plt

This section holds the procedure linkage table

#### 9.3.2 Linux Special Sections

The following Linux S/390 specific sections are defined here.

Table 9-2 Additional Special Sections

Name	Type	Attributes
.rela.dyn	SHT_RELA	SHF_ALLOC
.rela.plt	SHT_RELA	SHF_ALLOC
.sbss	SHT_PROGBITS	SHF_WRITE

.rela.dyn

This section holds RELA type relocation information for all sections of a shared library except the PLT

.rela.plt

This section holds RELA type relocation information for the PLT section of a shared library or dynamically linked application

.sbss

This section holds uninitialized data that contribute to the program's memory image. The system initializes the data with zeroes when the program begins to run.

## 9.4 Symbol Table

LSB-conforming applications shall use the Symbol Table as defined in Chapter 2 of the [LINUX for zSeries Application Binary Interface Supplement](#).

## 9.5 Relocation

LSB-conforming applications shall use Relocations as defined in Chapter 2 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 9.5.1 Relocation Types

See chapter 2 of the [LINUX for zSeries Application Binary Interface Supplement](#).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 23360-8:2006

## 10 Program Loading and Dynamic Linking

### 10.1 Introduction

LSB-conforming implementations shall support the object file information and system actions that create running programs as specified in the [System V ABI](#), [System V ABI Update](#), [LINUX for zSeries Application Binary Interface Supplement](#) and as supplemented by the [ISO/IEC 23360-1](#) and this document.

### 10.2 Program Loading

See Chapter 3 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### 10.3 Dynamic Linking

See Chapter 3 of the [LINUX for zSeries Application Binary Interface Supplement](#).

#### 10.3.1 Dynamic Section

The following dynamic entries are defined in the [LINUX for zSeries Application Binary Interface Supplement](#).

DT\_JMPREL

This entry is associated with a table of relocation entries for the procedure linkage table. This entry is mandatory both for executable and shared object files

DT\_PLTGOT

This entry's `d_ptr` member gives the address of the first byte in the procedure linkage table

#### 10.3.2 Global Offset Table

See Chapter 3 of the [LINUX for zSeries Application Binary Interface Supplement](#).

#### 10.3.3 Function Addresses

See chapter 3 of the [LINUX for zSeries Application Binary Interface Supplement](#).

#### 10.3.4 Procedure Linkage Table

See chapter 3 of the [LINUX for zSeries Application Binary Interface Supplement](#).

### III Base Libraries

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 23360-8:2006

## 11 Libraries

An LSB-conforming implementation shall support base libraries which provide interfaces for accessing the operating system, processor and other hardware in the system.

Only those interfaces that are unique to the z/Architecture platform are defined here. This section should be used in conjunction with the corresponding section in the Linux Standard Base Specification.

### 11.1 Program Interpreter/Dynamic Linker

The Program Interpreter shall be `/lib64/ld-lsb-s390x.so.3`.

### 11.2 Interfaces for libc

Table 11-1 defines the library name and shared object name for the libc library

**Table 11-1 libc Definition**

Library:	libc
SONAME:	libc.so.6

The behavior of the interfaces in this library is specified by the following specifications:

[LFS] [Large File Support](#)

[LSB] [ISO/IEC 23360-1](#)

[SUSv2] [SUSv2](#)

[SUSv3] [ISO POSIX \(2003\)](#)

[SVID.3] [SVID Issue 3](#)

[SVID.4] [SVID Issue 4](#)

#### 11.2.1 RPC

##### 11.2.1.1 Interfaces for RPC

An LSB conforming implementation shall provide the architecture specific functions for RPC specified in Table 11-2, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-2 libc - RPC Function Interfaces**

authnone_create(GLIBC_2.2) [SVID.4]	clnt_create(GLIBC_2.2) [SVID.4]	clnt_pcreateerror(GLIBC_2.2) [SVID.4]	clnt_pereno(GLIBC_2.2) [SVID.4]
clnt_perror(GLIBC_2.2) [SVID.4]	clnt_screateerror(GLIBC_2.2) [SVID.4]	clnt_sperrno(GLIBC_2.2) [SVID.4]	clnt_sperror(GLIBC_2.2) [SVID.4]
key_decryptsession(GLIBC_2.2) [SVID.3]	pmap_getport(GLIBC_2.2) [LSB]	pmap_set(GLIBC_2.2) [LSB]	pmap_unset(GLIBC_2.2) [LSB]
svc_getreqset(GLIBC_2.2) [SVID.3]	svc_register(GLIBC_2.2) [LSB]	svc_run(GLIBC_2.2) [LSB]	svc_sendreply(GLIBC_2.2) [LSB]

svcerr_auth(GLIBC_2.2) [SVID.3]	svcerr_decode(GLIBC_2.2) [SVID.3]	svcerr_noproc(GLIBC_2.2) [SVID.3]	svcerr_noprog(GLIBC_2.2) [SVID.3]
svcerr_progvers(GLIBC_2.2) [SVID.3]	svcerr_systemerr(GLIBC_2.2) [SVID.3]	svcerr_weakauth(GLIBC_2.2) [SVID.3]	svctcp_create(GLIBC_2.2) [LSB]
svcdup_create(GLIBC_2.2) [LSB]	xdr_accepted_reply(GLIBC_2.2) [SVID.3]	xdr_array(GLIBC_2.2) [SVID.3]	xdr_bool(GLIBC_2.2) [SVID.3]
xdr_bytes(GLIBC_2.2) [SVID.3]	xdr_callhdr(GLIBC_2.2) [SVID.3]	xdr_callmsg(GLIBC_2.2) [SVID.3]	xdr_char(GLIBC_2.2) [SVID.3]
xdr_double(GLIBC_2.2) [SVID.3]	xdr_enum(GLIBC_2.2) [SVID.3]	xdr_float(GLIBC_2.2) [SVID.3]	xdr_free(GLIBC_2.2) [SVID.3]
xdr_int(GLIBC_2.2) [SVID.3]	xdr_long(GLIBC_2.2) [SVID.3]	xdr_opaque(GLIBC_2.2) [SVID.3]	xdr_opaque_auth(GLIBC_2.2) [SVID.3]
xdr_pointer(GLIBC_2.2) [SVID.3]	xdr_reference(GLIBC_2.2) [SVID.3]	xdr_rejected_reply(GLIBC_2.2) [SVID.3]	xdr_replymsg(GLIBC_2.2) [SVID.3]
xdr_short(GLIBC_2.2) [SVID.3]	xdr_string(GLIBC_2.2) [SVID.3]	xdr_u_char(GLIBC_2.2) [SVID.3]	xdr_u_int(GLIBC_2.2) [LSB]
xdr_u_long(GLIBC_2.2) [SVID.3]	xdr_u_short(GLIBC_2.2) [SVID.3]	xdr_union(GLIBC_2.2) [SVID.3]	xdr_vector(GLIBC_2.2) [SVID.3]
xdr_void(GLIBC_2.2) [SVID.3]	xdr_wrapstring(GLIBC_2.2) [SVID.3]	xdrmem_create(GLIBC_2.2) [SVID.3]	xdrrec_create(GLIBC_2.2) [SVID.3]
xdrrec_eof(GLIBC_2.2) [SVID.3]			

## 11.2.2 System Calls

### 11.2.2.1 Interfaces for System Calls

An LSB conforming implementation shall provide the architecture specific functions for System Calls specified in Table 11-3, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-3 libc - System Calls Function Interfaces

__fxstat(GLIBC_2.2) [LSB]	__getpgid(GLIBC_2.2) [LSB]	__lxstat(GLIBC_2.2) [LSB]	__xmknod(GLIBC_2.2) [LSB]
__xstat(GLIBC_2.2) [LSB]	access(GLIBC_2.2) [SUSv3]	acct(GLIBC_2.2) [LSB]	alarm(GLIBC_2.2) [SUSv3]
brk(GLIBC_2.2) [SUSv2]	chdir(GLIBC_2.2) [SUSv3]	chmod(GLIBC_2.2) [SUSv3]	chown(GLIBC_2.2) [SUSv3]
chroot(GLIBC_2.2) [SUSv2]	clock(GLIBC_2.2) [SUSv3]	close(GLIBC_2.2) [SUSv3]	closedir(GLIBC_2.2) [SUSv3]

creat(GLIBC_2.2) [SUSv3]	dup(GLIBC_2.2) [SUSv3]	dup2(GLIBC_2.2) [SUSv3]	execl(GLIBC_2.2) [SUSv3]
execle(GLIBC_2.2) [SUSv3]	execlp(GLIBC_2.2) [SUSv3]	execv(GLIBC_2.2) [SUSv3]	execve(GLIBC_2.2) [SUSv3]
execvp(GLIBC_2.2) [SUSv3]	exit(GLIBC_2.2) [SUSv3]	fchdir(GLIBC_2.2) [SUSv3]	fchmod(GLIBC_2.2) [SUSv3]
fchown(GLIBC_2.2) [SUSv3]	fcntl(GLIBC_2.2) [LSB]	fdatasync(GLIBC_2.2) [SUSv3]	flock(GLIBC_2.2) [LSB]
fork(GLIBC_2.2) [SUSv3]	fstatvfs(GLIBC_2.2) [SUSv3]	fsync(GLIBC_2.2) [SUSv3]	ftime(GLIBC_2.2) [SUSv3]
ftruncate(GLIBC_2.2) [SUSv3]	getcontext(GLIBC_2.2) [SUSv3]	getegid(GLIBC_2.2) [SUSv3]	geteuid(GLIBC_2.2) [SUSv3]
getgid(GLIBC_2.2) [SUSv3]	getgroups(GLIBC_2.2) [SUSv3]	getitimer(GLIBC_2.2) [SUSv3]	getloadavg(GLIBC_2.2) [LSB]
getpagesize(GLIBC_2.2) [SUSv2]	getpgid(GLIBC_2.2) [SUSv3]	getpgrp(GLIBC_2.2) [SUSv3]	getpid(GLIBC_2.2) [SUSv3]
getppid(GLIBC_2.2) [SUSv3]	getpriority(GLIBC_2.2) [SUSv3]	getrlimit(GLIBC_2.2) [SUSv3]	getrusage(GLIBC_2.2) [SUSv3]
getsid(GLIBC_2.2) [SUSv3]	getuid(GLIBC_2.2) [SUSv3]	getwd(GLIBC_2.2) [SUSv3]	initgroups(GLIBC_2.2) [LSB]
ioctl(GLIBC_2.2) [LSB]	kill(GLIBC_2.2) [LSB]	killpg(GLIBC_2.2) [SUSv3]	lchown(GLIBC_2.2) [SUSv3]
link(GLIBC_2.2) [LSB]	lockf(GLIBC_2.2) [SUSv3]	lseek(GLIBC_2.2) [SUSv3]	mkdir(GLIBC_2.2) [SUSv3]
mkfifo(GLIBC_2.2) [SUSv3]	mlock(GLIBC_2.2) [SUSv3]	mlockall(GLIBC_2.2) [SUSv3]	mmap(GLIBC_2.2) [SUSv3]
mprotect(GLIBC_2.2) [SUSv3]	msync(GLIBC_2.2) [SUSv3]	munlock(GLIBC_2.2) [SUSv3]	munlockall(GLIBC_2.2) [SUSv3]
munmap(GLIBC_2.2) [SUSv3]	nanosleep(GLIBC_2.2) [SUSv3]	nice(GLIBC_2.2) [SUSv3]	open(GLIBC_2.2) [SUSv3]
opendir(GLIBC_2.2) [SUSv3]	pathconf(GLIBC_2.2) [SUSv3]	pause(GLIBC_2.2) [SUSv3]	pipe(GLIBC_2.2) [SUSv3]
poll(GLIBC_2.2) [SUSv3]	read(GLIBC_2.2) [SUSv3]	readdir(GLIBC_2.2) [SUSv3]	readdir_r(GLIBC_2.2) [SUSv3]
readlink(GLIBC_2.2) [SUSv3]	readv(GLIBC_2.2) [SUSv3]	rename(GLIBC_2.2) [SUSv3]	rmdir(GLIBC_2.2) [SUSv3]
sbrk(GLIBC_2.2) [SUSv2]	sched_get_priority_max(GLIBC_2.2) [SUSv3]	sched_get_priority_min(GLIBC_2.2) [SUSv3]	sched_getparam(GLIBC_2.2) [SUSv3]
sched_getscheduler(GLIBC_2.2) [SUSv3]	sched_rr_get_interval(GLIBC_2.2) [SUSv3]	sched_setparam(GLIBC_2.2) [SUSv3]	sched_setscheduler(GLIBC_2.2) [SUSv3]
sched_yield(GLIBC_2.2) [SUSv3]	select(GLIBC_2.2) [SUSv3]	setcontext(GLIBC_2.2) [SUSv3]	setegid(GLIBC_2.2) [SUSv3]

BC_2.2) [SUSv3]	) [SUSv3]	C_2.2) [SUSv3]	2) [SUSv3]
seteuid(GLIBC_2.2) [SUSv3]	setgid(GLIBC_2.2) [SUSv3]	setitimer(GLIBC_2.2) [SUSv3]	setpgid(GLIBC_2.2) [SUSv3]
setpgrp(GLIBC_2.2) [SUSv3]	setpriority(GLIBC_2.2) [SUSv3]	setregid(GLIBC_2.2) [SUSv3]	setreuid(GLIBC_2.2) [SUSv3]
setrlimit(GLIBC_2.2) [SUSv3]	setrlimit64(GLIBC_2.2) [LFS]	setsid(GLIBC_2.2) [SUSv3]	setuid(GLIBC_2.2) [SUSv3]
sleep(GLIBC_2.2) [SUSv3]	statvfs(GLIBC_2.2) [SUSv3]	stime(GLIBC_2.2) [LSB]	symlink(GLIBC_2.2) [SUSv3]
sync(GLIBC_2.2) [SUSv3]	sysconf(GLIBC_2.2) [SUSv3]	time(GLIBC_2.2) [SUSv3]	times(GLIBC_2.2) [SUSv3]
truncate(GLIBC_2.2) [SUSv3]	ulimit(GLIBC_2.2) [SUSv3]	umask(GLIBC_2.2) [SUSv3]	uname(GLIBC_2.2) [SUSv3]
unlink(GLIBC_2.2) [LSB]	utime(GLIBC_2.2) [SUSv3]	utimes(GLIBC_2.2) [SUSv3]	vfork(GLIBC_2.2) [SUSv3]
wait(GLIBC_2.2) [SUSv3]	wait4(GLIBC_2.2) [LSB]	waitpid(GLIBC_2.2) [LSB]	write(GLIBC_2.2) [SUSv3]
writew(GLIBC_2.2) [SUSv3]			

### 11.2.3 Standard I/O

#### 11.2.3.1 Interfaces for Standard I/O

An LSB conforming implementation shall provide the architecture specific functions for Standard I/O specified in Table 11-4, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-4 libc - Standard I/O Function Interfaces

_IO_feof(GLIBC_2.2) [LSB]	_IO_getc(GLIBC_2.2) [LSB]	_IO_putc(GLIBC_2.2) [LSB]	_IO_puts(GLIBC_2.2) [LSB]
asprintf(GLIBC_2.2) [LSB]	clearerr(GLIBC_2.2) [SUSv3]	ctermid(GLIBC_2.2) [SUSv3]	fclose(GLIBC_2.2) [SUSv3]
fdopen(GLIBC_2.2) [SUSv3]	feof(GLIBC_2.2) [SUSv3]	ferror(GLIBC_2.2) [SUSv3]	fflush(GLIBC_2.2) [SUSv3]
fflush_unlocked(GLIBC_2.2) [LSB]	fgetc(GLIBC_2.2) [SUSv3]	fgetpos(GLIBC_2.2) [SUSv3]	fgets(GLIBC_2.2) [SUSv3]
fgetwc_unlocked(GLIBC_2.2) [LSB]	fileno(GLIBC_2.2) [SUSv3]	flockfile(GLIBC_2.2) [SUSv3]	fopen(GLIBC_2.2) [SUSv3]
fprintf(GLIBC_2.2) [SUSv3]	fputc(GLIBC_2.2) [SUSv3]	fputs(GLIBC_2.2) [SUSv3]	fread(GLIBC_2.2) [SUSv3]
freopen(GLIBC_2.2) [SUSv3]	fscanf(GLIBC_2.2) [LSB]	fseek(GLIBC_2.2) [SUSv3]	fseeko(GLIBC_2.2) [SUSv3]
fsetpos(GLIBC_2.2) [SUSv3]	ftell(GLIBC_2.2) [SUSv3]	ftello(GLIBC_2.2) [SUSv3]	fwrite(GLIBC_2.2) [SUSv3]

2) [SUSv3]	[SUSv3]	[SUSv3]	) [SUSv3]
getc(GLIBC_2.2) [SUSv3]	getc_unlocked(GLIBC_2.2) [SUSv3]	getchar(GLIBC_2.2) [SUSv3]	getchar_unlocked(GLIBC_2.2) [SUSv3]
getw(GLIBC_2.2) [SUSv2]	pclose(GLIBC_2.2) [SUSv3]	popen(GLIBC_2.2) [SUSv3]	printf(GLIBC_2.2) [SUSv3]
putc(GLIBC_2.2) [SUSv3]	putc_unlocked(GLIBC_2.2) [SUSv3]	putchar(GLIBC_2.2) [SUSv3]	putchar_unlocked(GLIBC_2.2) [SUSv3]
puts(GLIBC_2.2) [SUSv3]	putw(GLIBC_2.2) [SUSv2]	remove(GLIBC_2.2) [SUSv3]	rewind(GLIBC_2.2) [SUSv3]
rewinddir(GLIBC_2.2) [SUSv3]	scanf(GLIBC_2.2) [LSB]	seekdir(GLIBC_2.2) [SUSv3]	setbuf(GLIBC_2.2) [SUSv3]
setbuffer(GLIBC_2.2) [LSB]	setvbuf(GLIBC_2.2) [SUSv3]	snprintf(GLIBC_2.2) [SUSv3]	sprintf(GLIBC_2.2) [SUSv3]
sscanf(GLIBC_2.2) [LSB]	telldir(GLIBC_2.2) [SUSv3]	tempnam(GLIBC_2.2) [SUSv3]	ungetc(GLIBC_2.2) [SUSv3]
vasprintf(GLIBC_2.2) [LSB]	vdprintf(GLIBC_2.2) [LSB]	vfprintf(GLIBC_2.2) [SUSv3]	vprintf(GLIBC_2.2) [SUSv3]
vsnprintf(GLIBC_2.2) [SUSv3]	vsprintf(GLIBC_2.2) [SUSv3]		

An LSB conforming implementation shall provide the architecture specific data interfaces for Standard I/O specified in Table 11-5, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-5 libc - Standard I/O Data Interfaces**

stderr(GLIBC_2.2) [SUSv3]	stdin(GLIBC_2.2) [SUSv3]	stdout(GLIBC_2.2) [SUSv3]	
---------------------------	--------------------------	---------------------------	--

## 11.2.4 Signal Handling

### 11.2.4.1 Interfaces for Signal Handling

An LSB conforming implementation shall provide the architecture specific functions for Signal Handling specified in Table 11-6, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-6 libc - Signal Handling Function Interfaces**

__libc_current_sigrtmax(GLIBC_2.2) [LSB]	__libc_current_sigrtmin(GLIBC_2.2) [LSB]	__sigsetjmp(GLIBC_2.2) [LSB]	__sysv_signal(GLIBC_2.2) [LSB]
bsd_signal(GLIBC_2.2) [SUSv3]	psignal(GLIBC_2.2) [LSB]	raise(GLIBC_2.2) [SUSv3]	sigaction(GLIBC_2.2) [SUSv3]
sigaddset(GLIBC_2.2) [SUSv3]	sigaltstack(GLIBC_2.2) [SUSv3]	sigandset(GLIBC_2.2) [LSB]	sigdelset(GLIBC_2.2) [SUSv3]
sigemptyset(GLIBC_2.2) [SUSv3]	sigfillset(GLIBC_2.2) [SUSv3]	sighold(GLIBC_2.2) [SUSv3]	sigignore(GLIBC_2.2) [SUSv3]

BC_2.2) [SUSv3]	2.2) [SUSv3]	.2) [SUSv3]	_2.2) [SUSv3]
siginterrupt(GLIBC_2.2) [SUSv3]	sigisemptyset(GLIBC_2.2) [LSB]	sigismember(GLIBC_2.2) [SUSv3]	siglongjmp(GLIBC_2.2) [SUSv3]
signal(GLIBC_2.2) [SUSv3]	sigorset(GLIBC_2.2) [LSB]	sigpause(GLIBC_2.2) [SUSv3]	sigpending(GLIBC_2.2) [SUSv3]
sigprocmask(GLIBC_2.2) [SUSv3]	sigqueue(GLIBC_2.2) [SUSv3]	sigrelse(GLIBC_2.2) [SUSv3]	sigreturn(GLIBC_2.2) [LSB]
sigset(GLIBC_2.2) [SUSv3]	sigsuspend(GLIBC_2.2) [SUSv3]	sigtimedwait(GLIBC_2.2) [SUSv3]	sigwait(GLIBC_2.2) [SUSv3]
sigwaitinfo(GLIBC_2.2) [SUSv3]			

An LSB conforming implementation shall provide the architecture specific data interfaces for Signal Handling specified in Table 11-7, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-7 libc - Signal Handling Data Interfaces**

_sys_siglist(GLIBC_2.3.3) [LSB]			
---------------------------------	--	--	--

## 11.2.5 Localization Functions

### 11.2.5.1 Interfaces for Localization Functions

An LSB conforming implementation shall provide the architecture specific functions for Localization Functions specified in Table 11-8, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-8 libc - Localization Functions Function Interfaces**

bind_textdomain_codeset(GLIBC_2.2) [LSB]	bindtextdomain(GLIBC_2.2) [LSB]	catclose(GLIBC_2.2) [SUSv3]	catgets(GLIBC_2.2) [SUSv3]
catopen(GLIBC_2.2) [SUSv3]	dcgettext(GLIBC_2.2) [LSB]	dcngettext(GLIBC_2.2) [LSB]	dgettext(GLIBC_2.2) [LSB]
dngettext(GLIBC_2.2) [LSB]	gettext(GLIBC_2.2) [LSB]	iconv(GLIBC_2.2) [SUSv3]	iconv_close(GLIBC_2.2) [SUSv3]
iconv_open(GLIBC_2.2) [SUSv3]	localeconv(GLIBC_2.2) [SUSv3]	ngettext(GLIBC_2.2) [LSB]	nl_langinfo(GLIBC_2.2) [SUSv3]
setlocale(GLIBC_2.2) [SUSv3]	textdomain(GLIBC_2.2) [LSB]		

An LSB conforming implementation shall provide the architecture specific data interfaces for Localization Functions specified in Table 11-9, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-9 libc - Localization Functions Data Interfaces**

_nl_msg_cat_cntr (GLIBC_2.2)			
------------------------------	--	--	--

[LSB]			
-------	--	--	--

## 11.2.6 Socket Interface

### 11.2.6.1 Interfaces for Socket Interface

An LSB conforming implementation shall provide the architecture specific functions for Socket Interface specified in Table 11-10, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-10 libc - Socket Interface Function Interfaces**

__h_errno_location(GLIBC_2.2) [LSB]	accept(GLIBC_2.2) [SUSv3]	bind(GLIBC_2.2) [SUSv3]	bindresvport(GLIBC_2.2) [LSB]
connect(GLIBC_2.2) [SUSv3]	gethostid(GLIBC_2.2) [SUSv3]	gethostname(GLIBC_2.2) [SUSv3]	getpeername(GLIBC_2.2) [SUSv3]
getsockname(GLIBC_2.2) [SUSv3]	getsockopt(GLIBC_2.2) [LSB]	if_freenameindex(GLIBC_2.2) [SUSv3]	if_indextoname(GLIBC_2.2) [SUSv3]
if_nameindex(GLIBC_2.2) [SUSv3]	if_nametoindex(GLIBC_2.2) [SUSv3]	listen(GLIBC_2.2) [SUSv3]	recv(GLIBC_2.2) [SUSv3]
recvfrom(GLIBC_2.2) [SUSv3]	recvmsg(GLIBC_2.2) [SUSv3]	send(GLIBC_2.2) [SUSv3]	sendmsg(GLIBC_2.2) [SUSv3]
sendto(GLIBC_2.2) [SUSv3]	setsockopt(GLIBC_2.2) [LSB]	shutdown(GLIBC_2.2) [SUSv3]	socketatmark(GLIBC_2.2.4) [SUSv3]
socket(GLIBC_2.2) [SUSv3]	socketpair(GLIBC_2.2) [SUSv3]		

## 11.2.7 Wide Characters

### 11.2.7.1 Interfaces for Wide Characters

An LSB conforming implementation shall provide the architecture specific functions for Wide Characters specified in Table 11-11, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-11 libc - Wide Characters Function Interfaces**

__wcstod_internal(GLIBC_2.2) [LSB]	__wcstof_internal(GLIBC_2.2) [LSB]	__wcstol_internal(GLIBC_2.2) [LSB]	__wcstold_internal(GLIBC_2.2) [LSB]
__wcstoul_internal(GLIBC_2.2) [LSB]	btowc(GLIBC_2.2) [SUSv3]	fgetwc(GLIBC_2.2) [SUSv3]	fgetws(GLIBC_2.2) [SUSv3]
fputwc(GLIBC_2.2) [SUSv3]	fputws(GLIBC_2.2) [SUSv3]	fwide(GLIBC_2.2) [SUSv3]	fwprintf(GLIBC_2.2) [SUSv3]
fwscanf(GLIBC_2.2) [LSB]	getwc(GLIBC_2.2) [SUSv3]	getwchar(GLIBC_2.2) [SUSv3]	mblen(GLIBC_2.2) [SUSv3]

mbrlen(GLIBC_2.2) [SUSv3]	mbrtowc(GLIBC_2.2) [SUSv3]	mbsinit(GLIBC_2.2) [SUSv3]	mbsnrtowcs(GLIBC_2.2) [LSB]
mbsrtowcs(GLIBC_2.2) [SUSv3]	mbstowcs(GLIBC_2.2) [SUSv3]	mbtowc(GLIBC_2.2) [SUSv3]	putwc(GLIBC_2.2) [SUSv3]
putwchar(GLIBC_2.2) [SUSv3]	swprintf(GLIBC_2.2) [SUSv3]	swscanf(GLIBC_2.2) [LSB]	towctrans(GLIBC_2.2) [SUSv3]
towlower(GLIBC_2.2) [SUSv3]	towupper(GLIBC_2.2) [SUSv3]	ungetwc(GLIBC_2.2) [SUSv3]	vfwprintf(GLIBC_2.2) [SUSv3]
vfwscanf(GLIBC_2.2) [LSB]	vswprintf(GLIBC_2.2) [SUSv3]	vswscanf(GLIBC_2.2) [LSB]	vwprintf(GLIBC_2.2) [SUSv3]
vwscanf(GLIBC_2.2) [LSB]	wcpcpy(GLIBC_2.2) [LSB]	wcpncpy(GLIBC_2.2) [LSB]	wcrtomb(GLIBC_2.2) [SUSv3]
wcscasecmp(GLIBC_2.2) [LSB]	wcscat(GLIBC_2.2) [SUSv3]	wcschr(GLIBC_2.2) [SUSv3]	wcscmp(GLIBC_2.2) [SUSv3]
wcscoll(GLIBC_2.2) [SUSv3]	wcscpy(GLIBC_2.2) [SUSv3]	wcscspn(GLIBC_2.2) [SUSv3]	wcsdup(GLIBC_2.2) [LSB]
wcsftime(GLIBC_2.2) [SUSv3]	wcslen(GLIBC_2.2) [SUSv3]	wcsncasecmp(GLIBC_2.2) [LSB]	wcsncat(GLIBC_2.2) [SUSv3]
wcsncmp(GLIBC_2.2) [SUSv3]	wcsncpy(GLIBC_2.2) [SUSv3]	wcsnlen(GLIBC_2.2) [LSB]	wcsnrtombs(GLIBC_2.2) [LSB]
wcspbrk(GLIBC_2.2) [SUSv3]	wcsrchr(GLIBC_2.2) [SUSv3]	wcsrtombs(GLIBC_2.2) [SUSv3]	wcsspn(GLIBC_2.2) [SUSv3]
wcsstr(GLIBC_2.2) [SUSv3]	wctod(GLIBC_2.2) [SUSv3]	wctof(GLIBC_2.2) [SUSv3]	wcstoimax(GLIBC_2.2) [SUSv3]
wcstok(GLIBC_2.2) [SUSv3]	wctol(GLIBC_2.2) [SUSv3]	wctold(GLIBC_2.2) [SUSv3]	wctoll(GLIBC_2.2) [SUSv3]
wcstombs(GLIBC_2.2) [SUSv3]	wcstoq(GLIBC_2.2) [LSB]	wctoul(GLIBC_2.2) [SUSv3]	wctoull(GLIBC_2.2) [SUSv3]
wcstoumax(GLIBC_2.2) [SUSv3]	wcstouq(GLIBC_2.2) [LSB]	wcswcs(GLIBC_2.2) [SUSv3]	wcswidth(GLIBC_2.2) [SUSv3]
wcsxfrm(GLIBC_2.2) [SUSv3]	wctob(GLIBC_2.2) [SUSv3]	wctomb(GLIBC_2.2) [SUSv3]	wctrans(GLIBC_2.2) [SUSv3]
wctype(GLIBC_2.2) [SUSv3]	wcwidth(GLIBC_2.2) [SUSv3]	wmemchr(GLIBC_2.2) [SUSv3]	wmemcmp(GLIBC_2.2) [SUSv3]
wmemcpy(GLIBC_2.2) [SUSv3]	wmemmove(GLIBC_2.2) [SUSv3]	wmemset(GLIBC_2.2) [SUSv3]	wprintf(GLIBC_2.2) [SUSv3]
wscanf(GLIBC_2.2) [LSB]			

## 11.2.8 String Functions

### 11.2.8.1 Interfaces for String Functions

An LSB conforming implementation shall provide the architecture specific functions for String Functions specified in Table 11-12, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-12 libc - String Functions Function Interfaces

__memcpy(GLIBC_2.2) [LSB]	__rawmemchr(GLIBC_2.2) [LSB]	__stpcpy(GLIBC_2.2) [LSB]	__strdup(GLIBC_2.2) [LSB]
__strtod_internal(GLIBC_2.2) [LSB]	__strtof_internal(GLIBC_2.2) [LSB]	__strtok_r(GLIBC_2.2) [LSB]	__strtol_internal(GLIBC_2.2) [LSB]
__strtold_internal(GLIBC_2.2) [LSB]	__strtoll_internal(GLIBC_2.2) [LSB]	__strtoul_internal(GLIBC_2.2) [LSB]	__strtoull_internal(GLIBC_2.2) [LSB]
bcmp(GLIBC_2.2) [SUSv3]	bcopy(GLIBC_2.2) [SUSv3]	bzero(GLIBC_2.2) [SUSv3]	ffs(GLIBC_2.2) [SUSv3]
index(GLIBC_2.2) [SUSv3]	memcpy(GLIBC_2.2) [SUSv3]	memchr(GLIBC_2.2) [SUSv3]	memcmp(GLIBC_2.2) [SUSv3]
memcpy(GLIBC_2.2) [SUSv3]	memmove(GLIBC_2.2) [SUSv3]	memrchr(GLIBC_2.2) [LSB]	memset(GLIBC_2.2) [SUSv3]
rindex(GLIBC_2.2) [SUSv3]	stpcpy(GLIBC_2.2) [LSB]	stpncpy(GLIBC_2.2) [LSB]	strcasecmp(GLIBC_2.2) [SUSv3]
strcasestr(GLIBC_2.2) [LSB]	strcat(GLIBC_2.2) [SUSv3]	strchr(GLIBC_2.2) [SUSv3]	strcmp(GLIBC_2.2) [SUSv3]
strcoll(GLIBC_2.2) [SUSv3]	strcpy(GLIBC_2.2) [SUSv3]	strcspn(GLIBC_2.2) [SUSv3]	strdup(GLIBC_2.2) [SUSv3]
strerror(GLIBC_2.2) [SUSv3]	strerror_r(GLIBC_2.2) [LSB]	strfmon(GLIBC_2.2) [SUSv3]	strftime(GLIBC_2.2) [SUSv3]
strlen(GLIBC_2.2) [SUSv3]	strncasecmp(GLIBC_2.2) [SUSv3]	strncat(GLIBC_2.2) [SUSv3]	strncmp(GLIBC_2.2) [SUSv3]
strncpy(GLIBC_2.2) [SUSv3]	strndup(GLIBC_2.2) [LSB]	strnlen(GLIBC_2.2) [LSB]	strpbrk(GLIBC_2.2) [SUSv3]
strptime(GLIBC_2.2) [LSB]	strrchr(GLIBC_2.2) [SUSv3]	strsep(GLIBC_2.2) [LSB]	strsignal(GLIBC_2.2) [LSB]
strspn(GLIBC_2.2) [SUSv3]	strstr(GLIBC_2.2) [SUSv3]	strtof(GLIBC_2.2) [SUSv3]	strtoimax(GLIBC_2.2) [SUSv3]
strtok(GLIBC_2.2) [SUSv3]	strtok_r(GLIBC_2.2) [SUSv3]	strtold(GLIBC_2.2) [SUSv3]	strtoll(GLIBC_2.2) [SUSv3]
strtoq(GLIBC_2.2) [LSB]	strtoull(GLIBC_2.2) [SUSv3]	strtoumax(GLIBC_2.2) [SUSv3]	strtouq(GLIBC_2.2) [LSB]
strxfrm(GLIBC_2.2) [SUSv3]	swab(GLIBC_2.2) [SUSv3]		

## 11.2.9 IPC Functions

### 11.2.9.1 Interfaces for IPC Functions

An LSB conforming implementation shall provide the architecture specific functions for IPC Functions specified in Table 11-13, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-13 libc - IPC Functions Function Interfaces**

ftok(GLIBC_2.2) [SUSv3]	msgctl(GLIBC_2.2) [SUSv3]	msgget(GLIBC_2.2) [SUSv3]	msgrcv(GLIBC_2.2) [SUSv3]
msgsnd(GLIBC_2.2) [SUSv3]	semctl(GLIBC_2.2) [SUSv3]	semget(GLIBC_2.2) [SUSv3]	semop(GLIBC_2.2) [SUSv3]
shmat(GLIBC_2.2) [SUSv3]	shmctl(GLIBC_2.2) [SUSv3]	shmdt(GLIBC_2.2) [SUSv3]	shmget(GLIBC_2.2) [SUSv3]

## 11.2.10 Regular Expressions

### 11.2.10.1 Interfaces for Regular Expressions

An LSB conforming implementation shall provide the architecture specific functions for Regular Expressions specified in Table 11-14, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-14 libc - Regular Expressions Function Interfaces**

regcomp(GLIBC_2.2) [SUSv3]	regerror(GLIBC_2.2) [SUSv3]	regexexec(GLIBC_2.3.4) [LSB]	regfree(GLIBC_2.2) [SUSv3]
----------------------------	-----------------------------	------------------------------	----------------------------

## 11.2.11 Character Type Functions

### 11.2.11.1 Interfaces for Character Type Functions

An LSB conforming implementation shall provide the architecture specific functions for Character Type Functions specified in Table 11-15, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-15 libc - Character Type Functions Function Interfaces**

__ctype_get_mb_cur_max(GLIBC_2.2) [LSB]	_tolower(GLIBC_2.2) [SUSv3]	_toupper(GLIBC_2.2) [SUSv3]	isalnum(GLIBC_2.2) [SUSv3]
isalpha(GLIBC_2.2) [SUSv3]	isascii(GLIBC_2.2) [SUSv3]	isctrl(GLIBC_2.2) [SUSv3]	isdigit(GLIBC_2.2) [SUSv3]
isgraph(GLIBC_2.2) [SUSv3]	islower(GLIBC_2.2) [SUSv3]	isprint(GLIBC_2.2) [SUSv3]	ispunct(GLIBC_2.2) [SUSv3]
isspace(GLIBC_2.2) [SUSv3]	isupper(GLIBC_2.2) [SUSv3]	iswalnum(GLIBC_2.2) [SUSv3]	iswalpha(GLIBC_2.2) [SUSv3]
iswblank(GLIBC_2.2) [SUSv3]	iswcntrl(GLIBC_2.2) [SUSv3]	iswctype(GLIBC_2.2) [SUSv3]	iswdigit(GLIBC_2.2) [SUSv3]
iswgraph(GLIBC_2.2) [SUSv3]	iswlower(GLIBC_2.2) [SUSv3]	iswprint(GLIBC_2.2) [SUSv3]	iswpunct(GLIBC_2.2) [SUSv3]

iswspace(GLIBC_2.2) [SUSv3]	iswupper(GLIBC_2.2) [SUSv3]	iswxdigit(GLIBC_2.2) [SUSv3]	isxdigit(GLIBC_2.2) [SUSv3]
toascii(GLIBC_2.2) [SUSv3]	tolower(GLIBC_2.2) [SUSv3]	toupper(GLIBC_2.2) [SUSv3]	

## 11.2.12 Time Manipulation

### 11.2.12.1 Interfaces for Time Manipulation

An LSB conforming implementation shall provide the architecture specific functions for Time Manipulation specified in Table 11-16, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-16 libc - Time Manipulation Function Interfaces**

adjtime(GLIBC_2.2) [LSB]	asctime(GLIBC_2.2) [SUSv3]	asctime_r(GLIBC_2.2) [SUSv3]	ctime(GLIBC_2.2) [SUSv3]
ctime_r(GLIBC_2.2) [SUSv3]	difftime(GLIBC_2.2) [SUSv3]	gmtime(GLIBC_2.2) [SUSv3]	gmtime_r(GLIBC_2.2) [SUSv3]
localtime(GLIBC_2.2) [SUSv3]	localtime_r(GLIBC_2.2) [SUSv3]	mktime(GLIBC_2.2) [SUSv3]	tzset(GLIBC_2.2) [SUSv3]
ualarm(GLIBC_2.2) [SUSv3]			

An LSB conforming implementation shall provide the architecture specific data interfaces for Time Manipulation specified in Table 11-17, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-17 libc - Time Manipulation Data Interfaces**

__daylight(GLIBC_2.2) [LSB]	__timezone(GLIBC_2.2) [LSB]	__tzname(GLIBC_2.2) [LSB]	daylight(GLIBC_2.2) [SUSv3]
timezone(GLIBC_2.2) [SUSv3]	tzname(GLIBC_2.2) [SUSv3]		

## 11.2.13 Terminal Interface Functions

### 11.2.13.1 Interfaces for Terminal Interface Functions

An LSB conforming implementation shall provide the architecture specific functions for Terminal Interface Functions specified in Table 11-18, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-18 libc - Terminal Interface Functions Function Interfaces**

cfgetispeed(GLIBC_2.2) [SUSv3]	cfgetospeed(GLIBC_2.2) [SUSv3]	cfmakeraw(GLIBC_2.2) [LSB]	cfsetispeed(GLIBC_2.2) [SUSv3]
cfsetospeed(GLIBC_2.2) [SUSv3]	cfsetspeed(GLIBC_2.2) [LSB]	tcdrain(GLIBC_2.2) [SUSv3]	tcflow(GLIBC_2.2) [SUSv3]
tcflush(GLIBC_2.2) [SUSv3]	tcgetattr(GLIBC_2.2) [SUSv3]	tcgetpgrp(GLIBC_2.2) [SUSv3]	tcgetsid(GLIBC_2.2) [SUSv3]
tcsendbreak(GLIBC_2.2) [SUSv3]	tcsetattr(GLIBC_2.2) [SUSv3]	tcsetpgrp(GLIBC_2.2) [SUSv3]	

BC_2.2) [SUSv3]	2.2) [SUSv3]	_2.2) [SUSv3]	
-----------------	--------------	---------------	--

## 11.2.14 System Database Interface

### 11.2.14.1 Interfaces for System Database Interface

An LSB conforming implementation shall provide the architecture specific functions for System Database Interface specified in Table 11-19, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-19 libc - System Database Interface Function Interfaces**

endgrent(GLIBC_2.2) [SUSv3]	endprotoent(GLIBC_2.2) [SUSv3]	endpwent(GLIBC_2.2) [SUSv3]	endservent(GLIBC_2.2) [SUSv3]
endutent(GLIBC_2.2) [LSB]	endutxent(GLIBC_2.2) [SUSv3]	getgrent(GLIBC_2.2) [SUSv3]	getgrgid(GLIBC_2.2) [SUSv3]
getgrgid_r(GLIBC_2.2) [SUSv3]	getgrnam(GLIBC_2.2) [SUSv3]	getgrnam_r(GLIBC_2.2) [SUSv3]	getgrouplist(GLIBC_2.2.4) [LSB]
gethostbyaddr(GLIBC_2.2) [SUSv3]	gethostbyname(GLIBC_2.2) [SUSv3]	getprotobyname(GLIBC_2.2) [SUSv3]	getprotobynumber(GLIBC_2.2) [SUSv3]
getprotoent(GLIBC_2.2) [SUSv3]	getpwent(GLIBC_2.2) [SUSv3]	getpwnam(GLIBC_2.2) [SUSv3]	getpwnam_r(GLIBC_2.2) [SUSv3]
getpwuid(GLIBC_2.2) [SUSv3]	getpwuid_r(GLIBC_2.2) [SUSv3]	getservbyname(GLIBC_2.2) [SUSv3]	getservbyport(GLIBC_2.2) [SUSv3]
getservent(GLIBC_2.2) [SUSv3]	getutent(GLIBC_2.2) [LSB]	getutent_r(GLIBC_2.2) [LSB]	getutxent(GLIBC_2.2) [SUSv3]
getutxid(GLIBC_2.2) [SUSv3]	getutxline(GLIBC_2.2) [SUSv3]	pututxline(GLIBC_2.2) [SUSv3]	setgrent(GLIBC_2.2) [SUSv3]
setgroups(GLIBC_2.2) [LSB]	setprotoent(GLIBC_2.2) [SUSv3]	setpwent(GLIBC_2.2) [SUSv3]	setservent(GLIBC_2.2) [SUSv3]
setutent(GLIBC_2.2) [LSB]	setutxent(GLIBC_2.2) [SUSv3]	utmpname(GLIBC_2.2) [LSB]	

## 11.2.15 Language Support

### 11.2.15.1 Interfaces for Language Support

An LSB conforming implementation shall provide the architecture specific functions for Language Support specified in Table 11-20, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-20 libc - Language Support Function Interfaces**

__libc_start_main(GLIBC_2.2) [LSB]			
------------------------------------	--	--	--

## 11.2.16 Large File Support

### 11.2.16.1 Interfaces for Large File Support

An LSB conforming implementation shall provide the architecture specific functions for Large File Support specified in Table 11-21, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-21 libc - Large File Support Function Interfaces

__fxstat64(GLIBC_C_2.2) [LSB]	__lxstat64(GLIBC_2.2) [LSB]	__xstat64(GLIBC_2.2) [LSB]	creat64(GLIBC_2.2) [LFS]
fgetpos64(GLIBC_2.2) [LFS]	fopen64(GLIBC_2.2) [LFS]	freopen64(GLIBC_2.2) [LFS]	fseeko64(GLIBC_2.2) [LFS]
fsetpos64(GLIBC_2.2) [LFS]	fstatvfs64(GLIBC_2.2) [LFS]	ftello64(GLIBC_2.2) [LFS]	ftruncate64(GLIBC_C_2.2) [LFS]
ftw64(GLIBC_2.2) [LFS]	getrlimit64(GLIBC_C_2.2) [LFS]	lockf64(GLIBC_2.2) [LFS]	mkstemp64(GLIBC_2.2) [LFS]
mmap64(GLIBC_2.2) [LFS]	nftw64(GLIBC_2.3) [LFS]	readdir64(GLIBC_2.2) [LFS]	statvfs64(GLIBC_2.2) [LFS]
tmpfile64(GLIBC_2.2) [LFS]	truncate64(GLIBC_C_2.2) [LFS]		

## 11.2.17 Standard Library

### 11.2.17.1 Interfaces for Standard Library

An LSB conforming implementation shall provide the architecture specific functions for Standard Library specified in Table 11-22, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-22 libc - Standard Library Function Interfaces

_Exit(GLIBC_2.2) [SUSv3]	__assert_fail(GLIBC_2.2) [LSB]	__cxa_atexit(GLIBC_2.2) [LSB]	__errno_location(GLIBC_2.2) [LSB]
__fpending(GLIBC_C_2.2) [LSB]	__getpagesize(GLIBC_2.2) [LSB]	__isinf(GLIBC_2.2) [LSB]	__isinf(GLIBC_2.2) [LSB]
__isnfl(GLIBC_2.2) [LSB]	__isnan(GLIBC_2.2) [LSB]	__isnanf(GLIBC_2.2) [LSB]	__isnanl(GLIBC_2.2) [LSB]
__sysconf(GLIBC_2.2) [LSB]	_exit(GLIBC_2.2) [SUSv3]	_longjmp(GLIBC_2.2) [SUSv3]	_setjmp(GLIBC_2.2) [SUSv3]
a64l(GLIBC_2.2) [SUSv3]	abort(GLIBC_2.2) [SUSv3]	abs(GLIBC_2.2) [SUSv3]	atof(GLIBC_2.2) [SUSv3]
atoi(GLIBC_2.2) [SUSv3]	atol(GLIBC_2.2) [SUSv3]	atoll(GLIBC_2.2) [SUSv3]	basename(GLIBC_2.2) [SUSv3]
bsearch(GLIBC_2.2) [SUSv3]	calloc(GLIBC_2.2) [SUSv3]	closelog(GLIBC_2.2) [SUSv3]	confstr(GLIBC_2.2) [SUSv3]
cuserid(GLIBC_2.2) [SUSv2]	daemon(GLIBC_2.2) [LSB]	dirname(GLIBC_2.2) [SUSv3]	div(GLIBC_2.2) [SUSv3]

drand48(GLIBC_2.2) [SUSv3]	ecvt(GLIBC_2.2) [SUSv3]	erand48(GLIBC_2.2) [SUSv3]	err(GLIBC_2.2) [LSB]
error(GLIBC_2.2) [LSB]	errx(GLIBC_2.2) [LSB]	fcvt(GLIBC_2.2) [SUSv3]	fmtmsg(GLIBC_2.2) [SUSv3]
fnmatch(GLIBC_2.2.3) [SUSv3]	fpathconf(GLIBC_2.2) [SUSv3]	free(GLIBC_2.2) [SUSv3]	freeaddrinfo(GLIBC_2.2) [SUSv3]
ftrylockfile(GLIBC_2.2) [SUSv3]	ftw(GLIBC_2.2) [SUSv3]	funlockfile(GLIBC_2.2) [SUSv3]	gai_strerror(GLIBC_2.2) [SUSv3]
gcvt(GLIBC_2.2) [SUSv3]	getaddrinfo(GLIBC_2.2) [SUSv3]	getcwd(GLIBC_2.2) [SUSv3]	getdate(GLIBC_2.2) [SUSv3]
getenv(GLIBC_2.2) [SUSv3]	getlogin(GLIBC_2.2) [SUSv3]	getlogin_r(GLIBC_2.2) [SUSv3]	getnameinfo(GLIBC_2.2) [SUSv3]
getopt(GLIBC_2.2) [LSB]	getopt_long(GLIBC_2.2) [LSB]	getopt_long_only(GLIBC_2.2) [LSB]	getsubopt(GLIBC_2.2) [SUSv3]
gettimeofday(GLIBC_2.2) [SUSv3]	glob(GLIBC_2.2) [SUSv3]	glob64(GLIBC_2.2) [LSB]	globfree(GLIBC_2.2) [SUSv3]
globfree64(GLIBC_2.2) [LSB]	grantpt(GLIBC_2.2) [SUSv3]	hcreate(GLIBC_2.2) [SUSv3]	hdestroy(GLIBC_2.2) [SUSv3]
hsearch(GLIBC_2.2) [SUSv3]	htonl(GLIBC_2.2) [SUSv3]	htons(GLIBC_2.2) [SUSv3]	imaxabs(GLIBC_2.2) [SUSv3]
imaxdiv(GLIBC_2.2) [SUSv3]	inet_addr(GLIBC_2.2) [SUSv3]	inet_ntoa(GLIBC_2.2) [SUSv3]	inet_ntop(GLIBC_2.2) [SUSv3]
inet_pton(GLIBC_2.2) [SUSv3]	initstate(GLIBC_2.2) [SUSv3]	insque(GLIBC_2.2) [SUSv3]	isatty(GLIBC_2.2) [SUSv3]
isblank(GLIBC_2.2) [SUSv3]	jrand48(GLIBC_2.2) [SUSv3]	l64a(GLIBC_2.2) [SUSv3]	labs(GLIBC_2.2) [SUSv3]
lcong48(GLIBC_2.2) [SUSv3]	ldiv(GLIBC_2.2) [SUSv3]	lfind(GLIBC_2.2) [SUSv3]	llabs(GLIBC_2.2) [SUSv3]
lldiv(GLIBC_2.2) [SUSv3]	longjmp(GLIBC_2.2) [SUSv3]	lrand48(GLIBC_2.2) [SUSv3]	lsearch(GLIBC_2.2) [SUSv3]
makecontext(GLIBC_2.2) [SUSv3]	malloc(GLIBC_2.2) [SUSv3]	memmem(GLIBC_2.2) [LSB]	mkstemp(GLIBC_2.2) [SUSv3]
mktemp(GLIBC_2.2) [SUSv3]	mrnd48(GLIBC_2.2) [SUSv3]	nftw(GLIBC_2.3) [SUSv3]	nrnd48(GLIBC_2.2) [SUSv3]
ntohl(GLIBC_2.2) [SUSv3]	ntohs(GLIBC_2.2) [SUSv3]	openlog(GLIBC_2.2) [SUSv3]	perror(GLIBC_2.2) [SUSv3]
posix_memalign(GLIBC_2.2) [SUSv3]	posix_openpt(GLIBC_2.2.1) [SUSv3]	ptsname(GLIBC_2.2) [SUSv3]	putenv(GLIBC_2.2) [SUSv3]
qsort(GLIBC_2.2) [SUSv3]	rand(GLIBC_2.2) [SUSv3]	rand_r(GLIBC_2.2) [SUSv3]	random(GLIBC_2.2) [SUSv3]
realloc(GLIBC_2.2) [SUSv3]	realpath(GLIBC_2.2) [SUSv3]	remque(GLIBC_2.2) [SUSv3]	seed48(GLIBC_2.2) [SUSv3]

2) [SUSv3]	2.3) [SUSv3]	.2) [SUSv3]	2) [SUSv3]
setenv(GLIBC_2.2) [SUSv3]	sethostname(GLIBC_2.2) [LSB]	setlogmask(GLIBC_2.2) [SUSv3]	setstate(GLIBC_2.2) [SUSv3]
srand(GLIBC_2.2) [SUSv3]	srand48(GLIBC_2.2) [SUSv3]	srandom(GLIBC_2.2) [SUSv3]	strtod(GLIBC_2.2) [SUSv3]
strtol(GLIBC_2.2) [SUSv3]	strtoul(GLIBC_2.2) [SUSv3]	swapcontext(GLIBC_2.2) [SUSv3]	syslog(GLIBC_2.2) [SUSv3]
system(GLIBC_2.2) [LSB]	tdelete(GLIBC_2.2) [SUSv3]	tfind(GLIBC_2.2) [SUSv3]	tmpfile(GLIBC_2.2) [SUSv3]
tmpnam(GLIBC_2.2) [SUSv3]	tsearch(GLIBC_2.2) [SUSv3]	ttyname(GLIBC_2.2) [SUSv3]	ttyname_r(GLIBC_2.2) [SUSv3]
twalk(GLIBC_2.2) [SUSv3]	unlockpt(GLIBC_2.2) [SUSv3]	unsetenv(GLIBC_2.2) [SUSv3]	usleep(GLIBC_2.2) [SUSv3]
verrx(GLIBC_2.2) [LSB]	vfscanf(GLIBC_2.2) [LSB]	vscanf(GLIBC_2.2) [LSB]	vsscanf(GLIBC_2.2) [LSB]
vsyslog(GLIBC_2.2) [LSB]	warn(GLIBC_2.2) [LSB]	warnx(GLIBC_2.2) [LSB]	wordexp(GLIBC_2.2) [SUSv3]
wordfree(GLIBC_2.2) [SUSv3]			

An LSB conforming implementation shall provide the architecture specific data interfaces for Standard Library specified in Table 11-23, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-23 libc - Standard Library Data Interfaces**

__environ(GLIBC_C_2.2) [LSB]	_environ(GLIBC_2.2) [LSB]	_sys_errlist(GLIBC_C_2.3) [LSB]	environ(GLIBC_2.2) [SUSv3]
getdate_err(GLIBC_C_2.2) [SUSv3]	optarg(GLIBC_2.2) [SUSv3]	opterr(GLIBC_2.2) [SUSv3]	optind(GLIBC_2.2) [SUSv3]
optopt(GLIBC_2.2) [SUSv3]			

### 11.3 Data Definitions for libc

This section defines global identifiers and their values that are associated with interfaces contained in libc. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the [ISO C \(1999\)](#) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language

description of these data objects does not preclude their use by other programming languages.

### 11.3.1 ctype.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.2 dirent.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.3 errno.h

```
#define EDEADLOCK      35
```

### 11.3.4 fcntl.h

```
#define F_GETLK64      5
#define F_SETLK64      6
#define F_SETLKW64     7
```

### 11.3.5 fnmatch.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.6 ftw.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.7 getopt.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.8 glob.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

**11.3.9 iconv.h**

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */

```

**11.3.10 inttypes.h**

```

typedef long int intmax_t;
typedef unsigned long int uintmax_t;
typedef unsigned long int uintptr_t;
typedef unsigned long int uint64_t;

```

**11.3.11 langinfo.h**

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */

```

**11.3.12 limits.h**

```

#define ULONG_MAX 0xFFFFFFFFFFFFFFFFUL
#define LONG_MAX 9223372036854775807L

#define CHAR_MIN 0
#define CHAR_MAX 255

#define PTHREAD_STACK_MIN 16384

```

**11.3.13 locale.h**

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */

```

**11.3.14 net/if.h**

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */

```

**11.3.15 netdb.h**

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */

```

**11.3.16 netinet/in.h**

```

/*
 * This header is architecture neutral

```

```
* Please refer to the generic specification for details
*/
```

### 11.3.17 netinet/ip.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.18 netinet/tcp.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.19 netinet/udp.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.20 nl\_types.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.21 pwd.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.22 regex.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.23 rpc/auth.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.24 rpc/clnt.h

```
/*
 * This header is architecture neutral
```

```
* Please refer to the generic specification for details
*/
```

### 11.3.25 rpc/rpc\_msg.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.26 rpc/svc.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.27 rpc/types.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.28 rpc/xdr.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.29 sched.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.30 search.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.31 setjmp.h

```
typedef long int __jmp_buf[18];
```

### 11.3.32 signal.h

```
#define __NUM_ACRS 16
#define __NUM_FPRS 16
#define __NUM_GPRS 16
```

```
typedef struct {
```

```

    unsigned long int mask;
    unsigned long int addr;
} __attribute__((aligned(8)))
    _psw_t;
typedef struct {
    _psw_t psw;
    unsigned long int gprs[16];
    unsigned int acrs[16];
} _s390_regs_common;

#define SIGEV_PAD_SIZE ((SIGEV_MAX_SIZE/sizeof(int))-4)

#define SI_PAD_SIZE ((SI_MAX_SIZE/sizeof(int))-4)

struct sigaction {
    union {
        sighandler_t _sa_handler;
        void (*_sa_sigaction) (int, siginfo_t *, void *);
    } __sigaction_handler;
    unsigned long int sa_flags;
    void (*sa_restorer) (void);
    sigset_t sa_mask;
};

#define MINSIGSTKSZ 2048
#define SIGSTKSZ 8192

typedef struct {
    unsigned int fpc;
    double fprs[__NUM_FPRS];
} _s390_fp_regs;
typedef struct {
    _s390_regs_common regs;
    _s390_fp_regs fpregs;
} _sigregs;

struct sigcontext {
    unsigned long int oldmask;
    _sigregs *sregs;
};

```

### 11.3.33 stddef.h

```

typedef unsigned long int size_t;
typedef long int ptrdiff_t;

```

### 11.3.34 stdio.h

```

#define __IO_FILE_SIZE 216

```

### 11.3.35 stdlib.h

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */

```

### 11.3.36 sys/file.h

```

/*
 * This header is architecture neutral

```

```

* Please refer to the generic specification for details
*/

```

### 11.3.37 sys/ioctl.h

```

#define TIOCGWINSZ      0x5413
#define FIONREAD        21531
#define TIOCNOTTY      21538

```

### 11.3.38 sys/ipc.h

```

struct ipc_perm {
    key_t __key;
    uid_t uid;
    gid_t gid;
    uid_t cuid;
    gid_t cgid;
    mode_t mode;
    unsigned short __seq;
    unsigned short __pad2;
    unsigned long int __unused1;
    unsigned long int __unused2;
};

```

### 11.3.39 sys/mman.h

```

#define MCL_CURRENT      1
#define MCL_FUTURE      2

```

### 11.3.40 sys/msg.h

```

typedef unsigned long int msgqnum_t;
typedef unsigned long int msglen_t;

```

```

struct msqid_ds {
    struct ipc_perm msg_perm;
    time_t msg_stime;
    time_t msg_rtime;
    time_t msg_ctime;
    unsigned long int __msg_cbytes;
    msgqnum_t msg_qnum;
    msglen_t msg_qbytes;
    pid_t msg_lspid;
    pid_t msg_lrpid;
    unsigned long int __unused4;
    unsigned long int __unused5;
};

```

### 11.3.41 sys/param.h

```

/*
* This header is architecture neutral
* Please refer to the generic specification for details
*/

```

### 11.3.42 sys/poll.h

```

/*

```

```

* This header is architecture neutral
* Please refer to the generic specification for details
*/

```

### 11.3.43 sys/resource.h

```

/*
* This header is architecture neutral
* Please refer to the generic specification for details
*/

```

### 11.3.44 sys/sem.h

```

struct semid_ds {
    struct ipc_perm sem_perm;
    time_t sem_otime;
    time_t sem_ctime;
    unsigned long int sem_nsems;
    unsigned long int __unused3;
    unsigned long int __unused4;
};

```

### 11.3.45 sys/shm.h

```

#define SHMLBA 4096

typedef unsigned long int shmatt_t;

struct shmid_ds {
    struct ipc_perm shm_perm;
    size_t shm_segsz;
    time_t shm_atime;
    time_t shm_dtime;
    time_t shm_ctime;
    pid_t shm_cpid;
    pid_t shm_lpid;
    shmatt_t shm_nattch;
    unsigned long int __unused4;
    unsigned long int __unused5;
};

```

### 11.3.46 sys/socket.h

```

typedef uint64_t __ss_aligntype;

#define SO_RCVLOWAT 18
#define SO_SNDLOWAT 19
#define SO_RCVTIMEO 20
#define SO_SNDTIMEO 21

```

### 11.3.47 sys/stat.h

```

#define _STAT_VER 1

struct stat {
    dev_t st_dev;
    ino_t st_ino;
    nlink_t st_nlink;
    mode_t st_mode;
    uid_t st_uid;
};

```

```

    gid_t st_gid;
    int pad0;
    dev_t st_rdev;
    off_t st_size;
    struct timespec st_atim;
    struct timespec st_mtim;
    struct timespec st_ctim;
    blksize_t st_blksize;
    blkcnt_t st_blocks;
    long int __unused[3];
};
struct stat64 {
    dev_t st_dev;
    ino64_t st_ino;
    nlink_t st_nlink;
    mode_t st_mode;
    uid_t st_uid;
    gid_t st_gid;
    int pad0;
    dev_t st_rdev;
    off_t st_size;
    struct timespec st_atim;
    struct timespec st_mtim;
    struct timespec st_ctim;
    blksize_t st_blksize;
    blkcnt64_t st_blocks;
    long int __unused[3];
};

```

### 11.3.48 sys/statvfs.h

```

struct statvfs {
    unsigned long int f_bsize;
    unsigned long int f_frsize;
    fsblkcnt64_t f_blocks;
    fsblkcnt64_t f_bfree;
    fsblkcnt64_t f_bavail;
    fsfilcnt64_t f_files;
    fsfilcnt64_t f_ffree;
    fsfilcnt64_t f_favail;
    unsigned long int f_fsid;
    unsigned long int f_flag;
    unsigned long int f_namemax;
    int _f_spare[6];
};
struct statvfs64 {
    unsigned long int f_bsize;
    unsigned long int f_frsize;
    fsblkcnt64_t f_blocks;
    fsblkcnt64_t f_bfree;
    fsblkcnt64_t f_bavail;
    fsfilcnt64_t f_files;
    fsfilcnt64_t f_ffree;
    fsfilcnt64_t f_favail;
    unsigned long int f_fsid;
    unsigned long int f_flag;
    unsigned long int f_namemax;
    int __f_spare[6];
};

```

### 11.3.49 sys/time.h

```

/*
 * This header is architecture neutral

```

```
* Please refer to the generic specification for details
*/
```

### 11.3.50 sys/timeb.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.51 sys/times.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.52 sys/types.h

```
typedef long int int64_t;

typedef int64_t ssize_t;

#define __FDSET_LONGS 16
```

### 11.3.53 sys/un.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.54 sys/utsname.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.55 sys/wait.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.56 syslog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.3.57 termios.h

```
#define CR2 1024
```

```

#define CR3      1536
#define CRDLY    1536
#define VT1      16384
#define VTDLY    16384
#define OLCUC    2
#define TAB1     2048
#define NLDLY    256
#define FF1      32768
#define FFDLY    32768
#define ONLCR    4
#define XCASE    4
#define TAB2     4096
#define CR1      512
#define IUCLC    512
#define TAB3     6144
#define TABDLY   6144
#define BS1      8192
#define BSDLY    8192

#define VSUSP    10
#define VEOL     11
#define VREPRINT 12
#define VDISCARD 13
#define VWERASE  14
#define VEOL2    16
#define VMIN     6
#define VSWTC    7
#define VSTART   8
#define VSTOP    9

#define IXON     1024
#define IXOFF    4096

#define HUPCL    1024
#define CREAD    128
#define CS6      16
#define CLOCAL   2048
#define PARENB   256
#define CS7      32
#define CS8      48
#define CSIZE    48
#define VTIME    5
#define PARODD   512
#define CSTOPB   64

#define ISIG     1
#define ECHOPRT  1024
#define NOFLSH   128
#define ECHOE    16
#define PENDIN   16384
#define ICANON   2
#define ECHOKE   2048
#define TOSTOP   256
#define ECHOK    32
#define IEXTEN   32768
#define FLUSHO   4096
#define ECHOCTL  512
#define ECHONL   64

```

### 11.3.58 ucontext.h

```

#define NGREG    27

typedef union {
    double d;

```

```

    float f;
} fpreg_t;

typedef struct {
    unsigned int fpc;
    fpreg_t fprs[16];
} fpregset_t;

typedef struct {
    _psw_t psw;
    unsigned long int gregs[16];
    unsigned int aregs[16];
    fpregset_t fpregs;
} mcontext_t;

typedef struct ucontext {
    unsigned long int uc_flags;
    struct ucontext *uc_link;
    stack_t uc_stack;
    mcontext_t uc_mcontext;
    sigset_t uc_sigmask;
} ucontext_t;

```

### 11.3.59 ulimit.h

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */

```

### 11.3.60 unistd.h

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */

```

### 11.3.61 utime.h

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */

```

### 11.3.62 utmp.h

```

struct lastlog {
    time_t ll_time;
    char ll_line[UT_LINESIZE];
    char ll_host[UT_HOSTSIZE];
};

struct utmp {
    short ut_type;
    pid_t ut_pid;
    char ut_line[UT_LINESIZE];
    char ut_id[4];
    char ut_user[UT_NAMESIZE];
    char ut_host[UT_HOSTSIZE];
    struct exit_status ut_exit;
    long int ut_session;
};

```

```

    struct timeval ut_tv;
    int32_t ut_addr_v6[4];
    char __unused[20];
};

```

### 11.3.63 utmpx.h

```

struct utmpx {
    short ut_type;
    pid_t ut_pid;
    char ut_line[UT_LINESIZE];
    char ut_id[4];
    char ut_user[UT_NAMESIZE];
    char ut_host[UT_HOSTSIZE];
    struct exit_status ut_exit;
    long int ut_session;
    struct timeval ut_tv;
    int32_t ut_addr_v6[4];
    char __unused[20];
};

```

### 11.3.64 wctype.h

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */

```

### 11.3.65 wordexp.h

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */

```

## 11.4 Interfaces for libm

Table 11-24 defines the library name and shared object name for the libm library

**Table 11-24 libm Definition**

Library:	libm
SONAME:	libm.so.6

The behavior of the interfaces in this library is specified by the following specifications:

- [ISOC99] [ISO C \(1999\)](#)
- [LSB] [ISO/IEC 23360-1](#)
- [SUSv2] [SUSv2](#)
- [SUSv3] [ISO POSIX \(2003\)](#)
- [SVID.3] [SVID Issue 3](#)

## 11.4.1 Math

### 11.4.1.1 Interfaces for Math

An LSB conforming implementation shall provide the architecture specific functions for Math specified in Table 11-25, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-25 libm - Math Function Interfaces**

<code>__finite(GLIBC_2.2)</code> [ISOC99]	<code>__finitef(GLIBC_2.2)</code> [ISOC99]	<code>__finitel(GLIBC_2.2)</code> [ISOC99]	<code>__fpclassify(GLIBC_2.2)</code> [LSB]
<code>__fpclassifyf(GLIBC_2.2)</code> [LSB]	<code>acos(GLIBC_2.2)</code> [SUSv3]	<code>acosf(GLIBC_2.2)</code> [SUSv3]	<code>acosh(GLIBC_2.2)</code> [SUSv3]
<code>acoshf(GLIBC_2.2)</code> [SUSv3]	<code>acoshl(GLIBC_2.2)</code> [SUSv3]	<code>acosl(GLIBC_2.2)</code> [SUSv3]	<code>asin(GLIBC_2.2)</code> [SUSv3]
<code>asinf(GLIBC_2.2)</code> [SUSv3]	<code>asinh(GLIBC_2.2)</code> [SUSv3]	<code>asinhf(GLIBC_2.2)</code> [SUSv3]	<code>asinhf(GLIBC_2.2)</code> [SUSv3]
<code>asinl(GLIBC_2.2)</code> [SUSv3]	<code>atan(GLIBC_2.2)</code> [SUSv3]	<code>atan2(GLIBC_2.2)</code> [SUSv3]	<code>atan2f(GLIBC_2.2)</code> [SUSv3]
<code>atan2l(GLIBC_2.2)</code> [SUSv3]	<code>atanf(GLIBC_2.2)</code> [SUSv3]	<code>atanh(GLIBC_2.2)</code> [SUSv3]	<code>atanhf(GLIBC_2.2)</code> [SUSv3]
<code>atanhl(GLIBC_2.2)</code> [SUSv3]	<code>atanl(GLIBC_2.2)</code> [SUSv3]	<code>cabs(GLIBC_2.2)</code> [SUSv3]	<code>cabsf(GLIBC_2.2)</code> [SUSv3]
<code>cabsl(GLIBC_2.2)</code> [SUSv3]	<code>cacos(GLIBC_2.2)</code> [SUSv3]	<code>cacosf(GLIBC_2.2)</code> [SUSv3]	<code>cacosh(GLIBC_2.2)</code> [SUSv3]
<code>cacoshf(GLIBC_2.2)</code> [SUSv3]	<code>cacoshl(GLIBC_2.2)</code> [SUSv3]	<code>cacosl(GLIBC_2.2)</code> [SUSv3]	<code>carg(GLIBC_2.2)</code> [SUSv3]
<code>cargf(GLIBC_2.2)</code> [SUSv3]	<code>cargl(GLIBC_2.2)</code> [SUSv3]	<code>casin(GLIBC_2.2)</code> [SUSv3]	<code>casinf(GLIBC_2.2)</code> [SUSv3]
<code>casinh(GLIBC_2.2)</code> [SUSv3]	<code>casinhf(GLIBC_2.2)</code> [SUSv3]	<code>casinhf(GLIBC_2.2)</code> [SUSv3]	<code>casinl(GLIBC_2.2)</code> [SUSv3]
<code>catan(GLIBC_2.2)</code> [SUSv3]	<code>catanf(GLIBC_2.2)</code> [SUSv3]	<code>catanh(GLIBC_2.2)</code> [SUSv3]	<code>catanhf(GLIBC_2.2)</code> [SUSv3]
<code>catanhl(GLIBC_2.2)</code> [SUSv3]	<code>catanl(GLIBC_2.2)</code> [SUSv3]	<code>cbrt(GLIBC_2.2)</code> [SUSv3]	<code>cbrtf(GLIBC_2.2)</code> [SUSv3]
<code>cbrtl(GLIBC_2.2)</code> [SUSv3]	<code>ccos(GLIBC_2.2)</code> [SUSv3]	<code>ccosf(GLIBC_2.2)</code> [SUSv3]	<code>ccosh(GLIBC_2.2)</code> [SUSv3]
<code>ccoshf(GLIBC_2.2)</code> [SUSv3]	<code>ccoshl(GLIBC_2.2)</code> [SUSv3]	<code>ccosl(GLIBC_2.2)</code> [SUSv3]	<code>ceil(GLIBC_2.2)</code> [SUSv3]
<code>ceilf(GLIBC_2.2)</code> [SUSv3]	<code>ceil(GLIBC_2.2)</code> [SUSv3]	<code>cexp(GLIBC_2.2)</code> [SUSv3]	<code>cexpf(GLIBC_2.2)</code> [SUSv3]
<code>cexpl(GLIBC_2.2)</code> [SUSv3]	<code>cimag(GLIBC_2.2)</code> [SUSv3]	<code>cimagf(GLIBC_2.2)</code> [SUSv3]	<code>cimagl(GLIBC_2.2)</code> [SUSv3]
<code>clog(GLIBC_2.2)</code>	<code>clog10(GLIBC_2.2)</code>	<code>clog10f(GLIBC_2.2)</code>	<code>clog10l(GLIBC_2.2)</code>

[SUSv3]	2) [ISOC99]	.2) [ISOC99]	2) [ISOC99]
clogf(GLIBC_2.2) [SUSv3]	clogl(GLIBC_2.2) [SUSv3]	conj(GLIBC_2.2) [SUSv3]	conjf(GLIBC_2.2) [SUSv3]
conjl(GLIBC_2.2) [SUSv3]	copysign(GLIBC_2.2) [SUSv3]	copysignf(GLIBC_2.2) [SUSv3]	copysignl(GLIBC_2.2) [SUSv3]
cos(GLIBC_2.2) [SUSv3]	cosf(GLIBC_2.2) [SUSv3]	cosh(GLIBC_2.2) [SUSv3]	coshf(GLIBC_2.2) [SUSv3]
coshl(GLIBC_2.2) [SUSv3]	cosl(GLIBC_2.2) [SUSv3]	cpow(GLIBC_2.2) [SUSv3]	cpowf(GLIBC_2.2) [SUSv3]
cpowl(GLIBC_2.2) [SUSv3]	cproj(GLIBC_2.2) [SUSv3]	cprojf(GLIBC_2.2) [SUSv3]	cprojl(GLIBC_2.2) [SUSv3]
creal(GLIBC_2.2) [SUSv3]	crealf(GLIBC_2.2) [SUSv3]	creall(GLIBC_2.2) [SUSv3]	csin(GLIBC_2.2) [SUSv3]
csinf(GLIBC_2.2) [SUSv3]	csinh(GLIBC_2.2) [SUSv3]	csinhf(GLIBC_2.2) [SUSv3]	csinhl(GLIBC_2.2) [SUSv3]
csinl(GLIBC_2.2) [SUSv3]	csqrt(GLIBC_2.2) [SUSv3]	csqrtf(GLIBC_2.2) [SUSv3]	csqrtl(GLIBC_2.2) [SUSv3]
ctan(GLIBC_2.2) [SUSv3]	ctanf(GLIBC_2.2) [SUSv3]	ctanh(GLIBC_2.2) [SUSv3]	ctanhf(GLIBC_2.2) [SUSv3]
ctanhl(GLIBC_2.2) [SUSv3]	ctanl(GLIBC_2.2) [SUSv3]	dremf(GLIBC_2.2) [ISOC99]	dreml(GLIBC_2.2) [ISOC99]
erf(GLIBC_2.2) [SUSv3]	erfc(GLIBC_2.2) [SUSv3]	erfcf(GLIBC_2.2) [SUSv3]	erfcl(GLIBC_2.2) [SUSv3]
erff(GLIBC_2.2) [SUSv3]	erfl(GLIBC_2.2) [SUSv3]	exp(GLIBC_2.2) [SUSv3]	exp2(GLIBC_2.2) [SUSv3]
exp2f(GLIBC_2.2) [SUSv3]	expf(GLIBC_2.2) [SUSv3]	expl(GLIBC_2.2) [SUSv3]	expm1(GLIBC_2.2) [SUSv3]
expm1f(GLIBC_2.2) [SUSv3]	expm1l(GLIBC_2.2) [SUSv3]	fabs(GLIBC_2.2) [SUSv3]	fabsf(GLIBC_2.2) [SUSv3]
fabsl(GLIBC_2.2) [SUSv3]	fdim(GLIBC_2.2) [SUSv3]	fdimf(GLIBC_2.2) [SUSv3]	fdiml(GLIBC_2.2) [SUSv3]
feclearexcept(GLIBC_2.2) [SUSv3]	fegetenv(GLIBC_2.2) [SUSv3]	fegetexceptflag(GLIBC_2.2) [SUSv3]	fegetround(GLIBC_2.2) [SUSv3]
feholdexcept(GLIBC_2.2) [SUSv3]	feraiseexcept(GLIBC_2.2) [SUSv3]	fesetenv(GLIBC_2.2) [SUSv3]	fesetexceptflag(GLIBC_2.2) [SUSv3]
fesetround(GLIBC_2.2) [SUSv3]	fetestexcept(GLIBC_2.2) [SUSv3]	feupdateenv(GLIBC_2.2) [SUSv3]	finite(GLIBC_2.2) [SUSv2]
finitf(GLIBC_2.2) [ISOC99]	finitel(GLIBC_2.2) [ISOC99]	floor(GLIBC_2.2) [SUSv3]	floorf(GLIBC_2.2) [SUSv3]
floorl(GLIBC_2.2) [SUSv3]	fma(GLIBC_2.2) [SUSv3]	fmaf(GLIBC_2.2) [SUSv3]	fmal(GLIBC_2.2) [SUSv3]

fmax(GLIBC_2.2) [SUSv3]	fmaxf(GLIBC_2.2) [SUSv3]	fmaxl(GLIBC_2.2) [SUSv3]	fmin(GLIBC_2.2) [SUSv3]
fminf(GLIBC_2.2) [SUSv3]	fminl(GLIBC_2.2) [SUSv3]	fmod(GLIBC_2.2) [SUSv3]	fmodf(GLIBC_2.2) [SUSv3]
fmodl(GLIBC_2.2) [SUSv3]	frexp(GLIBC_2.2) [SUSv3]	frexpf(GLIBC_2.2) [SUSv3]	frexpl(GLIBC_2.2) [SUSv3]
gamma(GLIBC_2.2) [SUSv2]	gammaf(GLIBC_2.2) [ISOC99]	gammal(GLIBC_2.2) [ISOC99]	hypot(GLIBC_2.2) [SUSv3]
hypotf(GLIBC_2.2) [SUSv3]	hypotl(GLIBC_2.2) [SUSv3]	ilogb(GLIBC_2.2) [SUSv3]	ilogbf(GLIBC_2.2) [SUSv3]
ilogbl(GLIBC_2.2) [SUSv3]	j0(GLIBC_2.2) [SUSv3]	j0f(GLIBC_2.2) [ISOC99]	j0l(GLIBC_2.2) [ISOC99]
j1(GLIBC_2.2) [SUSv3]	j1f(GLIBC_2.2) [ISOC99]	j1l(GLIBC_2.2) [ISOC99]	jn(GLIBC_2.2) [SUSv3]
jnf(GLIBC_2.2) [ISOC99]	jnl(GLIBC_2.2) [ISOC99]	ldexp(GLIBC_2.2) [SUSv3]	ldexpf(GLIBC_2.2) [SUSv3]
ldexpl(GLIBC_2.2) [SUSv3]	lgamma(GLIBC_2.2) [SUSv3]	lgamma_r(GLIBC_2.2) [ISOC99]	lgammaf(GLIBC_2.2) [SUSv3]
lgammaf_r(GLIBC_2.2) [ISOC99]	lgammal(GLIBC_2.2) [SUSv3]	lgamma_r(GLIBC_2.2) [ISOC99]	llrint(GLIBC_2.2) [SUSv3]
llrintf(GLIBC_2.2) [SUSv3]	llrintl(GLIBC_2.2) [SUSv3]	llround(GLIBC_2.2) [SUSv3]	llroundf(GLIBC_2.2) [SUSv3]
llroundl(GLIBC_2.2) [SUSv3]	log(GLIBC_2.2) [SUSv3]	log10(GLIBC_2.2) [SUSv3]	log10f(GLIBC_2.2) [SUSv3]
log10l(GLIBC_2.2) [SUSv3]	log1pf(GLIBC_2.2) [SUSv3]	log1pf(GLIBC_2.2) [SUSv3]	log1pl(GLIBC_2.2) [SUSv3]
log2(GLIBC_2.2) [SUSv3]	log2f(GLIBC_2.2) [SUSv3]	log2l(GLIBC_2.2) [SUSv3]	logb(GLIBC_2.2) [SUSv3]
logbf(GLIBC_2.2) [SUSv3]	logbl(GLIBC_2.2) [SUSv3]	logf(GLIBC_2.2) [SUSv3]	logl(GLIBC_2.2) [SUSv3]
lrint(GLIBC_2.2) [SUSv3]	lrintf(GLIBC_2.2) [SUSv3]	lrintl(GLIBC_2.2) [SUSv3]	lround(GLIBC_2.2) [SUSv3]
lroundf(GLIBC_2.2) [SUSv3]	lroundl(GLIBC_2.2) [SUSv3]	matherr(GLIBC_2.2) [SVID.3]	modf(GLIBC_2.2) [SUSv3]
modff(GLIBC_2.2) [SUSv3]	modfl(GLIBC_2.2) [SUSv3]	nan(GLIBC_2.2) [SUSv3]	nanf(GLIBC_2.2) [SUSv3]
nanl(GLIBC_2.2) [SUSv3]	nearbyint(GLIBC_2.2) [SUSv3]	nearbyintf(GLIBC_2.2) [SUSv3]	nearbyintl(GLIBC_2.2) [SUSv3]
nextafter(GLIBC_2.2) [SUSv3]	nextafterf(GLIBC_2.2) [SUSv3]	nextafterl(GLIBC_2.2) [SUSv3]	nexttoward(GLIBC_2.2) [SUSv3]
nexttowardf(GLIBC_2.2) [SUSv3]	nexttowardl(GLIBC_2.2) [SUSv3]	pow(GLIBC_2.2) [SUSv3]	pow10(GLIBC_2.2) [ISOC99]

pow10f(GLIBC_2.2) [ISOC99]	pow10l(GLIBC_2.2) [ISOC99]	powf(GLIBC_2.2) [SUSv3]	powl(GLIBC_2.2) [SUSv3]
remainder(GLIBC_2.2) [SUSv3]	remainderf(GLIBC_2.2) [SUSv3]	remainderl(GLIBC_2.2) [SUSv3]	remquo(GLIBC_2.2) [SUSv3]
remquof(GLIBC_2.2) [SUSv3]	remquol(GLIBC_2.2) [SUSv3]	rint(GLIBC_2.2) [SUSv3]	rintf(GLIBC_2.2) [SUSv3]
rintl(GLIBC_2.2) [SUSv3]	round(GLIBC_2.2) [SUSv3]	roundf(GLIBC_2.2) [SUSv3]	roundl(GLIBC_2.2) [SUSv3]
scalb(GLIBC_2.2) [SUSv3]	scalbf(GLIBC_2.2) [ISOC99]	scalbl(GLIBC_2.2) [ISOC99]	scalbln(GLIBC_2.2) [SUSv3]
scalblnf(GLIBC_2.2) [SUSv3]	scalblnl(GLIBC_2.2) [SUSv3]	scalbn(GLIBC_2.2) [SUSv3]	scalbnf(GLIBC_2.2) [SUSv3]
scalbnl(GLIBC_2.2) [SUSv3]	significand(GLIBC_2.2) [ISOC99]	significandf(GLIBC_2.2) [ISOC99]	significandl(GLIBC_2.2) [ISOC99]
sin(GLIBC_2.2) [SUSv3]	sincos(GLIBC_2.2) [ISOC99]	sincosf(GLIBC_2.2) [ISOC99]	sincosl(GLIBC_2.2) [ISOC99]
sinf(GLIBC_2.2) [SUSv3]	sinh(GLIBC_2.2) [SUSv3]	sinhf(GLIBC_2.2) [SUSv3]	sinhl(GLIBC_2.2) [SUSv3]
sinl(GLIBC_2.2) [SUSv3]	sqrt(GLIBC_2.2) [SUSv3]	sqrtf(GLIBC_2.2) [SUSv3]	sqrtl(GLIBC_2.2) [SUSv3]
tan(GLIBC_2.2) [SUSv3]	tanf(GLIBC_2.2) [SUSv3]	tanh(GLIBC_2.2) [SUSv3]	tanhf(GLIBC_2.2) [SUSv3]
tanhf(GLIBC_2.2) [SUSv3]	tanl(GLIBC_2.2) [SUSv3]	tgamma(GLIBC_2.2) [SUSv3]	tgammaf(GLIBC_2.2) [SUSv3]
tgammaf(GLIBC_2.2) [SUSv3]	trunc(GLIBC_2.2) [SUSv3]	truncf(GLIBC_2.2) [SUSv3]	truncl(GLIBC_2.2) [SUSv3]
y0(GLIBC_2.2) [SUSv3]	y0f(GLIBC_2.2) [ISOC99]	y0l(GLIBC_2.2) [ISOC99]	y1(GLIBC_2.2) [SUSv3]
y1f(GLIBC_2.2) [ISOC99]	y1l(GLIBC_2.2) [ISOC99]	yn(GLIBC_2.2) [SUSv3]	ynf(GLIBC_2.2) [ISOC99]
ynl(GLIBC_2.2) [ISOC99]			

An LSB conforming implementation shall provide the architecture specific data interfaces for Math specified in Table 11-26, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-26 libm - Math Data Interfaces**

signgam(GLIBC_2.2) [SUSv3]			
----------------------------	--	--	--

## 11.5 Data Definitions for libm

This section defines global identifiers and their values that are associated with interfaces contained in libm. These definitions are organized into groups that

correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the [ISO C \(1999\)](#) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 11.5.1 complex.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 11.5.2 fenv.h

```
#define FE_INEXACT          0x08
#define FE_UNDERFLOW       0x10
#define FE_OVERFLOW        0x20
#define FE_DIVBYZERO       0x40
#define FE_INVALID         0x80

#define FE_ALL_EXCEPT    \
    (FE_INEXACT | FE_DIVBYZERO | FE_UNDERFLOW | FE_OVERFLOW |
FE_INVALID)

#define FE_TONEAREST       0
#define FE_TOWARDZERO      0x1
#define FE_UPWARD          0x2
#define FE_DOWNWARD        0x3

typedef unsigned int fexcept_t;

typedef struct {
    fexcept_t fpc;
    void *ieee_instruction_pointer;
} fenv_t;

#define FE_DFL_ENV        ((__const fenv_t *) -1)
```

### 11.5.3 math.h

```
#define fpclassify(x)      \
    (sizeof (x) == sizeof (float) ? __fpclassifyf (x) :
__fpclassify (x) )
#define signbit(x)        \
    (sizeof (x) == sizeof (float)? __signbitf (x): __signbit (x))

#define FP_ILOGB0         -2147483647
#define FP_ILOGBNAN       2147483647
```

## 11.6 Interfaces for libpthread

Table 11-27 defines the library name and shared object name for the libpthread library

**Table 11-27 libpthread Definition**

Library:	libpthread
SONAME:	libpthread.so.0

The behavior of the interfaces in this library is specified by the following specifications:

[LFS] [Large File Support](#)

[LSB] [ISO/IEC 23360-1](#)

[SUSv3] [ISO POSIX \(2003\)](#)

### 11.6.1 Realtime Threads

#### 11.6.1.1 Interfaces for Realtime Threads

An LSB conforming implementation shall provide the architecture specific functions for Realtime Threads specified in Table 11-28, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-28 libpthread - Realtime Threads Function Interfaces**

pthread_attr_getinheritsched(GLIBC_2.2) [SUSv3]	pthread_attr_getschedpolicy(GLIBC_2.2) [SUSv3]	pthread_attr_getscope(GLIBC_2.2) [SUSv3]	pthread_attr_setinheritsched(GLIBC_2.2) [SUSv3]
pthread_attr_setschedpolicy(GLIBC_2.2) [SUSv3]	pthread_attr_setscope(GLIBC_2.2) [SUSv3]	pthread_getschedparam(GLIBC_2.2) [SUSv3]	pthread_setschedparam(GLIBC_2.2) [SUSv3]

### 11.6.2 Advanced Realtime Threads

#### 11.6.2.1 Interfaces for Advanced Realtime Threads

No external functions are defined for libpthread - Advanced Realtime Threads in this part of the specification. See also the generic specification, ISO/IEC 23360-1.

### 11.6.3 Posix Threads

#### 11.6.3.1 Interfaces for Posix Threads

An LSB conforming implementation shall provide the architecture specific functions for Posix Threads specified in Table 11-29, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-29 libpthread - Posix Threads Function Interfaces**

_pthread_cleanups_push(GLIBC_2.2) [LSB]	_pthread_cleanups_push(GLIBC_2.2) [LSB]	pthread_attr_desctroy(GLIBC_2.2) [SUSv3]	pthread_attr_getdetachstate(GLIBC_2.2) [SUSv3]
pthread_attr_getguardsize(GLIBC_2.2) [SUSv3]	pthread_attr_getschedparam(GLIBC_2.2) [SUSv3]	pthread_attr_getstack(GLIBC_2.2) [SUSv3]	pthread_attr_getstackaddr(GLIBC_2.2) [SUSv3]

pthread_attr_get stacksize(GLIBC _2.2) [SUSv3]	pthread_attr_init (GLIBC_2.2) [SUSv3]	pthread_attr_set detachstate(GLIB C_2.2) [SUSv3]	pthread_attr_set guardsize(GLIBC _2.2) [SUSv3]
pthread_attr_sets chedparam(GLIB C_2.2) [SUSv3]	pthread_attr_sets tackaddr(GLIBC _2.2) [SUSv3]	pthread_attr_sets tacksize(GLIBC_ 2.2) [SUSv3]	pthread_cancel( GLIBC_2.2) [SUSv3]
pthread_cond_br oadcast(GLIBC_2 .3.2) [SUSv3]	pthread_cond_de stroy(GLIBC_2.3. 2) [SUSv3]	pthread_cond_in it(GLIBC_2.3.2) [SUSv3]	pthread_cond_si gnal(GLIBC_2.3. 2) [SUSv3]
pthread_cond_ti medwait(GLIBC _2.3.2) [SUSv3]	pthread_cond_w ait(GLIBC_2.3.2) [SUSv3]	pthread_condattr _destroy(GLIBC_ 2.2) [SUSv3]	pthread_condattr _getpshared(GLI BC_2.2) [SUSv3]
pthread_condattr _init(GLIBC_2.2) [SUSv3]	pthread_condattr _setpshared(GLI BC_2.2) [SUSv3]	pthread_create(G LIBC_2.2) [SUSv3]	pthread_detach( GLIBC_2.2) [SUSv3]
pthread_equal(G LIBC_2.2) [SUSv3]	pthread_exit(GLI BC_2.2) [SUSv3]	pthread_getconc urrency(GLIBC_ 2.2) [SUSv3]	pthread_getspeci fic(GLIBC_2.2) [SUSv3]
pthread_join(GLI BC_2.2) [SUSv3]	pthread_key_cre ate(GLIBC_2.2) [SUSv3]	pthread_key_del ete(GLIBC_2.2) [SUSv3]	pthread_kill(GLI BC_2.2) [SUSv3]
pthread_mutex_ destroy(GLIBC_2 .2) [SUSv3]	pthread_mutex_i nit(GLIBC_2.2) [SUSv3]	pthread_mutex_l ock(GLIBC_2.2) [SUSv3]	pthread_mutex_t rylock(GLIBC_2. 2) [SUSv3]
pthread_mutex_ unlock(GLIBC_2. 2) [SUSv3]	pthread_mutexat tr_destroy(GLIB C_2.2) [SUSv3]	pthread_mutexat tr_getpshared(G LIBC_2.2) [SUSv3]	pthread_mutexat tr_gettype(GLIB C_2.2) [SUSv3]
pthread_mutexat tr_init(GLIBC_2. 2) [SUSv3]	pthread_mutexat tr_setpshared(GL IBC_2.2) [SUSv3]	pthread_mutexat tr_settype(GLIBC _2.2) [SUSv3]	pthread_once(GL IBC_2.2) [SUSv3]
pthread_rwlock_ destroy(GLIBC_2 .2) [SUSv3]	pthread_rwlock_ init(GLIBC_2.2) [SUSv3]	pthread_rwlock_ rdlock(GLIBC_2. 2) [SUSv3]	pthread_rwlock_ timedrdlock(GLI BC_2.2) [SUSv3]
pthread_rwlock_ timedwrlock(GLI BC_2.2) [SUSv3]	pthread_rwlock_ tryrdlock(GLIBC _2.2) [SUSv3]	pthread_rwlock_ trywrlock(GLIBC _2.2) [SUSv3]	pthread_rwlock_ unlock(GLIBC_2. 2) [SUSv3]
pthread_rwlock_ wrlock(GLIBC_2. 2) [SUSv3]	pthread_rwlockka ttr_destroy(GLIB C_2.2) [SUSv3]	pthread_rwlockka ttr_getpshared(G LIBC_2.2) [SUSv3]	pthread_rwlockka ttr_init(GLIBC_2. 2) [SUSv3]
pthread_rwlockka ttr_setpshared(G LIBC_2.2) [SUSv3]	pthread_self(GLI BC_2.2) [SUSv3]	pthread_setcance lstate(GLIBC_2.2 ) [SUSv3]	pthread_setcance ltype(GLIBC_2.2) [SUSv3]
pthread_setconc	pthread_setspeci	pthread_sigmask	pthread_testcanc

urrency(GLIBC_2.2) [SUSv3]	fic(GLIBC_2.2) [SUSv3]	(GLIBC_2.2) [SUSv3]	el(GLIBC_2.2) [SUSv3]
sem_close(GLIBC_2.2) [SUSv3]	sem_destroy(GLIBC_2.2) [SUSv3]	sem_getvalue(GLIBC_2.2) [SUSv3]	sem_init(GLIBC_2.2) [SUSv3]
sem_open(GLIBC_2.2) [SUSv3]	sem_post(GLIBC_2.2) [SUSv3]	sem_timedwait(GLIBC_2.2) [SUSv3]	sem_trywait(GLIBC_2.2) [SUSv3]
sem_unlink(GLIBC_2.2) [SUSv3]	sem_wait(GLIBC_2.2) [SUSv3]		

## 11.6.4 Thread aware versions of libc interfaces

### 11.6.4.1 Interfaces for Thread aware versions of libc interfaces

An LSB conforming implementation shall provide the architecture specific functions for Thread aware versions of libc interfaces specified in Table 11-30, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-30 libpthread - Thread aware versions of libc interfaces Function Interfaces**

lseek64(GLIBC_2.2) [LFS]	open64(GLIBC_2.2) [LFS]	pread(GLIBC_2.2) [SUSv3]	pread64(GLIBC_2.2) [LFS]
pwrite(GLIBC_2.2) [SUSv3]	pwrite64(GLIBC_2.2) [LFS]		

## 11.7 Data Definitions for libpthread

This section defines global identifiers and their values that are associated with interfaces contained in libpthread. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the [ISO C \(1999\)](#) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 11.7.1 pthread.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 11.7.2 semaphore.h

```

/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */

```

## 11.8 Interfaces for libgcc\_s

Table 11-31 defines the library name and shared object name for the libgcc\_s library

**Table 11-31 libgcc\_s Definition**

Library:	libgcc_s
SONAME:	libgcc_s.so.1

The behavior of the interfaces in this library is specified by the following specifications:

[LSB] [ISO/IEC 23360-1](#)

### 11.8.1 Unwind Library

#### 11.8.1.1 Interfaces for Unwind Library

An LSB conforming implementation shall provide the architecture specific functions for Unwind Library specified in Table 11-32, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-32 libgcc\_s - Unwind Library Function Interfaces**

_Unwind_Backtrace(GCC_3.3) [LSB]	_Unwind_DeleteException(GCC_3.0) [LSB]	_Unwind_FindEnclosingFunction(GCC_3.3) [LSB]	_Unwind_FindFrame(GCC_3.0) [LSB]
_Unwind_ForcedUnwind(GCC_3.0) [LSB]	_Unwind_GetCFA(GCC_3.3) [LSB]	_Unwind_GetDataRelBase(GCC_3.0) [LSB]	_Unwind_GetGR(GCC_3.0) [LSB]
_Unwind_GetIP(GCC_3.0) [LSB]	_Unwind_GetLanguageSpecificData(GCC_3.0) [LSB]	_Unwind_GetRegionStart(GCC_3.0) [LSB]	_Unwind_GetTextRelBase(GCC_3.0) [LSB]
_Unwind_RaiseException(GCC_3.0) [LSB]	_Unwind_Resume(GCC_3.0) [LSB]	_Unwind_Resume_or_Rethrow(GCC_3.3) [LSB]	_Unwind_SetGR(GCC_3.0) [LSB]
_Unwind_SetIP(GCC_3.0) [LSB]			

## 11.9 Data Definitions for libgcc\_s

This section defines global identifiers and their values that are associated with interfaces contained in libgcc\_s. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content.