

---

---

**Information technology —  
Conformance testing methodology for  
biometric data interchange formats  
defined in ISO/IEC 19794 —**

**Part 5:  
Face image data**

*Technologies de l'information — Méthodologie d'essai de conformité  
pour les formats d'échange de données biométriques définis dans  
l'ISO/CEI 19794 —*

*Partie 5: Données d'image de la face*

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 29109-5:2014

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 29109-5:2014



**COPYRIGHT PROTECTED DOCUMENT**

© ISO/IEC 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
Foreword .....	iv
Introduction .....	v
<b>1 Scope</b> .....	<b>1</b>
<b>2 Conformance</b> .....	<b>1</b>
<b>3 Normative references</b> .....	<b>2</b>
<b>4 Terms and definitions</b> .....	<b>2</b>
<b>5 Symbols and abbreviated terms</b> .....	<b>2</b>
<b>6 Conformance testing methodology</b> .....	<b>2</b>
6.1 Overview .....	2
6.2 Table of requirements in the base standard .....	2
6.3 ISO/IEC 19794-5:2005 Level 1 and 2 test assertions .....	13
<b>Bibliography</b> .....	<b>28</b>

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 29109-5:2014

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/IEC JTC 1, *Information technology*, Subcommittee SC 37, *Biometrics*.

This third edition cancels and replaces the second edition (ISO/IEC 29109-5:2012), the tables of which have been technically revised.

ISO/IEC 29109 consists of the following parts, under the general title *Information technology — Conformance testing methodology for biometric data interchange formats defined in ISO/IEC 19794*:

- *Part 1: Generalized conformance testing methodology*
- *Part 2: Finger minutiae data*
- *Part 4: Finger image data*
- *Part 5: Face image data*
- *Part 6: Iris image data*
- *Part 7: Signature/sign time series data*
- *Part 8: Finger pattern skeletal data*
- *Part 9: Vascular image data*
- *Part 10: Hand geometry silhouette data*

## Introduction

The ISO/IEC 19794-5:2005 standard specifies a data record interchange format for storing, recording, and transmitting one or more face images within a Common Biometric Exchange Formats Framework (CBEFF) data structure. Each image is accompanied by subject-specific and image-specific metadata contained in a header record. This part of the ISO/IEC 29109 multipart standard establishes tests for checking the correctness of the binary record.

The objective of ISO/IEC 19794-5:2005 cannot be completely achieved until biometric products can be tested to determine whether they conform to those specifications. Conforming implementations are a necessary prerequisite for achieving interoperability among implementations; therefore there is a need for a standardized conformance testing methodology, test assertions, and test procedures as applicable to specific modalities addressed by each part of ISO/IEC 19794. The test assertions will cover as much as practical of the ISO/IEC 19794 requirements (covering the most critical features), so that the conformity results produced by the test suites will reflect the real degree of conformity of the implementations to ISO/IEC 19794 Data Interchange Format records. This is the motivation for the development of this conformance testing methodology.

This part of ISO/IEC 29109 supports those applications that require use of face image data according to ISO/IEC 19794-5:2005. It defines a testing methodology to ensure conformance of a vendor's application or service to the base ISO/IEC 19794-5:2005 specification. Thus this document is intended to

- establish elements of the Conformance Testing Methodology framework that are specific to the Face Image-based Data Record requirements of ISO/IEC 19794-5:2005 conformance testing,
- define requirements and guidelines for specifying conformance test suites and related test methods for measuring conformity of products and services to the Face Image-based Data Record requirements of ISO/IEC 19794-5:2005, and
- define test procedures to be followed before, during, and after conformance testing.

This standard is applicable to the development and use of conformity test method specifications, conformity test suites for ISO/IEC 19794-5:2005 records, and conformance testing programs for ISO/IEC 19794-5:2005 conformant products. It is intended primarily for use by testing organizations, but may be applied by developers and users of test method specifications and test method implementations.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 29109-5:2014

# Information technology — Conformance testing methodology for biometric data interchange formats defined in ISO/IEC 19794 —

## Part 5: Face image data

### 1 Scope

This part of ISO/IEC 29109 specifies elements of conformance testing methodology, test assertions, and test procedures as applicable to two-dimensional face images defined in the ISO/IEC 19794-5:2005 biometric data interchange format standard for face image data.

This part of ISO/IEC 29109 establishes

- test assertions of the structure of the face image data format as specified in ISO/IEC 19794-5:2005 (Type A Level 1 as defined in ISO/IEC 29109-1:2009),
- test assertions of internal consistency by checking the types of values that may be contained within each field (Type A Level 2 as defined in ISO/IEC 29109-1:2009).

This part of ISO/IEC 29109 does not establish

- tests of conformance of 3D face records defined in ISO/IEC 19794-5:2005/Amd.2,
- tests of conformance of CBEFF structures required by ISO/IEC 19794-5:2005,
- tests of consistency with the input biometric data record (Level 3),
- tests of conformance of the image data to the quality-related specifications of ISO/IEC 19794-5:2005,
- tests of conformance of the image data blocks to the respective JPEG or JPEG 2000 standards,
- tests of other characteristics of biometric products or other types of testing of biometric products (e.g. acceptance, performance, robustness, security).

### 2 Conformance

Biometric data interchange format conformance tests conform to this part of ISO/IEC 29109 if they satisfy all of the normative requirements related to [Clause 6](#). Specifically, they shall use the test methodology specified in Clauses 6, 7 and 8 of ISO/IEC 29109-1, and all Level 1 and Level 2 tests shall use the assertions defined in [Table 2](#) of this part of ISO/IEC 29109.

Implementations of ISO/IEC 19794-5:2005 tested according to the methodology specified shall be able to claim conformance only to those biometric data record requirements specified in ISO/IEC 19794-5:2005 that are tested by the test methods established by this methodology.

Implementations of ISO/IEC 19794-5:2005 do not necessarily need to conform to all possible aspects of ISO/IEC 19794-5:2005, but only to those ISO/IEC 19794-5:2005 requirements that are claimed to be supported by the implementation in an Implementation Conformance Statement, filled out in accordance with Clause 8 of ISO/IEC 29109-1 and [Table 1](#) of this part of ISO/IEC 29109.

### 3 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 19794-5:2005, *Information technology — Biometric data interchange formats — Part 5: Face image data*

ISO/IEC 29109-1:2009, *Information technology — Conformance testing methodology for biometric data interchange formats defined in ISO/IEC 19794 — Part 1: Generalized conformance testing methodology*

### 4 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 29109-1 apply.

### 5 Symbols and abbreviated terms

For the purposes of this document, the symbols and abbreviated terms given in ISO/IEC 29109-1 apply.

### 6 Conformance testing methodology

#### 6.1 Overview

The testing methodology specified in Clauses 6, 7 and 8 of ISO/IEC 29109-1 shall apply. The content of the tables below is based on the conformance testing methodology outlined in ISO/IEC 29109-1 and shall only be used in the context of that testing methodology.

#### 6.2 Table of requirements in the base standard

The normative requirements of ISO/IEC 19794-5:2005 Biometric Data Interchange Format – Part 5: Face Image Data are listed in [Table 1](#). The supplier of the IUT can explain which optional components of the standard are supported and the testing laboratory can note the results of the test.

Under subformat applicability the columns labelled B, F and T indicate the Basic, Full Frontal and Token Frontal image types.

**Table 1 — Requirements of the Base Standard (ISO/IEC 19794-5:2005)**

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-1	5.2.1	Within the record format and all well-defined data blocks therein, all multi-byte quantities <b>are [implied shall]</b> stored in Big-Endian format. That is, the more significant bytes of any multi-byte quantity <b>are</b> stored at lower addresses in memory than less significant bytes. For example, the value 1025 (2 to the 10th power plus one) would be stored as first byte = 00000100 and second byte = 00000001.	1	M	Y	Y	Y			
R-2	5.2.2	Numeric Values All numeric values <b>are</b> fixed-length unsigned integer quantities, unless otherwise specified.	3C	0-3	Y	Y	Y			

Table 1 (continued)

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-3	5.4.1	Format Identifier The (4 byte) Format Identifier <b>shall</b> consist of three ASCII characters "FAC" followed by a zero byte as a NULL string terminator to identify the record format as the face record format.	1	M	Y	Y	Y			
R-4	5.4.2	Version Number The (4 byte) Version Number block <b>shall</b> consist of three ASCII numerals followed by a zero byte as a NULL string terminator. The first and second character <b>will</b> represent the major version number and the third character <b>will</b> represent the minor revision number. The version number of this specification <b>shall</b> be 0x30313000; "010" – Version 1 revision 0..	1	M	Y	Y	Y			
R-5	Table 2	$57 \leq \text{Length of Record} \leq 2^{32} - 1$	1	M	Y	Y	Y			
R-6	5.4.3	Length of Record The (4 byte) Record Length Block <b>shall</b> be the combined length in bytes for the record. This is the entire length of the record including the Facial Record Header and Facial Record Data.	2	M	Y	Y	Y			
R-7	Table 2	$1 \leq \text{Number of Facial Images} \leq 65\ 535$	1	M	Y	Y	Y			
R-8	5.4.4	Number of Facial Images The (2 byte) Number of Facial Images block <b>shall</b> be the number of facial images included in the record.	2	M	Y	Y	Y			
R-9	5.5	The Facial Information block The (20 byte) Facial Information block is intended to describe discrete properties of the individual discernable from the image, one is included for each facial image included in the record. The structure of this block is shown in [ISO/IEC 19794-5:2005] Figure 2. Zero or more Facial Feature blocks, one Image Information block, and one Image Data block <b>follow</b> this block.	2	M-2	Y	Y	Y			
R-10	5.5.1	Facial Record Data Length The (4 byte) Facial Record Data Length field denotes the sum of the lengths of the Facial Information block, the Feature Point block(s), the Image Information block, and the Image Data block. The minimum value of the Facial Record Data Length is 32 bytes plus the size of the Image Data block (in bytes).	2	M	Y	Y	Y			
R-11	5.5.2	Number of Feature Points The (2 byte) Number of Feature Points block <b>shall</b> be the number of Feature Point blocks that follow the Facial Information block. The Feature Point block is defined in [ISO/IEC 19794-5:2005] Clause 5.6.	2	M	Y	Y	Y			
R-12	5.5.3	Gender The (1 byte) Gender block <b>shall</b> be specified in accordance with [ISO/IEC 19794-5:2005] Table 3.	1	M	Y	Y	Y			
R-13	5.5.4	Eye Colour The (1 byte) Eye Colour field <b>shall</b> represent the colour of irises of the eyes according to [ISO/IEC 19794-5:2005] Table 4. If the eyes are different colours, then right eye colour is to be encoded.	1	M	Y	Y	Y			

Table 1 (continued)

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-14	5.5.5	Hair Colour The (1 byte) Hair Colour field <b>shall</b> represent the colour of the hair according to the [ISO/IEC 19794-5:2005] Table 5.	1	M	Y	Y	Y			
R-15	5.5.6	Property Mask The (3 byte) Property Mask is a bit mask of 3 bytes and each bit of the mask position listed in [ISO/IEC 19794-5:2005] Table 6 <b>shall</b> be set to 1 if the corresponding property is present, and set to 0 if absent. The mask position starts from 0 at the lowest bit. The lowest bit set to 0 shall indicate that properties are not specified (and all bits shall be zero); the lowest bit set to 1 <b>shall</b> indicate that all listed properties have been considered and that a zero value of any property bit indicates an absence of that property.  Note that a Blink flag set to "1" <b>will</b> indicate non-compliance with the Frontal, Full Frontal, and Token image types.	2	M	Y	Y	Y			
R-16	5.5.7	Expression The (2 byte) Expression field <b>shall</b> represent the expression of the face according to [ISO/IEC 19794-5:2005] Table 7.	1	M	Y	Y	Y			
R-17	5.5.8	Pose Angle The (3 multi byte) Pose Angle field (B <sub>Y</sub> , B <sub>P</sub> , B <sub>R</sub> ) <b>shall</b> represent the estimate or measure pose of the subject in the image. Each byte in the field respectively represents pose angles of yaw, pitch and roll in that order. The pose angle is given by Tait-Bryan angles.  • Yaw angle: Rotation about the vertical (y) axis. • Pitch angle: Rotation about the horizontal side-to-side (x) horizontal axis. • Roll angle: Rotation about the horizontal back to front (z) axis.  The angles are defined relative to the frontal view of the subject, which has angles (0,0,0) as shown in [ISO/IEC 19794-5:2005] Figure 4. The examples are shown in [ISO/IEC 19794-5:2005] Figure 5.  As order of the successive rotation around the different axes does matter, the encoded rotation angle <b>shall</b> correspond to an order of execution starting from the frontal view. This order <b>shall</b> be given by Roll (about the front axis), then Pitch (about the horizontal axis) and finally Yaw (about the vertical axis). The (first executed) Roll transformation will therefore always be in the image (x,y) plane.  From the point of view of executing a transformation from the observed view to a frontal view, the transformation order <b>will therefore be</b> Yaw, Pitch, and then Roll. Note however that the encoded angle <b>is from</b> the frontal view to the observed view.	3C	O-1	Y	Y	Y			

STANDARD PREVIEW. Click to view the full PDF of ISO/IEC 29109-5:2014

Table 1 (continued)

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-18	5.5.8.1	<p>Pose Angle – Yaw</p> <p>The yaw angle, <math>Y</math>, is the rotation in degrees about the y-axis (vertical axis) shown in [ISO/IEC 19794-5:2005] Figure 4. Frontal faces have a yaw angle of 0 degrees. Positive angles represent faces looking to their left (a counter-clockwise rotation around the y-axis).</p> <p>“The encoded value, <math>B_Y</math>, shall be stored in 1 byte with values 0 to 180 computed from a real-valued yaw angle estimate, <math>-180 \leq Y &lt; 180</math>, as follows”:</p> <p>If <math>180 \geq Y \geq 0</math> and <math>Y</math> is even, then <math>B_Y = Y/2+1</math></p> <p>If <math>180 \geq Y &gt; 0</math> and <math>Y</math> is odd, then <math>B_Y = (Y+1)/2</math></p> <p>If <math>-180 \leq Y &lt; 0</math> and <math>Y</math> is even, then <math>B_Y = 181+Y/2</math>.</p> <p>If <math>-180 \leq Y &lt; 0</math> and <math>Y</math> is odd, then <math>B_Y = 181+(Y-1)/2</math></p> <p>The maximum value of <math>B_Y</math> is 180. If the yaw angle is not specified, the value of <math>B_Y</math> shall be 0.</p>	1	M	Y	Y	Y			
R-19	5.5.8.2	<p>Pose Angle – Pitch</p> <p>The pitch angle, <math>P</math>, is the rotation in degrees about the x-axis (horizontal axis) shown in [ISO/IEC 19794-5:2005] Figure 4. Frontal faces have a pitch angle of 0 degrees. Positive angles represent faces looking down (a counterclockwise rotation around the x-axis).</p> <p>The encoded value, <math>B_P</math>, shall be stored in 1 byte with values 0 to 180 computed from a real-valued pitch angle estimate, <math>-180 \leq P &lt; 180</math>, as follows</p> <p>If <math>180 \geq P \geq 0</math> and <math>P</math> is even, then <math>B_P = P/2+1</math></p> <p>If <math>180 \geq P &gt; 0</math> and <math>P</math> is odd, then <math>B_P = (P+1)/2</math></p> <p>If <math>-180 \leq P &lt; 0</math> and <math>P</math> is even, then <math>B_P = 181+P/2</math>.</p> <p>If <math>-180 \leq P &lt; 0</math> and <math>P</math> is odd, then <math>B_P = 181+(P-1)/2</math></p> <p>The maximum value of <math>B_P</math> is 180. If the pitch angle is not specified, the value of <math>B_P</math> shall be 0.</p>	1	M	Y	Y	Y			
R-20	5.5.8.3	<p>Pose Angle – Roll</p> <p>The roll angle, <math>R</math>, is the rotation in degrees about the z-axis (the horizontal axis from front to back) shown in [ISO/IEC 19794-5:2005] Figure 4. Frontal faces have a roll angle of 0 degrees. Positive angles represent faces tilted toward their right shoulder (counter-clockwise rotation around the z-axis).</p> <p>The encoded value, <math>B_R</math>, shall be stored in 1 byte with values 0 to 180 computed from a real-valued roll angle estimate, <math>-180 \leq R &lt; 180</math>, as follows:</p> <p>If <math>180 \geq R \geq 0</math> and <math>R</math> is even, then <math>B_R = R/2+1</math></p> <p>If <math>180 \geq R &gt; 0</math> and <math>R</math> is odd, then <math>B_R = (R+1)/2</math></p> <p>If <math>-180 \leq R &lt; 0</math> and <math>R</math> is even, then <math>B_R = 181+R/2</math>.</p> <p>If <math>-180 \leq R &lt; 0</math> and <math>R</math> is odd, then <math>B_R = 181+(R-1)/2</math></p> <p>The maximum value of <math>B_R</math> is 180. If the roll angle is not specified, the value of <math>B_R</math> shall be 0.</p>	1	M	Y	Y	Y			

Table 1 (continued)

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-21	5.5.9	<p>Pose Angle Uncertainty</p> <p>The (3 multi-byte) Pose Angle Uncertainty (<math>U_Y, U_P, U_R</math>) represents the expected degree of accuracy of the pose angle yaw, pitch, and roll. Each byte in the field respectively represents the uncertainty of yaw, pitch and roll in that order. The uncertainty is allowed to represent experimental uncertainty specified by each vendor.</p> <p>The encoding of Pose Angle Uncertainty is given by bytes (<math>U_Y, U_P, U_R</math>) where each byte <math>U_K</math> in the field (<math>k = Y, P, R</math>) represents 1 degree of uncertainty with minimum and maximum values of 1 and 181 where <math>U_K = (\text{uncertainty} + 1)</math>. The more uncertain, the value of the uncertainty <math>U_K</math> <b>shall</b> become larger. If the uncertainty is not specified, then the values of <math>U_Y, U_P</math> and <math>U_R</math> <b>shall</b> be set to zero (0).</p>	1	M	Y	Y	Y			
R-22	5.6	<p>The Feature Point Block</p> <p>The optional (8 byte) Feature Point block specifies the type, code and position of a Feature Point in the facial image. The number of Feature Point blocks <b>shall</b> be specified in the Number of Feature Points field of the Facial Information Block. The structure of this block is shown in [ISO/IEC 19794-5:2005] Table 8.</p>	1	M	Y	Y	Y			
R-23	5.6.1	<p>Feature Point Type</p> <p>The (1 byte) Feature Point Type field represents the type of the Feature Point stored in the Feature Point block. This field <b>shall</b> be set to 0x01 to denote that the position of the Feature Point is represented by the coordinate of the image. All other field values are reserved for future definition of Feature Point types.</p>	1	M	Y	Y	Y			
R-24	5.6.2	<p>Feature Point Code</p> <p>The (1 byte) Feature Point Code field <b>shall</b> specify the Feature Point that is stored in the Feature Point block. The codes of the Feature Points in [ISO/IEC 19794-5:2005] Clause 5.6.3, taken from the MPEG4 standard and defined as MPEG4 Feature Points, or the additional eye and nostril Feature Points in [ISO/IEC 19794-5:2005] Clause 5.6.4 <b>shall</b> be stored in this block.</p> <p>Each Feature Point code is represented by a notation A.B using a major (A) and a minor (B) value. The encoding of the Feature Point code <b>is given</b> by the (1 byte) value of <math>A * 16 + B</math>.</p>	1	M	Y	Y	Y			
R-25	5.6.3	<p>MPEG4 Feature Points</p> <p>[ISO/IEC 19794-5:2005] Figure 6 denotes the Feature Point codes associated with Feature Points as given by Annex C of ISO/IEC 14496-2</p>	3C	O-1	Y	Y	Y			
R-26	5.6.4	<p>Eye and nostril centre Feature Points</p> <p>The eye centre Feature Points 12.1 (left) and 12.2 (right) <b>are defined</b> to be the horizontal and vertical midpoints of the eye corners (3.7, 3.11) and (3.8, 3.12) respectively. The left nostril centre Feature Point 12.3 <b>is defined</b> to be the midpoint of the nose Feature Points (9.1, 9.15) in the horizontal direction and (9.3, 9.15) in the vertical direction. Similarly, the right nostril centre Feature Point 12.4 <b>is defined</b> to be the midpoint of the nose Feature Points (9.2, 9.15) in the horizontal direction and (9.3, 9.15) in the vertical direction. Both the eye centre and nostril centre Feature Points are shown in [ISO/IEC 19794-5:2005] Figure 7 and values given in [ISO/IEC 19794-5:2005] Table 9.</p>	3C	O-1	Y	Y	Y			

Table 1 (continued)

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-27	5.7	The Image Information Block  The (16 byte) Image Information block is intended to describe digital properties of the facial image, one <b>is</b> included for each facial image included in the record. The structure of this block <b>is</b> shown in [ISO/IEC 19794-5:2005] Figure 2. One Image Data block <b>shall</b> follow this block.	2	M-2	Y	Y	Y			
R-28	5.7.1	Face Image Type  The Face Image Type field <b>shall</b> represent the type of the facial image stored in the Image Data Block according to [ISO/IEC 19794-5:2005] Table 10. Note that all Frontal Image Types are either Full Frontal or Token Frontal. Therefore a separate Frontal Value is not required.  The Basic Face Image Type is defined in [ISO/IEC 19794-5:2005] Clause 6. The Frontal, Frontal/Full and Frontal/Token Face Image Types are defined in [ISO/IEC 19794-5:2005] Clauses 7, 8, and 9 respectively. Face Image Types use the notion of inheritance. For example, the Frontal Face Image Type inherits all of the requirements of the Basic Face Image Type - the Frontal Face Image type obeys all normative requirements of the Basic Face Image Type. The inheritance structure of currently defined image types is shown in [ISO/IEC 19794-5:2005] Figure 8.	1	M	Y	Y	Y			
R-29	5.7.2	Image Data Type  The (1 byte) Image Data Type field denotes the encoding type of the Image Data block. Either JPEG (ISO/IEC 10918-1 and ITU-T Rec. T.81) or JPEG2000 (ISO/IEC 15444-1) <b>shall</b> be specified. Note that a "Unspecified" Value cannot be encoded.	2	M	Y	Y	Y			
R-30	5.7.3	Width  The (2 byte) Width field <b>shall</b> specify the number of pixels in the horizontal direction.	2	M	Y	Y	Y			
R-31	5.7.4	Height  The (2 byte) Height field <b>shall</b> specify the number of pixels in the vertical direction.	2	M	Y	Y	Y			
R-32	5.7.5	Image Colour Space  The (1 byte) Image Colour Space field indicates the colour space used in the encoded Image Data block <b>according to</b> the values in [ISO/IEC 19794-5:2005] Table 12. The values of 128–255 are vendor specific. Application developers may obtain the values for these codes from the vendor.	2	M	Y	Y	Y			
R-33	5.7.6	Source Type  The (1 byte) Source Type field denotes the classification of the source of the captured image and <b>is given</b> in [ISO/IEC 19794-5:2005] Table 13.	1	M	Y	Y	Y			
R-34	5.7.7	Device Type  The (2 byte) Device Type field denotes the vendor specific capture device type ID. A value of all zeros will be acceptable and will indicate that the capture device type ID is unspecified. Application developers may obtain the values for these codes from the vendor.	1	M	Y	Y	Y			
R-35	5.7.8	Quality  The (2 byte) Quality field <b>shall</b> be reserved for future definition to represent a quality of the facial image. This field <b>shall</b> be set to the value 0 indicating "unspecified".	1	M	Y	Y	Y			

Table 1 (continued)

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-36	5.8.1	Data structure The (variable byte) Image Data block <b>shall</b> be the image data encoded by either the JPEG or JPEG2000 standards.	2	M	Y	Y	Y			
<b>Basic Face Image Type</b>										
R-37	6.2	Image data encoding requirements for the Basic Face Image Type One of two possible encodings <b>is to be used</b> for all image types (Basic) 1) The JPEG Sequential baseline (ISO/IEC 10918-1) mode of operation and encoded in the JFIF file format (the JPEG file format) 2) The JPEG-2000 Part-1 Code Stream Format (ISO/IEC 15444-1) and encoded in the JP2 file format (the JPEG2000 file format).	2	M	Y	Y	Y			
R-38	6.4.1	Facial Header [for the Basic Face Image Type] The Format Identifier, Version Number, Length of Record, and Number of Faces fields <b>shall</b> be specified.	1	M	Y	Y	Y			
R-39	6.4.2	Facial Information [for the Basic Face Image Type] The Block Length and Number of Feature Points fields <b>shall</b> be specified.	1	M	Y	Y	Y			
R-40	6.4.3	Image Information [for the Basic Face Image Type] The Face Image Type field <b>shall</b> be specified with value 0x00.	1	M	Y	Y	Y			
R-41	6.4.3	The Image Data Type, Width, and Height fields <b>shall</b> be specified.	1	M	Y	Y	Y			
<b>The Frontal Face Image Type</b>										
R-42	7.2.2	Pose Thus, the full-face frontal pose <b>shall</b> be used. Rotation of the head <b>shall</b> be less than $\pm 5^\circ$ from frontal in pitch and yaw (see 5.5.8). Pose variations that lead to an in-plane rotation of the head can be more easily compensated by automated face recognition systems. Therefore, the rotation of the head <b>shall</b> be less than $\pm 8^\circ$ from frontal in roll (see 5.5.8). [ISO/IEC 19794-5:2005/Cor.2] Figure Cor.1-1 shows an example of $\pm 8^\circ$ rotation in roll. The best practice recommendation as outlined in A.2.2 is that the rotation of the head should be less than $\pm 5^\circ$ from frontal in roll. This constraint refers to the pose of the subject associated with the face image format data for all applications that call for this format to be used. [NOTE: This text is from ISO/IEC 19794-5:2005/Cor.2 Published 2008-07-01]	3C	O-1	N	Y	Y			
R-43	7.2.4	Assistance in positioning the face In <b>no cases will</b> any other face be captured in the Frontal image. See informative Annex A.2 for best practices on this topic.	3C	O-1	N	Y	Y			
R-44	7.2.5	Shoulders Shoulders <b>shall</b> be "square on" to the camera. "Portrait style" photographs where the subject is looking over one shoulder are not acceptable.	3C	O-1	N	Y	Y			
R-45	7.2.7	Subject and scene lighting Lighting <b>shall</b> be equally distributed on the face.	3C	O-1	N	Y	Y			

Table 1 (continued)

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-46	7.2.7	There <b>shall</b> be no significant direction of the light from the point of view of the photographer, as further described in [ISO/IEC 19794-5:2005] Clauses 7.2.8 and 7.2.9	3C	0-1	N	Y	Y			
R-47	7.2.8	Shadows over the face  The region of the face, from the crown (as defined in section 4.6) to the base of the chin, and from ear-to-ear, <b>shall</b> be clearly visible and free of shadows.	3C	0-1	N	Y	Y			
R-48	7.2.8	Special care <b>shall</b> be taken in cases when veils, scarves or headdresses cannot be removed for religious reasons to ensure these coverings do not obscure any facial features and do not generate shadow. In all other cases head coverings <b>shall</b> be absent.	3C	0-1	N	Y	Y			
R-49	7.2.9	Shadows in eye-sockets  There <b>shall</b> be no dark shadows in the eye-sockets due to the brow.	3C	0-1	N	Y	Y			
R-50	7.2.9	The iris and pupil of the eyes <b>shall</b> be clearly visible.	3C	0-1	N	Y	Y			
R-51	7.2.10	Hot Spots  Care <b>shall</b> be taken to avoid "hot spots" (bright areas of light shining on the face). These artefacts are typically caused when one, high intensity, focused light source is used for illumination.	3C	0-1	N	Y	Y			
R-52	7.2.10	Instead, diffused lighting, multiple balanced sources or other lighting methods <b>shall</b> be used.  A single bare "point" light source <b>is not acceptable</b> for imaging. Instead, the illumination should be accomplished using other methods that meet requirements specified in this [ISO/IEC 19794-5:2005] clause.	3C	0-1	N	Y	Y			
R-53	7.2.11	Eye Glasses  If the person normally wears glasses then they should wear glasses when their photograph is taken. Glasses <b>shall</b> be clear glass and transparent so the eye pupils and irises are clearly visible.	3C	0-1	N	Y	Y			
R-54	7.2.11	Permanently tinted glasses or sunglasses are acceptable only for medical reasons (and <b>shall</b> otherwise be removed). In cases where tinted glasses or sunglasses are worn, the specification of dark glasses in the header structure is recommended.	3C	0-1	N	Y	Y			
R-55	7.2.11	Care <b>shall</b> be taken that the glasses frames do not obscure the eyes.	3C	0-1	N	Y	Y			
R-56	7.2.11	There <b>shall</b> be no lighting artefacts or flash reflections on glasses. This can typically be achieved by increasing the angle between the lighting, subject and camera to 45° (degrees) or more.	3C	0-1	N	Y	Y			
R-57	7.2.12	Eye Patches  The wearing of eye patches <b>is allowed only</b> for medical reasons. In these cases, the specification of the patch, in the header structure is recommended.	3C	0-1	N	Y	Y			
R-58	7.3.2	No Over or Under Exposure  For each patch of skin on the person's face, the gradations in textures <b>shall</b> be clearly visible. In this sense, there <b>will be no</b> saturation (over or under exposure) on the face.	3C	0-1	N	Y	Y			

Table 1 (continued)

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-59	7.3.3	Focus and Depth of Field The subject's captured image <b>shall</b> always be in focus from nose to ears and chin to crown.	3C	O-1	N	Y	Y			
R-60	7.3.3	All images <b>will</b> have sufficient depth of focus to maintain greater than two millimetre resolution on the subject's facial features at time of capture.	3C	O-1	N	Y	Y			
R-61	7.3.4	Unnatural Colour Unnaturally coloured lighting, yellow, red, etc. <b>is not allowed</b> . Care <b>shall</b> be taken to correct the "white balance" of image capture devices.	3C	O-1	N	Y	Y			
R-62	7.3.4	The lighting <b>shall</b> produce a face image with natural looking flesh tones when viewed in typical examination environments.	3C	O-1	N	Y	Y			
R-63	7.3.4	"Red-eye" <b>is not acceptable</b> .	3C	O-1	N	Y	Y			
R-64	7.3.5	Colour or Grayscale Enhancement A process that overexposes or under-develops a colour or greyscale image for purposes of beauty enhancement or artistic pleasure is not allowed. The full spectrum <b>shall</b> be represented on the face image where appropriate. Teeth and whites of eyes <b>shall</b> be clearly light or white (when appropriate) and dark hair or features (when appropriate) <b>shall</b> be clearly dark.	3C	O-1	N	Y	Y			
R-65	7.3.6	Radial Distortion of the Camera Lens The fish eye (ref. 4.11) that is associated with unusually large noses in the image <b>is not allowed</b> .	3C	O-1	N	Y	Y			
R-66	7.4.1.1	Pixel aspect ratio Digital cameras and scanners used to capture facial images <b>shall</b> produce images with a pixel aspect ratio of 1:1. That is, the number of pixels per inch in the vertical dimension <b>shall</b> equal the number of pixels per inch in the horizontal direction.	3C	O-1	N	Y	Y			
R-67	7.4.1.2	Origin at Upper Left The origin of coordinates <b>shall</b> be at the upper left given by coordinate (0,0) with positive entries from left to right (first dimension) and top to bottom (second dimension).	3C	O-1	N	Y	Y			
R-68	7.4.2.3	Colour space Frontal images <b>shall</b> be represented as one of the following a) The 24-bit RGB colour space where for every pixel, eight (8) bits will be used to represent each of the Red, Green, and Blue components. b) An 8-bit monochrome colour space where for every pixel, (8) bits will be used to represent the luminance component. c) The YUV422 colour space where twice as many bits are dedicated to luminance as to each of the two colour components. YUV422 images typically contain two 8-bit Y samples along with one 8-bit sample of each of U and V in every four bytes.	2	O-1	N	Y	Y			
R-69	7.4.3	Video interlacing Interlaced video frames are not allowed for the Frontal Image Type. All interlacing <b>must be</b> absent (not simply removed, but absent).	3C	O-1	N	Y	Y			

Table 1 (continued)

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-70	7.5.2	Image Information [for the Frontal Image Type]  Frontal Images are either Full Frontal or Token Frontal images and the Face Image Type field <b>shall</b> be set accordingly (ref. 8.5.2, 9.3.2).	1	M	N	Y	Y			
<b>The Full Frontal Image Type</b>										
R-71	8.3.1	Introduction  In addition to the requirements of 8.3.2 to 8.3.6, the face from chin to crown as defined in 8.3.5 and with the full width as defined in 8.3.4 <b>shall</b> be visible in the image.  [NOTE: This text is from ISO/IEC 19794-5:2005/Cor.2 Published 2008-07-01]	3C	0-1	N	Y	Y			
R-72	8.3.2	Horizontally centred face  The approximate horizontal midpoints of the mouth and of the bridge of the nose define the imaginary line AA (usually the symmetry axis of the face). Furthermore, the imaginary line BB is defined as the line through the centre of the left eye and the centre of the right eye. The intersection of AA and BB defines the point M as the centre of the face. The x-coordinate M <sub>x</sub> of M <b>shall</b> be between 45 % and 55 % of the image width.  [NOTE: This text is from ISO/IEC 19794-5:2005/Cor.2 Published 2008-07-01]	3C	0-1	N	Y	N			
R-73	8.3.3	Vertical position of the face  The y-coordinate M <sub>y</sub> of M <b>shall</b> be between 30 % and 50 % of the image height.  [NOTE: This text is from ISO/IEC 19794-5:2005/Cor.2 Published 2008-07-01]	3C	0-1	N	Y	N			
R-74	8.3.3	A single exception is allowed for children under the age of 11 years, in which case the higher limit <b>shall</b> be modified to 60 % (i.e. the centre point of the head is allowed to be lower in the image for children under the age of 11). Note that the origin O of the coordinate system is in the upper left corner of the image.  [NOTE: This text is from ISO/IEC 19794-5:2005/Cor.2 Published 2008-07-01]	3C	0-1	N	Y	N			
R-75	8.3.4	Width of head  The width of a head is defined as the distance between the two imaginary lines parallel to the line AA; each imaginary line is drawn between the upper and lower lobes of each ear and <b>shall</b> be positioned where the external ear connects to the head. The head width is shown as length CC in [ISO/IEC 19794-5:2005] Figure 9.  [NOTE: This text is from ISO/IEC 19794-5:2005/Cor.2 Published 2008-07-01]	3C	0-1	N	Y	N			
R-76	8.3.4	To ensure that the entire face is visible in the image, the head width (CC) <b>shall</b> be between 50 % and 75 % of the image width (A).  [NOTE: This text is from ISO/IEC 19794-5:2005/Cor.2 Published 2008-07-01]	3C	0-1	N	Y	N			

Table 1 (continued)

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Sta-tus	Subformat Applicabil-ity			IUT Sup-port	Sup-ported Range	Test Result
					B	F	T			
R-77	8.3.5	Length of head  The length of a head is defined as the distance between the base of the chin and the crown measured on the imaginary line AA. This is shown as length DD in [ISO/IEC 19794-5:2005] Figure 9. The crown is defined as the top of the head ignoring any hair.  In order to ensure that the entire face is visible in the image, the minimum image height <b>shall</b> be specified by requiring that the crown-to-chin portion (DD) of the full frontal image pose shall be between 60 % and 90 % of the vertical length of the image (B).  [NOTE: This text is from ISO/IEC 19794-5:2005/Cor.2 Published 2008-07-01]	3C	O-1	N	Y	N			
R-78	8.3.5	A single exception is allowed for children under the age of 11 years, in which case the lower limit <b>shall</b> be modified to 50 %.	3C	O-1	N	Y	N			
R-79	8.4.1	Resolution [Digital requirements for the Full Frontal Face Image Type]  For an image for optimal human examination and permanent storage, the resolution of the full images <b>shall</b> be at least 180 pixels of resolution for the width of the head, or roughly 90 pixels from eye centre to eye centre. See informative annex section A.3.1.1 for best practices on this topic.	3C	O-1	N	Y	N			
R-80	8.5.2	Image Information  The Face Image Type field <b>shall</b> be specified with value 0x01.  [NOTE: This text is from ISO/IEC 19794-5:2005/Cor.1 Published 2008-07-01]	1	M	N	Y	N			
<b>The Token Face Image Type</b>										
R-81	9.2.2	Eye positions  To create a Token Face image, the eye socket centres, or simply eye positions, defined as Feature Points 12.1 and 12.2, <b>shall</b> be determined. For the determination of eye positions, it is possible:  1 - to use computer inspection 2 - to use human visual inspection 3 - to use computer and human visual inspection.	3C	O-1	N	N	Y			
R-82	9.2.3	Token image geometric format  A Token image is a colour or greyscale image with image dimensions and eye position coordinates <b>given by</b> [ISO/IEC 19794-5:2005] Table 16. Note that [ISO/IEC 19794-5:2005] Clause 5.2.3 specifies conversion of values to integer.  Image Height $W/0,75$ where W is the Image Width.	2	M	N	N	Y			
R-83	9.2.3	Y coordinate of Eyes $0,6 * W$  [NOTE: This text is from ISO/IEC 19794-5:2005, Table 16 column 1.]	3C	O-1	N	N	Y			
R-84	9.2.3	X coordinate of First (right) Eye $0,375 * W$  [NOTE: This text is from ISO/IEC 19794-5:2005, Table 16 column 1.]	3C	O-1	N	N	Y			
R-85	9.2.3	X coordinate of Second (left) Eye = $(0,625 * W) - 1$  [NOTE: This text corrects typographical error in ISO/IEC 19794-5:2005, Table 16 column 1.]	3C	O-1	N	N	Y			

Table 1 (continued)

Requirement ID	Ref. in Base Std	Requirement Summary	Level	Status	Subformat Applicability			IUT Support	Supported Range	Test Result
					B	F	T			
R-86	9.2.3	Width from eye to eye (inclusive) 0,25 *W [NOTE: This text is from ISO/IEC 19794-5:2005, Table 16 column 1.]	3C	0-1	N	N	Y			
R-87	9.2.4	Minimum Width Token Image The <b>minimum required</b> image width is 240 pixels.	2	M	N	N	Y			
R-88	9.2.4	The distance from eye to eye (inclusive) in this case is therefore <b>[at least]</b> 60 pixels. This example is shown in [ISO/IEC 19794-5:2005] Figure 10.	3C	0-1	N	N	Y			
R-89	9.2.4	Coordinates <b>are</b> relative to the top left corner of the image (0,0) and all measurements <b>are</b> in units of pixels.	3C	0-1	N	N	Y			
R-90	9.2.5	Padding The normative practice <b>shall</b> be to fill any undefined set of pixels with any colour. See informative Annex A.4.3 for best practices on this matter.	3C	0-1	N	N	Y			
R-91	9.3.2	Image Information The Face Image Type field in the Image Information structure <b>shall</b> be specified with value 0x02.	1	M	N	N	Y			

NOTE 1 Level 3C conformance test assertions are not specified. In all cases, the reason for this is that no method has been defined to test the conformance of the IUT or BDIR for this mandatory requirement of the base standard. For the purposes of this part of ISO/IEC 29109, the requirements are optional ("O") until an appropriate test method is established. The 3C label indicates that conformance testing of this Level 3 conformance requirement is beyond the scope of the present version of the conformance testing standard containing the table. However, most of the requirements could be tested by means of suitable image processing operations. For example, there is a large academic literature on methods for pose estimation (see [5] for a review).

NOTE 2 These Level 2 requirements appear in clauses which define the block structure of a conformant ISO/IEC 19794-5:2005 record. The requirements do not appear in Tables 2, 3, and 4 below because other conformance test assertions cover these requirements.

NOTE 3 This is not a Level 1 requirement because testing requires more information than is contained in the field. It could be addressed on a case-by-case basis by the requirements / assertions pertaining to those fields.

### 6.3 ISO/IEC 19794-5:2005 Level 1 and 2 test assertions

A subsystem that claims to produce face image records that conformant to the Level 1 and Level 2 requirements of the **Basic** Face Image Type of ISO/IEC 19794-5:2005 Face Image Format for Data Interchange **shall** be assessed by execution of all of the specific test assertions listed in Table 2. The test notes which follow Table 2 are normative.

A subsystem that claims to produce face image records that conformant to the Level 1 and Level 2 requirements of the **Full Frontal** Face Image Type of ISO/IEC 19794-5:2005 Face Image Format for Data Interchange **shall** be assessed by execution of all of the specific test assertions listed in Table 3. The test notes which follow Table 3 are normative.

A subsystem that claims to produce face image records that conformant to the Level 1 and Level 2 requirements of the **Token** Face Image Type of ISO/IEC 19794-5:2005 Face Image Format for Data Interchange **shall** be assessed by execution of all of the specific test assertions listed in Table 4. The test notes which follow Table 4 are normative.

NOTE A blank entry in the Subformat column indicates assertions common to all Subformats (Basic, Full Frontal and Token Frontal).

Table 2 — Conformance Test Assertions for ISO/IEC 19794-5:2005 Basic Type Images

Test Sub-Format	Requirement ID	Level	Field	Operator	Operands	Test Note	Status	IUT Support	Supported range	Test Result
1.	R-3	1	Format Identifier	EQ	0x46414300		M			
2.	R-3	1	Format Identifier	NEQ	0x00434146	1	M			
3.	R-4	1	Version Number	EQ	0x30313000		M			
4.	R-4	1	Version Number	NEQ	0x00303130	1	M			
5.	R-5, R-6	1	Record Length	C	57 to 232 - 1	2	M			
6.	R-5, R-6	2	Record Length	EQ	Total Bytes Read		M			
7.	R-5, R-6	2	Record Length	EQ	Total Bytes Expected	3	M			
8.	R-7, R-8	1	Number of Facial Images	EQ	1 to 65 535		M			
9.	R-7, R-8	2	Number of Facial Images	EQ	Total Number of Facial Images Read		M			
10.	R-10	2	Facial Record Data Length	C	See Note	4	M			
11.	R-10	2	Facial Record Data Length	EQ	Tot. Facial Record Data Bytes Read		M			
12.	R-10	2	Facial Record Data Length	EQ	Tot. Facial Record Data Bytes Expected	5	M			
13.	R-10	2	Facial Record Data Length	GT	Minimum {Facial Record Data Length} = 32 + sizeof {Image Data}		M			
14.	R-10	1	Facial Record Data Length	LE	0xFFFFFFFF - sizeof {Facial Header} = 0xFFFFFFFF - 0xE = 0xFFFFFFFF1		M			
15.	R-11	1	Number of Feature Points	EQ	0 to 65 535		M			
16.	R-11, R-22	2	Number of Feature Points	EQ	Total Number of Feature Points Read		M			
17.	R-12	1	Gender	EQ	0 to 2, 255		M			
18.	R-13	1	Eye Colour	EQ	0 to 7, 255		M			
19.	R-14	1	Hair Colour	EQ	0 to 7, 255		M			
20.	R-15	1	Property Mask	EQ	0x000000 to 0x0007FF	6	M			
20.1	R-15	1	Property Mask	EQ	{Property Mask} EQ 0 OR Is Odd {Property Mask} Modulo 2 EQ 1	13	M			
21.	R-16	1	Expression	EQ	0 to 7, 32 768 to 65 535		M			
22.	R-17, R-18	1	Pose Angle Yaw	EQ	0 to 180		M			

Table 2 (continued)

Test Sub-Format	Requirement ID	Level	Field	Operator	Operands	Test Note	Status	IUT Support	Supported range	Test Result
23.	R-17, R-19	1	Pose Angle Pitch	EQ	0 to 180		M			
24.	R-17, R-20	1	Pose Angle Roll	EQ	0 to 180		M			
25.	R-21	1	Yaw Angle Uncertainty	EQ	0 to 181		M			
26.	R-21	1	Pitch Angle Uncertainty	EQ	0 to 181		M			
27.	R-21	1	Roll Angle Uncertainty	EQ	0 to 181		M			
28.	R-23	1	Feature Point Type	EQ	1		O			
29.	R-24	1	Feature Point Code	EQ	See Note	7	O			
30.	R-22, R-25	2	X coordinate range check	EQ	0 to (Width - 1)		O			
31.	R-22, R-26	2	Y coordinate range check	EQ	0 to (Height - 1)		O			
32.	R-22	1	Reserved	EQ	0		O			
33.	R-28	1	Face Image Type	EQ	0 to 2		M			
34.	R-40	1	Face Image Type	EQ	0		M			
35.	R-29	1	Image Data Type	EQ	0, 1		M			
36.	R-30	1	Image Width	EQ	0 to 65 535		M			
37.	R-31	1	Image Height	EQ	0 to 65 535		M			
38.	R-30	2	Image Width	C			M			
39.	R-31	2	Image Height	C			M			
40.	R-32	1	Colour Space	EQ	0 to 4, 128 to 255		M			
41.	R-33	1	Source Type	EQ	0 to 7, 128 to 255	10	M			
42.	R-34	1	Device Type	EQ	0 to 65 535		M			
43.	R-35	1	Quality	EQ	0		M			
44.	R-30, R-29, R-36, R-37	1	Image Marker	EQ	See Note	11	M			
45.	R-30, R-29, R-37	2	Image Data Length	EQ	Total Bytes Read	12	M			

Test Notes

1	<p>Test 2 and Test 4 check to see if these multi-byte quantities have been encoded as the Little-Endian equivalent of the correct Big-Endian value. These tests fail if that is true but pass in all other cases. By reviewing the combination of the results of Test 1, 2, 3 and 4, it should be simple to determine whether or not the implementation under test is using the correct Big-Endian encoding.</p>
2	<p>Clause 6.2 of ISO/IEC 19794-5:2005 standard requires JFIF File Interchange Format for JPEG images<sup>[4]</sup> and JP2 file type extension for JPEG2000<sup>[3]</sup>.</p> <p>For JPEG [ref. ISO/IEC 10918-1 / Figure B.2, Table B.2, and “JPEG File Interchange Format, Version1.02”]  Minimum {Image Data} = sizeof (Start of Image marker) + sizeof (Frame Header) + sizeof (JFIF marker) + sizeof (End of Image marker)  Minimum {Image Data} = 2 + 2 + 5 + 2 bytes  Minimum {Image Data} = 11 bytes</p> <p>For JPEG 2000 [Reference <sup>[3]</sup>, specifically ISO/IEC 15444-1 / Figure I-1, Table I-2, and Annex I]  Minimum {Image Data} = sizeof (Signature box) + sizeof (Profile box) + sizeof (JP2 Header box) + sizeof (Contiguous Codestream box)  Minimum {Image Data} = 12 + 8 + 4 + 16 bytes  Minimum {Image Data} = 40 bytes</p> <p>Therefore, Minimum {Image Data} Length = 11 bytes  Minimum {Record Length} = sizeof {Facial Header} + sizeof {Facial Information} + sizeof {Image Information} + sizeof (Minimum {Image Data})  Minimum {Record Length} = 14 + 20 + 12 + 11 = 57 bytes</p>
3	<p>The following calculation will be evaluated once the Image Data block for the last Facial image has been parsed successfully (not having reached an End-of-File marker prematurely). In the event that End-of-File marker is reached prematurely this will be marked as having failed, but no value of {Total Bytes Expected} will be produced.</p> <p>Length = 14  FOR j = 1: {Number of Facial Images}  Length = Length + 32 + {Number of Feature Points} * 8 + sizeof {Image Data}  END  {Total Bytes Expected} = Length</p>
4	<p>Minimum {Facial Record Data Length} = 32 + sizeof {Image Data}</p> <p>IF {Image Data Type} EQ 0 THEN  Minimum {Facial Record Data Length} = sizeof {Facial Information} + sizeof {Image Information} + sizeof (Minimum JPEG {Image Data})  Minimum {Facial Record Data Length} = 20 + 12 + 11 = 43  ENDIF</p> <p>IF {Image Data Type} EQ 1 THEN  Minimum {Facial Record Data Length} = sizeof {Facial Information} + sizeof {Image Information} + sizeof (Minimum JPEG2000 {Image Data})  Minimum {Facial Record Data Length} = 20 + 12 + 40 = 72  ENDIF</p>
5	<p>The following calculation will be evaluated once the {Image Data} block for the last Facial image has been parsed successfully (not having reached an End-of-File marker prematurely). In the event that an End-of-File marker is reached prematurely this will be marked as having failed, but no value of {Total Bytes Expected} will be produced.</p> <p>{Total Facial Record Data Bytes Expected} = 32 + {Number of Feature Points} * 8 + sizeof {Image Data}</p>
6	<p>The Feature Mask is a bit mask of 3 bytes with bits 11–23 currently reserved. Thus 0x7FF is the maximum value.</p> <p>Some combinations of bits may be inappropriate (if the least significant bit is set high to indicate that all bits in the mask count)</p> <p>Examples might include bit 5, bit 7 and bit 8 are high, since a blink should not be detectable if the subject has both left and right eye-patches.</p> <p>These issues are not obvious, however, and should not be used to make an absolute declaration of conformance so they are ignored here.</p>

7	Valid range for specific Feature Point(s)																																				
	<table border="1"> <thead> <tr> <th>Major value</th> <th>Minor value</th> <th>Range</th> </tr> </thead> <tbody> <tr> <td>2</td> <td>1 to 14</td> <td>33 to 46</td> </tr> <tr> <td>3</td> <td>1 to 14</td> <td>49 to 62</td> </tr> <tr> <td>4</td> <td>1 to 6</td> <td>65 to 70</td> </tr> <tr> <td>5</td> <td>1 to 4</td> <td>81 to 84</td> </tr> <tr> <td>6</td> <td>1 to 4</td> <td>97 to 100</td> </tr> <tr> <td>7</td> <td>1</td> <td>113</td> </tr> <tr> <td>8</td> <td>1 to 10</td> <td>129 to 138</td> </tr> <tr> <td>9</td> <td>1 to 15</td> <td>145 to 159</td> </tr> <tr> <td>10</td> <td>1 to 10</td> <td>161 to 170</td> </tr> <tr> <td>11</td> <td>1 to 6</td> <td>177 to 182</td> </tr> <tr> <td>12</td> <td>1 to 4</td> <td>193 to 196</td> </tr> </tbody> </table>	Major value	Minor value	Range	2	1 to 14	33 to 46	3	1 to 14	49 to 62	4	1 to 6	65 to 70	5	1 to 4	81 to 84	6	1 to 4	97 to 100	7	1	113	8	1 to 10	129 to 138	9	1 to 15	145 to 159	10	1 to 10	161 to 170	11	1 to 6	177 to 182	12	1 to 4	193 to 196
Major value	Minor value	Range																																			
2	1 to 14	33 to 46																																			
3	1 to 14	49 to 62																																			
4	1 to 6	65 to 70																																			
5	1 to 4	81 to 84																																			
6	1 to 4	97 to 100																																			
7	1	113																																			
8	1 to 10	129 to 138																																			
9	1 to 15	145 to 159																																			
10	1 to 10	161 to 170																																			
11	1 to 6	177 to 182																																			
12	1 to 4	193 to 196																																			
10	Note that values 0 to 7 have specific meaning from Table 13, but 128 to 255 are vendor defined. Values 8 to 127 are reserved.																																				
11	<p>ISO/IEC 19794-5:2005 standard (Clause 6.2) requires JFIF File Interchange Format for JPEG images and JP2 file type extension for JPEG2000.</p> <p>Minimum conformance and extended requirements need to be tested<sup>[2][4]</sup></p> <p>IF {Image Data Type} EQ 0 THEN (JPEG format)</p> <p style="padding-left: 20px;">first four bytes of image = 0xFFD8 FFE0</p> <p style="padding-left: 20px;">last two bytes of image = 0xFFD9</p> <p>ENDIF</p> <p>IF {Image Data Type} EQ 1 THEN (JPEG 2000)</p> <p style="padding-left: 20px;">Start of Image Marker = 0x0000 000C 6A50 2020 0D0A 870A (See Reference <sup>[3]</sup> Signature box, ISO/IEC 15444-1, I.7.1)</p> <p>ENDIF</p>																																				
12	{Image Data Length} = sizeof {Facial Data} - sizeof {Facial Information} - sizeof{Facial Features} - sizeof {Image Information}																																				
13	The least significant bit determines whether an integer value is even or odd. Even numbers have a least significant bit of 0, odd numbers have 1. When the least significant bit is 0 (even) all other bits shall be 0 according to requirement R-15, or to say the integer value of the whole field shall be 0.																																				

Table 3 — Conformance Test Assertions for ISO/IEC 19794-5:2005 Full Frontal Images

Test Sub-Format	Requirement ID	Level	Field	Operator	Operands	Test Note	Status	IUT Support	Supported range	Test Result
1.	R-3	1	Format Identifier	EQ	0x46414300		M			
2.	R-3	1	Format Identifier	NEQ	0x00434146	1	M			
3.	R-4	1	Version Number	EQ	0x30313000		M			
4.	R-4	1	Version Number	NEQ	0x00303130	1	M			
5.	R-5, R-6	1	Record Length	C	57 to 232 - 1	2	M			
6.	R-5, R-6	2	Record Length	EQ	Total Bytes Read		M			
7.	R-5, R-6	2	Record Length	EQ	Total Bytes Expected	3	M			
8.	R-7, R-8	1	Number of Facial Images	EQ	1 to 65 535		M			
9.	R-7, R-8	2	Number of Facial Images	EQ	Total Number of Facial Images Read		M			
10.	R-10	2	Facial Record Data Length	C	See Note	4	M			
11.	R-10	2	Facial Record Data Length	EQ	Tot. Facial Record Data Bytes Read		M			
12.	R-10	2	Facial Record Data Length	EQ	Tot. Facial Record Data Bytes Expected	5	M			
13.	R-10	2	Facial Record Data Length	GT	Minimum {Facial Record Data Length} = 32 + sizeof {Image Data}		M			
14.	R-10	1	Facial Record Data Length	LE	0xFFFFFFFF - sizeof {Facial Header} = 0xFFFFFFFF - 0xE = 0xFFFFFFFF1		M			
15.	R-11	1	Number of Feature Points	EQ	0 to 65 535		M			
16.	R-11, R-22	2	Number of Feature Points	EQ	Total Number of Feature Points Read		M			
17.	R-12	1	Gender	EQ	0 to 2, 255		M			
18.	R-13	1	Eye Colour	EQ	0 to 7, 255		M			
19.	R-14	1	Hair Colour	EQ	0 to 7, 255		M			
20.	R-15	1	Property Mask	EQ	0x000000 to 0x0007FF	6	M			
20.1	R-15	1	Property Mask	EQ	{Property Mask} EQ 0 OR Is Odd {Property Mask} Modulo 2 EQ 1	13	M			
21.	Full Ft R-15	2	Property Mask & 0x000020 (Blink Bit 5)	EQ	0		M			

Table 3 (continued)

Test Sub-Format	Requirement ID	Level	Field	Operator	Operands	Test Note	Status	IUT Support	Supported range	Test Result
22.	R-16	1	Expression	EQ	0 to 7, 32 768 to 65 535		M			
23.	R-17, R-18	1	Pose Angle Yaw	EQ	0 to 180		M			
24.	R-17, R-19	1	Pose Angle Pitch	EQ	0 to 180		M			
25.	R-17, R-20	1	Pose Angle Roll	EQ	0 to 180		M			
26.	Full Ftl R-18, R-42	1	Pose Angle Yaw	EQ	0 to 5		M			
27.	Full Ftl R-19, R-42	1	Pose Angle Pitch	EQ	0 to 5		M			
28.	Full Ftl R-20, R-42	1	Pose Angle Roll	EQ	0 to 8		M			
29.	R-21	1	Yaw Angle Uncertainty	EQ	0 to 181		M			
30.	R-21	1	Pitch Angle Uncertainty	EQ	0 to 181		M			
31.	R-21	1	Roll Angle Uncertainty	EQ	0 to 181		M			
32.	R-23	1	Feature Point Type	EQ	1		O			
33.	R-24	1	Feature Point Code	EQ	See Note	7	O			
34.	R-22, R-25	2	X coordinate range check	EQ	0 to (Width - 1)		O			
35.	R-22, R-26	2	Y coordinate range check	EQ	0 to (Height - 1)		O			
36.	R-22	1	Reserved	EQ	0		O			
37.	R-28	1	Face Image Type	EQ	0 to 2		M			
38.	Full Ftl R-70, R-80	1	Face Image Type	EQ	1		M			
39.	R-29	1	Image Data Type	EQ	0, 1		M			
40.	R-30	1	Image Width	EQ	0 to 65 535		M			
41.	R-31	1	Image Height	EQ	0 to 65 535		M			
42.	R-30	2	Image Width	C			M			
43.	R-31	2	Image Height	C			M			
44.	Full Ftl R-76, R-79	1	Image Width (relation to head width)	GTE	240	9	M			
45.	Full Ftl R-32, R-68	2	Colour Space	EQ	1 to 3		M			
46.	R-33	1	Source Type	EQ	0 to 7, 128 to 255	10	M			
47.	R-34	1	Device Type	EQ	0 to 65 535		M			
48.	R-35	1	Quality	EQ	0		M			

Table 3 (continued)

Test	Sub-Format	Requirement ID	Level	Field	Operator	Operands	Test Note	Status	IUT Support	Supported range	Test Result
49.		R-30, R-29, R-36, R-37	1	Image Marker	EQ	See Note	11	M			
50.		R-30, R-29, R-37	2	Image Data Length	EQ	Total Bytes Read	12	M			

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 29109-5:2014

Test Notes

1	<p>Test 2 and Test 4 check to see if these multi-byte quantities have been encoded as the Little-Endian equivalent of the correct Big-Endian value. These tests fail if that is true but pass in all other cases. By reviewing the combination of the results of Test 1, 2, 3 and 4, it should be simple to determine whether or not the implementation under test is using the correct Big-Endian encoding.</p>
2	<p>Clause 6.2 of ISO/IEC 19794-5:2005 standard requires JFIF File Interchange Format for JPEG images<sup>[1]</sup> and JP2 file type extension for JPEG2000<sup>[3]</sup>.</p> <p>For JPEG [ref. ISO/IEC 10918-1 / Figure B.2, Table B.2, and "JPEG File Interchange Format, Version1.02"]  Minimum {Image Data} = sizeof (Start of Image marker) + sizeof (Frame Header) + sizeof (JFIF marker) + sizeof (End of Image marker)  Minimum {Image Data} = 2 + 2 + 5 + 2 bytes  Minimum {Image Data} = 11 bytes</p> <p>For JPEG 2000 [Reference 3, specifically ISO/IEC 15444-1 / Figure I-1, Table I-2, and Annex I]  Minimum {Image Data} = sizeof (Signature box) + sizeof (Profile box) + sizeof (JP2 Header box) + sizeof (Contiguous Codestream box)  Minimum {Image Data} = 12 + 8 + 4 + 16 bytes  Minimum {Image Data} = 40 bytes</p> <p>Therefore, Minimum {Image Data} Length = 11 bytes  Minimum {Record Length} = sizeof {Facial Header} + sizeof {Facial Information} + sizeof {Image Information} + sizeof (Minimum {Image Data})  Minimum {Record Length} = 14 + 20 + 12 + 11 = 57 bytes</p>
3	<p>The following calculation will be evaluated once the Image Data block for the last Facial image has been parsed successfully (not having reached an End-of-File marker prematurely). In the event that End-of-File marker is reached prematurely this will be marked as having failed, but no value of {Total Bytes Expected} will be produced.</p> <p>Length = 14  FOR j = 1: {Number of Facial Images}  Length = Length + 32 + {Number of Feature Points} * 8 + sizeof {Image Data}  END  {Total Bytes Expected} = Length</p>
4	<p>Minimum {Facial Record Data Length} = 32 + sizeof {Image Data}</p> <p>IF {Image Data Type} EQ 0 THEN  Minimum {Facial Record Data Length} = sizeof {Facial Information} + sizeof {Image Information} + sizeof (Minimum JPEG {Image Data})  Minimum {Facial Record Data Length} = 20 + 12 + 11 = 43  ENDIF</p> <p>IF {Image Data Type} EQ 1 THEN  Minimum {Facial Record Data Length} = sizeof {Facial Information} + sizeof {Image Information} + sizeof (Minimum JPEG2000 {Image Data})  Minimum {Facial Record Data Length} = 20 + 12 + 40 = 72  ENDIF</p>
5	<p>The following calculation will be evaluated once the {Image Data} block for the last Facial image has been parsed successfully (not having reached an End-of-File marker prematurely). In the event that an End-of-File marker is reached prematurely this will be marked as having failed, but no value of {Total Bytes Expected} will be produced.</p> <p>{Total Facial Record Data Bytes Expected} = 32 + {Number of Feature Points} * 8 + sizeof {Image Data}</p>
6	<p>The Feature Mask is a bit mask of 3 bytes with bits 11–23 currently reserved. Thus 0x7FF is the maximum value.</p> <p>Some combinations of bits may be inappropriate (if the least significant bit is set high to indicate that all bits in the mask count)</p> <p>Examples might include bit 5, bit 7 and bit 8 are high, since a blink should not be detectable if the subject has both left and right eye-patches.</p> <p>These issues are not obvious, however, and should not be used to make an absolute declaration of conformance so they are ignored here.</p>

7	<p>Valid range for specific Feature Point(s)</p> <table border="1" data-bbox="549 304 965 775"> <thead> <tr> <th>Major value</th> <th>Minor value</th> <th>Range</th> </tr> </thead> <tbody> <tr> <td>2</td> <td>1 to 14</td> <td>33 to 46</td> </tr> <tr> <td>3</td> <td>1 to 14</td> <td>49 to 62</td> </tr> <tr> <td>4</td> <td>1 to 6</td> <td>65 to 70</td> </tr> <tr> <td>5</td> <td>1 to 4</td> <td>81 to 84</td> </tr> <tr> <td>6</td> <td>1 to 4</td> <td>97 to 100</td> </tr> <tr> <td>7</td> <td>1</td> <td>113</td> </tr> <tr> <td>8</td> <td>1 to 10</td> <td>129 to 138</td> </tr> <tr> <td>9</td> <td>1 to 15</td> <td>145 to 159</td> </tr> <tr> <td>10</td> <td>1 to 10</td> <td>161 to 170</td> </tr> <tr> <td>11</td> <td>1 to 6</td> <td>177 to 182</td> </tr> <tr> <td>12</td> <td>1 to 4</td> <td>193 to 196</td> </tr> </tbody> </table>	Major value	Minor value	Range	2	1 to 14	33 to 46	3	1 to 14	49 to 62	4	1 to 6	65 to 70	5	1 to 4	81 to 84	6	1 to 4	97 to 100	7	1	113	8	1 to 10	129 to 138	9	1 to 15	145 to 159	10	1 to 10	161 to 170	11	1 to 6	177 to 182	12	1 to 4	193 to 196
Major value	Minor value	Range																																			
2	1 to 14	33 to 46																																			
3	1 to 14	49 to 62																																			
4	1 to 6	65 to 70																																			
5	1 to 4	81 to 84																																			
6	1 to 4	97 to 100																																			
7	1	113																																			
8	1 to 10	129 to 138																																			
9	1 to 15	145 to 159																																			
10	1 to 10	161 to 170																																			
11	1 to 6	177 to 182																																			
12	1 to 4	193 to 196																																			
9	<p>IF {Face Image Type} EQ 1 THEN The minimum {Head Width} = 180</p> <p>IF {Face Image Type} EQ 1 THEN The maximum {Head Width: Image Width} ratio is 0,75</p> <p>IF {Face Image Type} EQ 1 THEN The minimum {Image Width} = maximum {Head Width} / 0,75 = 240</p>																																				
10	<p>Note that values 0 to 7 have specific meaning from Table 13, but 128 to 255 are vendor defined. Values 8 to 127 are reserved.</p>																																				
11	<p>ISO/IEC 19794-5:2005 standard (Clause 6.2) requires JFIF File Interchange Format for JPEG images and JP2 file type extension for JPEG2000.</p> <p>Minimum conformance and extended requirements need to be tested<sup>[2][4]</sup></p> <p>IF {Image Data Type} EQ 0 THEN (JPEG format)</p> <p style="padding-left: 20px;">first four bytes of image = 0xFFD8 FFE0</p> <p style="padding-left: 20px;">last two bytes of image = 0xFFD9</p> <p>ENDIF</p> <p>IF {Image Data Type} EQ 1 THEN (JPEG 2000)</p> <p style="padding-left: 20px;">Start of Image Marker = 0x0000 000C 6A50 2020 0D0A 870A (See Reference <sup>[3]</sup> Signature box, ISO/IEC 15444-1, I.7.1)</p> <p>ENDIF</p>																																				
12	<p>{Image Data Length} = sizeof {Facial Data} - sizeof {Facial Information} - sizeof {Facial Features} - sizeof {Image Information}</p>																																				
13	<p>The least significant bit determines whether an integer value is even or odd. Even numbers have a least significant bit of 0, odd numbers have 1. When the least significant bit is 0 (even) all other bits shall be 0 according to requirement R-15, or to say the integer value of the whole field shall be 0.</p>																																				