



ISO/IEC 29341-8-4

Edition 1.0 2008-11

# INTERNATIONAL STANDARD

Information technology – UPnP Device Architecture –  
Part 8-4: Internet Gateway Device Control Protocol – Wide Area Network  
Connection Device

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 29341-8-4:2008



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2008 ISO/IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

### **About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: [www.iec.ch/webstore/custserv](http://www.iec.ch/webstore/custserv)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)  
Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 23241-8-4:2008



ISO/IEC 29341-8-4

Edition 1.0 2008-11

# INTERNATIONAL STANDARD

---

**Information technology – UPnP Device Architecture –  
Part 8-4: Internet Gateway Device Control Protocol – Wide Area Network  
Connection Device**

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 29341-8-4:2008

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE

**E**

---

ICS 35.200

ISBN 2-8318-1009-5

## CONTENTS

FOREWORD .....	3
ORIGINAL UPNP DOCUMENTS (informative) .....	5
<b>1. Overview and Scope .....</b>	<b>7</b>
<b>2. Device Definitions .....</b>	<b>8</b>
2.1. Device Type .....	8
2.2. Device Model.....	8
2.2.1. Description of Device Requirements .....	9
2.2.2. Relationships Between Services.....	9
2.3. Theory of Operation .....	10
<b>3. Test.....</b>	<b>15</b>

## LIST OF TABLES

Table 1: Device Requirements .....	9
------------------------------------	---

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 29341-8-4:2008

## INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

### Part 8-4: Internet Gateway Device Control Protocol – Wide Area Network Connection Device

#### FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

IEC and ISO draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of the putative patent rights. The holders of the putative patent rights have assured IEC and ISO that they are willing to negotiate free licences or licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of the putative patent rights are registered with IEC and ISO.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation  
Standards Licensing Department  
5200 NE Elam Young Parkway  
MS: JFS-98  
USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US; 7069312 / US; 10/783 524 / US

Information may be obtained from:

Microsoft Corporation  
One Microsoft Way  
USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S  
High Tech campus, building 44 3A21  
NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL)  
High Tech campus 60  
NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd.  
1-3-7 Shiromi, Chuoh-ku  
JP – Osaka 540-6139

Hewlett Packard Company has informed IEC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139 177 / US; 6 529 936 / US; 6 470 339 / US; 6 571 388 / US; 6 205 466 / US

Information may be obtained from:

Hewlett Packard Company  
1501 Page Mill Road  
USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd.  
416 Maetan-3 Dong, Yeongtang-Gu,  
KR – Suwon City 443-742

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 29341-8-4 was prepared by UPnP Implementers Corporation and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Universal plug and play (UPnP) architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

## ORIGINAL UPnP DOCUMENTS (informative)

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

UPnP Document Title	ISO/IEC 29341 Part
UPnP Device Architecture 1.0	ISO/IEC 29341-1
UPnP Basic:1 Device	ISO/IEC 29341-2
UPnP AV Architecture:1	ISO/IEC 29341-3-1
UPnP MediaRenderer:1 Device	ISO/IEC 29341-3-2
UPnP MediaServer:1 Device	ISO/IEC 29341-3-3
UPnP AVTransport:1 Service	ISO/IEC 29341-3-10
UPnP ConnectionManager:1 Service	ISO/IEC 29341-3-11
UPnP ContentDirectory:1 Service	ISO/IEC 29341-3-12
UPnP RenderingControl:1 Service	ISO/IEC 29341-3-13
UPnP MediaRenderer:2 Device	ISO/IEC 29341-4-2
UPnP MediaServer:2 Device	ISO/IEC 29341-4-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11
UPnP ContentDirectory:2 Service	ISO/IEC 29341-4-12
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13
UPnP ScheduledRecording:1	ISO/IEC 29341-4-14
UPnP DigitalSecurityCamera:1 Device	ISO/IEC 29341-5-1
UPnP DigitalSecurityCameraMotionImage:1 Service	ISO/IEC 29341-5-10
UPnP DigitalSecurityCameraSettings:1 Service	ISO/IEC 29341-5-11
UPnP DigitalSecurityCameraStillImage:1 Service	ISO/IEC 29341-5-12
UPnP HVAC_System:1 Device	ISO/IEC 29341-6-1
UPnP HVAC_ZoneThermostat:1 Device	ISO/IEC 29341-6-2
UPnP ControlValve:1 Service	ISO/IEC 29341-6-10
UPnP HVAC_FanOperatingMode:1 Service	ISO/IEC 29341-6-11
UPnP FanSpeed:1 Service	ISO/IEC 29341-6-12
UPnP HouseStatus:1 Service	ISO/IEC 29341-6-13
UPnP HVAC_SetpointSchedule:1 Service	ISO/IEC 29341-6-14
UPnP TemperatureSensor:1 Service	ISO/IEC 29341-6-15
UPnP TemperatureSetpoint:1 Service	ISO/IEC 29341-6-16
UPnP HVAC_UserOperatingMode:1 Service	ISO/IEC 29341-6-17
UPnP BinaryLight:1 Device	ISO/IEC 29341-7-1
UPnP DimmableLight:1 Device	ISO/IEC 29341-7-2
UPnP Dimming:1 Service	ISO/IEC 29341-7-10
UPnP SwitchPower:1 Service	ISO/IEC 29341-7-11
UPnP InternetGatewayDevice:1 Device	ISO/IEC 29341-8-1
UPnP LANDevice:1 Device	ISO/IEC 29341-8-2
UPnP WANDevice:1 Device	ISO/IEC 29341-8-3
UPnP WANConnectionDevice:1 Device	ISO/IEC 29341-8-4
UPnP WLANAccessPointDevice:1 Device	ISO/IEC 29341-8-5
UPnP LANHostConfigManagement:1 Service	ISO/IEC 29341-8-10
UPnP Layer3Forwarding:1 Service	ISO/IEC 29341-8-11
UPnP LinkAuthentication:1 Service	ISO/IEC 29341-8-12
UPnP RadiusClient:1 Service	ISO/IEC 29341-8-13
UPnP WANCableLinkConfig:1 Service	ISO/IEC 29341-8-14
UPnP WANCommonInterfaceConfig:1 Service	ISO/IEC 29341-8-15
UPnP WANDSLLinkConfig:1 Service	ISO/IEC 29341-8-16
UPnP WANEthernetLinkConfig:1 Service	ISO/IEC 29341-8-17
UPnP WANIPConnection:1 Service	ISO/IEC 29341-8-18
UPnP WANPOTSLinkConfig:1 Service	ISO/IEC 29341-8-19
UPnP WANPPPConnection:1 Service	ISO/IEC 29341-8-20
UPnP WLANConfiguration:1 Service	ISO/IEC 29341-8-21
UPnP Printer:1 Device	ISO/IEC 29341-9-1
UPnP Scanner:1.0 Device	ISO/IEC 29341-9-2
UPnP ExternalActivity:1 Service	ISO/IEC 29341-9-10
UPnP Feeder:1.0 Service	ISO/IEC 29341-9-11
UPnP PrintBasic:1 Service	ISO/IEC 29341-9-12
UPnP Scan:1 Service	ISO/IEC 29341-9-13
UPnP QoS Architecture:1.0	ISO/IEC 29341-10-1
UPnP QoSDevice:1 Service	ISO/IEC 29341-10-10
UPnP QoSManager:1 Service	ISO/IEC 29341-10-11
UPnP QoSPolicyHolder:1 Service	ISO/IEC 29341-10-12
UPnP QoS Architecture:2	ISO/IEC 29341-11-1
UPnP QOS v2 Schema Files	ISO/IEC 29341-11-2

<b>UPnP Document Title</b>	<b>ISO/IEC 29341 Part</b>
UPnP QosDevice:2 Service	ISO/IEC 29341-11-10
UPnP QosManager:2 Service	ISO/IEC 29341-11-11
UPnP QosPolicyHolder:2 Service	ISO/IEC 29341-11-12
UPnP RemoteUIClientDevice:1 Device	ISO/IEC 29341-12-1
UPnP RemoteUIServerDevice:1 Device	ISO/IEC 29341-12-2
UPnP RemoteUIClient:1 Service	ISO/IEC 29341-12-10
UPnP RemoteUIServer:1 Service	ISO/IEC 29341-12-11
UPnP DeviceSecurity:1 Service	ISO/IEC 29341-13-10
UPnP SecurityConsole:1 Service	ISO/IEC 29341-13-11

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 29341-8-4:2008

# 1. Overview and Scope

This device template is compliant with the UPnP Device Architecture, Version 1.0.

**WANConnectionDevice** is a REQUIRED virtual device defined under **urn:schemas-upnp-org:device:WANDevice**

An instance of **WANDevice** is specified under the root device **urn:schemas-upnp-org:device:InternetGatewayDevice**

**WANConnectionDevice** is a container for a link and connection services specific to a link on a WAN interface. Most types of WAN interfaces can be modeled by a single instance of **WANConnectionDevice**. However, in the case of DSL, each VC can have unique link attributes and can be provisioned for connection services that are different from other VCs. In this case, each VC will be modeled by an instance of **WANConnectionDevice**. Also, in the case of a POTS modem based **InternetGatewayDevice** (IGD), each separate ISP instance can be modeled as an instance of **WANConnectionDevice**.

The *Theory of Operation* section describes the services contained in **WANConnectionDevice** in more detail.




Figure 1: **WANConnectionDevice** Devices and Services Hierarchy

## 2. Device Definitions

### 2.1. Device Type

The following device type identifies a device that is compliant with this template:

urn:[schemas-upnp-org:device:WANConnectionDevice:1](#)

### 2.2. Device Model

Products that expose devices of the type [urn:schemas-upnp-org:device:WANConnectionDevice:1](#) must implement minimum version numbers of all required embedded devices and services specified in the table below.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 29341-8-4:2008

Table 1: Device Requirements

DeviceType	Root	Req. or Opt. <sup>1</sup>	ServiceType	Req. or Opt. <sup>1</sup>	Service ID <sup>2</sup>
			<u>WANPOTSLinkConfig:1</u>	<u>O for POTS modems</u>	<u>WANPOTSLinkC1</u>
			<u>WANDSLLinkConfig:1</u>	<u>O for DSL modems</u>	<u>WANDSLLinkC1</u>
			<u>WANCableLinkConfig:1</u>	<u>O for Cable modems</u>	<u>WANCableLinkC1</u>
			<u>WANEthernetLinkConfig:1</u>	<u>O for Ethernet attached modems</u>	<u>WANEthernetLinkC1</u>
			<u>WANPPPConnection:1</u>	<u>R for modems that support PPP based connections</u>	<u>Multiple instances possible within a WANConnectionDevice. ServiceIDs for multiple instances will be WANPPPConn1, WANPPPConn2, WANPPPConn3 and so on.</u>
			<u>WANIPConnection:1</u>	<u>R for modems that support IP based connections</u>	<u>Multiple instances possible within a WANConnectionDevice. ServiceIDs for multiple instances will be WANIPConn1, WANIPConn2, WANIPConn3 and so on.</u>
			<i>Non-standard services embedded by an UPnP vendor go here.</i>	<i>X</i>	<i>TBD</i>
<i>Non-standard devices embedded by a UPnP vendor go here.</i>	<i>TBD</i>	<i>X</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>

<sup>1</sup> R = Required, O = Optional, X = Non-standard.

<sup>2</sup> Prefixed by urn:[standards.iso.org:serviceId:](http://standards.iso.org/29341-8-4-2008).

Note: the word modem in the table above refers to the WAN interface (or **WANDevice**).

## 2.2.1. Description of Device Requirements

Each **WANConnectionDevice** models a link on a physical WAN interface. A **WANDevice** may contain one or more instances of **WANConnectionDevice** corresponding to one or more active links on a modem.

**WANCommonInterfaceConfig** is a service in **WANDevice** that models attributes and actions that are common across all links and all connection instances on a link.

## 2.2.2. Relationships Between Services

The DefaultConnectionService state variable in the **Layer3Forwarding** service refers to the UDN of a **WANConnectionDevice** instance – this is an external dependency. There may also be dependencies between a specific instance of **WAN\*LinkConfig** and **WAN\*\*Connection** service in a **WANConnectionDevice**.

## 2.3. Theory of Operation

Connections to the Internet are initiated either from the WAN interface of an IGD or are relayed or bridged through the WAN interface. DSL can be provisioned to support multiple Virtual Circuits (VCs) simultaneously. Each VC can in turn be provisioned to support one or more PPP connections or an IP connection. To handle these scenarios, each *WANDevice* includes one or more instances of *WANConnectionDevice*. A *WANConnectionDevice* encapsulates a logical or physical link on a WAN interface over which connections are modeled. Furthermore, connections on a WAN interface can be of type PPP or IP. These are modeled by corresponding *WAN{PPP/IP}Connection* service instances. Properties specific to a link are modeled in a *WAN{POTS/DSL/Cable/Ethernet}LinkConfig* service.

In accordance with UPnP Device Architecture version 1.0, the maximum number of *WANConnectionDevice* instances is static and specified in the *InternetGatewayDevice* description document. Similarly, the number of *WAN{PPP/IP}Connection* service instances contained in each *WANConnectionDevice* is also pre-specified..

The definition of the *WAN\*LinkConfig*<sup>1</sup> and *WAN\*Connection*<sup>2</sup> services is based on the following broad objectives:

- To allow for the distinction between Internet access scenarios that are typically independent of the modem types used and configuration scenarios that are specific to modem types. This enables easier modeling of various connectivity scenarios independent of the underlying modem type or its configuration.
- To support most of the commonly deployed connection types (either originating at the WAN interface of the gateway or relayed/bridged through the gateway)
- To support manual (may need Out-Of-Band security and access control mechanisms) or automatic configuration of parameters on a modem
- To ensure extensibility for new connection types in future.

Configuration and connectivity scenarios are independent of each other. However, there is an implied relationship in that control points will first need to complete configuration actions (unless this process is completed automatically) before initiating any connectivity related actions. It is also important to note that auto and manual configuration of a modem are mutually exclusive operations in most cases. Furthermore, in most deployment scenarios, auto configuration is given higher priority over manual configuration.

The process of configuration and subsequent management of WAN connections is via 3 variables:

- *LinkType*: This variable, if defined in a *WAN\*LinkConfig* service, indicates the protocol configured on a specific link. This variable can be set manually, or through an automatic mechanism (for example, *AutoConfig*<sup>3</sup> specified by DSLForum)
- *PossibleConnectionTypes*: specifies only those connection types that are permissible in a particular implementation for a specific modem link configuration (as indicated by the value of *LinkType*). This variable is defined in *WAN\*Connection* service.
- *ConnectionType*: indicates a specific connection type selected from those permissible on a link, as indicated by *PossibleConnectionTypes*. This variable is defined in *WAN\*Connection* service.

Figure 2 illustrates the process of configuration and connection management, using a DSL modem as an example. Note that the configuring agent and subsequent user(s) of connections need not be the same network entities. The 4 conceptual steps are described below.


- **Step 1:** A configuring entity sets up the *LinkType* to an appropriate value.
- **Step 2:** The value of *LinkType* is combined with the capabilities of the modem to come up with a list of possible connection types appropriate for the particular configuration.
- **Step 3:** The variable *PossibleConnectionTypes* is updated with the list derived from step above.

<sup>1</sup> Refer to companion DCP drafts for specific *WAN\*LinkConfig* descriptions and description of variables such as *LinkType*.

<sup>2</sup> Refer to companion DCP drafts for specific *WAN\*Connection* service descriptions and variables such as *PossibleConnectionTypes* and *ConnectionType*.

<sup>3</sup> Refer to the DSL Forum website ([www.dslforum.org](http://www.dslforum.org)) for more details.

- **Step 4:** A control point may subsequently initiate a connection by setting `ConnectionType` to a value from the allowable list specified in `PossibleConnectionTypes`. In this step, a control point evaluates its own capabilities vis-à-vis the capabilities exposed in `PossibleConnectionTypes` and selects one that is appropriate for its use. In some deployment scenarios, the value of `ConnectionType` may be strictly read-only from a control point perspective.



**Figure 2: Configuration and Connection Management**

The following table lists valid combinations of `LinkType` and `PossibleConnectionTypes` as well as connection service type for different types of WAN interfaces.

Modem Type	LinkType	Available Modem Capabilities	Possible Connection Types	Connection Service Type
DSL	Unconfigured	Not Applicable	Unconfigured	Not Applicable
	EoA <sup>4</sup>	Bridge	IP_Bridged	<b>WANIPConnection</b>
		Router	IP_Routed	WANIPConnection
	IPoA	Router	IP_Routed	WANIPConnection
	CIP	Router + CIP	IP_Routed	WANIPConnection
	PPPoA	Router	IP_Routed	<b>WANPPPConnection</b>
		PPTP Relay	PPTP_Relay	WANPPPConnection
		PPPoE Relay	PPPoE_Relay	WANPPPConnection

<sup>4</sup> Refer to the *WAN\*LinkConfig* service descriptions for a more detailed description of each of the `LinkType` and `PossibleConnectionTypes` values, including acronym expansions.

		L2TP Relay	L2TP_Relay	WANPPPConnection
		DHCP Spoofer	DHCP_Spoofed	WANPPPConnection
	PPPoE	Router	IP_Routed	WANPPPConnection
		PPTP Relay	PPTP_Relay	WANPPPConnection
		L2TP Relay	L2TP_Relay	WANPPPConnection
		Bridge	PPPoE_Bridged	WANPPPConnection
		DHCP Spoofer	DHCP_Spoofed	WANPPPConnection
Cable	Ethernet	Router	IP_Routed	<b>WANIPConnection</b>
		Bridge	IP_Bridged	WANIPConnection
POTS	DialupPPP	Router	IP_Routed	<b>WANPPPConnection</b>
Ethernet-Attached (External)	Ethernet	Router	IP_Routed	<b>WANIPConnection</b>
		Bridge	IP_Bridged	WANIPConnection
		Router*	IP_Routed	<b>WANPPPConnection</b>

**\*NOTE TO IMPLEMENTERS:** PPP-based connected types, originating from the WAN interface of an IGD, are possible for an Ethernet-attached external modem, most likely over an Ethernet or IP link. For example, a PPPoE connection can originate on the WAN interface of the IGD, terminating at the ISP head-end, with the externally attached modem acting as a pass-through Ethernet bridge. However, modeling this (or other similar) connection type(s) may require additional variables and/or actions in the WANPPPConnection service not currently defined by the IGD working committee. If needed, these features should be implemented as vendor extensions.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 29341-8-4:2008

### 3. XML Device Description

```

<?xml version="1.0"?>
<root xmlns="urn:schemas-upnp-org:device-1-0">
  <specVersion>
    <major>1</major>
    <minor>0</minor>
  </specVersion>
  <URLBase>base URL for all relative URLs</URLBase>
  <device>
    <deviceType>urn:schemas-upnp-org:device:
      WANConnectionDevice:1</deviceType>
    <friendlyName>short user-friendly title</friendlyName>
    <manufacturer>manufacturer name</manufacturer>
    <manufacturerURL>URL to manufacturer site</manufacturerURL>
    <modelDescription>long user-friendly title</modelDescription>
    <modelName>model name</modelName>
    <modelName>model number</modelName>
    <modelURL>URL to model site</modelURL>
    <serialNumber>manufacturer's serial number</serialNumber>
    <UDN>uuid:UUID</UDN>
    <UPC>Universal Product Code</UPC>
    <iconList>
      <icon>
        <mimetype>image/format</mimetype>
        <width>horizontal pixels</width>
        <height>vertical pixels</height>
        <depth>color depth</depth>
        <url>URL to icon</url>
      </icon>
      <!-- XML to declare other icons, if any, go here -->
    </iconList>
    <serviceList>
      <service>
        <serviceType>urn:schemas-upnp-org:service:
          WANDSLLinkConfig5:1</serviceType>
        <serviceId>urn:upnp-
          org:serviceId:WANDSLLinkC1</serviceId>
        <SCPDURL>URL to service description</SCPDURL>
        <controlURL>URL for control</controlURL>
        <eventSubURL>URL for eventing</eventSubURL>
      </service>
      <service>
        <serviceType>urn:schemas-upnp-org:service:
          WANPPPConnection6:1</serviceType>
        <serviceId>urn:upnp-
          org:serviceId:WANPPPConn1</serviceId>
        <SCPDURL>URL to service description</SCPDURL>
        <controlURL>URL for control</controlURL>
        <eventSubURL>URL for eventing</eventSubURL>
      </service>
      <!-- Declarations for other services added by UPnP vendor
      (if any) go here -->
    </serviceList>
  </deviceList>

```

<sup>5</sup> NOTE to implementers: This template is representative of one link type; DSL in this case. Depending on the type of modem, substitute or add device specific service names.

<sup>6</sup> NOTE to implementers: This template is representative of one connection type; PPP in this case. Depending on the type of connection, substitute or add service names.

```
        <!-- Description of embedded devices added by UPnP vendor
        (if any) go here -->
        </deviceList>
        <presentationURL>URL for presentation</presentationURL>
    </device>
</root>
```

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 29341-8-4:2008